



# **FCC RADIO TEST REPORT**

## **FCC ID: 2AHL5-ST907**

**Product:** Industrial Tablet PC  
**Trade Name:** SENTER  
**Model No.:** ST907  
**Serial Model:** N/A  
**Report No.:** NTEK-2016NT02014175F2  
**Issue Date:** 09 Mar. 2016

### **Prepared for**

SHANDONG SENTER ELECTRONIC CO.,LTD.  
NO. 18, LIUYISHAN ROAD, NEW & HI-TECH AREA, ZIBO  
CITY, SHANDONG PROVINCE, CHINA

### **Prepared by**

NTEK TESTING TECHNOLOGY CO., LTD.  
1/F, Building E, Fenda Science Park, Sanwei Community,  
Xixiang Street Bao'an District, Shenzhen, P.R. China  
Tel.: +86-0755-61156588  
Fax.: +86-0755-61156599  
Website: [www.ntek.org.cn](http://www.ntek.org.cn)

### TABLE OF CONTENTS

<b>1</b>	<b>TEST RESULT CERTIFICATION .....</b>	<b>3</b>
<b>2</b>	<b>SUMMARY OF TEST RESULTS.....</b>	<b>4</b>
<b>3</b>	<b>FACILITIES AND ACCREDITATIONS .....</b>	<b>5</b>
3.1	FACILITIES.....	5
3.2	LABORATORY ACCREDITATIONS AND LISTINGS .....	5
3.3	MEASUREMENT UNCERTAINTY .....	5
<b>4</b>	<b>GENERAL DESCRIPTION OF EUT .....</b>	<b>6</b>
<b>5</b>	<b>DESCRIPTION OF TEST MODES .....</b>	<b>8</b>
<b>6</b>	<b>SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>9</b>
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	9
6.2	SUPPORT EQUIPMENT.....	10
6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS.....	11
<b>7</b>	<b>TEST REQUIREMENTS .....</b>	<b>12</b>
7.1	CONDUCTED EMISSIONS TEST .....	12
7.2	RADIATED SPURIOUS EMISSION .....	17
7.3	NUMBER OF HOPPING CHANNEL.....	25
7.4	HOPPING CHANNEL SEPARATION MEASUREMENT .....	27
7.5	AVERAGE TIME OF OCCUPANCY (DWELL TIME) .....	33
7.6	20BANDWIDTH TEST.....	40
7.7	PEAK OUTPUT POWER .....	46
7.8	CONDUCTED BAND EDGE MEASUREMENT.....	52
7.9	ANTENNA APPLICATION .....	60



### 1 TEST RESULT CERTIFICATION

Applicant's name .....	Shandong Senter Electronic Co.,Ltd.
Address .....	No. 18, Liuyishan Road, New & Hi-tech Area, Zibo City, Shandong Province, China
Manufacture's Name .....	Shandong Senter Electronic Co.,Ltd.
Address .....	No. 18, Liuyishan Road, New & Hi-tech Area, Zibo City, Shandong Province, China
Product description	
Product name .....	Industrial Tablet PC
Model and/or type reference .....	ST907
Serial Model .....	N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J:2015 FCC 47 CFR Part 15, Subpart C:2015 KDB 174176 D01 Line Conducted FAQ v01r01 ANSI C63.10-2013 DA 00-705	Complied

This device described above has been tested by NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK Testing Technology Co., Ltd., this document may be altered or revised by NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : 01 Feb. 2016 ~ 09 Mar. 2016

Testing Engineer : Eileen Liu.  
(Eileen Liu)

Technical Manager : Jason Chen  
(Jason Chen)

Authorized Signatory : Sam. Chen  
(Sam Chen)

**2 SUMMARY OF TEST RESULTS**

<b>FCC Part15 (15.247), Subpart C</b>			
<b>Standard Section</b>	<b>Test Item</b>	<b>Verdict</b>	<b>Remark</b>
15.207	Conducted Emission	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

### 3 FACILITIES AND ACCREDITATIONS

#### 3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

#### 3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : Accredited by CNAS, 2014.09.04  
 The certificate is valid until 2017.09.03  
 The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)  
 The Certificate Registration Number is L5516.

Accredited by Industry Canada, August 29, 2012  
 The Certificate Registration Number is 9270A-1.

Name of Firm : NTEK Testing Technology Co., Ltd  
 Site Location : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

#### 3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$

#### 4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	Industrial Tablet PC
Trade Name	SENER
FCC ID	2AHL5-ST907
Model No.	ST907
Serial Model	N/A
Model Difference	N/A
Operating Frequency	2402MHz~2480MHz
Modulation	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of Channels	79 Channels
Antenna Type	PCB Antenna
Antenna Gain	1 dBi
Power supply	<input checked="" type="checkbox"/> DC supply: DC 3.7V/7200mAh from Li-ion Battery or DC 5V from USB Port.
	<input checked="" type="checkbox"/> Adapter supply: Model: P12050200 Input: 100-240V~, 50/60Hz, 0.3A Output: 5.0V $\overline{\text{---}}$ , 2.0A
HW Version	N/A
SW Version	N/A

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.



## 5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation; 2Mbps for  $\pi/4$ -DQPSK modulation; 3Mbps for 8DPSK modulation) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency(MHz)
0	2402
1	2403
...	...
39	2441
40	2442
...	...
77	2479
78	2480

Note:  $fc=2402MHz+k \times 1MHz$   $k=0$  to 78

The following summary table is showing all test modes to demonstrate in compliance with the standard.

For AC Conducted Emission	
Final Test Mode	Description
Mode 1	normal link mode

Note: AC power line Conducted Emission was tested under maximum output power.

For Radiated Test Cases	
Final Test Mode	Description
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)

Note: For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.

For Conducted Test Cases	
Final Test Mode	Description
Mode 5	CH00(2402MHz)
Mode 6	CH39(2441MHz)
Mode 7	CH78(2480MHz)
Mode 8	Hopping

Note: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.




## 6 SETUP OF EQUIPMENT UNDER TEST

### 6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



**6.2 SUPPORT EQUIPMENT**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Note
E-1	Industrial Tablet PC	SENER	ST907	2AHL5-ST907	EUT
E-2	Adapter	N/A	P12050200	N/A	Peripherals
E-3	Earphone	N/A	L662	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	NO	NO	1.0m
C-2	Earphone	NO	NO	0.8m
C-3	RF Cable	NO	NO	0.5m

**Notes:**

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

### 6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

#### Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2015.07.06	2016.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2015.06.07	2016.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2015.07.06	2016.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.07	2016.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.07	2016.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2015.07.06	2016.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2015.12.22	2016.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2015.07.06	2016.07.05	1 year
12	Test Cable	N/A	R-01	N/A	2015.07.06	2016.07.05	1 year
13	Test Cable	N/A	R-02	N/A	2015.07.06	2016.07.05	1 year

#### Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2015.06.06	2016.06.05	1 year
2	LISN	R&S	ENV216	101313	2015.08.24	2016.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2015.08.24	2016.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.07	2016.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2015.06.07	2016.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2015.06.08	2016.06.07	1 year
7	Test Cable	N/A	C01	N/A	2015.06.08	2016.06.07	1 year
8	Test Cable	N/A	C02	N/A	2015.06.08	2016.06.07	1 year
9	Test Cable	N/A	C03	N/A	2015.06.08	2016.06.07	1 year

1	Attenuation	MCE	24-10-34	BN9258	2015.06.08	2016.06.07	1 year
---	-------------	-----	----------	--------	------------	------------	--------

Note: Each piece of equipment is scheduled for calibration once a year.

## 7 TEST REQUIREMENTS

### 7.1 CONDUCTED EMISSIONS TEST

#### 7.1.1 Applicable Standard


According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

#### 7.1.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. \*Decreases with the logarithm of the frequency  
 2. The lower limit shall apply at the transition frequencies  
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

#### 7.1.3 Test Configuration



#### 7.1.4 Test Procedure


According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 7.1.5 Test Results


Pass

### 7.1.6 Test Results




Site: NTEK Conducted Chamber#1      Phase: **L1**      Temperature: 26  
 Limit: FCC Part 15B\_(0.15-30MHz) \_Main\_QP      Power: AC 120V/60Hz      Humidity: 56 %  
 Mode: Mode 1  
 Note: Adapter

No.	Frequency (MHz)	Reading (dBuV)	Correct dB	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Remark
1	0.1539	38.75	10.26	49.01	65.78	-16.77	QP
2	0.3500	32.69	10.28	42.97	58.96	-15.99	QP
3	0.5420	40.40	10.02	50.42	56.00	-5.58	QP
4	0.7340	36.03	9.99	46.02	56.00	-9.98	QP
5	4.0260	33.45	9.86	43.31	56.00	-12.69	QP
6	0.1539	29.58	10.26	39.84	55.78	-15.94	AVG
7	0.4660	32.31	10.09	42.40	46.58	-4.18	AVG
8	0.7340	30.19	9.99	40.18	46.00	-5.82	AVG
9	0.8860	28.08	10.01	38.09	46.00	-7.91	AVG




Site: NTEK Conducted Chamber#1      Phase: **N**      Temperature: 26  
 Limit: FCC Part 15B\_(0.15-30MHz) \_Main\_QP      Power: AC 120V/60Hz      Humidity: 56 %  
 Mode: Mode 1  
 Note: Adapter

No.	Frequency (MHz)	Reading (dBuV)	Correct dB	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Remark
1	0.1580	37.16	10.21	47.37	65.56	-18.19	QP
2	0.2740	32.52	10.27	42.79	60.99	-18.20	QP
3	0.5420	40.51	10.04	50.55	56.00	-5.45	QP
4	0.7340	35.17	10.02	45.19	56.00	-10.81	QP
5	2.7780	33.81	9.84	43.65	56.00	-12.35	QP
6	0.1580	24.89	10.21	35.10	55.56	-20.46	AVG
7	0.3460	22.96	10.28	33.24	49.06	-15.82	AVG
8	0.5340	30.48	10.04	40.52	46.00	-5.48	AVG
9	0.7300	24.02	10.02	34.04	46.00	-11.96	AVG



Site NTEK Conducted Chamber#1 Phase: **L1** Temperature: 26  
 Limit: FCC Part 15B\_(0.15-30MHz) \_Main\_QP Power: AC 240V/50Hz Humidity: 56 %  
 Mode: Mode 1  
 Note: Adapter

No.	Frequency (MHz)	Reading (dBuV)	Correct dB	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Remark
1	1.0140	33.14	10.02	43.16	46.00	-2.84	AVG
2	1.0140	33.14	10.02	43.16	46.00	-2.84	AVG
3	0.2300	33.03	10.29	43.32	52.45	-9.13	AVG
4	0.4900	26.75	10.04	36.79	46.17	-9.38	AVG
5	0.2300	37.10	10.29	47.39	62.45	-15.06	QP
6	0.4863	37.24	10.05	47.29	56.23	-8.94	QP
7	1.0300	40.39	10.02	50.41	56.00	-5.59	QP
8	0.7100	37.81	9.99	47.80	56.00	-8.20	QP
9	1.9300	38.84	9.84	48.68	56.00	-7.32	QP



Site NTEK Conducted Chamber#1 Phase: *N* Temperature: 26  
 Limit: FCC Part 15B\_(0.15-30MHz) \_Main\_QP Power: AC 240V/50Hz Humidity: 56 %  
 Mode: Mode 1  
 Note: Adapter

No.	Frequency (MHz)	Reading (dBuV)	Correct dB	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Remark
1	0.2620	36.01	10.26	46.27	61.36	-15.09	QP
2	0.2620	25.52	10.26	35.78	51.36	-15.58	AVG
3	0.5260	31.99	10.04	42.03	46.00	-3.97	AVG
4	0.5340	41.48	10.04	51.52	56.00	-4.48	QP
5	0.6380	39.26	10.02	49.28	56.00	-6.72	QP
6	1.0300	38.68	10.04	48.72	56.00	-7.28	QP
7	1.0580	29.95	10.03	39.98	46.00	-6.02	AVG
8	1.4740	32.77	9.95	42.72	46.00	-3.28	AVG
9	2.2420	37.82	9.85	47.67	56.00	-8.33	QP
10	27.9540	34.96	10.23	45.19	60.00	-14.81	QP



**7.2 RADIATED SPURIOUS EMISSION**

**7.2.1 Applicable Standard**

According to FCC Part 15.247(d) and 15.209 and DA 00-705

**7.2.2 Conformance Limit**

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).  
According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54


- Remark :1. Emission level in dBuV/m=20 log (uV/m)  
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.  
 3. Distance extrapolation factor =40log(Specific distance/ test distance)( dB);  
 Limit line=Specific limits(dBuV) + distance extrapolation factor.

**7.2.3 Measuring Instruments**


The Measuring equipment is listed in the section 6.3 of this test report.

**7.2.4 Test Configuration**


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



**7.2.5 Test Procedure**

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where  $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW [kHz]})$ . , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

**7.2.6 Test Results**

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	Industrial Tablet PC	Model No.:	ST907
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu


Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =20log(Specific distance/ test distance)( dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor

- Spurious Emission below 1GHz (30MHz to 1GHz)  
All the modulation modes have been tested, and the worst result was report as below:



Site NTEK 9\*6\*6 Chamber #1      Polarization: *Horizontal*      Temperature: 24  
 Limit: FCC\_PART15\_B\_03m\_QP      Power:      Humidity: 50 %  
 Mode: Mode 1  
 Note:

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Remark
1	148.9625	23.97	11.61	35.58	43.50	-7.92	QP
2	289.0021	21.45	12.18	33.63	46.00	-12.37	QP
3	109.4116	16.85	10.24	27.09	43.50	-16.41	QP
4	480.5276	13.10	16.56	29.66	46.00	-16.34	QP
5	668.1422	12.65	20.83	33.48	46.00	-12.52	QP



Site NTEK 9\*6\*6 Chamber #1      Polarization: *Vertical*      Temperature: 24  
 Limit: FCC\_PART15\_B\_03m\_QP      Power:      Humidity: 50 %  
 Mode: Mode 1  
 Note:

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Remark
1	171.9946	19.29	12.46	31.75	43.50	-11.75	QP
2	99.5281	19.26	10.30	29.56	43.50	-13.94	QP
3	291.0360	19.34	12.30	31.64	46.00	-14.36	QP
4	372.0045	13.14	14.72	27.86	46.00	-18.14	QP
5	665.8034	12.43	20.77	33.20	46.00	-12.80	QP

■ Spurious Emission Above 1GHz (1GHz to 26GHz)

EUT:	Industrial Tablet PC	Model No.:	ST907
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)-Above 1G							
4804.236	60.36	-3.64	56.72	74.00	-17.28	Pk	Vertical
4804.236	50.25	-3.64	46.61	54.00	-7.39	AV	Vertical
7206.135	57.11	-0.95	56.16	74.00	-17.84	Pk	Vertical
7206.135	43.36	-0.95	42.41	54.00	-11.59	AV	Vertical
4804.245	64.25	-3.64	60.61	74.00	-13.39	Pk	Horizontal
4804.245	48.33	-3.64	44.69	54.00	-9.31	AV	Horizontal
7206.231	57.15	-0.96	56.19	74.00	-17.81	Pk	Horizontal
7206.231	44.02	-0.96	43.06	54.00	-10.94	AV	Horizontal
Mid Channel (2441 MHz)-Above 1G							
4882.158	61.36	-3.67	57.69	74.00	-16.31	Pk	Vertical
4882.158	45.69	-3.67	42.02	54.00	-11.98	AV	Vertical
7323.245	54.18	-0.82	53.36	74.00	-20.64	Pk	Vertical
7323.245	43.69	-0.82	42.87	54.00	-11.13	AV	Vertical
4882.177	63.69	-3.67	60.02	74.00	-13.98	Pk	Horizontal
4882.177	45.58	-3.67	41.91	54.00	-12.09	AV	Horizontal
7323.255	59.58	-0.82	58.76	74.00	-15.24	Pk	Horizontal
7323.255	43.69	-0.82	42.87	54.00	-11.13	AV	Horizontal
High Channel (2480 MHz)- Above 1G							
4960.058	55.66	-3.59	52.07	74.00	-21.93	Pk	Vertical
4960.058	49.36	-3.59	45.77	54.00	-8.23	AV	Vertical
7440.147	53.47	-0.68	52.79	74.00	-21.21	Pk	Vertical
7440.147	44.19	-0.68	43.51	54.00	-10.49	AV	Vertical
4960.177	60.25	-3.59	56.66	74.00	-17.34	Pk	Horizontal
4960.177	49.33	-3.59	45.74	54.00	-8.26	AV	Horizontal
7440.236	60.15	-0.68	59.47	74.00	-14.53	Pk	Horizontal
7440.236	45.77	-0.68	45.09	54.00	-8.91	AV	Horizontal

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
 (3)All other emissions more than 20dB below the limit.

■ Spurious Emission in Restricted Band 2310MHz -18000MHz

EUT:	Industrial Tablet PC	Model No.:	ST907
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

All the modulation modes have been tested and all other emissions more than 20dB below the limit, the worst result was report as below:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
1Mbps Non-hopping							
2390	60.31	-13.06	47.25	74.00	-26.75	Pk	Vertical
2390	59.45	-13.06	46.39	54.00	-7.61	AV	Vertical
2390	61.02	-13.06	47.96	74.00	-26.04	Pk	Horizontal
2390	60.76	-13.06	47.70	54.00	-6.30	AV	Horizontal
2483.5	61.95	-12.78	49.17	74.00	-24.83	Pk	Vertical
2483.5	60.87	-12.78	48.09	54.00	-5.91	AV	Vertical
2483.5	61.28	-12.78	48.50	74.00	-25.50	Pk	Horizontal
2483.5	59.74	-12.78	46.96	54.00	-7.04	AV	Horizontal
1Mbps hopping							
2390	60.81	-13.06	47.75	74.00	-26.25	Pk	Vertical
2390	60.38	-13.06	47.32	54.00	-6.68	AV	Vertical
2390	59.19	-13.06	46.13	74.00	-27.87	Pk	Horizontal
2390	59.76	-13.06	46.70	54.00	-7.30	AV	Horizontal
2483.5	58.94	-12.78	46.16	74.00	-27.84	Pk	Vertical
2483.5	60.82	-12.78	48.04	54.00	-5.96	AV	Vertical
2483.5	60.11	-12.78	47.33	74.00	-26.67	Pk	Horizontal
2483.5	58.54	-12.78	45.76	54.00	-8.24	AV	Horizontal



**7.3 NUMBER OF HOPPING CHANNEL**

**7.3.1 Applicable Standard**

According to FCC Part 15.247(a)(1) (iii) and DA 00-705

**7.3.2 Conformance Limit**

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

**7.3.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

**7.3.4 Test Setup**

Please refer to Section 6.1 of this test report.

**7.3.5 Test Procedure**


The testing follows ANSI C63.10-2013 clause 7.8.3  
 The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.  
 The path loss was compensated to the results for each measurement.  
 Set to the maximum power setting and enable the EUT transmit continuously.  
 The EUT must have its hopping function enabled.  
 Use the following spectrum analyzer settings:  
 Span = the frequency band of operation  
 RBW  $\geq$  1% of the span  
 VBW  $\geq$  RBW  
 Sweep = auto  
 Detector function = peak  
 Trace = max hold

**7.3.6 Test Results**

EUT:	Industrial Tablet PC	Model No.:	ST907
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode 8	Test By:	Eileen Liu

Number of Hopping (Channel)	Adaptive Frequency hopping (Channel)	limit	Verdict
79	20	$\geq$ 15	Pass

Number of Hopping Channel Plot



**7.4 HOPPING CHANNEL SEPARATION MEASUREMENT**

**7.4.1 Applicable Standard**

According to FCC Part 15.247(a)(1) and DA 00-705

**7.4.2 Conformance Limit**

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

**7.4.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

**7.4.4 Test Setup**

Please refer to Section 6.1 of this test report.

**7.4.5 Test Procedure**

The testing follows ANSI C63.10-2013 clause 7.8.2  
 The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.  
 The path loss was compensated to the results for each measurement.  
 Set to the maximum power setting and enable the EUT transmit continuously.  
 The EUT was operating in controlled its channel.  
 Use the following spectrum analyzer settings:  
 Span = Measurement Bandwidth or Channel Separation  
 RBW ≥ 30KHz  
 VBW ≥ 3\*RBW  
 Sweep = auto  
 Detector function = peak  
 Trace = max hold


**7.4.6 Test Results**

EUT:	Industrial Tablet PC	Model No.:	ST907
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode5/Mode6/Mode7	Test By:	Eileen Liu

Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)		Verdict
				>	2/3 of 20dB BW	
GFSK	0	2402	1000.00	>874.309	2/3 of 20dB BW	PASS
	39	2441	1004.00	>869.687	2/3 of 20dB BW	PASS
	78	2480	1000.00	>867.954	2/3 of 20dB BW	PASS
π/4-DQPSK	0	2402	1004.00	>806.000	2/3 of 20dB BW	PASS
	39	2441	1004.00	>815.333	2/3 of 20dB BW	PASS
	78	2480	1000.00	>814.667	2/3 of 20dB BW	PASS
8DPSK	0	2402	1004.00	>806.667	2/3 of 20dB BW	PASS
	39	2441	1000.00	>808.667	2/3 of 20dB BW	PASS
	78	2480	1000.00	>810.000	2/3 of 20dB BW	PASS


Channel Separation plot on channel 00-01

1Mbps




Channel Separation plot on channel 39-40


1Mbps



Channel Separation plot on channel 77-78 1Mbps




Channel Separation plot on channel 00-01 2Mbps




Channel Separation plot on channel 39-40

2Mbps




Channel Separation plot on channel 77-78

2Mbps




Channel Separation plot on channel 00-01

3Mbps




Channel Separation plot on channel 39-40

3Mbps



Channel Separation plot on channel 77-78

3Mbps





## **7.5 AVERAGE TIME OF OCCUPANCY (DWELL TIME)**

### **7.5.1 Applicable Standard**

According to FCC Part 15.247(a)(1)(iii) and DA 00-705

### **7.5.2 Conformance Limit**

The average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

### **7.5.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

### **7.5.4 Test Setup**

Please refer to Section 6.1 of this test report.

### **7.5.5 Test Procedure**

The testing follows ANSI C63.10-2013 clause 7.8.4

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW  $\geq$  1MHz

VBW  $\geq$  RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

Measure the maximum time duration of one single pulse.

Set the EUT for DH5, DH3 and DH1 packet transmitting.

Measure the maximum time duration of one single pulse.

**7.5.6 Test Results**

EUT:	Industrial Tablet PC	Model No.:	ST907
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode 8	Test By:	Eileen Liu

Modulation Mode	Channel Number	Packet type	Mode	Hops Over Occupancy Time (ms)	Pulse width (ms)	dwll time (ms)	Limit (ms)	Verdict
GFSK	39	DH1	Normal	320.00	0.497	159.040	<400	PASS
	39		AFH	160.00	0.497	79.520	<400	PASS
	39	DH3	Normal	160.00	1.750	280.000	<400	PASS
	39		AFH	80.00	1.750	140.000	<400	PASS
	39	DH5	Normal	106.67	2.981	317.983	<400	PASS
	39		AFH	53.33	2.981	158.977	<400	PASS
π/4-DQPSK	39	2DH1	Normal	320.00	0.518	165.760	<400	PASS
	39		AFH	160.00	0.518	82.880	<400	PASS
	39	2DH3	Normal	160.00	1.760	281.600	<400	PASS
	39		AFH	80.00	1.760	140.800	<400	PASS
	39	2DH5	Normal	106.67	3.035	323.743	<400	PASS
	39		AFH	53.33	3.035	161.857	<400	PASS
8DPSK	39	3DH1	Normal	320.00	0.508	162.560	<400	PASS
	39		AFH	160.00	0.508	81.280	<400	PASS
	39	3DH3	Normal	160.00	1.771	283.360	<400	PASS
	39		AFH	80.00	1.771	141.680	<400	PASS
	39	3DH5	Normal	106.67	3.046	324.917	<400	PASS
	39		AFH	53.33	3.046	162.443	<400	PASS

**Note:**

A Period Time = (channel number)\*0.4


DH1 Time Slot: Reading \* (1600/2)\*31.6/(channel number)

DH3 Time Slot: Reading \* (1600/4)\*31.6/(channel number)


DH5 Time Slot: Reading \* (1600/6)\*31.6/(channel number)

**For Example:**


- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time




Package Transfer Time Plot CH39-DH5




Package Transfer Time Plot CH39-2DH1




Package Transfer Time Plot CH39-2DH3




Package Transfer Time Plot CH39-2DH5




Package Transfer Time Plot CH39-3DH1



Package Transfer Time Plot CH39-3DH3





**7.6 20BANDWIDTH TEST**

**7.6.1 Applicable Standard**

According to FCC Part 15.247(a)(1) and DA 00-705

**7.6.2 Conformance Limit**

No limit requirement.

**7.6.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

**7.6.4 Test Setup**

Please refer to Section 6.1 of this test report.

**7.6.5 Test Procedure**

The testing follows ANSI C63.10-2013 clause 6.9.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW ≥ 1% of the 20 dB bandwidth

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

**7.6.6 Test Results**


EUT:	Industrial Tablet PC	Model No.:	ST907
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode5/Mode6/Mode7	Test By:	Eileen Liu

Test Channel	Frequency (MHz)	Measurement Bandwidth (KHz)	Limit (kHz)	Verdict
<b>1Mbps</b>				
00	2402	1094.000	N/A	PASS
39	2441	1079.000	N/A	PASS
78	2480	1094.000	N/A	PASS
<b>2Mbps</b>				
00	2402	1489.000	N/A	PASS
39	2441	1502.000	N/A	PASS
78	2480	1495.000	N/A	PASS
<b>3Mbps</b>				
00	2402	1518.000	N/A	PASS
39	2441	1516.000	N/A	PASS
78	2480	1509.000	N/A	PASS


Note: N/A (Not Applicable)




20dB Bandwidth plot on channel 00 1Mbps




20dB Bandwidth plot on channel 39 1Mbps




20dB Bandwidth plot on channel 78 1Mbps




20dB Bandwidth plot on channel 00 2Mbps




20dB Bandwidth plot on channel 39 2Mbps




20dB Bandwidth plot on channel 78 2Mbps




20dB Bandwidth plot on channel 00 3Mbps



20dB Bandwidth plot on channel 39 3Mbps





**7.7 PEAK OUTPUT POWER**

**7.7.1 Applicable Standard**

According to FCC Part 15.247(b)(1) and DA 00-705

**7.7.2 Conformance Limit**

The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

**7.7.3 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

**7.7.4 Test Setup**

Please refer to Section 6.1 of this test report.


**7.7.5 Test Procedure**

The testing follows ANSI C63.10-2013 clause 7.8.5.  
 The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.  
 The path loss was compensated to the results for each measurement.  
 Set to the maximum power setting and enable the EUT transmit continuously.  
 The EUT was operating in controlled its channel.  
 Use the following spectrum analyzer settings:  
 Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel  
 RBW ≥ the 20 dB bandwidth of the emission being measured  
 VBW ≥ RBW  
 Sweep = auto  
 Detector function = peak  
 Trace = max hold


**7.7.6 Test Results**

EUT:	Industrial Tablet PC	Model No.:	ST907
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode5/Mode6/Mode7	Test By:	Eileen Liu


Test Channel	Frequency (MHz)	Power Setting	Peak Output Power (dBm)	LIMIT (dBm)	Verdict
<b>1Mbps</b>					
00	2402	MAXIMUM	3.60	20.97	PASS
39	2441	MAXIMUM	4.15	20.97	PASS
78	2480	MAXIMUM	4.36	20.97	PASS
<b>2Mbps</b>					
00	2402	MAXIMUM	4.20	20.97	PASS
39	2441	MAXIMUM	4.72	20.97	PASS
78	2480	MAXIMUM	4.88	20.97	PASS
<b>3Mbps</b>					
00	2402	MAXIMUM	4.13	20.97	PASS
39	2441	MAXIMUM	4.61	20.97	PASS
78	2480	MAXIMUM	4.80	20.97	PASS




Peak output Power plot on channel 78 1Mbps




Peak output Power plot on channel 00 2Mbps









Peak output Power plot on channel 00 3Mbps



Peak output Power plot on channel 39 3Mbps





## 7.8 CONDUCTED BAND EDGE MEASUREMENT

### 7.8.1 Applicable Standard

According to FCC Part 15.247(d) and DA 00-705

### 7.8.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 7.8.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

### 7.8.4 Test Setup

Please refer to Section 6.1 of this test report.

### 7.8.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.6.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = 100KHz

VBW = 300KHz

Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.



**7.8.6 Test Results**

EUT:	Industrial Tablet PC	Model No.:	ST907
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode5/Mode6/Mode7/Mode8	Test By:	Eileen Liu



Frequency Band	Delta Peak to band emission(dBc)	>Limit(dBc)	Verdict
1Mbps Non-hopping			
2400	62.57	20	Pass
2483.5	62.39	20	Pass
2Mbps Non-hopping			
2400	48.88	20	Pass
2483.5	60.24	20	Pass
3Mbps Non-hopping			
2400	45.03	20	Pass
2483.5	58.42	20	Pass
1Mbps hopping			
2400	58.26	20	Pass
2483.5	48.11	20	Pass
2Mbps hopping			
2400	49.05	20	Pass
2483.5	55.36	20	Pass
3Mbps hopping			
2400	61.16	20	Pass
2483.5	58.33	20	Pass

Note: Hopping enabled and disabled have evaluated, and the worstest data was reported



BDR mode (GFSK): Band Edge-Low Channel



BDR mode (GFSK): Band Edge-High Channel





EDR mode ( $\pi/4$ -DQPSK): Band Edge-Low Channel









EDR mode ( $\pi/4$ -DQPSK): Band Edge- High Channel



EDR mode (8DPSK): Band Edge-Low Channel



EDR mode (8DPSK): Band Edge- High Channel



## **7.9 ANTENNA APPLICATION**

### **7.9.1 Antenna Requirement**

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### **7.9.2 Result**

The EUT antenna is permanent attached antenna. It comply with the standard requirement.

END OF REPORT