

**FCC ID:2AHM7GCYYW773**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHZ})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHZ})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	0.103	1.02	0±1	1.00	1.26	<5	0.39023	3.00	YES
	2.441	0.48	1.12	0±1	1.00	1.26	<5	0.39338	3.00	YES
	2.480	-0.167	0.96	0±1	1.00	1.26	<5	0.39651	3.00	YES
$\pi$ / 4DQPSK	2.402	0.732	1.18	0±1	1.00	1.26	<5	0.39023	3.00	YES
	2.441	1.163	1.31	1±1	2.00	1.58	<5	0.49524	3.00	YES
	2.480	0.507	1.12	0±1	1.00	1.26	<5	0.39651	3.00	YES
8DQPSK	2.402	1.091	1.29	1±1	2.00	1.58	<5	0.49127	3.00	YES
	2.441	1.42	1.39	1±1	2.00	1.58	<5	0.49524	3.00	YES
	2.480	0.757	1.19	0±1	1.00	1.26	<5	0.39651	3.00	YES

**Conclusion:**

For the max result :  $0.49524 \leq$  FCC Limit 3.0 for 1g SAR.