



FCC TEST REPORT

Test report

On Behalf of

Shenzhen Ai-Thinker Technology Co., Ltd.

For

Wi-Fi+BT SoC Module

Model No.: BW16

FCC ID: 2AHMR-BW16

Prepared for: Shenzhen Ai-Thinker Technology Co., Ltd.
6/F, Block C2, Huafeng Industrial Park, Hangcheng Road, Baoan district,
Shenzhen China

Prepared By: Shenzhen HUAKE Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: Dec. 16, 2019 ~ Dec. 25, 2019

Date of Report: Dec. 25, 2019

Report Number: HK1911293047-1E



TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Ai-Thinker Technology Co., Ltd.
 Address : 6/F, Block C2, Huafeng Industrial Park, Hangcheng Road, Baoan district, Shenzhen China
Manufacture's Name..... : Shenzhen Ai-Thinker Technology Co., Ltd.
 Address : 6/F, Block C2, Huafeng Industrial Park, Hangcheng Road, Baoan district, Shenzhen China


Product description

Trade Mark: N/A
 Product name : Wi-Fi+BT SoC Module
 Model and/or type reference : BW16


Standards : FCC Rules and Regulations Part 15 Subpart C Section 15.249
 ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.


Date of Test :
 Date (s) of performance of tests : Dec. 16, 2019 ~ Dec. 25, 2019
 Date of Issue..... : Dec. 25, 2019
 Test Result..... : **Pass**

Testing Engineer : 

 (Gary Qian)

Technical Manager : 

 (Eden Hu)

Authorized Signatory : 

 (Jason Zhou)



| Table of Contents | Page |
|---|-------------|
| 1 . TEST SUMMARY | 4 |
| 2 . GENERAL INFORMATION | 5 |
| 2.1 GENERAL DESCRIPTION OF EUT | 5 |
| 2.2 Carrier Frequency of Channels | 6 |
| 2.3 Operation of EUT during testing | 6 |
| 2.4 DESCRIPTION OF TEST SETUP | 6 |
| 2.5 MEASUREMENT INSTRUMENTS LIST | 7 |
| 3 . CONDUCTED EMISSIONS TEST | 8 |
| 3.1 Conducted Power Line Emission Limit | 8 |
| 3.2 Test Setup | 8 |
| 3.3 Test Procedure | 8 |
| 3.4 Test Result | 8 |
| 4 RADIATED EMISSION TEST | 11 |
| 4.1 Radiation Limit | 11 |
| 4.2 Test Setup | 11 |
| 4.3 Test Procedure | 12 |
| 4.4 Test Result | 12 |
| 5 BAND EDGE | 18 |
| 5.1 Limits | 18 |
| 5.2 Test Procedure | 18 |
| 5.3 Test Result | 18 |
| 6 OCCUPIED BANDWIDTH MEASUREMENT | 20 |
| 6.1 Test Setup | 20 |
| 6.2 Test Procedure | 20 |
| 6.3 Measurement Equipment Used | 20 |
| 6.4 Test Result | 20 |
| 7 ANTENNA REQUIREMENT | 22 |
| 8 PHOTOGRAPH OF TEST | 23 |
| Radiated Emission | 23 |
| Conducted Emission | 24 |



1. TEST SUMMARY

1.1 TEST PROCEDURES AND RESULTS

| DESCRIPTION OF TEST | | RESULT |
|---------------------|--|-----------|
| 15.207 | Conducted Emission | COMPLIANT |
| 15.249&15.209 | Fundamental & Radiated Spurious Emission Measurement | COMPLIANT |
| 15.215 | Bandwidth | COMPLIANT |
| 15.205 | Band Edge Emission | COMPLIANT |
| 15.203 | Antenna Requirement | COMPLIANT |

1.2 TEST FACILITY

Test Firm : Shenzhen HUAKE Testing Technology Co., Ltd.

Address : 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China

1.3 MEASUREMENT UNCERTAINTY

Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty(9kHz-30MHz) = 3.08dB, k=2

Radiated emission expanded uncertainty(30MHz-1000MHz) = 4.42dB, k=2

Radiated emission expanded uncertainty(Above 1GHz) = 4.06dB, k=2



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

| | |
|------------------------|---------------------|
| Equipment | Wi-Fi+BT SoC Module |
| Model Name | BW16 |
| Serial No. | N/A |
| Trade Mark | N/A |
| Model Difference | N/A |
| FCC ID | 2AHMR-BW16 |
| Antenna Type | PCB Antenna |
| Antenna Gain | 2dBi |
| BT Operation frequency | 2402-2480MHz |
| Number of Channels | 40CH |
| Modulation Type | GFSK |
| Battery | N/A |
| Power Source | DC 3.3V |



2.2 Carrier Frequency of Channels

| Channel List | | | | | | | |
|--------------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 0 | 2402 | 10 | 2422 | 20 | 2442 | 30 | 2462 |
| 1 | 2404 | 11 | 2424 | 21 | 2444 | 31 | 2464 |
| 2 | 2406 | 12 | 2426 | 22 | 2446 | 32 | 2466 |
| 3 | 2408 | 13 | 2428 | 23 | 2448 | 33 | 2468 |
| 4 | 2410 | 14 | 2430 | 24 | 2450 | 34 | 2470 |
| 5 | 2412 | 15 | 2432 | 25 | 2452 | 35 | 2472 |
| 6 | 2414 | 16 | 2434 | 26 | 2454 | 36 | 2474 |
| 7 | 2416 | 17 | 2436 | 27 | 2456 | 37 | 2476 |
| 8 | 2418 | 18 | 2438 | 28 | 2458 | 38 | 2478 |
| 9 | 2420 | 19 | 2440 | 29 | 2460 | 39 | 2480 |

2.3 Operation of EUT during testing

Operating Mode

The mode is used: **Transmitting mode**


Low Channel: 2402MHz

Middle Channel: 2440MHz

High Channel: 2480MHz

2.4 DESCRIPTION OF TEST SETUP

Operation of EUT during Conducted testing:





2.5 MEASUREMENT INSTRUMENTS LIST

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|---|-----------------|--------------------------------|------------|---------------|---------------|
| 1. | L.I.S.N. Artificial Mains Network | R&S | ENV216 | HKE-002 | Sep. 28, 2019 | 1 Year |
| 2. | Receiver | R&S | ESCI 7 | HKE-010 | Sep. 28, 2019 | 1 Year |
| 3. | RF automatic control unit | Tonscend | JS0806-2 | HKE-060 | Sep. 28, 2019 | 1 Year |
| 4. | Spectrum analyzer | R&S | FSP40 | HKE-025 | Sep. 28, 2019 | 1 Year |
| 5. | Spectrum analyzer | Agilent | N9020A | HKE-048 | Sep. 28, 2019 | 1 Year |
| 6. | Preamplifier | Schwarzbeck | BBV 9743 | HKE-006 | Sep. 28, 2019 | 1 Year |
| 7. | EMI Test Receiver | Rohde & Schwarz | ESCI 7 | HKE-010 | Sep. 28, 2019 | 1 Year |
| 8. | Bilog Broadband Antenna | Schwarzbeck | VULB9163 | HKE-012 | Sep. 28, 2019 | 1 Year |
| 9. | Loop Antenna | Schwarzbeck | FMZB 1519 B | HKE-014 | Sep. 28, 2019 | 1 Year |
| 10. | Horn Antenna | Schwarzbeck | 9120D | HKE-013 | Sep. 28, 2019 | 1 Year |
| 11. | Pre-amplifier | EMCI | EMC051845 SE | HKE-015 | Sep. 28, 2019 | 1 Year |
| 12. | Pre-amplifier | Agilent | 83051A | HKE-016 | Sep. 28, 2019 | 1 Year |
| 13. | EMI Test Software EZ-EMC | Tonscend | JZOZtheBO T120-B Version | HKE-083 | N/A | N/A |
| 14. | Power Sensor | Agilent | E9300A | HKE-086 | Sep. 28, 2019 | 1 Year |
| 15. | Spectrum analyzer | Agilent | N9020A | HKE-048 | Sep. 28, 2019 | 1 Year |
| 16. | Signal generator | Agilent | N5182A | HKE-029 | Sep. 28, 2019 | 1 Year |
| 17. | Signal Generator | Agilent | 83630A | HKE-028 | Sep. 28, 2019 | 1 Year |
| 18. | Shielded room | Shiel Hong | 4*3*3 | HKE-039 | Sep. 28, 2017 | 3 Year |
| 19. | Hf antenna | Schwarzbeck | LB-180400- KF | HKE-031 | Sep. 28, 2019 | 1 Year |



3. CONDUCTED EMISSIONS TEST

3.1 Conducted Power Line Emission Limit


For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following

| Frequency (MHz) | Maximum RF Line Voltage (dB μ V) | | | |
|-----------------|--------------------------------------|------|---------|--------|
| | CLASS A | | CLASS B | |
| | Q.P. | Ave. | Q.P. | Ave. |
| 0.15 - 0.50 | 79 | 66 | 66-56* | 56-46* |
| 0.50 - 5.00 | 73 | 60 | 56 | 46 |
| 5.00 - 30.0 | 73 | 60 | 60 | 50 |

* Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

3.2 Test Setup



3.3 Test Procedure

- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.


3.4 Test Result

PASS

1. All modes were tested at AC 120V and 240V, only the worst result of AC 120V 60Hz was reported.
2. All modes of Low, Middle, and High channel were tested, only the worst result of Low Channel was reported as below:



Test Specification: Neutral




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|--------------|----------|---------|
| 1 | | 0.1740 | 28.38 | 10.35 | 38.73 | 64.77 | -26.04 | peak | |
| 2 | | 0.2900 | 27.58 | 10.23 | 37.81 | 60.52 | -22.71 | peak | |
| 3 | | 0.5940 | 26.64 | 10.34 | 36.98 | 56.00 | -19.02 | peak | |
| 4 | | 0.9860 | 27.30 | 10.32 | 37.62 | 56.00 | -18.38 | peak | |
| 5 | * | 2.6380 | 31.86 | 10.42 | 42.28 | 56.00 | -13.72 | peak | |
| 6 | | 4.7780 | 30.94 | 10.71 | 41.65 | 56.00 | -14.35 | peak | |

Remark:

Factor = Cable loss + LISN factor, Margin = Limit – Measurement



Test Specification: Line



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|--------------|----------|---------|
| 1 | | 0.1740 | 29.14 | 10.07 | 39.21 | 64.77 | -25.56 | peak | |
| 2 | | 0.2980 | 28.66 | 10.06 | 38.72 | 60.30 | -21.58 | peak | |
| 3 | | 0.8139 | 27.85 | 10.21 | 38.06 | 56.00 | -17.94 | peak | |
| 4 | | 0.9940 | 28.79 | 10.11 | 38.90 | 56.00 | -17.10 | peak | |
| 5 | * | 2.8540 | 34.16 | 10.24 | 44.40 | 56.00 | -11.60 | peak | |
| 6 | | 4.7580 | 33.91 | 10.39 | 44.30 | 56.00 | -11.70 | peak | |

Remark:

Factor = Cable loss + LISN factor, Margin = Limit – Measurement

4 RADIATED EMISSION TEST

4.1 Radiation Limit


For unintentional device, according to § 15.109(a), except for Class B digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequency (MHz) | Distance (Meters) | Radiated (dB μ V/m) | Radiated (μ V/m) |
|-----------------|-------------------|-------------------------|-----------------------|
| 30-88 | 3 | 40 | 100 |
| 88-216 | 3 | 43.5 | 150 |
| 216-960 | 3 | 46 | 200 |
| Above 960 | 3 | 54 | 500 |


For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

4.2 Test Setup


(1) Radiated Emission Test-Up Frequency Below 30MHz



(2) Radiated Emission Test-Up Frequency 30MHz~1GHz



(3) Radiated Emission Test-Up Frequency Above 1GHz



4.3 Test Procedure

1. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The test frequency range from 9KHz to 25GHz per FCC PART 15.33(a).

Note:

For battery operated equipment, the equipment tests shall be performed using a new battery.

4.4 Test Result

PASS


Remark:

1. All the test modes completed for test. The worst case of Radiated Emission is Low channel, the test data of this mode was reported.
2. By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, and test data recorded in this report.
3. Radiated emission test from 9KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9KHz to 30MHz and not recorded in this report.



Below 1GHz Test Results:

Antenna polarity: H




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB/m | Measure- ment dBuV/m | Limit dB/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|---------------------------|----------------------------|---------------|--------------|----------|---------|
| 1 | | 39.4371 | 29.45 | -5.87 | 23.58 | 40.00 | -16.42 | QP | |
| 2 | | 58.4074 | 29.62 | -6.66 | 22.96 | 40.00 | -17.04 | QP | |
| 3 | | 100.2283 | 30.78 | -9.20 | 21.58 | 43.50 | -21.92 | QP | |
| 4 | * | 227.6904 | 41.79 | -7.54 | 34.25 | 46.00 | -11.75 | QP | |
| 5 | | 361.7137 | 29.16 | -3.41 | 25.75 | 46.00 | -20.25 | QP | |
| 6 | | 638.3686 | 26.46 | 2.66 | 29.12 | 46.00 | -16.88 | QP | |

Remark: Factor= Cableloss + Antenna factor - Pre-amplifier; Margin = Measurement – Limit



Antenna polarity: V



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB/m | Measure- ment dBuV/m | Limit dB/m | Margin dB | Detector | Comment |
|-----|-----|--------------|--------------------------|---------------------------|----------------------------|---------------|--------------|----------|---------|
| 1 | * | 32.6340 | 39.77 | -7.14 | 32.63 | 40.00 | -7.37 | QP | |
| 2 | | 36.2539 | 33.58 | -6.46 | 27.12 | 40.00 | -12.88 | QP | |
| 3 | | 60.9174 | 33.48 | -6.93 | 26.55 | 40.00 | -13.45 | QP | |
| 4 | | 97.4557 | 35.19 | -9.55 | 25.64 | 43.50 | -17.86 | QP | |
| 5 | | 229.2930 | 40.42 | -7.42 | 33.00 | 46.00 | -13.00 | QP | |
| 6 | | 642.8612 | 27.58 | 2.76 | 30.34 | 46.00 | -15.66 | QP | |

Remark: Factor= Cableloss + Antenna factor - Pre-amplifier; Margin = Measurement – Limit

Remark:

- (1) Measuring frequencies from 9 KHz to the 1 GHz, radiated emission test from 9KHz to 30MHz was verified, and no any emission was found except system noise floor.
- (2) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (3) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.



Above 1 GHz Test Results:
CH Low (2402MHz)

Horizontal:

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
|-----------|---------------|--------|----------------|----------------|--------|---------------|
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | |
| 2402 | 109.31 | -5.84 | 103.47 | 114 | -10.53 | peak |
| 2402 | 94.81 | -5.84 | 88.97 | 94 | -5.03 | AVG |
| 4804 | 55.34 | -3.64 | 51.70 | 74 | -22.30 | peak |
| 4804 | 49.83 | -3.64 | 46.19 | 54 | -7.81 | AVG |
| 7206 | 56.58 | -0.95 | 55.63 | 74 | -18.37 | peak |
| 7206 | 45.95 | -0.95 | 45.00 | 54 | -9.00 | AVG |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits+9:11

Vertical:

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
|-----------|---------------|--------|----------------|----------------|--------|---------------|
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | |
| 2402 | 110.09 | -5.84 | 104.25 | 114 | -9.75 | peak |
| 2402 | 93.22 | -5.84 | 87.38 | 94 | -6.62 | AVG |
| 4804 | 57.03 | -3.64 | 53.39 | 74 | -20.61 | peak |
| 4804 | 49.05 | -3.64 | 45.41 | 54 | -8.59 | AVG |
| 7206 | 58.16 | -0.95 | 57.21 | 74 | -16.79 | peak |
| 7206 | 46.09 | -0.95 | 45.14 | 54 | -8.86 | AVG |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits



CH Middle (2440MHz)

Horizontal:

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
|-----------|---------------|--------|----------------|----------------|--------|---------------|
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | |
| 2440 | 108.16 | -5.71 | 102.45 | 114 | -11.55 | peak |
| 2440 | 93.50 | -5.71 | 87.79 | 94 | -6.21 | AVG |
| 4880 | 56.33 | -3.51 | 52.82 | 74 | -21.18 | peak |
| 4880 | 50.46 | -3.51 | 46.95 | 54 | -7.05 | AVG |
| 7320 | 58.66 | -0.82 | 57.84 | 74 | -16.16 | peak |
| 7320 | 47.17 | -0.82 | 46.35 | 54 | -7.65 | AVG |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits

Vertical:

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
|-----------|---------------|--------|----------------|----------------|--------|---------------|
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | |
| 2440 | 110.57 | -5.71 | 104.86 | 114 | -9.14 | peak |
| 2440 | 94.94 | -5.71 | 89.23 | 94 | -4.77 | AVG |
| 4880 | 58.51 | -3.51 | 55.00 | 74 | -19.00 | peak |
| 4880 | 47.16 | -3.51 | 43.65 | 54 | -10.35 | AVG |
| 7320 | 59.08 | -0.82 | 58.26 | 74 | -15.74 | peak |
| 7320 | 47.30 | -0.82 | 46.48 | 54 | -7.52 | AVG |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits



CH High (2480MHz)

Horizontal:

| Frequency (MHz) | Meter Reading (dB μ V) | Factor (dB) | Emission Level (dB μ V/m) | Limits (dB μ V/m) | Margin (dB) | Detector Type |
|--------------------|-------------------------------|----------------|----------------------------------|--------------------------|----------------|------------------|
| 2480 | 110.47 | -5.65 | 104.82 | 114 | -9.18 | peak |
| 2480 | 91.65 | -5.65 | 86.00 | 94 | -8.00 | AVG |
| 4960 | 55.71 | -3.43 | 52.28 | 74 | -21.72 | peak |
| 4960 | 45.05 | -3.43 | 41.62 | 54 | -12.38 | AVG |
| 7440 | 58.11 | -0.75 | 57.36 | 74 | -16.64 | peak |
| 7440 | 46.36 | -0.75 | 45.61 | 54 | -8.39 | AVG |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits

Vertical:

| Frequency (MHz) | Meter Reading (dB μ V) | Factor (dB) | Emission Level (dB μ V/m) | Limits (dB μ V/m) | Margin (dB) | Detector Type |
|--------------------|-------------------------------|----------------|----------------------------------|--------------------------|----------------|------------------|
| 2480 | 111.84 | -5.65 | 106.19 | 114 | -7.81 | peak |
| 2480 | 93.49 | -5.65 | 87.84 | 94 | -6.16 | AVG |
| 4960 | 57.11 | -3.43 | 53.68 | 74 | -20.32 | peak |
| 4960 | 48.20 | -3.43 | 44.77 | 54 | -9.23 | AVG |
| 7440 | 60.13 | -0.75 | 59.38 | 74 | -14.62 | peak |
| 7440 | 48.42 | -0.75 | 47.67 | 54 | -6.33 | AVG |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits

Remark :

- (1) Measuring frequencies from 1 GHz to the 25 GHz.
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.
- (7) RBW > 20dB BW, VBW>=3XRBW, PK detector for PK value, RMS detector for AV value
- (8) All modes of operation were investigated and the worst-case emissions are reported.



5 BAND EDGE

5.1 Limits

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. RBW 1MHz VBW 3MHz PK detector is for PK value, RBW 1MHz VBW 10Hz PK detector is for AV value. The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW to 100 KHz and VBW to 300 KHz, to measure the conducted peak band edge.

5.3 Test Result

PASS

Radiated Band Edge Test:

Operation Mode: TX CH Low (2402MHz)

Horizontal (Worst case)

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Detector Type |
|--------------------|----------------------------|----------------|----------------------------|--------------------|----------------|------------------|
| 2310 | 53.43 | -5.81 | 47.62 | 74 | -26.38 | peak |
| 2310 | / | -5.81 | / | 54 | / | AVG |
| 2390 | 52.98 | -5.84 | #VALUE! | 74 | #VALUE! | peak |
| 2390 | / | -5.84 | / | 54 | / | AVG |
| 2400 | 54.23 | -5.84 | 48.39 | 74 | -25.61 | peak |
| 2400 | / | -5.84 | / | 54 | / | AVG |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits

Vertical:

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Detector Type |
|--------------------|----------------------------|----------------|----------------------------|--------------------|----------------|------------------|
| 2310 | 52.37 | -5.81 | 46.56 | 74 | -27.44 | peak |
| 2310 | / | -5.81 | / | 54 | / | AVG |
| 2390 | 51.32 | -5.84 | 45.48 | 74 | -28.52 | peak |
| 2390 | / | -5.84 | / | 54 | / | AVG |
| 2400 | 55.53 | -5.84 | 49.69 | 74 | -24.31 | peak |
| 2400 | / | -5.84 | / | 54 | / | AVG |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits



Operation Mode: TX CH High (2480MHz)

Horizontal (Worst case)

| Frequency | Reading Result | Factor | Emission Level | Limits | Margin | Detector Type |
|-----------|----------------|--------|----------------|----------|--------|---------------|
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | |
| 2483.50 | 55.42 | -5.65 | 49.77 | 74 | -24.23 | peak |
| 2483.50 | / | -5.65 | / | 54 | / | AVG |
| 2500.00 | 58.46 | -5.65 | 52.81 | 74 | -21.19 | peak |
| 2500.00 | / | -5.65 | / | 54 | / | AVG |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits

Vertical:

| Frequency | Reading Result | Factor | Emission Level | Limits | Margin | Detector Type |
|-----------|----------------|--------|----------------|----------|--------|---------------|
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | |
| 2483.50 | 54.53 | -5.81 | 48.72 | 74.00 | -25.28 | peak |
| 2483.50 | / | -5.81 | / | 54.00 | / | AVG |
| 2500.00 | 57.49 | -6.06 | 51.43 | 74.00 | -22.57 | peak |
| 2500.00 | / | -6.06 | / | 54 | / | AVG |

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits

Remark: All the other emissions not reported were too low to read and deemed to comply with FCC limit.



6 OCCUPIED BANDWIDTH MEASUREMENT

6.1 Test Setup

Same as Radiated Emission Measurement

6.2 Test Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set EUT as normal operation.
3. Based on ANSI C63.10 section 6.9.2: RBW= 100KHz. VBW= 300KHz, Span=2MHz.
4. The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector.

6.3 Measurement Equipment Used


Same as Radiated Emission Measurement

6.4 Test Result

PASS


| Frequency | 20dB Bandwidth (MHz) | Result |
|-----------|----------------------|-------------|
| 2402 MHz | 1.199 | PASS |
| 2440 MHz | 1.201 | PASS |
| 2480 MHz | 1.202 | PASS |

CH: 2402MHz






CH: 2440MHz



CH: 2480MHz



7 ANTENNA REQUIREMENT


Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.249, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Antenna Connected Construction



The antenna used in this product is PCB Antenna, the directional gains of antenna used for transmitting is 2dBi.

BT ANTENNA



8 PHOTOGRAPH OF TEST

Radiated Emission





Conducted Emission



End of Report