

TEST REPORT

Applicant Name : Bytech NY Inc.
Address : 2585 West 13th Street Brooklyn NY 11223 USA
Report Number: SZ3220510-14849E-RF
FCC ID: 2AHN6-MSWS104

Test Standard (s)
FCC PART 15.249


Sample Description

Product Type: 2.4G Wireless Mouse
Model No.: BY-MS-WS-104-AC, BY-MS-WS-104-BK, BY-MS-WS-104-WT, BY-MS-WS-104-BL, BY-MS-WS-104-PU
Date Received: 2022-05-10
Date of Test: 2022-05-24 to 2022-08-05
Report Date: 2022-08-05

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:



Audy Yu
EMC Engineer

Approved By:



Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".
Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION.....3

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)3

 OBJECTIVE3

 TEST METHODOLOGY3

 MEASUREMENT UNCERTAINTY4

 TEST FACILITY4

SYSTEM TEST CONFIGURATION.....5

 JUSTIFICATION5

 EUT EXERCISE SOFTWARE5

 EQUIPMENT MODIFICATIONS5

 SUPPORT EQUIPMENT LIST AND DETAILS5

 SUPPORT CABLE DESCRIPTIONS5

 BLOCK DIAGRAM OF TEST SETUP6

SUMMARY OF TEST RESULTS7

TEST EQUIPMENT LIST8

FCC §1.1307 (B) – RF EXPOSURE.....9

 APPLICABLE STANDARD9

 TEST RESULT9

FCC §15.203 - ANTENNA REQUIREMENT.....10

 APPLICABLE STANDARD10

 ANTENNA CONNECTOR CONSTRUCTION10

FCC §15.205, §15.209 & §15.249(D) - RADIATED EMISSIONS.....11

 APPLICABLE STANDARD11

 TEST EQUIPMENT SETUP11

 EUT SETUP12

 TEST PROCEDURE13

 CORRECTED AMPLITUDE & MARGIN CALCULATION13

 TEST RESULTS SUMMARY13

 TEST DATA13

FCC §15.215(C) - 20DB EMISSION BANDWIDTH19

 APPLICABLE STANDARD19

 TEST PROCEDURE19

 TEST DATA19

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	2.4G Wireless Mouse
Tested Model	BY-MS-WS-104-WT
Multiple Model	BY-MS-WS-104-BK, BY-MS-WS-104-AC, BY-MS-WS-104-BL, BY-MS-WS-104-PU
UPC Number	80511208925 80511208932 80511208918 80511208949
SKU Number	6525052
Lot Number	BY051622
Model difference	Please refer to DOS letter.
Frequency Range	2405~2478MHz
Maximum E-Field Strength (Peak)	82.41dBuV/m@3m
Modulation Technique	GFSK
Antenna Specification	internal On-board antenna: 0dBi (It is provided by the applicant)
Voltage Range	DC 1.5V from battery
Sample serial number	SZ3220510-14849E-RF-S1
Sample/EUT Status	Good condition

Objective

This type approval report is in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliant Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189.

Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing by manufacturer.

Frequency list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405	7	2451	13	2469
2	2408	8	2454	14	2472
3	2411	9	2457	15	2475
4	2414	10	2460	16	2478
5	2417	11	2463	/	/
6	2448	12	2466	/	/

Channel 1, Channel 7 and Channel 16 were selected for testing.

EUT Exercise Software

Test in the engineering mode which switch channel by button and power level is default*.

Equipment Modifications

No modifications were made to the unit tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

Support Cable Descriptions

Cable Description	Length (m)	From/Port	To
/	/	/	/

Block Diagram of Test Setup

For Radiated Emmission



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b)	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	Conduction Emissions	Not Applicable
15.205, §15.209, §15.249(d)	Radiated Emissions& Outside of Band Emission	Compliant
§15.215 (c)	20dB Bandwidth	Compliant

Note: The device is powered by battery only.

Test Equipment List

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Rohde & Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2021/11/11	2022/11/10
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Wainwright	High Pass Filter	WHKX3.6/18G-10SS	5	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
Radiated Emission Test Software: e3 19821b (V9)					
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2021/12/13	2022/12/12
WEINSCHL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 (b) – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.2 – 1-mW test Exemption:

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

Test Result

For worst case:

Mode	Frequency	Maximum Tune-up Power		1-mW test Exemption
	(MHz)	(dBm)	(mW)	
SRD	2405-2478	-12.0	0.063	Yes

Note 1: Test maximum EIRP=82.41(dBμV/m) - 95.2= -12.79dBm

Note 2: The tune-up power was -12.0dBm, which declared by the applicant.

Result: Compliant.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal On-board antenna which was permanently attached and the antenna gain is 0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.

FCC §15.205, §15.209 & §15.249(d) - RADIATED EMISSIONS

Applicable Standard

As per FCC §15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC §15.249 (c), Field strength limits are specified at a distance of 3 meters.

As per FCC §15.249 (d), Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Test Equipment Setup

The spectrum analyzer or receiver is set as:

Below 1000MHz:

$$\text{RBW} = 100 \text{ kHz} / \text{VBW} = 300 \text{ kHz} / \text{Sweep} = \text{Auto}$$


Above 1000MHz:

$$\begin{aligned} \text{Peak: RBW} &= 1\text{MHz} / \text{VBW} = 1\text{MHz} / \text{Sweep} = \text{Auto} \\ \text{Average: RBW} &= 1\text{MHz} / \text{VBW} = 10\text{Hz} / \text{Sweep} = \text{Auto} \end{aligned}$$


If the maximized peak measured value complies with the limit, then it is unnecessary to perform QP/Average measurement.

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission and out of band emission tests were performed in the 3meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane for below 1GHz or 1.5 meter for above 1GHz, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

Corrected Amplitude & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Results Summary

According to the EUT complied with the FCC Part 15.205, 15.209 & §15.249

Test Data

Environmental Conditions

Temperature:	25-27°C
Relative Humidity:	60%
ATM Pressure:	101.1-101.2 kPa


The testing was performed by Level Li on 2022-05-24 for Below 1G and on 2022-07-19 for Above 1G.

Test Mode: Transmitting

30MHz-1GHz: (Worst case)

Low Channel


Horizontal



Site : chamber
 Condition: 3m HORIZONTAL
 Job No. : SZN3220510-14849E-RF
 Test Mode: Transmitting

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	36.064	-11.18	29.33	18.15	40.00	-21.85	Peak
2	45.078	-9.94	28.33	18.39	40.00	-21.61	Peak
3	100.669	-11.72	27.94	16.22	43.50	-27.28	Peak
4	349.863	-7.30	30.53	23.23	46.00	-22.77	Peak
5	458.511	-5.44	33.20	27.76	46.00	-18.24	Peak
6	785.438	-0.04	28.11	28.07	46.00	-17.93	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : SZN3220510-14849E-RF
 Test Mode: Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	31.399	-12.24	38.25	26.01	40.00	-13.99	Peak
2	50.431	-9.92	32.16	22.24	40.00	-17.76	Peak
3	100.097	-11.79	28.61	16.82	43.50	-26.68	Peak
4	148.376	-15.36	33.62	18.26	43.50	-25.24	Peak
5	455.906	-5.49	29.12	23.63	46.00	-22.37	Peak
6	839.550	0.26	28.79	29.05	46.00	-16.95	Peak

Above 1 GHz:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	Reading (dBuV)	PK/AV		Height (m)	Polar (H/V)				
Low Channel									
2310	50.67	PK	28	1.8	H	-7.23	43.44	74	-30.56
2310	44.76	PK	28	1.8	V	-7.23	37.53	74	-36.47
2372	65.73	PK	287	1.6	H	-7.2	58.53	74	-15.47
2372	56.83	AV	287	1.6	H	-7.2	49.63	54	-4.37
2390	63.19	PK	80	1.5	H	-7.21	55.98	74	-18.02
2390	54.24	AV	80	1.5	H	-7.21	47.03	54	-6.97
2390	52.36	PK	15	1.7	V	-7.21	45.15	74	-28.85
2400	51.75	PK	28	1.8	H	-7.23	44.52	74	-29.48
2400	46.28	PK	287	1.6	V	-7.23	39.05	74	-34.95
2405	89.63	PK	215	2.1	H	-7.22	82.41	114	-31.59
2405	79.32	PK	215	2.1	V	-7.22	72.1	114	-41.9
4810	62.51	PK	204	1.3	H	-3.52	58.99	74	-15.01
4810	54.5	AV	204	1.3	H	-3.52	50.98	54	-3.02
4810	54	PK	125	2	V	-3.52	50.48	74	-23.52
Middle Channel									
2451	88.97	PK	251	1.2	H	-7.24	81.73	114	-32.27
2451	78.66	PK	353	1.2	V	-7.24	71.42	114	-42.58
4902	60.33	PK	80	1.8	H	-3.27	57.06	74	-16.94
4902	52.03	AV	80	1.8	H	-3.27	48.76	54	-5.24
4902	52.13	PK	338	2	V	-3.27	48.86	74	-25.14
High Channel									
2483.5	52.33	PK	304	1.8	H	-7.2	45.13	74	-28.87
2483.5	47.52	PK	248	1.7	V	-7.2	40.32	74	-33.68
2500	49.62	PK	304	1.8	H	-7.18	42.44	74	-31.56
2500	48.08	PK	248	1.7	V	-7.18	40.9	74	-33.1
2478	88.96	PK	113	1.3	H	-7.2	81.76	114	-32.24
2478	79.29	PK	306	1.6	V	-7.2	72.09	114	-41.91
4956	58.86	PK	113	1.3	H	-3.02	55.84	74	-18.16
4956	49.54	AV	113	1.3	H	-3.02	46.52	54	-7.48
4956	52.51	PK	326	1.1	V	-3.02	49.49	74	-24.51

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading

Margin = Absolute Level (Corrected Amplitude) – Limit


The other spurious emission which is in the noise floor level was not recorded.

For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.


Pre-scan plots:

1-18GHz: Low Channel

Horizontal




Vertical




18-25GHz: Low Channel

Horizontal



Vertical



FCC §15.215(c) - 20dB EMISSION BANDWIDTH

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that indicated 20dB bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	26°C
Relative Humidity:	56%
ATM Pressure:	101.0 kPa


The testing was performed by Glenn Jiang on 2022-08-05.

Test Mode: Transmitting

Please refer to the following table and plots.


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
Low	2405	2.547
Middle	2451	2.583
High	2478	2.576

Low Channel




Date: 5.AUG.2022 14:43:48

Middle Channel



Date: 5.AUG.2022 14:46:48

High Channel



Date: 5.AUG.2022 14:49:17

**** END OF REPORT ****