





BUREAU
VERITAS

Curtis-Straus LLC, a wholly owned subsidiary of BV CPS

Test Report

Report No	ER2500-9
Client	Harman International Industries, Inc. Mark Bowman
Address	30001 Cabot Drive Novi, MI 48377
Phone	248-254-7751
Items tested	G31 BASE
FCC ID	2AHPN-BE2831
IC	6434C-BE2831
FRN	0026894154
Equipment Type	Part 15 Spread Spectrum Transmitter
Equipment Code	DSS
FCC/IC Rule Parts	CFR Title 47 FCC Part 15.247, ISED Canada RSS-247 Issue 2
Test Dates	September 22 - October 17, 2017
Results	As detailed within this report
Prepared by	 Zachary Johnson – Test Engineer
Authorized by	 Yunus Faziloglu – Sr. EMC Engineer
Issue Date	<u>10/30/2017</u>
Conditions of Issue	This Test Report is issued subject to the conditions stated in the 'Conditions of Testing' section on page 15 of this report.

Contents

Contents.....	2
Summary.....	3
Test Methodology.....	4
Product Tested - Configuration Documentation	5
Statement of Conformity.....	6
Test Results	7
Radiated Spurious Emissions	7
AC Line Conducted Emissions	13
Measurement Uncertainty.....	14
Conditions Of Testing	15
Appendix A:.....	17

Report REV Sep-08-2017 - YF



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 2 of 48

Summary

This test report supports an application for certification of a transmitter operating pursuant to:
CFR Title 47 FCC Part 15.247, ISED Canada RSS-247 Issue 2

The product is the G31 BASE. It is a frequency hopping spread spectrum transmitter that operates in the 2402 – 2480MHz frequency range. This report covers the Bluetooth portion of the device.

Antenna Type: Switching PCB trace antenna

Gain: Maximum 1.18dBi in 2.4GHz - 2.5GHz range

We found that the product met the above requirements without modification.

Test samples were received in good condition.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Test Methodology

All testing was performed according to the following rules/procedures/documents; CFR 47 Part 15.247, RSS-247 Issue 2, RSS-Gen Issue 4 and ANSI C63.10-2013.

Radiated emissions were maximized by measuring the device in normal operating position, as well as varying the test antenna's height and polarity.

EUT operating voltage is 11-16V DC

The following bandwidths were used during radiated spurious and AC line conducted emissions testing.

Frequency	RBW	VBW
0.15-30MHz	9kHz	30kHz
30-1000MHz	120kHz	1MHz
1-25GHz	1MHz	3MHz



Product Tested - Configuration Documentation

EUT Configuration										
Work Order:	R2500									
Company:	Harman International Industries, Incorporated									
Company Address:	30001 Cabot Drive									
	Novi, MI, 48377									
Contact:	Mark Bowman									
EUT:	MN	G31 BASE			PN	--			SN	--
EUT Description:	Car Stereo System									
EUT Components	MN							SN		
Back up camera	--							--		
FM/AM antenna	--							--		
Support Equipment	MN							SN		
13.5Vdc Power Supply	--							--		
CS Supplied Laptop.	--							--		
USB to Ethernet Converter	--							--		
Port Label	Port Type	# ports	# populated	cable type	shielded	ferrites	length (m)	in/out	under test	comment
DC main	Power DC	2	2	Power DC	No	No	1.2	in	yes	
Audio		1	1		Yes	No	1.2	in	yes	
USB	USB	3	1	USB	Yes	No	1	in	yes	
Dab/XM Radio		1	1	Coaxial	Yes	No	1.2	in	yes	
FM/AM antenna	-	1	1	-	Yes	No	0.4	in	yes	
Back up camera	-	1	1	-	Yes	No	0.3	in	yes	
Next Gen port	-	1	0	-				in	no	
Software Operating Mode Description:										
EUT will be operating in a test mode for Immunity tests, RX for non intentional REMI, and Constant TX internal mode for Spurious.										
Performance Criteria:										
EUT will connect to CMW and preform less than 10% PER during test.BT- EUT will connect to tablet or CMW over bluetooth and stay connected at appropriate distance.										



Statement of Conformity

RSS-GEN	RSP-100	RSS 247	Part 15	Comments
6.3			15.15(b)	There are no controls accessible to the user that varies the output power to operate in violation of the regulatory requirements.
	3.1		15.19	The label is shown in the label exhibit.
	4		15.21	Information to the user is shown in the instruction manual exhibit.
			15.27	No special accessories are required for compliance.
3, 6.1			15.31	The EUT was tested in accordance with the measurement standards in this section.
6.13			15.33	Frequency range was investigated according to this section, unless noted in specific rule section under which the equipment operates.
8.1			15.35	The EUT emissions were measured using the measurement detector and bandwidth specified in this section, unless noted in specific rule section under which the equipment operates.
8.3			15.203	EUT employs single switching PCB trace antenna with maximum 1.18dBi gain.
8.10			15.205 15.209	The fundamental is not in a Restricted band and the spurious and harmonic emissions in the Restricted bands comply with the general emission limits of 15.209 or RSS-Gen as applicable
8.8			15.207	N/A. Unit is powered by a vehicle battery only.

Refer to Appendix A of this report for antenna port conducted measurements.



Test Results

Radiated Spurious Emissions

LIMITS

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

[15.247(d)]

Device was measured in normal operating position.

MEASUREMENTS / RESULTS

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 30-1000MHz Horizontal Data Operator: CCH Notes: FCC B Bluetooth mode Ch39. filter 2300-2500MHz. Table hieght0							Work Order - R2500 EUT Power Input - 13.8V DC Test Site - CH1 Conditions - 25.1°C; 56%RH; 1007mBar Witnessed by - FCC B Spurious						
Frequency (MHz)	Raw QP Reading (dB μ V)	Correction Factor (dB/m)	Adjusted QP Amplitude (dB μ V/m)	Lim1: FCC_pt15_1 09_Class_B (dB μ V/m)	Margin to Lim1 (dB)	Test Results Lim1 (Pass/Fail)	Worst Margin Lim1 (dB)	Lim2: FCC_pt15_1 09_Class_B (dB μ V/m)	Margin to Lim2 (dB)	Test Results Lim2 (Pass/Fail)	Worst Margin Lim2 (dB)	Antenna Height (cm)	EUT Azimuth (degrees)
30.656	19.3	-4.5	14.9	40	-25.1	PASS		40	-25.1	PASS		129	160
197.851	31.3	-12.6	18.6	43.5	-24.9	PASS		43.5	-24.9	PASS		136	115
486.384	26	-6	20	46	-26	PASS		46	-26	PASS		193	104
683.711	24.6	-3.3	21.3	46	-24.7	PASS		46	-24.7	PASS		100	93
767.23	29.3	-1.9	27.4	46	-18.6	PASS	-18.6	46	-18.6	PASS	-18.6	114	203
906.932	21.4	-1.1	20.3	46	-25.7	PASS		46	-25.7	PASS		175	187

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 30-1000MHz Vertical Data Operator: CCH Notes: FCC B Bluetooth mode Ch39. filter 2300-2500MHz. Table hieght0							Work Order - R2500 EUT Power Input - 13.8V DC Test Site - CH1 Conditions - 25.1°C; 56%RH; 1007mBar Witnessed by - FCC B Spurious						
Frequency (MHz)	Raw QP Reading (dB μ V)	Correction Factor (dB/m)	Adjusted QP Amplitude (dB μ V/m)	Lim1: FCC_pt15_1 09_Class_B (dB μ V/m)	Margin to Lim1 (dB)	Test Results Lim1 (Pass/Fail)	Worst Margin Lim1 (dB)	Lim2: FCC_pt15_1 09_Class_B (dB μ V/m)	Margin to Lim2 (dB)	Test Results Lim2 (Pass/Fail)	Worst Margin Lim2 (dB)	Antenna Height (cm)	EUT Azimuth (degrees)
382.498	36.5	-8.8	27.7	46	-18.3	PASS		46	-18.3	PASS		101	121
384.92	37.2	-8.7	28.5	46	-17.5	PASS	-17.5	46	-17.5	PASS	-17.5	100	133
387.672	36.4	-8.7	27.7	46	-18.3	PASS		46	-18.3	PASS		102	123
389.855	34	-8.7	25.3	46	-20.7	PASS		46	-20.7	PASS		116	115
435.158	31.7	-7.4	24.3	46	-21.7	PASS		46	-21.7	PASS		125	44
437.122	30.6	-7.2	23.4	46	-22.7	PASS		46	-22.7	PASS		115	70

30-1000MHz Mid Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 1-6GHz Horizontal Data Operator: CCH Notes: FCC B Bluetooth mode Ch0. filter 2300-2500MHz.								Work Order - R2500 EUT Power Input - 13.8V DC Test Site - CH1 Conditions - 25.1°C; 56%RH; 1007mBar Witnessed by - FCC B Spurious 0							
--	--	--	--	--	--	--	--	---	--	--	--	--	--	--	--

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_1 09_ClassB_Peak (dB μ V/m)	Peak (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	Av Lim: FCC_pt15_1 09_ClassB_AVG (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Average Margin (dB)	Antenna Height (cm)	EUT Azimuth (degrees)
2801.8	33.5	25.6	11.2	44.7	74	-29.3	PASS		36.7	54	-17.2	PASS		100	216
4248.5	33.2	23.8	11.1	44.3	74	-29.7	PASS		34.9	54	-19.1	PASS		175	302
4826	33	23.5	12.8	45.9	74	-28.1	PASS		36.3	54	-17.7	PASS		297	81
4857	34.1	23.4	13.1	47.1	74	-26.9	PASS		36.5	54	-17.5	PASS		294	284
4953.8	32.9	23.8	13.5	46.4	74	-27.6	PASS		37.3	54	-16.7	PASS		275	275
5768.4	31.7	24.1	15.8	47.4	74	-26.6	PASS	-26.6	39.9	54	-14.1	PASS	-14.1	295	334

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 1-6GHz Vertical Data Operator: CCH Notes: FCC B Bluetooth mode Ch0. filter 2300-2500MHz.								Work Order - R2500 EUT Power Input - 13.8V DC Test Site - CH1 Conditions - 25.1°C; 56%RH; 1007mBar Witnessed by - FCC B Spurious 0							
--	--	--	--	--	--	--	--	---	--	--	--	--	--	--	--

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_1 09_ClassB_Peak (dB μ V/m)	Peak (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	Av Lim: FCC_pt15_1 09_ClassB_AVG (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Avg Margin (dB)	Antenna Height (cm)	EUT Azimuth (degrees)
4810.9	32.6	23.6	12.7	45.3	74	-28.7	PASS		36.3	54	-17.7	PASS		193	276
4855.9	32.6	23.6	13.1	45.6	74	-28.3	PASS		36.6	54	-17.4	PASS		225	256
4884.7	34	23.6	13.3	47.2	74	-26.7	PASS	-26.7	36.9	54	-17.1	PASS		275	194
4898.7	33.3	23.6	13.4	46.7	74	-27.3	PASS		37	54	-17	PASS		284	88
4932	32.1	23.8	13.4	45.5	74	-28.5	PASS		37.2	54	-16.7	PASS	-16.7	117	209
4955.2	31.8	23.7	13.5	45.3	74	-28.7	PASS		37.2	54	-16.7	PASS		275	283

1-6GHz Low Channel

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 1-6GHz Horizontal Data Operator: CCH Notes: FCC B Bluetooth mode Ch39. filter 2300-2500MHz.								Work Order - R2500 EUT Power Input - 13.8V DC Test Site - CH1 Conditions - 25.1°C; 56%RH; 1007mBar Witnessed by - FCC B Spurious 0							
---	--	--	--	--	--	--	--	---	--	--	--	--	--	--	--

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	Pk Lim: FCC_pt15_1 09_ClassB_Peak (dB μ V/m)	Peak (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	Av Lim: FCC_pt15_1 09_ClassB_AVG (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Avg Margin (dB)	Antenna Height (cm)	EUT Azimuth (degrees)
4818	33.9	23.5	12.8	46.7	74	-27.3	PASS		36.3	54	-17.7	PASS		290	28
4827	31.2	23.5	12.9	44	74	-30	PASS		36.3	54	-17.6	PASS		275	145
4874	32.3	23.4	13.2	45.5	74	-28.5	PASS		36.6	54	-17.4	PASS		204	188
4911.9	32.5	23.6	13.4	45.9	74	-28.1	PASS		37	54	-17	PASS		109	334
4947.4	32.5	23.7	13.5	46	74	-28	PASS		37.2	54	-16.8	PASS		125	62
5928.8	33	24.1	15.6	48.7	74	-25.3	PASS	-25.3	39.7	54	-14.3	PASS	-14.3	225	327



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 1-6GHz Vertical Data Operator: CCH Notes: FCC B Bluetooth mode Ch39. filter 2300-2500MHz.								Work Order - R2500 EUT Power Input - 13.8V DC Test Site - CH1 Conditions - 25.1°C; 56%RH; 1007mBar Witnessed by - FCC B Spurious 0							
---	--	--	--	--	--	--	--	---	--	--	--	--	--	--	--

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	PK LIM. FCC_pt15_1_09_ClassB_Peak (dB μ V/m)	Peak (dB)	Peak Margin (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	AV LIM. FCC_pt15_1_09_ClassB_AVG (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Avg Margin (dB)	Antenna Height (cm)	EUT Azimuth (degrees)
4819.4	32.6	23.7	12.8	45.4	74	-28.6	PASS		36.5	54	-17.5	PASS		275	138	
4874.3	31.3	23.4	13.2	44.4	74	-29.5	PASS		36.6	54	-17.3	PASS		224	142	
4896.1	32.2	23.6	13.3	45.5	74	-28.5	PASS		36.9	54	-17.1	PASS		300	35	
4930.3	31.6	23.7	13.4	45.1	74	-28.9	PASS		37.2	54	-16.8	PASS		288	208	
4959.2	33.1	23.8	13.5	46.6	74	-27.3	PASS		37.3	54	-16.7	PASS		292	102	
5190.6	33	24	14.5	47.5	74	-26.4	PASS	-26.4	38.5	54	-15.4	PASS	-15.4	218	181	

1-6GHz Mid Channel

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 1-6GHz Horizontal Data Operator: CCH Notes: FCC B Bluetooth mode Ch78. filter 2300-2500MHz								Work Order - R2500 EUT Power Input - 13.8V DC Test Site - CH1 Conditions - 25.1°C; 56%RH; 1007mBar Witnessed by - FCC B Spurious 0							
--	--	--	--	--	--	--	--	---	--	--	--	--	--	--	--

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	PK LIM. ETSI_EN_30_0_328_TX_s_purious (dB μ V/m)	Peak (dB)	Peak Margin (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	AV LIM. ETSI_EN_30_0_328_TX_s_purious (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Average Margin (dB)	Antenna Height (cm)	EUT Azimuth (degrees)
2167.5	35	25.5	7.7	42.7	65.2	-22.5	PASS		33.2	65.2	-32	PASS		274	7	
2444.9	35.4	25.8	-95	-59.7	65.2	-124.9	PASS		-69.3	65.2	-134.5	PASS		175	0	
2803.1	35.8	25.7	11.1	46.9	65.2	-18.3	PASS		36.9	65.2	-28.3	PASS		106	246	
4960.5	34.1	27.5	13.5	47.6	65.2	-17.6	PASS		41	65.2	-24.2	PASS	-24.2	203	96	
5689.1	34.8	25	15.9	50.7	65.2	-14.5	PASS	-14.5	40.9	65.2	-24.3	PASS		125	223	

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance 1-6GHz Vertical Data Operator: CCH Notes: FCC B Bluetooth mode Ch78. filter 2300-2500MHz								Work Order - R2500 EUT Power Input - 13.8V DC Test Site - CH1 Conditions - 25.1°C; 56%RH; 1007mBar Witnessed by - FCC B Spurious 0							
--	--	--	--	--	--	--	--	---	--	--	--	--	--	--	--

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	PK LIM. ETSI_EN_30_0_328_TX_s_purious (dB μ V/m)	Peak (dB)	Peak Margin (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	AV LIM. ETSI_EN_30_0_328_TX_s_purious (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Avg Margin (dB)	Antenna Height (cm)	EUT Azimuth (degrees)
2182.7	34.3	25.5	7.8	42.1	65.2	-23.1	PASS		33.3	65.2	-31.9	PASS		175	28	
2807.7	34.7	25.7	10.9	45.6	65.2	-19.6	PASS		36.7	65.2	-28.5	PASS		113	15	
4960.5	42.4	30	13.5	56	65.2	-9.2	PASS	-9.2	43.5	65.2	-21.7	PASS	-21.7	175	232	
5845.9	34.8	24.2	15.6	50.4	65.2	-14.8	PASS		39.8	65.2	-25.4	PASS		189	146	

1-6GHz High Channel



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 1m Distance 6-18GHz Horizontal Data Operator: CCH Notes: FCC B Bluetooth mode Ch39. filter 2300-2500MHz.								Work Order - R2500 EUT Power Input - 13.8V DC Test Site - CH1 Conditions - 25.1°C; 56%RH; 1007mBar Witnessed by - FCC B Spurious 0							
--	--	--	--	--	--	--	--	---	--	--	--	--	--	--	--

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	PK CMM. FCC_pt15_1_09_ClassB_Peak (dB μ V/m)	Peak Margin (dB)	Peak Test Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	AV CMM. FCC_pt15_1_09_ClassB_AVG (dB μ V/m)	Avg Margin (dB)	Avg Test Results (Pass/Fail)	Worst Avg Margin (dB)	Antenna Height (cm)	EUT Azimuth (degrees)
7559.5	28.7	19.1	22	50.6	83.5	-32.9	PASS		41.1	63.5	-22.4	PASS		163	0
14190.8	29	20.1	29.7	58.6	83.5	-24.9	PASS		49.8	63.5	-13.7	PASS		150	150
17860.5	28.9	20.9	36.4	65.3	83.5	-18.2	PASS	-18.2	57.3	63.5	-6.2	PASS	-6.2	100	256

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 1m Distance 6-18GHz Vertical Data Operator: CCH Notes: FCC B Bluetooth mode Ch39. filter 2300-2500MHz.								Work Order - R2500 EUT Power Input - 13.8V DC Test Site - CH1 Conditions - 25.1°C; 56%RH; 1007mBar Witnessed by - FCC B Spurious 0							
--	--	--	--	--	--	--	--	---	--	--	--	--	--	--	--

Frequency (MHz)	Raw Peak Reading (dB μ V)	Raw Avg Reading (dB μ V)	Correction Factor (dB/m)	Adjusted Peak Amplitude (dB μ V/m)	PK CMM. FCC_pt15_1_09_ClassB_Peak (dB μ V/m)	Peak Margin (dB)	Peak Results (Pass/Fail)	Worst Peak Margin (dB)	Adjusted Avg Amplitude (dB μ V/m)	AV CMM. FCC_pt15_1_09_ClassB_AVG (dB μ V/m)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Avg Margin (dB)	Antenna Height (cm)	EUT Azimuth (degrees)
7614.6	29.8	19.2	22	51.8	83.5	-31.7	PASS		41.2	63.5	-22.3	PASS		100	1
9300.3	30	20.6	20.6	50.6	83.5	-32.9	PASS		41.2	63.5	-22.3	PASS		200	297
14201.4	30.4	20	29.6	60	83.5	-23.5	PASS		49.6	63.5	-13.9	PASS		200	326
17667.3	31.7	20.8	37.6	69.3	83.5	-14.2	PASS	-14.2	58.4	63.5	-5.1	PASS	-5.1	100	41

6-18GHz Mid Channel

Rev. 10/22/2017

Spectrum Analyzers / Receivers /Preselect		Range	MN	Mfr	SN	Asset	Calibration Due	Calibrated on
Rental MXE EMI Receiver(1168255)		20Hz-8.4GHz	N9038A	Agilent	IY5329000	1168255	I	8/15/2018
Rental MXE EMI Receiver(1170725)		20Hz-26.5GHz	N9038A	Agilent	IY5121015	1170725	I	12/22/2017

Radiated Emissions Sites		FCC Code	IC Code	VCCI Code	Range	Asset	Calibration Due	Calibrated on
EMI Chamber 1		719150	2762A-6	A-0015	30-1000MHz	1685	I	12/21/2018
EMI Chamber 1		719150	2762A-6	A-0015	1-18GHz	1685	I	12/21/2018

Preamps/Couplers Attenuators / Filters		Range	MN	Mfr	SN	Asset	Calibration Due	Calibrated on
Green		.009-2000MHz	ZFL-1000-LN	CS	N/A	802	II	9/23/2018
2463 HF PA		.5-18GHz	PAM-118A	COM-POWER	443005	2463	II	10/9/2018

Antennas		Range	MN	Mfr	SN	Asset	Calibration Due	Calibrated on
Red-Brown Bilog		30-2000MHz	JB1	Sunol	A0032406	1218	I	1/13/2019
Orange Horn		1-18GHz	3115	EMCO	0004-6123	390	I	10/13/2018

Meteorological Meters/Chambers		MN	Mfr	SN	Asset	Calibration Due	Calibrated on
Weather Clock (Pressure Only)		BA928	Oregon Scientific	C3166-1	831	I	4/28/2018
TH A#2084		HTC-1	HDE		2084	II	3/23/2018

Cables		Range	Mfr	Calibration Due	Calibrated on
Asset #1509		9kHz - 18GHz	Florida RF		II 10/2/2017
Asset #2051		9kHz - 18GHz	Florida RF		II 3/5/2017
Asset #2054		9kHz - 18GHz	Florida RF		II 10/30/2017

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

0.03-18GHz TEU



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Radiated Emissions Table

Date: 27-Oct-17	Company: Harman International	Work Order: R2500												
Engineer: Chris Hamel	EUT Desc: NA Base	EUT Operating Voltage/Frequency: 13.8V DC												
Temp: 24.2°C	Humidity: 52%	Pressure: 1000mBar												
Frequency Range:		Measurement Distance: 0.1 m												
Notes: No Emissions Found.		EUT Max Freq:												
Antenna Polarization (H / V)	Frequency (MHz)	Peak Reading (dB μ V)	Average Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dB μ V/m)	Adjusted Avg Reading (dB μ V/m)	FCC Class B High Frequency - Peak			FCC Class B High Frequency - Average		
		---	---	---	---	---	---	---	Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)	Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)

Table Result: Pass by N/A dB**Worst Freq:** N/A MHz

Test Site: EMI Chamber 1 Cable 1: Asset #2323
 Analyzer: Gold Preamp: 18-26.5GHz
 CSsoft Radiated Emissions Calculator v 1.017.195 Cable 2: ---
 Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor Antenna: 18-26.5GHz Horn Cable 3: ---
 Copyright Curtis-Straus LLC 2000
 Preselector: ---

18-26.5GHz Mid Channel**Radiated Emissions Table**

Date: 27-Oct-17	Company: Harman International	Work Order: R2500												
Engineer: Chris Hamel	EUT Desc: NA Base	EUT Operating Voltage/Frequency: 13.8V DC												
Temp: 24.2°C	Humidity: 52%	Pressure: 1000mBar												
Frequency Range:		Measurement Distance: 0.1 m												
Notes: No Emissions Found.		EUT Max Freq:												
Antenna Polarization (H / V)	Frequency (MHz)	Peak Reading (dB μ V)	Average Reading (dB μ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dB μ V/m)	Adjusted Avg Reading (dB μ V/m)	FCC Class B High Frequency - Peak			FCC Class B High Frequency - Average		
		---	---	---	---	---	---	---	Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)	Limit (dB μ V/m)	Margin (dB)	Result (Pass/Fail)

Table Result: Pass by N/A dB**Worst Freq:** N/A MHz

Test Site: EMI Chamber 1 Cable 1: Asset #2323
 Analyzer: Gold Preamp: None
 CSsoft Radiated Emissions Calculator v 1.017.195 Cable 2: Asset #2324
 Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor Antenna: 40GHz Mixer Cable 3: ---
 Copyright Curtis-Straus LLC 2000
 Preselector: ---

26.5-40GHz Mid Channel

Rev. 10/27/2017

Equipment	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Spectrum Analyzers / Receivers / Preselect	00Hz-26.5 GH	E4407B	Agilent	1Y4511381	1284	I	2/28/2018	2/28/2017
Gold								
Radiated Emissions Sites	FCC Code	IC Code	VCCI Code	Range	Asset	Cat	Calibration Due	Calibrated on
EMI Chamber 1	719150	2762A-6	A-0015	1-18GHz	1685	I	12/21/2018	12/21/2016
Mixers/Diplexers	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Mixer / Horn	26.5-40 GHz	11970A	Agilent	3003A1023C	2154	I	3/12/2019	3/12/2016
Preamps/Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
HF (Yellow)	18-26.5GHz	18002650-6	CS	467559	1266	II	10/16/2018	10/16/2017
Antennas	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
HF (White) Horn	18-26.5GHz	801-WLM	Waveline	758	758	III	Verify before Use	date of test
Meteorological Meters/Chambers	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only)		BA928	Oregon Scientific	C3166-1	831	I	4/28/2018	4/28/2016
TH A#2078		HTC-1	HDE		2078	II	3/23/2018	3/23/2017
Cables	Range	Mfr			Cat	Calibration Due	Calibrated on	
Asset 2323	1-26.5GHz	1/26-S1S1-1: MEGAPHASE 7139101 OC	2323		II	8/19/2018	8/19/2017	
Asset 2324	1-26.5GHz	1/26-S1S1-1: MEGAPHASE 7139101 OC	2324		II	8/19/2018	8/19/2017	

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

18-40GHz TEU

Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
 One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Radiated Band Edge

Radiated Emissions Table																
Date: 27-Oct-17	Company: Harman International Industries, Incorporated						Work Order: R2500									
Engineer: Chris Hamel	EUT Desc: G31 BASE+						EUT Operating Voltage/Frequency: 13.8V DC									
Temp: 23.4°C	Humidity: 42%						Pressure: 1000mBar									
Frequency Range:										Measurement Distance: 3 m						
Notes: No Pulsing emissions found.										EUT Max Freq:						
Antenna Polarization (H/V)	Frequency (MHz)	Peak Reading (dB _µ V)	Average Reading (dB _µ V)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dB _µ V/m)	Adjusted Avg Reading (dB _µ V/m)	FCC Class B High Frequency - Peak	FCC Class B High Frequency - Average						
									Limit (dB _µ V/m)	Margin (dB)	Result (Pass/Fail)	Limit (dB _µ V/m)	Margin (dB)	Result (Pass/Fail)		
Low V Max	2401.9	64.9		0.0	28.0	3.2	---	---	74.0	---	---	54.0	---	---		
H Max	2401.8	56.0		0.0	28.0	3.2	---	---	74.0	---	---	54.0	---	---		
V	2390.0	18.62	8.9	0.0	28.0	3.2	49.8	40.1	74.0	-24.2	Pass	54.0	-13.9	Pass		
V	2336.0	20.5	8.7	0.0	27.9	3.2	51.6	39.8	74.0	-22.4	Pass	54.0	-14.2	Pass		
High V Max	2479.9	62.7		0.0	28.2	3.2	---	---	74.0	---	---	54.0	---	---		
H Max	2479.9	54.5		0.0	28.2	3.2	---	---	74.0	---	---	54.0	---	---		
V	2483.5	18.3	8.6	0.0	28.2	3.2	49.7	40.0	74.0	-24.3	Pass	54.0	-14.0	Pass		
V	2495.8	21.3	8.6	0.0	28.3	3.2	52.8	40.1	74.0	-21.2	Pass	54.0	-13.9	Pass		
Table Result: Pass by -13.9 dB										Worst Freq: 2390.0 MHz						
Test Site: EMI Chamber 1	Cable 1: Asset #2051			Cable 2: Asset #2054			Cable 3: ---									
Analyzer: Rental SA#3	Preamp: None			Antenna: Orange Horn			Preselector: ---									
CSsoft Radiated Emissions Calculator v1.017.195							Copyright Curtis-Straus LLC 2000									
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor																

Rev. 10/22/2017										
Spectrum Analyzers / Receivers /Preselectors										
Rental MXE EMI Receiver(1170725)										
Range 20Hz-26.5GHz	MN N9038A	Mfr Agilent	SN MY51210151	Asset 1170725	Cat I	Calibration Due 12/22/2017	Calibrated on 12/22/2016			
Radiated Emissions Sites										
EMI Chamber 1	FCC Code 719150	IC Code 2762A-6	VCCI Code A-0015	Range 1-18GHz	Asset 1685	Cat I	Calibration Due 12/21/2018	Calibrated on 12/21/2016		
Antennas										
Orange Horn	Range 1-18GHz	MN 3115	Mfr EMCO	SN 0004-6123	Asset 390	Cat I	Calibration Due 10/13/2018	Calibrated on 10/13/2016		
Meteorological Meters/Chambers										
Weather Clock (Pressure Only) TH A#2084	MN BA928	Mfr Oregon Scientific	SN C3166-1	Asset 831	Cat I	Calibration Due 4/28/2018	Calibrated on 4/28/2016			
Cables										
Asset #2051	Range 9kHz - 18GHz	Mfr Florida RF	Asset 2084	Cat II	Calibration Due 3/5/2018	Calibrated on 3/5/2017				
Asset #2054	9kHz - 18GHz	Florida RF		II	10/30/2017	10/30/2016				

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



AC Line Conducted Emissions

LIMITS

Frequency of emission (MHz)	Quasi-peak limit (dB μ V)	Average limit (dB μ V)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

[47 CFR 15.207(a)]

MEASUREMENTS / RESULTS

**EUT is vehicle battery powered only



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Measurement Uncertainty

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Expanded Uncertainty k=2	Maximum allowable uncertainty
Radiated Emissions (30-1000MHz) NIST CISPR	5.6dB 4.6dB	N/A 5.2dB (Ucispr)
Radiated Emissions (1-26.5GHz)	4.6dB	N/A
Radiated Emissions (above 26.5GHz)	4.9dB	N/A
Magnetic Radiated Emissions	5.6dB	N/A
Conducted Emissions NIST CISPR	3.9dB 3.6dB	N/A 3.6dB (Ucispr)
Telco Conducted Emissions (Current)	2.9dB	N/A
Telco Conducted Emissions (Voltage)	4.4dB	N/A
Electrostatic Discharge	11.5%	N/A
Radiated RF Immunity (Uniform Field)	1.6dB	N/A
Electrical Fast Transients	23.1%	N/A
Surge	23.1%	N/A
Conducted RF Immunity	3dB	N/A
Magnetic Immunity	12.8%	N/A
Dips and Interrupts	2.3V	N/A
Harmonics	3.5%	N/A
Flicker	3.5%	N/A
Radio frequency (@ 2.4GHz)	3.23×10^{-8}	1×10^{-7}
RF power, conducted	0.40dB	0.75dB
Maximum frequency deviation:		
• Within 300Hz and 6kHz of audio frequency / Within 6kHz and 25kHz of audio frequency	3.4% 0.3dB	5% 3dB
Adjacent channel power	1.9dB	3dB
Conducted spurious emission of transmitter, valid up to 12.75GHz	2.39dB	3dB
Conducted emission of receivers	1.3dB	3dB
Radiated emission of transmitter, valid up to 26.5GHz	3.9dB	6dB
Radiated emission of transmitter, valid up to 80GHz	3.3dB	6dB
Radiated emission of receiver, valid up to 26.5GHz	3.9dB	6dB
Radiated emission of receiver, valid up to 80GHz	3.3dB	6dB
Humidity	2.37%	5%
Temperature	0.7°C	1.0°C
Time	4.1%	10%
RF Power Density, Conducted	0.4dB	3dB
DC and low frequency voltages	1.3%	3%
Voltage (AC, <10kHz)	1.3%	2%
Voltage (DC)	0.62%	1%
The above reflects a 95% confidence level		



Conditions Of Testing

[Bureau Veritas Consumer Products Services, Inc., a Massachusetts corporation], and/or its affiliates (collectively, the "Company") will conduct, at the request of the Submitter ("Client"), the tests specified on the submitted Test Request Form or equivalent in accordance with, and subject to, the following terms and conditions (collectively, "Conditions"):

1. All orders for tests are subject to acceptance by the Company, and no order will constitute a binding commitment of the Company unless and until such order is accepted by it, as evidenced by the issuance of a written report ("Test Report") by the Company. The Test Report is issued solely by the Company, is intended for the exclusive use of Client and shall not be published, used for advertising purposes, copied or replicated for distribution to any other person or entity or otherwise publicly disclosed without the prior written consent of the Company. By submitting a request for services to the Company, Client consents to the disclosure to accreditation bodies of those records of Client relevant to the accreditation body's assessment of the Company's competence and compliance with relevant accreditation criteria. The Company shall not be liable for any loss or damage whatsoever resulting from the failure of the Company to provide its services within any time period for completion estimated by the Company. If Client anticipates using the Test Report in any legal proceeding, arbitration, dispute resolution forum or other proceeding, it shall so notify the Company prior to submitting the Test Report in such proceeding. The Company has no obligation to provide a fact or expert witness at such proceeding unless the Company agrees in advance to do so for a separate and additional fee.
2. The Test Report will set forth the findings of the Company solely with respect to the test samples identified therein. Unless specifically and expressly indicated in the Test Report, the results set forth in such Test Report are not intended to be indicative or representative of the quality or characteristics of the lot from which a test sample is taken, and Client shall not rely upon the Test Report as being so indicative or representative of the lot or of the tested product in general. The Test Report will reflect the findings of the Company at the time of testing only, and the Company shall have no obligation to update the Test Report after its issuance. The Test Report will set forth the results of the tests performed by the Company based upon the written information provided to the Company. The Test Report will be based solely on the samples and written information submitted to the Company by Client, and the Company shall not be obligated to conduct any independent investigation or inquiry with respect thereto.
3. The Company may, in its sole discretion, destroy samples which have been furnished to the Company for testing and which have not been destroyed in the course of testing. The Company may delegate the performance of all or a portion of the services contemplated hereunder to an affiliate, agent or subcontractor of the Company, and Client consents to such delegation.
4. These Conditions and the Test Report represent the entire understanding of the parties hereto with respect to the subject matter hereof and of the Test Report, and no modification, variance or extrapolation with respect thereto shall be permitted without the prior written consent of the Company.
5. The names, service marks, trademarks and copyrights of the Company and its affiliates, including the names "**BUREAU VERITAS**," "**BUREAU VERITAS CONSUMER PRODUCTS SERVICES**," "**BVCPs**," "**MTL**," "**ACTS**," "**MTL-ACTS**" and **CURTIS-STRAUS** (collectively, the "Marks") are and shall remain the sole property of the Company or its affiliates and shall not be used by Client except solely to the extent that Client obtains the prior written approval of the Company and then only in the manner prescribed by the Company. Client shall not contest the validity of the Marks or take any action that might impair the value or goodwill associated with the Marks or the image or reputation of the Company or its affiliates.
6. Payment in full shall be due 30 days after the date of invoice. Interest shall be due on overdue amounts from the due date until paid at an interest rate of 1.5% per month or, if less, the maximum rate permitted by law. The Company reserves the right, at any time and from time to time, to revoke any credit extended to Client. Client shall reimburse the Company for any costs it incurs in collecting past due amounts, including court costs and fees and expenses of attorneys and collection agencies. The Test Report may not be used or relied upon by Client if and for so long as Client fails to pay when due any invoice issued by the Company or any affiliate of it to Client or any affiliate or subsidiary of Client together with interest and penalties, if any, accrued thereon.
7. The Company disclaims any and all responsibility or liability arising out of or in connection with e-mail transmissions of such information.
8. Client understands and agrees that the Company is neither an insurer nor a guarantor, that the Company does not take the place of Client or any designer, manufacturer, agent, buyer, distributor or transportation or shipping company, and that the Company disclaims all liability in such capacities. Client further understands that if it seeks assurance against loss or damage, it should obtain appropriate insurance.
9. Client agrees that the Company, by providing the services, does not take the place of Client nor any third party, nor does the Company release them from any of their obligations, nor does the Company otherwise assume, abridge, abrogate or undertake to discharge any duty of any third party to Client or any duty of Client or any third party to any other third party, and Client will not release any third party from its obligations and duties with respect to the tested goods.
10. Client shall, on a timely basis, (a) provide adequate instructions to the Company in order to enable the Company to perform properly its services, (b) provide, or cause Client's suppliers and contractors to provide, the Company with all documents necessary to enable the Company to perform its services, (c) furnish the Company with all relevant information regarding Client's intended use and purposes of the tested goods, (d) advise the Company of essential dates and deadlines relevant to the tested goods and (e) fully exercise all rights and remedies available to Client against third parties in respect of the tested goods.
11. The Company shall undertake due care and ordinary skill in the performance of its services to Client, and the Company shall accept responsibility only were such skill has not been exercised and, even in such event, only to the extent of the limitation of liability set forth herein.
12. If Client desires to assert a claim arising from or relating to (i) the performance, purported performance or non-performance of any services by the Company or (ii) the sale, resale, manufacture, distribution or use of any tested goods, it must submit that claim to the Company in a writing that sets forth with particularity the basis for such claim within 60 days from discovery of the potential claim and not more than six months after the date of issuance of the Test Report to Client. Client waives any and all such claims including, without limitation, claims that the Test Report is inaccurate, incomplete or misleading or that additional or different testing is required, unless and then only to the extent that Client submits a written claim to the Company within both such time periods.
13. CLIENT SHALL, EXCEPT TO THE EXTENT OF COMPANY'S LIABILITY TO CLIENT HEREUNDER (WHICH IN NO EVENT SHALL EXCEED THE LIMITATION OF LIABILITY HEREIN), HOLD HARMLESS AND INDEMNIFY THE COMPANY, ITS AFFILIATES AND THEIR RESPECTIVE DIRECTORS, OFFICERS, EMPLOYEES, AGENTS AND SUBCONTRACTORS AGAINST ALL ACTUAL OR ALLEGED THIRD PARTY CLAIMS FOR LOSS, DAMAGE OR EXPENSE OF WHATSOEVER NATURE AND HOWSOEVER ARISING FROM OR RELATING TO (i) THE PERFORMANCE, PURPORTED PERFORMANCE OR NON-PERFORMANCE OF ANY SERVICES BY THE COMPANY OR (ii) THE SALE, RESALE, MANUFACTURE, DISTRIBUTION OR USE OF ANY TESTED GOODS.
14. EXCEPT AS MAY OTHERWISE BE EXPRESSLY AGREED TO IN WRITING BY THE COMPANY AND NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN OR IN ANY TEST REPORT, NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR USE, IS MADE.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 15 of 48

Testing Cert. No. 1627-01

15. (A) IN NO EVENT WHATSOEVER SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, EXEMPLARY OR PUNITIVE DAMAGES IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE TEST REPORT OR THE SERVICES PROVIDED BY THE COMPANY HEREUNDER, INCLUDING WITHOUT LIMITATION LOSS OF OR DAMAGE TO PROPERTY; LOSS OF INCOME, PROFIT OR USE; OR ANY CLAIMS OR DEMANDS MADE AGAINST CLIENT OR ANY OTHER PERSON BY ANY THIRD PARTY IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE SERVICES PROVIDED BY THE COMPANY HEREUNDER.

(B) NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN, AND IN RECOGNITION OF THE RELATIVE RISKS AND BENEFITS TO CLIENT AND THE COMPANY ASSOCIATED WITH THE TESTING SERVICES CONTEMPLATED HEREBY, THE RISKS HAVE BEEN ALLOCATED SUCH THAT UNDER NO CIRCUMSTANCES WHATSOEVER SHALL THE LIABILITY OF THE COMPANY TO CLIENT OR ANY THIRD PARTY IN RESPECT OF ANY CLAIM FOR LOSS, DAMAGE OR EXPENSE, OF WHATSOEVER NATURE OR MAGNITUDE, AND HOWSOEVER ARISING, EXCEED AN AMOUNT EQUAL TO FIVE (5) TIMES THE AMOUNT OF THE FEES PAID TO THE COMPANY FOR THE SPECIFIC SERVICES WHICH GAVE RISE TO SUCH CLAIM OR U.S.\$10,000, WHICHEVER IS THE LESSER AMOUNT.

16. The Company shall not be liable for any loss or damage resulting from any delay or failure in performance of its obligations hereunder resulting directly or indirectly from any event of force majeure or any event outside the control of the Company. If any such event occurs, the Company may immediately cancel or suspend its performance hereunder without incurring any liability whatsoever to Client.

17. Company's services, including these Conditions, shall be governed by, and construed in accordance with, the local laws of the country where the Company performs the tests or, in the case of tests performed in the United States of America, the laws of Massachusetts without regard to conflicts of laws principles. If any aspect(s) of these Conditions is found to be illegal or unenforceable, the validity, legality and enforceability of all remaining aspects of these Conditions shall not in any way be affected or impaired thereby. Any proceeding related to the subject matter hereof shall be brought, if at all, in the courts of the country where the Company performs the tests or, in the case of tests performed in the United States of America, in the courts of Massachusetts. Client waives the right to interpose any counterclaim or setoffs of any nature in any litigation arising hereunder.

The complete list of the Approved Subcontractors Curtis-Straus may use to delegate the performance of work can be provided upon request. Rev.160009121(2)_#684340 v14CS



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Appendix A:**ER2500-9 Appendix A
CFR Title 47 FCC Part §15.247 and ISED Canada RSS-247 Issue 2****DUT Information**

DUT Name: G31 BASE
 Manufacturer: Harman International Industries, Inc.
 Serial Number: 069

Frequencies

BT CH 0 (2402 MHz)	BT CH 2 (2404 MHz)	BT CH 3 (2405 MHz)
BT CH 1 (2403 MHz)	BT CH 5 (2407 MHz)	BT CH 6 (2408 MHz)
BT CH 4 (2406 MHz)	BT CH 8 (2410 MHz)	BT CH 9 (2411 MHz)
BT CH 7 (2409 MHz)	BT CH 11 (2413 MHz)	BT CH 12 (2414 MHz)
BT CH 10 (2412 MHz)	BT CH 14 (2416 MHz)	BT CH 15 (2417 MHz)
BT CH 13 (2415 MHz)	BT CH 17 (2419 MHz)	BT CH 18 (2420 MHz)
BT CH 16 (2418 MHz)	BT CH 20 (2422 MHz)	BT CH 21 (2423 MHz)
BT CH 19 (2421 MHz)	BT CH 23 (2425 MHz)	BT CH 24 (2426 MHz)
BT CH 22 (2424 MHz)	BT CH 26 (2428 MHz)	BT CH 27 (2429 MHz)
BT CH 25 (2427 MHz)	BT CH 29 (2431 MHz)	BT CH 30 (2432 MHz)
BT CH 28 (2430 MHz)	BT CH 32 (2434 MHz)	BT CH 33 (2435 MHz)
BT CH 31 (2433 MHz)	BT CH 35 (2437 MHz)	BT CH 36 (2438 MHz)
BT CH 34 (2436 MHz)	BT CH 38 (2440 MHz)	BT CH 39 (2441 MHz)
BT CH 37 (2439 MHz)	BT CH 41 (2443 MHz)	BT CH 42 (2444 MHz)
BT CH 40 (2442 MHz)	BT CH 44 (2446 MHz)	BT CH 45 (2447 MHz)
BT CH 43 (2445 MHz)	BT CH 47 (2449 MHz)	BT CH 48 (2450 MHz)
BT CH 46 (2448 MHz)	BT CH 50 (2452 MHz)	BT CH 51 (2453 MHz)
BT CH 49 (2451 MHz)	BT CH 53 (2455 MHz)	BT CH 54 (2456 MHz)
BT CH 52 (2454 MHz)	BT CH 56 (2458 MHz)	BT CH 57 (2459 MHz)
BT CH 55 (2457 MHz)	BT CH 59 (2461 MHz)	BT CH 60 (2462 MHz)
BT CH 58 (2460 MHz)	BT CH 62 (2464 MHz)	BT CH 63 (2465 MHz)
BT CH 61 (2463 MHz)	BT CH 65 (2467 MHz)	BT CH 66 (2468 MHz)
BT CH 64 (2466 MHz)	BT CH 68 (2470 MHz)	BT CH 69 (2471 MHz)
BT CH 67 (2469 MHz)	BT CH 71 (2473 MHz)	BT CH 72 (2474 MHz)
BT CH 70 (2472 MHz)	BT CH 74 (2476 MHz)	BT CH 75 (2477 MHz)
BT CH 73 (2475 MHz)	BT CH 77 (2479 MHz)	BT CH 78 (2480 MHz)

DUT Settings

No. of transmission chains 1
 Equipment Type Frequency Hopping Spread Spectrum

Antenna Gain

Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
 One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828

page 17 of 48



Frequency (MHz)	Efficiency (dB)	Efficiency (%)	Gain (dBi)
2400	-4.35	36.70	0.94
2410	-4.40	36.33	0.93
2420	-4.43	36.06	0.92
2430	-4.46	35.78	1.18
2440	-4.44	35.94	0.95
2450	-4.50	35.47	0.87
2460	-4.61	34.60	0.88
2470	-4.80	33.13	0.71
2480	-4.90	32.38	0.93
2490	-5.06	31.18	0.85
2500	-5.33	29.32	0.24

Test Equipment Used:

Spectrum Analyzers / Receivers /Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
FSV40 Signal Generator	10Hz-40GHz	FSV40	ROHDE & SCHWARZ	101551	2200	I	6/30/2018	6/30/2017
Signal Generators	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
SMBV100A Vector Signal Generator	9KHz-6GHz	SMBV100A	ROHDE & SCHWARZ	261919	2201	I	6/26/2018	6/26/2017
SMB100A Signal Generator	100KHz-40GHz	SMB100A	ROHDE & SCHWARZ	179846	2434	I	5/30/2018	5/30/2017
R&S®OSP120 with R&S®OSP-B157	30MHz-18GHz	OSP120	ROHDE & SCHWARZ	101674		I	6/1/2018	6/1/2017
Cables	Range	Mfr			Cat	Calibration Due	Calibrated on	
Asset #2052	9KHz - 18GHz	Florida RF			II	3/5/2018	3/5/2017	
DUT1	30MHz-26GHz	Micro-Coax			II	6/21/2018	6/21/2017	
Attenuators	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
10dB Attenuator-01 Brown	30MHz-26GHz		Mini Circuits			II	7/13/2018	7/14/2017
10dB Attenuator-02 Yellow	30MHz-26GHz		Mini Circuits			II	7/13/2018	7/14/2017
Wideband Radio Communication Tester	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
(Rental)CMW500	DC to 6GHz	CMW500	ROHDE & SCHWARZ	155905		I	6/2/2018	6/2/2017



Summary

Test	Frequency (MHz)	DH1 Result	DH3 Result	DH5 Result	2-DH1 Result	2-DH3 Result	2-DH5 Result	3-DH1 Result	3-DH3 Result	3-DH5 Result
Hopping Frequencies	--- (hopping)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Band Edge (during hopping)	--- (hopping)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Carrier Frequency Separation	2402.000 (hopping)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Carrier Frequency Separation	2480.000 (hopping)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Time of Channel Occupancy	2402.000 (hopping)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Time of Channel Occupancy	2441.000 (hopping)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Time of Channel Occupancy	2480.000 (hopping)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Emission Bandwidth 20 dB	2402.000 (single)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Band Edge low	2402.000 (single)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Peak output power	2402.000 (single)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Conducted Spurious Emissions	2402.000 (single)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Emission Bandwidth 20 dB	2441.000 (single)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Peak output power	2441.000 (single)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Conducted Spurious Emissions	2441.000 (single)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Emission Bandwidth 20 dB	2480.000 (single)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Band Edge high	2480.000 (single)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Peak output power	2480.000 (single)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Conducted Spurious Emissions	2480.000 (single)	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS




Number of Hopping Frequencies

Test procedure in accordance with ANSI C63.10-2013

Channels

Channels	Limit Min	Result
79	15	PASS




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 20 of 48

Testing Cert. No. 1627-01



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 21 of 48

Testing Cert. No. 1627-01

Band Edge (during hopping)

Test procedure in accordance with ANSI C63.10-2013

Measurement uncertainty calculated in accordance with ETSI TR 100 028-1. Expanded Uncertainty (K=2) < 0.8 dB

Inband Peak



Data Rate	Frequency (MHz)	Level (dBm)
DH1	2403.811547	-1.3
DH3	2408.810297	-1.4
DH5	2402.811797	-1.4
2-DH1	2404.961260	-1.4
2-DH3	2413.959010	-1.5
2-DH5	2404.961260	-1.4
3-DH1	2406.810797	-1.3
3-DH3	2405.961010	-1.4
3-DH5	2404.161460	-1.3

Plots for packet type 3-DH5 shown below.

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2502.986753	-52.1	30.8	-21.3	PASS
2502.936766	-52.7	31.5	-21.3	PASS
2503.036741	-52.9	31.6	-21.3	PASS
2502.086978	-53.2	31.9	-21.3	PASS
2502.786803	-53.2	32.0	-21.3	PASS
2502.736816	-53.4	32.1	-21.3	PASS
2503.436641	-53.5	32.2	-21.3	PASS
2378.967758	-53.6	32.3	-21.3	PASS
2504.836291	-53.6	32.4	-21.3	PASS
2501.287178	-53.6	32.4	-21.3	PASS
2502.036991	-53.7	32.4	-21.3	PASS
2504.336416	-53.7	32.4	-21.3	PASS
2501.587103	-53.7	32.5	-21.3	PASS
2501.337166	-53.8	32.5	-21.3	PASS
2501.937016	-53.8	32.5	-21.3	PASS





Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Carrier Frequency Separation


Test procedure in accordance with ANSI C63.10-2013.


Measurement uncertainty calculated in accordance with ETSI TR 100 028-1. Expanded Uncertainty($k = 2$) < 1%**2402 MHz**

Limit is 2/3 of the widest 20dB bandwidth measured for worst case.

Packet Type	DUT Frequency (MHz)	Frequency Separation (MHz)	Minimum Limit (MHz)	Result
DH1	2402.000000	0.980392	0.882353	PASS
DH3	2402.000000	0.980392	0.882353	PASS
DH5	2402.000000	0.980392	0.882353	PASS
2-DH1	2402.000000	0.980392	0.882353	PASS
2-DH3	2402.000000	0.980392	0.882353	PASS
2-DH5	2402.000000	0.980392	0.882353	PASS
3-DH1	2402.000000	0.980392	0.882353	PASS
3-DH3	2402.000000	0.980392	0.882353	PASS
3-DH5	2402.000000	0.931373	0.882353	PASS

Plots for packet type 3-DH5 shown below.





Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 25 of 48

Testing Cert. No. 1627-01


2480 MHz

Limit is 2/3 of the widest 20dB bandwidth measured for worst case.

Packet Type	DUT Frequency (MHz)	Frequency Separation (MHz)	Minimum Limit (MHz)	Result
DH1	2480.000000	0.980392	0.86275	PASS
DH3	2480.000000	0.980392	0.86275	PASS
DH5	2480.000000	0.980392	0.86275	PASS
2-DH1	2480.000000	0.980392	0.86275	PASS
2-DH3	2480.000000	0.980392	0.86275	PASS
2-DH5	2480.000000	0.980392	0.86275	PASS
3-DH1	2480.000000	0.980392	0.86275	PASS
3-DH3	2480.000000	0.980392	0.86275	PASS
3-DH5	2480.000000	0.980392	0.86275	PASS

Plots for packet type 3-DH5 shown below.

CFS





Time of Channel Occupancy (Dwell Time)

Test procedure in accordance with ANSI C63.10-2013


Measurement uncertainty calculated in accordance with ETSI TR 100 028-1. Expanded Uncertainty (K=2) < 1%


2402 MHz

Data Rate	Time (ms)	Limit Max (ms)	Result
DH1	144.040	400.000	PASS
DH3	276.330	400.000	PASS
DH5	268.730	400.000	PASS
2-DH1	126.940	400.000	PASS
2-DH3	226.260	400.000	PASS
2-DH5	278.310	400.000	PASS
3-DH1	126.380	400.000	PASS
3-DH3	223.580	400.000	PASS
3-DH5	266.180	400.000	PASS

Plots for packet type 3-DH5 shown below.

Time of Channel Occupancy






2441 MHz

Data Rate	Time (ms)	Limit Max (ms)	Result
DH1	143.750	400.000	PASS
DH3	293.350	400.000	PASS
DH5	280.520	400.000	PASS
2-DH1	125.590	400.000	PASS
2-DH3	226.030	400.000	PASS
2-DH5	260.670	400.000	PASS
3-DH1	123.880	400.000	PASS
3-DH3	213.440	400.000	PASS
3-DH5	269.700	400.000	PASS

Plots for packet type 3-DH5 shown below.

Time of Channel Occupancy




Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 29 of 48

Testing Cert. No. 1627-01



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




2480 MHz

Data Rate	Time (ms)	Limit Max (ms)	Result
DH1	143.890	400.000	PASS
DH3	276.230	400.000	PASS
DH5	333.690	400.000	PASS
2-DH1	124.870	400.000	PASS
2-DH3	228.670	400.000	PASS
2-DH5	220.000	400.000	PASS
3-DH1	123.940	400.000	PASS
3-DH3	218.060	400.000	PASS
3-DH5	266.360	400.000	PASS


Plots for packet type 3-DH5 shown below.

Time of Channel Occupancy



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828





Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




Peak Output Power

Test procedure in accordance with ANSI C63.10-2013

Data Rate	2402MHz	2441MHz	2480MHz	Limit dBm
DH1	-2.05	-2.6	-2.75	30
DH3	-2.047	-2.596	-2.672	30
DH5	-2.08	-2.592	-2.71	30
2-DH1	-0.835	-1.26	-1.277	30
2-DH3	-0.653	-1.129	-1.276	30
2-DH5	-0.577	-1.21	-1.264	30
3-DH1	-0.422	-0.939	-0.987	30
3-DH3	-0.321	-0.635	-0.953	30
3-DH5	-0.221	-0.597	-0.834	30

Plot for packet type 3-DH5 shown below.



Emission Bandwidth 20 dB

Test procedure in accordance with ANSI C63.10-2013


Measurement uncertainty calculated in accordance with ETSI TR 100 028-1. Expanded Uncertainty (K=2) < 2%


2402 MHz

Data Rate	Bandwidth (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Result
DH1	0.882353	2401.514706	2402.397059	PASS
DH3	0.911765	2401.485294	2402.397059	PASS
DH5	1.000000	2401.485294	2402.485294	PASS
2-DH1	1.264706	2401.338235	2402.602941	PASS
2-DH3	1.294118	2401.338235	2402.632353	PASS
2-DH5	1.294118	2401.338235	2402.632353	PASS
3-DH1	1.235294	2401.367647	2402.602941	PASS
3-DH3	1.294117	2401.308824	2402.632353	PASS
3-DH5	1.323529	2401.308824	2402.602941	PASS

Plots for packet type 3-DH5 shown below.

20 dB Bandwidth





Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 35 of 48


Testing Cert. No. 1627-01

2441 MHz

Data Rate	Bandwidth (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Result
DH1	0.882353	2440.514706	2441.397059	PASS
DH3	0.911765	2440.485294	2441.397059	PASS
DH5	1.000000	2440.485294	2441.485294	PASS
2-DH1	1.264706	2440.338235	2441.602941	PASS
2-DH3	1.294118	2440.338235	2441.632353	PASS
2-DH5	1.294118	2440.338235	2441.632353	PASS
3-DH1	1.235294	2440.367647	2441.602941	PASS
3-DH3	1.294117	2440.308824	2441.602941	PASS
3-DH5	1.323529	2440.308824	2441.632353	PASS

Plots for packet type 3-DH5 shown below.

20 dB Bandwidth





Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 37 of 48


Testing Cert. No. 1627-01

2480 MHz

Data Rate	Bandwidth (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Result
DH1	0.882353	2479.514706	2480.397059	PASS
DH3	0.911765	2479.485294	2480.397059	PASS
DH5	0.970588	2479.485294	2480.455882	PASS
2-DH1	1.264706	2479.338235	2480.602941	PASS
2-DH3	1.294118	2479.338235	2480.632353	PASS
2-DH5	1.294118	2479.338235	2480.632353	PASS
3-DH1	1.235294	2479.367647	2480.602941	PASS
3-DH3	1.294117	2479.308824	2480.602941	PASS
3-DH5	1.323529	2479.308824	2480.632353	PASS

Plots for packet type 3-DH3 shown below.

20 dB Bandwidth



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Band Edge Low (2402 MHz)

Test procedure in accordance with ANSI C63.10-2013

Measurement uncertainty calculated in accordance with ETSI TR 100 028-1. Expanded Uncertainty (K=2) < 0.8 dB

Inband Peak

Data Rate	Frequency (MHz)	Level (dBm)
DH1	2401.778737	-1.3
DH3	2401.778737	-1.3
DH5	2402.128578	-1.3
2-DH1	2401.778737	-1.4
2-DH3	2401.928669	-1.4
2-DH5	2401.928669	-1.4
3-DH1	2401.778737	-1.4
3-DH3	2402.128578	-1.4
3-DH5	2402.128578	-1.3


Plots for packet type 3-DH5 shown below.

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.979555	-44.1	22.7	-21.3	PASS
2399.829623	-44.6	23.2	-21.3	PASS
2399.879600	-44.6	23.2	-21.3	PASS
2399.929577	-44.6	23.3	-21.3	PASS
2399.779646	-44.8	23.4	-21.3	PASS
2399.729668	-45.5	24.2	-21.3	PASS
2399.429805	-46.4	25.0	-21.3	PASS
2399.479782	-46.4	25.0	-21.3	PASS
2399.679691	-46.5	25.1	-21.3	PASS
2399.179918	-46.6	25.2	-21.3	PASS
2399.379827	-46.6	25.2	-21.3	PASS
2399.229896	-46.6	25.2	-21.3	PASS
2399.529759	-46.7	25.4	-21.3	PASS
2399.129941	-46.9	25.5	-21.3	PASS
2399.279873	-46.9	25.5	-21.3	PASS




Band Edge



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 40 of 48



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 41 of 48

Testing Cert. No. 1627-01

Band Edge High (2480 MHz)

Test procedure in accordance with ANSI C63.10-2013

Measurement uncertainty calculated in accordance with ETSI TR 100 028-1. Expanded Uncertainty (K=2) < 0.8 dB

Inband Peak

Data Rate	Frequency (MHz)	Level (dBm)
DH1	2479.820536	-1.9
DH3	2479.820536	-2
DH5	2479.820536	-1.9
2-DH1	2479.970468	-2.0
2-DH3	2479.970468	-2.0
2-DH5	2480.170377	-2.0
3-DH1	2479.820536	-2.0
3-DH3	2479.970468	-2.0
3-DH5	2480.170377	-1.9



Plots for packet type 3-DH5 shown below.

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2483.968651	-51.6	29.7	-21.9	PASS
2483.918673	-51.8	29.9	-21.9	PASS
2484.018628	-51.9	30.0	-21.9	PASS
2483.668787	-52.2	30.3	-21.9	PASS
2483.718764	-52.2	30.3	-21.9	PASS
2484.118582	-52.5	30.6	-21.9	PASS
2483.868696	-52.6	30.7	-21.9	PASS
2484.068605	-52.7	30.8	-21.9	PASS
2484.368469	-52.9	31.0	-21.9	PASS
2484.168560	-52.9	31.0	-21.9	PASS
2484.318492	-53.1	31.2	-21.9	PASS
2506.008632	-53.2	31.3	-21.9	PASS
2483.618810	-53.2	31.3	-21.9	PASS
2484.468423	-53.3	31.4	-21.9	PASS
2483.768741	-53.3	31.4	-21.9	PASS



Band Edge



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Conducted Spurious Emissions

Test procedure in accordance with ANSI C63.10-2013


Measurement uncertainty calculated in accordance with ETSI TR 100 028-1. Expanded Uncertainty (K=2) < 0.8 dB


2402 MHz

Plots for packet type 3-DH5 shown below.

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
7205.695425	-39.8	18.1	-21.7
7206.475689	-42.3	20.5	-21.7
2399.270827	-45.7	24.0	-21.7
7204.915162	-47.1	25.3	-21.7
19858.452128	-47.1	25.4	-21.7
19782.766546	-47.1	25.4	-21.7
20186.162896	-47.4	25.6	-21.7
19813.196831	-47.4	25.6	-21.7
20293.059028	-47.4	25.6	-21.7
19920.873227	-47.4	25.7	-21.7
19953.644303	-47.5	25.8	-21.7
19742.973095	-47.7	25.9	-21.7
17833.667740	-47.7	25.9	-21.7
20273.552434	-47.7	26.0	-21.7
19857.671864	-47.8	26.1	-21.7





2441 MHz



Plots for packet type 3-DH5 shown below.

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
7322.734985	-38.9	16.5	-22.4
7323.515249	-43.4	21.0	-22.4
7321.954722	-43.6	21.2	-22.4
20210.351072	-46.8	24.4	-22.4
19795.250766	-46.8	24.4	-22.4
19783.546810	-47.1	24.7	-22.4
19805.394194	-47.2	24.7	-22.4
20209.570808	-47.2	24.8	-22.4
19804.613930	-47.2	24.8	-22.4
20293.059028	-47.3	24.8	-22.4
20275.893225	-47.5	25.0	-22.4
19810.856040	-47.5	25.1	-22.4
20229.857665	-47.5	25.1	-22.4
19788.228392	-47.5	25.1	-22.4
19952.864040	-47.6	25.1	-22.4



Spurious



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
 One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828




2480 MHz


Plots for packet type 3-DH5 shown below.

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
7439.774545	-40.9	18.6	-22.3
7440.554809	-43.8	21.5	-22.3
7438.994282	-44.7	22.4	-22.3
19733.609931	-47.2	24.9	-22.3
19933.357446	-47.3	25.0	-22.3
19867.815293	-47.4	25.1	-22.3
20177.579995	-47.4	25.2	-22.3
20318.807731	-47.6	25.4	-22.3
20289.937973	-47.7	25.4	-22.3
18491.430067	-47.7	25.5	-22.3
20257.947160	-47.8	25.5	-22.3
20198.647116	-47.8	25.6	-22.3
20282.135335	-47.9	25.6	-22.3
19781.206018	-47.9	25.6	-22.3
19822.559996	-47.9	25.6	-22.3

Spurious





Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 48 of 48

ACREDITED
Testing Cert. No. 1627-01