

RF Exposure Report (FCC)

Report No.: FCC_RF_SL20010901-HAR-2221_MPE

FCC ID: 2AHPN-BE2849

Model: R1 EXT RW

Received Date: 02/10/2020

Test Date: 02/18/2020 - 02/29/2020

Issued Date: 03/20/2020

Applicant: HARMAN INTERNATIONAL,

Address: 30001 Cabot Drive, Novi, MI 48377, USA

Manufacturer: HARMAN INTERNATIONAL

Address: 30001 Cabot Drive, Novi, MI 48377, USA

Issued By: Bureau Veritas Consumer Products Services, Inc.

Lab Address: 775 Montague Expressway, Milpitas, CA 95035

FCC Registration / Designation Number: 540430 / 4842D





TESTING CERT # 2742-01

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.



Table of Contents

R	elea	se Control Record	. 3
1		Certificate of Conformity	. 4
2		RF Exposure	. 5
	2.1	Limits for Maximum Permissible Exposure (MPE)	. 5
		MPE Calculation Formula	
		Classification	
	2.4	Calculation Result of Maximum Conducted Power	. 6
3		Conclusion	. 6



Release Control Record

Issue No.	Description	Date Issued
FCC_RF_SL20010901-HAR-2221_MPE	Original Release	03/23/2020



1	Certificate	of Conformity
---	-------------	---------------

Product: Automotive Infotainment Unit

Brand: HARMAN

Test Model: R1 EXT RW

Sample Status: Engineering Sample

Applicant: HARMAN INTERNATIONAL

Test Date: 02/18/2020 - 03/18/2020

Standard: 47 CFR FCC Part 2.1093

The above equipment has been tested by **Bureau Veritas Consumer Products Services**, **Inc.**, **Milpitas Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

	Crary Chou			
Prepared by :	-	, Date:	03/23/2020	
	Gary Chou / Compliance Engineer			
Approved by :	and	_ , Date:	03/23/2020	
	Chen Ge / Engineer Reviewer			



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)			
	Limits For General Population / Uncontrolled Exposure						
0.3-1.34	614	1.63	(100)*	30			
1.34-30	824/f	2.19/f	(180/f ²)*	30			
30-300	27.5	0.073	0.2	30			
300-1500			f/1500	30			
1500-100,000			1.0	30			

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.



2.4 Calculation Result of Maximum Conducted Power

Type	Frequency Band (MHz)	Max Power (dBm)	Max Power (mW)	Turn-Up Tolerance	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
BT-BDR	2402	5.87	3.864	±1dB	1.43	20	0.001346	1
2.4GHz WLAN	2462	11.55	14.28	±1dB	1.43	20	0.003395	1
5GHz WLAN	5180	8.03	6.35	±1dB	2.60	20	0.002897	1

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

3 Conclusion

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---