



Test Report

Prepared for Harman International Industries, Inc.

This report presents Maximum Permissible Exposure for

INFO3.6 CSM

Prepared by

Aravind Buddana

Engineer II

Approved by

Jason Kanakry

General Manager

Issue date: 07/13/2023

Report No: AH22100701-HAR-053_FCC_MPE v3

This test result relates only to the described test object.

This document shall not be reproduced, except in full, without the written approval of Bureau Veritas Test Lab.

Customer must not use this test report as the product certification of each accreditation body or each national organization.

The test is traceable to national standard or related international standard

Contents

1. Test Request Information	3
2. Test Laboratory Information	4
3. RF Exposure	5

1. Test Request Information

Test Request #: 7700182604

Test Requested By: Mark Bowman
Harman International Industries, Inc.
30001 Cabot Drive, Novi, MI 48377

Test item Description: INFO3.6 CSM

Part Number: 8457687

DUT Sample Number: AH22100701-HAR-053#1

Hardware Version of DUT: PV

Software Version of DUT: 17.80.200.219

Component Category of DUT: N/A

FCC ID: 2AHPN-BE2866

Type of Test: FCC/ISED Certification

Test Method: CFR Title 47 FCC Part 15.247, 1.1307, 1.1310, 2.1091
KDB 447498 D04 General RF Exposure Guidance v01

Deviations from standard: None

Approved Test Plan Number: N/A

Test Plan Revision: N/A

Date test sample received: 10-07-2022

Date test started: 10-13-2022

Date test finished: 03-08-2023

2. Test Laboratory Information

Location of Test Lab:	The radiated and conducted emissions test sites are located at Bureau Veritas 815 N. Opdyke Rd #100, Auburn Hills, MI 48326, Phone: +1-248-836-4700
Key Contact:	Jason Kanakry (General Manager) Jason.Kanakry@BureauVeritas.com Phone: +1-248-836-4747
Laboratory Accreditations:	BUREAU VERITAS CONSUMER PRODUCTS SERVICES, INC is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.
ISO/IEC 17025:2017:	5678.01
FCC Test Site Number:	US1278 (242530)
IC Test Site Number:	US0229 (26240)

3. RF Exposure

3.1 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

3.2 Max Conducted Power and Antenna Information

Band	Antenna Type	Max Conducted Power (dBm)	Max Conducted Power (mW)	EIRP (W)	ERP(mW)	Antenna Gain (dBi)
BT Classic	Integrated PCB antenna	2.374	1.72742818	0.006845418	4.172535112	5.98
WLAN 2.4G	Integrated PCB antenna	6.915	4.914733802	0.00888178	5.413772479	2.57
WLAN 5G (UNII-1)	Integrated PCB antenna	13.428	22.01912211	0.060506217	36.88077172	4.39
WLAN 5G (UNII-3)	Integrated PCB antenna	10.923	12.36801491	0.039563982	24.11570707	5.05

3.3 Calculation for MPE

Simultaneous Transmission Configuration-1

Band	Transmit Frequency (MHz)	$\lambda/2\pi$ (m)	Separation Distance (m)	Radio Power (dBm)	Radio Power (W)	Antenna Gain (dBi)	Antenna Gain (Lin eq.)	ERP (W)	Threshold ERP (W)	Result ERP(W)/ERPth
BT Classic	2402	0.019864051	0.2	2.374	0.001727428	5.98	3.9627803	0.004172535	0.768	0.005432988
2.4G WLAN	2462	0.019379956	0.2	6.915	0.004914734	2.57	1.8071741	0.005413772	0.768	0.007049183
5G WLAN (UNII-1)	5240	0.009105621	0.2	13.428	0.022019122	4.39	2.7478942	0.036880772	0.768	0.048021838

ERP(W) of Simultaneous Transmission Configuration-1 of BT Classic + 2.4G WLAN + 5G WLAN (UNII-1) = 0.046467079 is less than equal to ERP Threshold.

Simultaneous Transmission Configuration-2

Band	Transmit Frequency (MHz)	$\lambda/2\pi$ (m)	Separation Distance (m)	Radio Power (dBm)	Radio Power (W)	Antenna Gain (dBi)	Antenna Gain (Lin eq.)	ERP (W)	Threshold ERP (W)	Result ERP(W)/ERPth
BT Classic	2402	0.019864051	0.2	2.374	0.001727428	5.98	3.9627803	0.004172535	0.768	0.005432988
2.4G WLAN	2462	0.019379956	0.2	6.915	0.004914734	2.57	1.8071741	0.005413772	0.768	0.007049183
5G WLAN (UNII-3)	5795	0.008233555	0.2	10.923	0.012368015	5.05	3.1988951	0.024115707	0.768	0.03140066

ERP(W) of Simultaneous Transmission Configuration-2 of BT Classic + 2.4G WLAN + 5G WLAN (UNII-3) = 0.033702014 is less than equal to ERP Threshold.

Notes:-

- Minimum separation distance must be $\geq \text{wavelength}/2\pi$ meters
Where Wavelength = $\text{Transmit Frequency} \times 10^6$
- Threshold ERP as per Transmit frequency

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

3.4 Conclusion

The maximum calculations of above situations, the ERP (W) is less than equal to ERP Threshold.

Document Revisions

Version	Date	Modifier	Changes
1.0	03/08/2023	Aravind Buddana	<ul style="list-style-type: none">Initial release
2.0	05/13/2023	Aravind Buddana	<ul style="list-style-type: none">Updated the Test Request Information with appropriate test methodRemoved BLE Data as BLE is not supported in this variant.
3.0	07/13/2023	Aravind Buddana	<ul style="list-style-type: none">Updated the data for UNII-3 band as well to demonstrate the simultaneous conditions.

End of Report