

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	WiFi repeater with LAN port
Test Model	EP-2911S
Series Model	OT2911S
FCC ID	2AHRDEP-2911S

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\left[\sqrt{f}(GHz)\right] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

BR/EDR

Pt=8.61dBm=7.26mW

The value of the Maximum output power Pt is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation SAR=(7.26mW /5mm) .[$\sqrt{2.412(GHz)}$]=2.26<3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the second device of the stand of the st