



# RADIO TEST REPORT

Report No: STS1606147F01


Issued for

Shenzhen EDUP Electronics Technology Co.,Ltd.

6 Floor, #6 Building, No.48, Kangzheng Road, Liantang  
Industrial Area, Buji Town, ShenZhen, China

<b>Product Name:</b>	Wireless Adapter
<b>Brand Name:</b>	CARDKING
<b>Model Name:</b>	KW-3016N
<b>Series Model:</b>	KW-3015N
<b>FCC ID:</b>	2AHRDKW-3016N
<b>Test Standard:</b>	FCC Part 15.247

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.





### TEST RESULT CERTIFICATION

**Applicant's name** ..... : Shenzhen EDUP Electronics Technology Co.,Ltd.  
**Address**..... : 6 Floor, #6 Building, No.48, Kangzheng Road, Liantang Industrial Area, Buji Town,ShenZhen, China  
**Manufacture's Name** ..... : Shenzhen EDUP Electronics Technology Co.,Ltd.  
**Address**..... : 6 Floor, #6 Building, No.48, Kangzheng Road, Liantang Industrial Area, Buji Town,ShenZhen, China

#### Product description

**Product name**..... : Wireless Adapter  
**Model and/or type reference** : KW-3016N  
**Series Model**..... : KW-3015N

**Standards** ..... : FCC Part15.247

**Test procedure** ..... ANSI C63.10-2013

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

**Date of Test**..... :

**Date (s) of performance of tests**..... : 21 June. 2016 ~12 July. 2016

**Date of Issue** ..... : 13 July. 2016

**Test Result** ..... : **Pass**

Testing Engineer :   
 \_\_\_\_\_  
 (Tony Liu)

Technical Manager :   
 \_\_\_\_\_  
 (Vita Li)


Authorized Signatory :   
 \_\_\_\_\_  
 (Bovey Yang)






Table of Contents	Page
<b>1. SUMMARY OF TEST RESULTS</b>	<b>6</b>
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
<b>2. GENERAL INFORMATION</b>	<b>8</b>
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS	12
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
<b>3. EMC EMISSION TEST</b>	<b>14</b>
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.2 RADIATED EMISSION MEASUREMENT	18
<b>4. CONDUCTED SPURIOUS &amp; BAND EDGE EMISSION</b>	<b>29</b>
4.1 APPLIED PROCEDURES / LIMIT	29
4.2 TEST PROCEDURE	29
4.3 DEVIATION FROM STANDARD	29
4.4 TEST SETUP	29
4.5 EUT OPERATION CONDITIONS	29
4.6 TEST RESULTS	30
<b>5. POWER SPECTRAL DENSITY TEST</b>	<b>39</b>
5.1 APPLIED PROCEDURES / LIMIT	39
5.2 TEST PROCEDURE	39
5.3 DEVIATION FROM STANDARD	39
5.4 TEST SETUP	39
5.5 EUT OPERATION CONDITIONS	39
5.6 TEST RESULTS	40
<b>6. BANDWIDTH TEST</b>	<b>46</b>
6.1 APPLIED PROCEDURES / LIMIT	46
6.2 TEST PROCEDURE	46
6.3 DEVIATION FROM STANDARD	46
6.4 TEST SETUP	46
6.5 EUT OPERATION CONDITIONS	46
6.6 TEST RESULTS	47



Table of Contents	Page
<b>7. PEAK OUTPUT POWER TEST</b>	<b>53</b>
7.1 APPLIED PROCEDURES / LIMIT	53
7.2 TEST PROCEDURE	53
7.3 DEVIATION FROM STANDARD	53
7.4 TEST SETUP	53
7.5 EUT OPERATION CONDITIONS	53
7.6 TEST RESULTS	54
<b>8. ANTENNA REQUIREMENT</b>	<b>55</b>
8.1 STANDARD REQUIREMENT	55
8.2 EUT ANTENNA	55
<b>APPENDIX - PHOTOS OF TEST SETUP</b>	<b>56</b>





**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	13 July. 2016	STS1606147F01	ALL	Initial Issue





## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:  
KDB 558074 D01 DTS Meas Guidance v03r04

FCC Part 15.247,Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)(3)	Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.205	Radiated Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

### NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

(2) all tests are according to ANSI C63.10-2013 .



## 1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F., Building B, Zhuoke Science Park, No.190,Chongqing Road,  
Fuyong Street, Bao'an District, Shenzhen, Guangdong,China

CNAS Registration No.: L7649;

FCC Registration No.: 842334; IC Registration No.: 12108A-1

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	$\pm 2.88\text{dB}$
2	Conducted Emission (150KHz-30MHz)	$\pm 2.67\text{dB}$
3	RF power,conducted	$\pm 0.70\text{dB}$
4	Spurious emissions,conducted	$\pm 1.19\text{dB}$
5	All emissions,radiated(<30M) (9KHz-30MHz)	$\pm 2.45\text{dB}$
6	All emissions,radiated(<1G) 30MHz-200MHz	$\pm 2.83\text{dB}$
7	All emissions,radiated(<1G) 200MHz-1000MHz	$\pm 2.94\text{dB}$
8	All emissions,radiated(>1G)	$\pm 3.03\text{dB}$
9	Temperature	$\pm 0.5^{\circ}\text{C}$
10	Humidity	$\pm 2\%$



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Wireless Adapter	
Trade Name	CARDKING	
Model Name	KW-3016N	
Series Model	KW-3015N	
Model Difference	Only different in model name	
Product Description	The EUT is a Wireless Adapter	
	Operation Frequency:	802.11b/g/n 20: 2412~2462 MHz
	Modulation Type:	CCK/BPSK/QPSK/16QAM
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20MHz):300/150/144.44/130/ 117/115.56/104/86.67/78/52/6.5Mbps
	Number Of Channel	802.11b/g/n20: 11CH
	Antenna Designation:	Please see Note 3.
	Antenna Gain (dBi)	18.01 dBi
	Duty Cycle	>98%
Channel List	Please refer to the Note 2.	
Power rating	DC 5V, 500mA	
Hardware version number	RT3072 v1.2	
Software version number	N/A	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

- 1 For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.





2

802.11b/g/n(20MHz)	
Channel	Frequency
01	2412
02	2417
03	2422
04	2427
05	2432
06	2437
07	2442
08	2447
09	2452
10	2457
11	2462

3 Note:  
 In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:  
 Carrier Frequency Channel

2.4GHz Test Frequency:

For 802.11b/g/n (HT20)	
Channel	Freq.(MHz)
01	2412
06	2437
11	2462

3 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.  
 For devices having two outputs driving a cross-polarized pair of antennas, see Attachment 662911 D02 of this publication for additional guidance.

d) *Unequal antenna gains, with equal transmit powers.* For antenna gains given by G1, G2, ..., GN dBi

(i) If transmit signals are *correlated*, then Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / NANT]$  dBi [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

(ii) If all transmit signals are *completely uncorrelated*, then Directional gain =  $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10}) / NANT]$  dBi

Not: If transmit signals are *correlated*, then Directional gain.

ANT-A=15 dBi  
 ANT-B=15 dBi

Total gain= $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / NANT]$  dBi  
 = $10 * \text{LOG}_{10}((10^{(15/20)} + 10^{(15/20)})^2 / 2) = 18.01$  dBi

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Total (dBi)
	CARDKING	KW-3016N	Onboard Antenna	N/A	ANT.A=15 ANT.B=15	18.01



## 2.2 DESCRIPTION OF TEST MODES

Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11b CH1	1 Mbps
Mode 2	TX IEEE 802.11b CH6	1 Mbps
Mode 3	TX IEEE 802.11 b CH11	1 Mbps
Mode 4	TX IEEE 802.11g CH1	6 Mbps
Mode 5	TX IEEE 802.11g CH6	6 Mbps
Mode 6	TX IEEE 802.11g CH11	6 Mbps
Mode 7	TX IEEE 802.11n HT20 CH1	MCS 0
Mode 8	TX IEEE 802.11n HT20 CH6	MCS 0
Mode 9	TX IEEE 802.11n HT20 CH11	MCS 0

Note:


- (1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported
- (2) We have be tested for all avaiable U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.
- (3) The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

### AC Conducted Emission


Test Case	
AC Conducted Emission	Mode10: Keeping TX + WLAN Link

### 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

#### Radiation Test Set



#### Conduction Test Set





## 2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-1	Wireless Adapter	CARDKING	KW-3016N	N/A	EUT
E-2	PC	4CV428DQXR	500-320cx	N/A	N/A
C-2	AC (PC Adapter)	LITEON	PA-1650-86	3X06399004	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable (FTP)	NO	100cm	N/A
C-2	USB Cable (FTP)	NO	100cm	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



## 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

## Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Spectrum Analyzer	Agilent	E4407B	MY50140340	2015.10.25	2016.10.24
Test Receiver	R&S	ESCI	101427	2015.10.25	2016.10.24
Bilog Antenna	TESEQ	CBL6111D	34678	2015.11.25	2016.11.24
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1343	2016.03.06	2017.03.05
Horn Antenna	Schwarzbeck	BBHA 9170	9170-0741	2016.03.06	2017.03.05
50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2016.06.06	2017.06.05
PreAmplifier	Agilent	8449B	60538	2015.10.25	2016.10.24
Loop Antenna	ARA	PLA-1030/B	1029	2016.06.08	2017.06.07
Preamplifier	Agilent	8449B	60538	2015.11.05	2016.11.05
Low frequency cable	EM	R01	N/A	N/A	N/A
High frequency cable	SCHWARZBECK	AK9515H	SN-96286/96287	N/A	N/A

## Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	102086	2015.11.20	2016.11.19
LISN	R&S	ENV216	101242	2015.10.25	2016.10.24
LISN	EMCO	3810/2NM	000-23625	2015.10.25	2016.10.24
Conduction Cable	EM	C01	N/A	N/A	N/A

## RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2015.10.25	2016.10.24
Spectrum Analyzer	Agilent	E4407B	MY50140340	2015.10.25	2016.10.24
Signal Analyzer	Agilent	N9020A	MY49100060	2015.11.18	2016.11.17



### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

operating frequency band. In case the emission fall within the restricted band specified on Part 15.207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

### 3.1.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 TEST SETUP



- Note: 1.Support units were connected to second LISN.**  
**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**

### 3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.5 TEST RESULT


Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	L
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 10

Frequency (MHz)	Reading (dBUV)	Correct Factor(dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Remark
0.1710	41.08	9.23	50.31	64.91	-14.60	QP
0.1710	26.04	9.23	35.27	54.91	-19.64	AVG
0.2250	33.09	9.20	42.29	62.63	-20.34	QP
0.2250	19.82	9.20	29.02	52.63	-23.61	AVG
0.3913	32.40	9.41	41.81	58.04	-16.23	QP
0.3913	19.70	9.41	29.11	48.04	-18.93	AVG
3.4714	24.27	9.26	33.53	56.00	-22.47	QP
3.4714	15.44	9.26	24.70	46.00	-21.30	AVG
9.7084	25.67	9.48	35.15	60.00	-24.85	QP
9.7084	17.77	9.48	27.25	50.00	-22.75	AVG
24.0004	27.52	9.75	37.27	60.00	-22.73	QP
24.0004	26.66	9.75	36.41	50.00	-13.59	AVG

Remark:

1. Margin = Result (Result =Reading + Factor )–Limit

100.0 dBUV








Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	N
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 10

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1703	39.94	9.23	49.17	64.95	-15.78	QP
0.1703	25.13	9.23	34.36	54.95	-20.59	AVG
0.1833	37.77	9.23	47.00	64.33	-17.33	QP
0.1833	23.85	9.23	33.08	54.33	-21.25	AVG
0.3914	30.97	9.23	40.20	58.03	-17.83	QP
0.3914	18.84	9.23	28.07	48.03	-19.96	AVG
3.4408	22.73	9.26	31.99	56.00	-24.01	QP
3.4408	13.78	9.26	23.04	46.00	-22.96	AVG
9.6544	27.40	9.39	36.79	60.00	-23.21	QP
9.6544	19.97	9.39	29.36	50.00	-20.64	AVG
24.0014	26.99	9.87	36.86	60.00	-23.14	QP
24.0014	26.21	9.87	36.08	50.00	-13.92	AVG

Remark:

1. Margin = Result (Result =Reading + Factor )–Limit

100.0 dBuV





### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 RADIATED EMISSION LIMITS

in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15. 205(a)&209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10 <sup>th</sup> carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz /3MHz

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2430 MHz Upper Band Edge: 2450 to 2500 MHz
RB / VB (emission in restricted band)	1 MHz /3MHz



Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

### 3.2.2 TEST PROCEDURE


- a. The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

**Note:**


Both horizontal and vertical antenna polarities were tested and performed test to three orthogonal axis. The worst case emissions were reported

### 3.2.3 TEST SETUP


#### (A) Radiated Emission Test-Up Frequency Below 30MHz



#### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



#### (C) Radiated Emission Test-Up Frequency Above 1GHz



### 3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



## 3.2.5 TEST RESULT

9KHz-30MHz

Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V From PC
Test Mode :	TX Mode	Polarization :	--


Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F	Test Result
--	--	--	--	--	PASS
--	--	--	--	--	PASS

## Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log(\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.





(30MHz - 1000MHz)


Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V From PC
Test Mode :	Mode 1/2/3/4/5/6/7/8/9 (Mode 3-1M worst mode)	Polarization :	Horizontal

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
47.8260	41.83	-20.36	21.47	40.00	-18.53	QP
89.5900	44.31	-20.30	24.01	43.50	-19.49	QP
141.8262	42.74	-17.59	25.15	43.50	-18.35	QP
236.6447	49.89	-17.99	31.90	46.00	-14.10	QP
472.1760	40.73	-9.69	31.04	46.00	-14.96	QP
962.1622	35.02	-0.12	34.90	54.00	-19.10	QP

Remark:

1. Margin = Result (Result =Reading + Factor )-Limit

80.0 dBuV/m






Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V From PC
Test Mode :	Mode 1/2/3/4/5/6/7/8/9 (Mode 3-1M worst mode)	Polarization :	Vertical

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
48.6720	37.93	-20.80	17.13	40.00	-22.87	QP
107.8876	39.04	-18.52	20.52	43.50	-22.98	QP
141.3298	39.19	-17.58	21.61	43.50	-21.89	QP
235.8164	47.84	-18.06	29.78	46.00	-16.22	QP
472.1760	42.38	-9.69	32.69	46.00	-13.31	QP
993.0113	35.37	-0.10	35.27	54.00	-18.73	QP

Remark:.

1. Margin = Result (Result =Reading + Factor )–Limit

80.0 dBuV/m





(1-25GHz)

## 802.11b Low Channel

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	Type	
3265.10	49.94	-9.80	40.14	74.00	-33.86	PK	Vertical
3265.10	39.93	-9.80	30.13	54.00	-23.87	AV	Vertical
3265.06	49.91	-9.80	40.11	74.00	-33.89	PK	Horizontal
3265.06	39.95	-9.80	30.15	54.00	-23.85	AV	Horizontal
4803.78	60.22	-3.56	56.66	74.00	-17.34	PK	Vertical
4803.78	50.25	-3.56	46.69	54.00	-7.31	AV	Vertical
4804.81	60.23	-3.56	56.67	74.00	-17.33	PK	Horizontal
4804.81	50.22	-3.56	46.66	54.00	-7.34	AV	Horizontal
5360.09	47.17	-2.34	44.83	74.00	-29.17	PK	Vertical
5360.09	39.16	-2.34	36.82	54.00	-17.18	AV	Vertical
5360.07	47.22	-2.34	44.88	74.00	-29.12	PK	Horizontal
5360.07	39.13	-2.34	36.79	54.00	-17.21	AV	Horizontal
11036.22	41.91	10.20	52.11	74.00	-21.89	PK	Vertical
11036.22	31.85	10.20	42.05	54.00	-11.95	AV	Vertical
11036.47	41.86	10.20	52.06	74.00	-21.94	PK	Horizontal
11036.47	31.89	10.20	42.09	54.00	-11.91	AV	Horizontal
13299.62	41.69	12.20	53.89	74.00	-20.11	PK	Vertical
13299.62	31.76	12.20	43.96	54.00	-10.04	AV	Vertical
13299.74	41.76	12.20	53.96	74.00	-20.04	PK	Horizontal
13299.74	30.71	12.20	42.91	54.00	-11.09	AV	Horizontal
17998.14	31.87	23.10	54.97	74.00	-19.03	PK	Vertical
17998.14	21.92	23.10	45.02	54.00	-8.98	AV	Vertical
17998.01	31.89	23.10	54.99	74.00	-19.01	PK	Horizontal
17998.01	21.95	23.10	45.05	54.00	-8.95	AV	Horizontal





## 802.11b Mid Channel

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3265.00	49.88	-9.80	40.08	74.00	-33.92	PK	Vertical
3265.00	39.84	-9.80	30.04	54.00	-23.96	AV	Vertical
3264.95	49.82	-9.80	40.02	74.00	-33.98	PK	Horizontal
3264.95	39.86	-9.80	30.06	54.00	-23.94	AV	Horizontal
4874.76	60.17	-3.56	56.61	74.00	-17.39	PK	Vertical
4874.76	50.17	-3.56	46.61	54.00	-7.39	AV	Vertical
4874.70	60.22	-3.56	56.66	74.00	-17.34	PK	Horizontal
4874.70	50.17	-3.56	46.61	54.00	-7.39	AV	Horizontal
5359.97	47.08	-2.34	44.74	74.00	-29.26	PK	Vertical
5359.97	39.10	-2.34	36.76	54.00	-17.24	AV	Vertical
5360.00	47.14	-2.34	44.80	74.00	-29.20	PK	Horizontal
5360.00	39.03	-2.34	36.69	54.00	-17.31	AV	Horizontal
11036.11	41.83	10.20	52.03	74.00	-21.97	PK	Vertical
11036.11	31.80	10.20	42.00	54.00	-12.00	AV	Vertical
11036.11	41.84	10.20	52.04	74.00	-21.96	PK	Horizontal
11036.11	31.82	10.20	42.02	54.00	-11.98	AV	Horizontal
13299.71	41.61	12.20	53.81	74.00	-20.19	PK	Vertical
13299.71	31.66	12.20	43.86	54.00	-10.14	AV	Vertical
13299.62	41.70	12.20	53.90	74.00	-20.10	PK	Horizontal
13299.62	30.64	12.20	42.84	54.00	-11.16	AV	Horizontal
17998.13	31.82	23.10	54.92	74.00	-19.08	PK	Vertical
17998.13	21.86	23.10	44.96	54.00	-9.04	AV	Vertical
17998.00	31.85	23.10	54.95	74.00	-19.05	PK	Horizontal
17998.00	21.88	23.10	44.98	54.00	-9.02	AV	Horizontal



## 802.11b High Channel

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	Type	
3265.07	49.81	-9.80	40.01	74.00	-33.99	PK	Vertical
3265.07	39.74	-9.80	29.94	54.00	-24.06	AV	Vertical
3265.04	49.72	-9.80	39.92	74.00	-34.08	PK	Horizontal
3265.04	39.79	-9.80	29.99	54.00	-24.01	AV	Horizontal
4924.82	60.05	-3.56	56.49	74.00	-17.51	PK	Vertical
4924.82	50.09	-3.56	46.53	54.00	-7.47	AV	Vertical
4924.78	60.10	-3.56	56.54	74.00	-17.46	PK	Horizontal
4924.78	50.04	-3.56	46.48	54.00	-7.52	AV	Horizontal
5360.04	46.99	-2.34	44.65	74.00	-29.35	PK	Vertical
5360.04	38.98	-2.34	36.64	54.00	-17.36	AV	Vertical
5360.03	47.04	-2.34	44.70	74.00	-29.30	PK	Horizontal
5360.03	38.98	-2.34	36.64	54.00	-17.36	AV	Horizontal
11036.21	41.74	10.20	51.94	74.00	-22.06	PK	Vertical
11036.21	31.73	10.20	41.93	54.00	-12.07	AV	Vertical
11036.19	41.77	10.20	51.97	74.00	-22.03	PK	Horizontal
11036.19	31.77	10.20	41.97	54.00	-12.03	AV	Horizontal
13299.70	41.58	12.20	53.78	74.00	-20.22	PK	Vertical
13299.70	31.56	12.20	43.76	54.00	-10.24	AV	Vertical
13299.70	41.65	12.20	53.85	74.00	-20.15	PK	Horizontal
13299.70	30.60	12.20	42.80	54.00	-11.20	AV	Horizontal
17998.22	31.74	23.10	54.84	74.00	-19.16	PK	Vertical
17998.22	21.76	23.10	44.86	54.00	-9.14	AV	Vertical
17998.09	31.78	23.10	54.88	74.00	-19.12	PK	Horizontal
17998.09	21.77	23.10	44.87	54.00	-9.13	AV	Horizontal

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- Scan with 802.11b, 802.11g, 802.11n (HT-20), the worst case is 802.11b.  
Emission Level = Meter Reading + Factor  
Margin = Limit - Emission Level
- The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



## 3.2.6 TEST RESULTS (Band edge)


Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
802.11 b							
2400.0	69.08	-12.99	56.09	74	-17.91	PK	Vertical
2400.0	54.91	-12.99	41.92	54	-12.08	AV	Vertical
2400.0	70.09	-12.99	57.10	74	-16.90	PK	Horizontal
2400.0	54.04	-12.99	41.05	54	-12.95	AV	Horizontal
2483.5	70.90	-12.78	58.12	74	-15.88	PK	Vertical
2483.5	53.95	-12.78	41.17	54	-12.83	AV	Vertical
2483.5	71.02	-12.78	58.24	74	-15.76	PK	Horizontal
2483.5	53.98	-12.78	41.20	54	-12.80	AV	Horizontal
802.11 g							
2400.0	67.87	-12.99	54.88	74	-19.12	PK	Vertical
2400.0	54.01	-12.99	41.02	54	-12.98	AV	Vertical
2400.0	67.01	-12.99	54.02	74	-19.98	PK	Horizontal
2400.0	54.88	-12.99	41.89	54	-12.11	AV	Horizontal
2483.5	70.76	-12.78	57.98	74	-16.02	PK	Vertical
2483.5	53.35	-12.78	40.57	54	-13.43	AV	Vertical
2483.5	71.23	-12.78	58.45	74	-15.55	PK	Horizontal
2483.5	53.67	-12.78	40.89	54	-13.11	AV	Horizontal



802.11 n20							
2400.0	67.01	-12.99	54.02	74	-19.98	PK	Vertical
2400.0	53.96	-12.99	40.97	54	-13.03	AV	Vertical
2400.0	66.97	-12.99	53.98	74	-20.02	PK	Horizontal
2400.0	53.99	-12.99	41.00	54	-13.00	AV	Horizontal
2483.5	67.11	-12.78	54.33	74	-19.67	PK	Vertical
2483.5	53.98	-12.78	41.20	54	-12.80	AV	Vertical
2483.5	66.95	-12.78	54.17	74	-19.83	PK	Horizontal
2483.5	62.31	-12.78	49.53	74	-24.47	AV	Horizontal

Low measurement frequencies is range from 2310 to 2400 MHz, high measurement frequencies is range from 2483.5 to 2500 MHz.

Only show the worst point data of the emissions in the frequency 2310-2400 MHz and 2483.5-2500 MHz.



#### 4. CONDUCTED SPURIOUS & BAND EDGE EMISSION

##### 4.1 APPLIED PROCEDURES / LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

##### 4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold


For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2430 MHz Upper Band Edge: 2450 to 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

##### 4.3 DEVIATION FROM STANDARD

No deviation.

##### 4.4 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

##### 4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




4.6 TEST RESULTS

NOT:1. Transmissions Level (dBm)=(Antenna A) Port. Antenna A Signal strength strongest.


2. Antenna A and Antenna B have test, only provides the worst antenna of A plot.

Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V From PC
Test Mode :	TX b Mode /CH01, CH06, CH11		

CH 01




CH 06






CH 11






Band edge

CH 01



CH 11









Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V From PC
Test Mode :	TX g Mode /CH01, CH06, CH11		

CH 01




CH06






CH 11






Band edge

CH 01




CH11






Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V From PC
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		

CH 01




CH 06






CH 11






Band edge

CH 01



CH 11





## 5. POWER SPECTRAL DENSITY TEST

### 5.1 APPLIED PROCEDURES / LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	$\leq 8$ dBm (RBW $\geq 3$ kHz)	2400-2483.5	PASS

### 5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the  $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$ .
4. Set the  $\text{VBW} \geq 3 \times \text{RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 5.3 DEVIATION FROM STANDARD

No deviation.

### 5.4 TEST SETUP



### 5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULTS


Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V From PC
Test Mode :	TX b Mode /CH01, CH06, CH11		

- NOT:1. Transmissions Level (dBm)=(Antenna A) Port. Antenna A Signal strength strongest.  
 2. Antenna A and Antenna B have test, only provides the worst antenna of A plot.  
 3. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

$$\text{LIMIT} = 8 \text{ dBm} - (18.01 \text{ dBi} - 6 \text{ dBi}) = 8 \text{ dBm} - 12 = -4 \text{ dBm}$$

Frequency	Power Density			Limit (dBm)	Result
	ANT A (dBm)	ANT B (dBm)	TOTAL (dBm)		
2412	-14.31	-14.54	-11.41	≤4	PASS
2437	-14.89	-14.96	-11.92	≤4	PASS
2462	-14.51	-14.37	-11.43	≤4	PASS


**TX CH01**








### TX CH06



### TX CH11






Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V From PC
Test Mode :	TX g Mode /CH01, CH06, CH11		

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

$$\text{LIMIT} = 8 \text{ dBm} - (18.01 \text{ dBi} - 6 \text{ dBi}) = 8 \text{ dBm} - 12 = -4 \text{ dBm}$$


Frequency	Power Density			Limit (dBm)	Result
	ANT A (dBm)	ANT B (dBm)	TOTAL (dBm)		
2412	-16.94	-17.01	-13.97	≤4	PASS
2437	-14.53	-14.67	-11.59	≤4	PASS
2462	-16.66	-16.75	-13.69	≤4	PASS

**TX CH01**






### TX CH06



### TX CH11






Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V From PC
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

$$\text{LIMIT} = 8 \text{ dBm} - (18.01 \text{ dBi} - 6 \text{ dBi}) = 8 \text{ dBm} - 12 = -4 \text{ dBm}$$


Frequency	Power Density			Limit (dBm)	Result
	ANT A (dBm)	ANT B (dBm)	TOTAL (dBm)		
2412	-17.72	-17.84	-14.77	≤ -4	PASS
2437	-13.85	-14.12	-10.97	≤ -4	PASS
2462	-16.88	-16.94	-13.90	≤ -4	PASS

**TX CH01**






### TX CH06



### TX CH11



## 6. BANDWIDTH TEST

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

### 6.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq$ 3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB.

### 6.3 DEVIATION FROM STANDARD

No deviation.

### 6.4 TEST SETUP



### 6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



6.6 TEST RESULTS


Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V From PC
Test Mode :	TX b Mode /CH01, CH06, CH11		

Remark: PEAK DETECTOR IS USED

- NOT:1.Transmissions Level (dBm)=(Antenna A) Port. Antenna A Signal strength strongest.  
 2. Antenna A and Antenna B have test, only provides the worst antenna of A plot.


Frequency	6dB Bandwidth (MHz)		Channel Separation (KHz)	Result
	ANTENNA -A	ANTENNA -B		
2412 MHz	10.13	10.11	≥500KHz	PASS
2437 MHz	10.15	10.13	≥500KHz	PASS
2462 MHz	10.14	10.12	≥500KHz	PASS

TX CH 01






TX CH 06



TX CH 11








Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V From PC
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)		Channel Separation (KHz)	Result
	ANTENNA -A	ANTENNA -B		
2412 MHz	16.31	16.28	≥500KHz	PASS
2437 MHz	15.12	15.10	≥500KHz	PASS
2462 MHz	15.72	15.70	≥500KHz	PASS

TX CH 01






TX CH 06



TX CH 11






Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V From PC
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)		Channel Separation (KHz)	Result
	ANTENNA -A	ANTENNA -B		
2412 MHz	17.56	17.53	≥500KHz	PASS
2437 MHz	15.11	15.10	≥500KHz	PASS
2462 MHz	16.32	16.31	≥500KHz	PASS

TX CH 01






TX CH 06



TX CH 11





## 7. PEAK OUTPUT POWER TEST

### 7.1 APPLIED PROCEDURES / LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

### 7.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power Sensor&PC

### 7.3 DEVIATION FROM STANDARD

No deviation.

### 7.4 TEST SETUP



### 7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



## 7.6 TEST RESULTS

Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V From PC

Note:

- (1) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

$$\text{LIMIT} = 30 \text{ dBm} - (18.01 \text{ dBi} - 6 \text{ dBi}) = 30 \text{ dBm} - 12 = 18 \text{ dBm}$$

**TX 802.11b Mode**

Test Channe	Frequency	Peak Conducted Output Power	Peak Conducted Output Power	Conducted Output Power	LIMIT
	(MHz)	(dBm)ANT A	(dBm)ANT B	PK(dBm)	dBm
CH01	2412	9.52	9.28	12.14	18
CH06	2437	9.23	9.37	12.31	18
CH11	2462	9.32	9.32	12.33	18

**TX 802.11g Mode**

Test Channe	Frequency	Peak Conducted Output Power	Peak Conducted Output Power	Conducted Output Power	LIMIT
	(MHz)	(dBm)ANT A	(dBm)ANT B	PK(dBm)	dBm
CH01	2412	8.20	8.14	11.18	18
CH06	2437	8.25	8.12	11.20	18
CH11	2462	8.34	8.21	11.29	18

**TX 802.11n20 Mode**

Test Channe	Frequency	Peak Conducted Output Power	Peak Conducted Output Power	Conducted Output Power	LIMIT
	(MHz)	(dBm)ANT A	(dBm)ANT B	PK(dBm)	dBm
CH01	2412	8.11	8.10	11.12	18
CH06	2437	8.86	8.76	11.82	18
CH11	2462	8.00	8.04	11.03	18



## 8. ANTENNA REQUIREMENT

### 8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 8.2 EUT ANTENNA



The EUT antenna is Onboard Antenna. It comply with the standard requirement.





APPENDIX - PHOTOS OF TEST SETUP

**Radiated Measurement Photos**







### Conducted Measurement Photos



※※※※END OF THE REPORT※※※※