

RF EXPOSURE REPORT
for
TIAN RUI HOLDINGS GROUP CO.,LTD
WIRELESS MIC
Model Number: 202.2

FCC ID: 2AHS62022

Prepared for : TIAN RUI HOLDINGS GROUP CO.,LTD
Address : Feiyang Industrial Zone, Baiyun District, Guangzhou, China

Prepared by : Shenzhen BCTC Technology Co., Ltd.
Address : No.101,Yousong Road, Longhua New District,
Shenzhen,China

1. RF EXPOSURE EVALUATION

Test Result of RF Exposure Evaluation

According to the KDB-447498 D01 V05, FCC 47CFR § 2.1093 the following RF exposure evaluation shall to demonstrate RF exposure compliance.

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right]$$

* $[\sqrt{f(\text{GHz})}]$

	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Maximum Output Power: mW	Separation distance mm	RF exposure
202.2MHz	-7.5 ±1.0	-6.5	0.224	5	0.02

The Max RF exposure is 0.02

Threshold at which no SAR required is ≤ 3.0 for 1-g SAR, Separation distance is 5mm.

Conclusion:

So no SAR is required.