


Label: silk-screen

Size: 124*80mm



zigbee
certified
product

SRPF-ZG9105-50CCT
ZigBee Dimmable Driver
LED CLASS 2 (CLASSE 2) POWER SUPPLY

0.5-1.5mm² (AWG20-16)
9mm(0.35in)













Prated	50W max				Output Voltage				6-48VDC			
INPUT	100-240V~ 0.6A 50/60Hz				Standby Power(W)				<0.5W			
	277V~ 0.22A 50/60Hz				tc°C				85°C			
	(277V~for North America only)				ta°C				-20~45°C			
					λ				>0.95@230VAC			
Irated	1500mA	1400mA	1300mA	1200mA	1100mA	1000mA	900mA	800mA				
Output Voltage	6-33V	6-36V	6-38.5V	6-41V	6-45V	6-48V	6-48V	6-48V				
Irated	700mA	600mA	500mA	450mA	400mA	350mA	300mA	250mA				
Output Voltage	6-48V	6-48V	6-48V	6-48V	6-48V	6-48V	6-48V	6-48V				

V Voltage Selection

● If output LED voltage > 16V DC
○ If output LED voltage ≤ 16V DC
This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: 1) this device may not cause harmful interference, and 2) this device must accept any interference received, including interference that may cause undesired operation.
FCC ID : ZAHST-SRPFZG9105
Made in China

LED Current Selection

<table border="0"> <tr><td>250mA</td><td>●●●●</td><td>800mA</td><td>○●●●</td></tr> <tr><td>300mA</td><td>●●●○</td><td>900mA</td><td>○●●○</td></tr> <tr><td>350mA</td><td>●●○●</td><td>1000mA</td><td>○●○●</td></tr> <tr><td>400mA</td><td>●●○○</td><td>1100mA</td><td>○●○○</td></tr> <tr><td>450mA</td><td>●●○●</td><td>1200mA</td><td>○●○●</td></tr> <tr><td>500mA</td><td>●●○○</td><td>1300mA</td><td>○●○○</td></tr> <tr><td>600mA</td><td>●○○●</td><td>1400mA</td><td>○○○●</td></tr> <tr><td>700mA</td><td>●○○○</td><td>1500mA</td><td>○○○○</td></tr> </table>	250mA	●●●●	800mA	○●●●	300mA	●●●○	900mA	○●●○	350mA	●●○●	1000mA	○●○●	400mA	●●○○	1100mA	○●○○	450mA	●●○●	1200mA	○●○●	500mA	●●○○	1300mA	○●○○	600mA	●○○●	1400mA	○○○●	700mA	●○○○	1500mA	○○○○	
250mA	●●●●	800mA	○●●●																														
300mA	●●●○	900mA	○●●○																														
350mA	●●○●	1000mA	○●○●																														
400mA	●●○○	1100mA	○●○○																														
450mA	●●○●	1200mA	○●○●																														
500mA	●●○○	1300mA	○●○○																														
600mA	●○○●	1400mA	○○○●																														
700mA	●○○○	1500mA	○○○○																														

NC=None connect Suitable for Damp Locations (CONVIENT AUX EMPLACEMENTS HUMIDES)

LED OUTPUT

NC
NC
NC
NC
NC
+
WW
+
CW-

AC INPUT

FG
L
N