

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

| 1. TROBOOT IN ORMATION | |
|------------------------|---------------------------------|
| Product Description | T711 Stereo Bluetooth Headphone |
| Model Name | BKM300 |
| Series Model | T711, T711TV, T720, T710, T701 |
| FCC ID | 2AHTV-BKM300 |

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation.

3. CALCULATION

P_t=-5.817dBm=0.26mW

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation SAR=(0.26mW / 5mm) .[$\sqrt{2.402\text{GHz}}$)]=0.081<3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.