

80.00mm


MODEL: HD1BT
AM/FM/WB/USB/SiriusXM Ready/BT
12VOLT DC NEG. GROUND
Power Input: DC 12V, --- 15A
USB Output: DC 5V, --- 1A(max)
FCC ID: 2AHU2HD1BT


GRAY --- RED-----RIGHT
(Rear Line Out) WHITE----LEFT

BROWN --- RED-----RIGHT
(Front Line Out) WHITE----LEFT

YELLOW --- RED-----RIGHT
(AUX IN) WHITE----LEFT

BLUE --- PWR AMP TRG






BLACK CONNECTOR

| PIN | DESCRIPTION | PIN | DESCRIPTION |
|-----|------------------------|-----|------------------------|
| 1 | FRONT RIGHT SPEAKER(-) | 13 | N/C |
| 2 | N/C | 14 | N/C |
| 3 | R0,(Factory Remote) | 15 | N/C |
| 4 | R1,(Factory Remote) | 16 | FRONT LEFT SPEAKER(+) |
| 5 | R2,(Factory Remote) | 17 | FRONT LEFT SPEAKER(-) |
| 6 | C4,(Factory Remote) | 18 | FRONT RIGHT SPEAKER(+) |
| 7 | C3,(Factory Remote) | 19 | GROUND |
| 8 | C2,(Factory Remote) | 20 | +12V BATTERY |
| 9 | AUTO_VOL_CTL | 21 | N/C |
| 10 | +12V BATTERY | 22 | C1,(Factory Remote) |
| 11 | GROUND | 23 | C0,(Factory Remote) |
| 12 | +12V ACC SWITCHED | | |

| PIN NO. | WIRE COLOR | DESCRIPTION |
|---------|--------------|------------------------|
| 1 | PURPLE/BLACK | REAR RIGHT SPEAKER (-) |
| 2 | PURPLE | REAR RIGHT SPEAKER (+) |
| 3 | GREEN | REAR LEFT SPEAKER (+) |
| 4 | GREEN/BLACK | REAR LEFT SPEAKER (-) |


*REPLACE FUSE WITH DC32V 15 AMP ATO TYPE FUSE
IMPORTANT: DO NOT BRIDGE (COMBINE) SPEAKER OUTPUTS
FAILURE TO WIRE CORRECTLY MAY CAUSE DAMAGE TO UNIT

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS:
(1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND
(2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRED OPERATION.



asa
ELECTRONICS.
www.asaelectronics.com
MADE IN CHINA

CE ROHS

| | |
|---------------------|---|
| Manufacturer name: | ASA Electronics,LLC. |
| Trade Name: | Jensen |
| Trade Mark (brand): |  |
| Postal address: | 2602 Marina Drive Elkhart,IN 46514 USA |

80.00mm

NOTES :

- 1、本貼紙貼於主機頂面上，表面有磨砂紋(要求背膠粘附性要好，不可翹起、脫落)。
- 2、印刷內容不可有漏印刷,文字歪斜,變型及脫落等狀況。
- 3、溫度範圍：-40~+85度。
- 4、公差範圍：+/-0.2mm。
- 5、符合ROHS。

| AR ELECTRONICS CO.LTD. | | | |
|-------------------------------|-------------|-------|---------------|
| 物料名稱 | MODEL LABEL | 本廠型號 | AWP0825 |
| 尺寸 | 80X80mm | 客戶型號 | HD1BT |
| 材質 | 消銀龍+過膠 | P / N | 90000008XXX01 |
| 背膠 | 高粘性背膠 | 制圖/日期 | 何再峰 5/5/2022 |
| 顏色 | 銀底黑字 | 確認/日期 | |

