

# RF EXPOSURE REPORT

## FOR

<b>Applicant</b>	:	ASA Electronics Shenzhen Limited
<b>Address</b>	:	Room 503, 5/F., Unit A, Skyworth Building, Gaoxin Avenue.1.S., Nanshan District, Shen Zhen
<b>Equipment under Test</b>	:	JENSEN 2-ZONE WALL STEREO
<b>Model No.</b>	:	JWM45, JWM452, RMJWM45, RMJWM452
<b>Trade Mark</b>	:	JENSEN
<b>FCC ID</b>	:	2AHU2JWM452
<b>Manufacturer</b>	:	Good Grace Far East Limited
<b>Address</b>	:	702 Kowloon Building, 555 Nathan Road, Kowloon, Hong Kong

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,  
Dongguan City, Guangdong Province, China, 523808

**Tel:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

### TABLE OF CONTENTS

- Test report declares.....3
- 1. General information..... 5
  - 1.1. Description of Equipment..... 5
  - 1.2. Assess laboratory ..... 5
- 2. RF Exposure evaluation..... 5
  - 2.1. Requirement..... 5
  - 2.2. Calculation Method..... 6
  - 2.3. Estimation Result ..... 6

## TEST REPORT DECLARE

<b>Applicant</b>	:	ASA Electronics Shenzhen Limited
<b>Address</b>	:	Room 503, 5/F., Unit A, Skyworth Building, Gaoxin Avenue.1.S., Nanshan District, Shen Zhen
<b>Equipment under Test</b>	:	JENSEN 2-ZONE WALL STEREO
<b>Model No.</b>	:	JWM45, JWM452, RMJWM45, RMJWM452
<b>Trade mark</b>	:	JENSEN
<b>Manufacturer</b>	:	Good Grace Far East Limited
<b>Address</b>	:	702 Kowloon Building, 555 Nathan Road, Kowloon, Hong Kong
<b>Factory 1</b>	:	ACTION INDUSTRIES (MALAYSIA) SDN. BHD
<b>Address</b>	:	2480, Tingkat Perusahaan Enam, Prai Free Trade Zone, 13600 Perai, Penang, Malaysia
<b>Factory 2</b>	:	ACTION ASIA (SHENZHEN) CO., LTD.
<b>Address</b>	:	4 Floor, Block 1, No.25 Jingxing Industrial Park, Jian'an Road, Fuyong Town, Bao'an District, Shenzhen, China

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R20022407-1E3		
<b>Date of Receipt:</b>	Feb. 27, 2020	<b>Date of Test:</b>	Feb. 27, 2020 ~ Mar. 30, 2020

**Prepared By:**

*Sam Li*

**Sam Li/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

### Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Mar. 30, 2020	

## 1. General information

### 1.1. Description of Equipment

EUT* Name	: JENSEN 2-ZONE WALL STEREO
Model Number	: JWM45, JWM452, RMJWM45, RMJWM452
Difference of model number	: They are all the same except for the model name, the model JWM452 is selected for testing.
EUT function description	: Please reference user manual of this device
Power supply	: DC 12V
Radio Specification	: Bluetooth 2.1+EDR
Operation frequency	: 2402MHz-2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data rate	: 1 Mbps, 2 Mbps, 3 Mbps
Antenna Type	: Integral PCB antenna, maximum PK gain: 0 dBi
Sample Type	: Series production

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com)

## 2. RF Exposure evaluation

### 2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

**2.2. Calculation Method**

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(mW/cm^2) = \frac{E^2}{377}$$

- E** = Electric field (V/m)
  - P** = Peak RF output power (mW)
  - G** = EUT Antenna numeric gain (numeric)=
  - d** = Separation distance between radiator and human body (m)
- The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

**2.3. Estimation Result**

Mode	PK Output power (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
Bluetooth Max power	7.54	5.68	0	1	0.001130	1

Note: The estimation distance is 20cm

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold

**END OF REPORT**