

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a Stunt Runner operating at 2.4G Band. The EUT can be powered by DC 6.0V (4 x 1.5V AA batteries). When charging to the vehicle, the EUT stop transmitting. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -6.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -6.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 90.4dB $\mu$ V/m at 3m in the frequency 2408MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -4.83dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 88.0dB $\mu$ V/m at 3m in the frequency 2467MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -7.23dBm

which is within the production variation.

The maximum conducted output power specified is -3dBm= 0.501mW

The source- based time-averaging conducted output power =0.501\* Duty cycle mW <0.501 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 \* 5 / sqrt (2.467) mW

= 9.55 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 15.000ms

Effective period of the cycle = 159.4 $\mu$ s x 4= 637.6  $\mu$ s =0.6376ms

DC =0.6376ms / 15.000ms =0.0425 or 4.25%

---