

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an Stunt Runner operating at 2.4G Band. The EUT can be powered by DC 4.5V (3 x 1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -1.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -1.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 96.3dB μ V/m at 3m in the frequency 2408MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = 1.07dBm
which is within the production variation.

The Minimum peak radiated emission for the EUT is 95.4dB μ V/m at 3m in the frequency 2434MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = 0.17dBm
which is within the production variation.

The maximum conducted output power specified is 2.0dBm= 1.585mW

The source- based time-averaging conducted output power
=1.585mW

The SAR Exclusion Threshold Level:

= $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

= $3.0 \cdot 5 / \text{sqrt}(2.462)$ mW

= 9.56 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

FCC ID: 2AHUVCXT0007