

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is an Iron Claw operating at 2.4G Band. The EUT can be powered by DC 4.5V (3 x 1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal peak radiated output power (e.i.r.p) is: 1.0dBm (tolerance: +/- 3dB).

The normal peak conducted output power is 1.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 96.3 dB μ V/m at 3m in the frequency 2467MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = 1.07dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 94.7dB μ V/m at 3m in the frequency 2408MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -0.53dBm

which is within the production variation.

The maximum conducted output power specified is 4dBm= 2.512mW

The source- based time-averaging conducted output power =2.512mW

The SAR Exclusion Threshold Level:

= $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

= $3.0 \cdot 5 / \text{sqrt}(2.467)$ mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.