

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a Ford Mustang Dark Horse operating at 2.4G Band. The EUT can be powered by DC 3.0V (2 x 1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal peak radiated output power (e.i.r.p) is: -9.0dBm (tolerance: +/- 3dB).

The normal peak conducted output power is -9.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 87.4 dB $\mu$ V/m at 3m in the frequency 2408MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -7.83dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 85.2dB $\mu$ V/m at 3m in the frequency 2434MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -10.03dBm

which is within the production variation.

The maximum conducted output power specified is -6.0dBm= 0.251mW

The source- based time-averaging conducted output power =0.251mW

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 \* 5 / sqrt (2.467) mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.