

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a Track Racer operating at 2.4G Band. The EUT can be powered by DC 3.0V (2 x 1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal peak radiated output power (e.i.r.p) is: -6.0dBm (tolerance: +/- 3dB).

The normal peak conducted output power is -6.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 89.5 dBμV/m at 3m in the frequency 2467MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -5.73dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 88.1dBμV/m at 3m in the frequency 2434MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -7.13dBm

which is within the production variation.

The maximum conducted output power specified is -3dBm= 0.501mW

The source- based time-averaging conducted output power
=0.501mW

The SAR Exclusion Threshold Level:

= $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

= $3.0 \cdot 5 / \text{sqrt}(2.467)$ mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.