



# EMC Test Data

Client: Barracuda Networks	Job Number: JD99428
Model: BNHW028 (Dome)	T-Log Number: T101416
	Project Manager: Christine Krebill
Contact: Gary Liu	Project Coordinator: -
Standard: FCC part 15, RSS-247	Class: N/A

## Maximum Permissible Exposure / SAR Exclusion

### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 4/25/2016

Test Engineer: David Bare

### General Test Configuration

Calculation uses the free space transmission formula:

$$S = (PG)/(4 \pi d^2)$$

Where: S is power density ( $W/m^2$ ), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

### Summary of Results

Device complies with Power Density requirements at 20cm separation:	Yes
If not, required separation distance (in cm):	

### Deviations From The Standard

No deviations were made from the requirements of the standard.



# EMC Test Data

Client: Barracuda Networks	Job Number: JD99428
Model: BNHW028 (Dome)	T-Log Number: T101416
	Project Manager: Christine Krebill
Contact: Gary Liu	Project Coordinator: -
Standard: FCC part 15, RSS-247	Class: N/A

### FCC MPE Calculation

Use: General  
 Antenna: 3.2 dBi Whip

Rated powr plus tolerance

Freq. MHz	EUT Power		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 20 cm mW/cm <sup>2</sup>	MPE Limit at 20 cm mW/cm <sup>2</sup>
	dBm	mW*						
2412	18.0	63.1	0	3.2	18.0	131.83	0.026	1.000
2437	18.0	63.1	0	3.2	18.0	131.83	0.026	1.000
2462	18.0	63.1	0	3.2	18.0	131.83	0.026	1.000

For the cases where S > the MPE Limit

Freq. MHz	S @ 20 cm mW/cm <sup>2</sup>	MPE Limit mW/cm <sup>2</sup>	Distance where S <= MPE Limit
2412	0.026	1.000	3.2cm
2437	0.026	1.000	3.2cm
2462	0.026	1.000	3.2cm

### Industry Canada MPE Calculation

Use: General  
 Antenna: 3.2 dBi Whip

Freq. MHz	EUT Power		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 20 cm mW/cm <sup>2</sup>	MPE Limit at 20 cm mW/cm <sup>2</sup>
	dBm	mW*						
2412	18.0	63.1	0	3.2	18.0	131.83	0.026	0.537
2437	18.0	63.1	0	3.2	18.0	131.83	0.026	0.540
2462	18.0	63.1	0	3.2	18.0	131.83	0.026	0.544

For the cases where S > the MPE Limit

Freq. MHz	Power Density (S) at 20 cm mW/cm <sup>2</sup>	MPE Limit at 20 cm mW/cm <sup>2</sup>	Distance where S <= MPE Limit
2412	0.026	0.537	4.4cm
2437	0.026	0.540	4.4cm
2462	0.026	0.544	4.4cm