



Report No: FCC 1607059-01 File reference No: 2016-07-30

Applicant: PHIMAX INTERNATIONAL LIMITED

Product: WiFi Speaker

Model No: X10

Trademark: PHIMAX

Test Standards: FCC Part 15.247

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10, FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: July 30, 2016

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Room 512-519, 5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen, Guangdong, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Report No.: FCC1607059-01 Page 2 of 104

Date: 2016-07-30



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAL-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

Page 3 of 104

Report No.: FCC1607059-01

Date: 2016-07-30



Test Report Conclusion Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	8
3.1	Summary of Test Results	8
3.2	Test Standards.	8
4.0	EUT Modification	8
5.0	Power Line Conducted Emission Test.	9
5.1	Schematics of the Test.	9
5.2	Test Method and Test Procedure.	9
5.3	Configuration of the EUT.	9
5.4	EUT Operating Condition.	10
5.5	Conducted Emission Limit.	10
5.6	Test Result.	10
6.0	Radiated Emission test.	13
5.1	Test Method and Test Procedure	13
6.2	Configuration of the EUT	13
6.3	EUT Operation Condition.	13
6.4	Radiated Emission Limit.	14
7.0	6dB and Bandwidth Measurement	38
8.0	Maximum Output Power	58
9.0	Power Spectral Density Measurement.	61
10.0	Out of Band Measurement	79
11.0	Antenna Requirement	90
12.0	FCC ID/IC Label.	91
13.0	Photo of Test Setup and EUT View.	92

Date: 2016-07-30



Page 4 of 104

1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Room 512-519,5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen,

Guangdong China

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: PHIMAX INTERNATIONAL LIMITED

Address: Room 1303, No.95 XinYan Building YanLing Road TianHe Distirct, Guangzhou, China

Telephone: 020-38937810

Fax: --

1.3 Description of EUT

Product: WiFi Speaker

Manufacturer: SHENZHEN PHIMAX INTERNATIONAL COMPANY LTD

Address: Room 401, 4 Floor Office Building ,ZhongKeNuo Indurstry , HeZhou of

BaoAn Distirct, Shenzhen, China

Brand Name: PHIMAX Model Number: X10

Additional Model Number: N/A

Type of Modulation IEEE 802.11b : DSSS (CCK, QPSK, DBPSK)

IEEE 802.11g/n (HT20/40): OFDM(64QAM, 16QAM, QPSK, BPSK)

Frequency range IEEE802.11b/g/n (HT20/40): 2412-2462MHz,IEEE802.11n (HT40) : 2422-2452MHz

Channel Spacing 5MHz for IEEE 802.11b/g/n(HT20/40)
Air Data Rate IEEE 802.11b: 11, 5.5, 2, 1 Mbps

IEEE 802.11g: 54, 48,36, 24, 18, 12, 9, 6 Mbps

IEEE 802.11n HT20/40: 150, 135, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6.5

Mbps

Frequency Selection By software

Channel Number IEEE 802.11b/g/n (HT20): 11 Channels; IEEE 802.11n (HT40): 7 Channels,

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: FCC1607059-01 Page 5 of 104

Date: 2016-07-30



Antenna: Integral Antenna and the maximum Gain of this antenna is 3.58dBi;

Power Adapter Model No.: BX-1802500

Input: AC100-240V, 50/60Hz, 1.5A; Output: 18V, 2.5A

Submitted Sample: 2 Samples

Test Duration 1.5

2016-07-15 to 2016-07-29

Test Uncertainty 1.6

> Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty =4.7dB

1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

Page 6 of 104

Report No.: FCC1607059-01

Date: 2016-07-30



2.0 Test Equipments					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2015-08-22	2016-08-21
TWO Line-V-NETW	R&S	EZH3-Z5	100294	2015-08-22	2016-08-21
TWO Line-V-NETW	R&S	EZH3-Z5	100253	2015-08-22	2016-08-21
Ultra Broadband ANT	R&S	HL562	100157	2015-08-23	2016-08-22
ESDV Test Receiver	R&S	ESDV	100008	2015-08-22	2016-08-21
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2015-08-22	2016-08-21
System Controller	CT	SC100	-		
Printer	EPSON	РНОТО ЕХЗ	CFNH234850		
Computer	IBM	8434	1S8434KCE99BLXLO*	-	-
Loop Antenna	EMCO	6502	00042960	2015-08-23	2016-08-22
ESPI Test Receiver	R&S	ESI26	838786/013	2015-08-22	2016-08-21
3m OATS			N/A	2015-08-24	2016-08-23
Horn Antenna	R&S	BBHA 9170	BBHA9170265	2015-08-24	2016-08-23
Horn Antenna	R&S	BBHA 9120D	9120D-631	2015-08-24	2016-08-23
Power meter	Anritsu	ML2487A	6K00003613	2015-08-22	2016-08-21
Power sensor	Anritsu	MA2491A	32263	2015-08-22	2016-08-21
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2015-08-23	2016-08-21
LISN	AFJ	LS16C	10010947251	2015-08-22	2016-08-21
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2015-08-23	2016-08-22
9*6*6 Anechoic			N/A	2015-08-24	2016-08-23
EMI Test Receiver	RS	ESCS30	100139	2015-08-22	2016-08-21

Date: 2016-07-30



Page 7 of 104

3. DESCRIPTION OF TEST MODES

IEEE 802.11b, 802.11g, 802.11n (HT20) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 11Mbps data rate (worst case) was chosen for full testing. IEEE 802.11g mode: 54Mbps data rate (worst case) was chosen for full testing. IEEE 802.11n (HT20) mode: 6.5Mbps data rate (worst case) were chosen for full testing (dutycycle>98%)

IEEE 802.11n (HT40) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2422
Middle	2437
High	2452

IEEE 802.11n (HT40) mode: 6.5Mbps data rate (worst case) were chosen for full testing

The worst-case data rates are determined according to the description above, based on the investigations by measuring the PSD and average power across all the data rates, bandwidths, modulations and spatial stream modes. (dutycycle>98%)

Page 8 of 104

Report No.: FCC1607059-01

Date: 2016-07-30



3.0 **Technical Details**

3.1 **Summary of test results**

Standard	Test Type	Result	Notes
CC Part 15, Paragraph 15.107 & 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	Maximum peak output power Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(d)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band limit: Table 15.209	PASS	Complies

3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247 and ANSI C63.4:2014 AND ANSI C63.10:2013

4.0 **EUT Modification**


No modification by SHENZHEN TIMEWAY TESTING LABORATORIES

Date: 2016-07-30



5.0 Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10-2013.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Model	FCC ID	
WiFi Chaolson	SHENZHEN PHIMAX	X10	2AHXMX-10	
wifi Speaker	iFi Speaker INTERNATIONAL COMPANY LTD		ZAHAMA-10	

B. Internal Device

Device	Manufacturer	Model	FCC
			ID/DOC
N/A			

The report refers only to the sample tested and does not apply to the bulk.

Report No.: FCC1607059-01 Page 10 of 104

Date: 2016-07-30



C. Accessory

Device	Manufacturer	Model	FCC ID/DOC	Rating
N/A				

5.4 **EUT Operating Condition**

Operating condition is according to ANSI C63.10-2013.

- Α Setup the EUT and simulators as shown on follow
- В Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207 and 15.107

Frequency	Class A Lim	its (dB µ V)	Class B Lim	nits (dB µ V)
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0
5.00 ~ 30.00	73.0	60.0	60.0	50.0

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 **Test Results**

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Date: 2016-07-30



A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Keep WIFI Transmitting

Equipment Level: Class B

Results: PASS

Please refer to following diagram for individual



No.	Mk.	Freq.	Reading Level		Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	25.3750	42.36	11.39	53.75	60.00	-6.25	QP
2		25.3750	25.05	11.39	36.44	50.00	-13.56	AVG

Date: 2016-07-30



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Keep WIFI Transmitting

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



No.	Mk.	Freq.	Reading Level		Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	×	25.8125	43.54	11.38	54.92	60.00	-5.08	QP
2		25.8125	24.16	11.38	35.54	50.00	-14.46	AVG

Report No.: FCC1607059-01 Page 13 of 104

Date: 2016-07-30



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10–2013. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10–2013.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. F For measurement above 1GHz, peak values with RBW=1MHz VBW=3MHz and PK detector. AV value with RBW=1MHz, VBW=3MHz and RMS detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "**OP**" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Distance = 3m Computer Pre – Amplifier Turn-table Receiver

6.2 Configuration of The EUT

Same as section 5.3 of this report

Block diagram of Test setup

6.3 EUT Operating Condition
Same as section 5.4 of this report.

The report refers only to the sample tested and does not apply to the bulk.

Report No.: FCC1607059-01 Page 14 of 104

Date: 2016-07-30



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Report No.: FCC1607059-01 Page 15 of 104

Date: 2016-07-30



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal/Vertical (30MHz----1000MHz)

Keep WIFI Transmitting **EUT set Condition:**

Results: Pass

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
321.920	42.06	Н	46.00
254.160	39.89	Н	46.00
135.520	38.33	Н	43.50
469.200	39.96	Н	46.00
468.440	43.17	V	46.00
491.280	44.70	V	46.00
254.360	31.75	V	46.00
135.520	34.52	V	43.50

Report No.: FCC1607059-01 Page 16 of 104

Date: 2016-07-30



Test Figure:

30 MHz

H MARKER 1 RBW 120 kHz Marker 1 [T1] 42.06 dBµV/m 321.92 MHz МТ 50 µs Att 10 dB PREAMP ON 321.920000000 MHz dBuV 80 100 MHz Marker dBµV/m 89 254 160 000000 MHz 1 РК МАХН 38 33 dВ 135 520 000 000 39 96 dВ TDF 469 200000000 -50 FCC15 6DB Mymy -10

1 GHz


Page 17 of 104

Report No.: FCC1607059-01

Date: 2016-07-30



Test Figure:



Report No.: FCC1607059-01 Page 18 of 104

Date: 2016-07-30



Operation Mode: Transmitting under CH01 for 11g at 54Mbps

	0		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
4824.00	52.28 (PK)	Н	74(Peak)/ 54(AV)
4824.00	52.32 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16884		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

3. For 802.11g mode 54Mbps

Report No.: FCC1607059-01 Page 19 of 104

Date: 2016-07-30



Operation Mode: Transmitting under CH06 for 11g at 54Mbps

	0	о I	
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4874.00	50.32 (PK)	V	74(Peak)/ 54(AV)
4874.00	50.47 (PK)	Н	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 54 Mbps

Operation Mode: Transmitting under CH11 for 11g at 54Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03bc V/m)
4924	51.58 (PK)	Н	74(Peak)/ 54(AV)
4924	51.64 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode at 54 Mbps

Date: 2016-07-30




Please refer to the following test plots for details:

CH01 for 11g at 54Mbps: Horizontal



CH01 for 11g at 54Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report

discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 21 of 104

Report No.: FCC1607059-01


Date: 2016-07-30



CH06 for 11g at 54Mbps: Vertical



CH06 for 11g at 54Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.


Date: 2016-07-30



CH11 for 11g at 54Mbps: Vertical



CH11 for 11g at 54Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Report No.: FCC1607059-01 Page 23 of 104

Date: 2016-07-30



Operation Mode: Transmitting under CH01 for 11b at 11Mbps

	0		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
4824.00	50.82 (PK)	Н	74(Peak)/ 54(AV)
4824.00	50.59 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

Operation Mode: Transmitting under CH06 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03ba V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4874.00	52.62 (PK)	Н	74(Peak)/ 54(AV)
4874.00	51.81 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

The report refers only to the sample tested and does not apply to the bulk.

Report No.: FCC1607059-01 Page 24 of 104

Date: 2016-07-30



Operation Mode: Transmitting under CH11 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4924	51.29 (PK)	Н	74(Peak)/ 54(AV)
4924	51.13 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured


3. For 802.11b mode at 11Mbps

Date: 2016-07-30




Please refer to the following test plots for details:

CH01 for 11b at 11Mbps: Horizontal



CH01 for 11b at 11Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.


Page 26 of 104

Report No.: FCC1607059-01


Date: 2016-07-30



CH06 for 11b at 11Mbps: Vertical



CH06 for 11b at 11Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report


discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Date: 2016-07-30



CH11 for 11b at 11Mbps: Vertical



CH11 for 11b at 11Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Report No.: FCC1607059-01 Page 28 of 104

Date: 2016-07-30



Operation Mode: Transmitting under CH01 for 11n HT20 at 6.5Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4824.00	49.85 (PK)	Н	74(Peak)/ 54(AV)
4824.00	49.59 (PK)	V	74(Peak)/ 54(AV)
7236.00	1	H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472	-	H/V	74(Peak)/ 54(AV)
16684	1	H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708	1	H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 6.5Mbps

Operation Mode: Transmitting under CH06 for 11n HT20 at 6.5Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03bc V/m)
4874.00	51.04 (PK)	Н	74(Peak)/ 54(AV)
4874.00	51.19 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 6.5Mbps

The report refers only to the sample tested and does not apply to the bulk.

Report No.: FCC1607059-01 Page 29 of 104

Date: 2016-07-30



Operation Mode: Transmitting under CH11 for 11n HT20 at 6.5Mbps

	0		<u> </u>
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
4924	52.19 (PK)	Н	74(Peak)/ 54(AV)
4924	50.14 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured


3. For 802.11n (HT20) mode 6.5Mbps

Date: 2016-07-30




Please refer to the following test plots for details:

CH01 for 11n HT20 at 6.5Mbps: Horizontal



CH01 for 11n HT20 at 6.5Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report

discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 31 of 104

Report No.: FCC1607059-01


Date: 2016-07-30



CH06 for 11n HT20 at 6.5Mbps: Vertical



CH06 for 11n HT20 at 6.5Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.


Date: 2016-07-30



CH11 for 11n HT20 at 6.5Mbps: Vertical



CH11 for 11n HT20 at 6.5Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Report No.: FCC1607059-01 Page 33 of 104

Date: 2016-07-30



Operation Mode: Transmitting under CH01 for 11n HT40 at 6.5Mbps

	0		1
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
4844.00	50.51 (PK)	Н	74(Peak)/ 54(AV)
4844.00	50.77 (PK)	V	74(Peak)/ 54(AV)
7266.00		H/V	74(Peak)/ 54(AV)
9688.00		H/V	74(Peak)/ 54(AV)
12110		H/V	74(Peak)/ 54(AV)
14532		H/V	74(Peak)/ 54(AV)
16954		H/V	74(Peak)/ 54(AV)
19376		H/V	74(Peak)/ 54(AV)
21798		H/V	74(Peak)/ 54(AV)
24220		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 6.5Mbps

Operation Mode: Transmitting under CH04 for 11n HT40 at 6.5Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4874.00	51.16 (PK)	Н	74(Peak)/ 54(AV)
4874.00	51.03 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 6.5Mbps

The report refers only to the sample tested and does not apply to the bulk.

Report No.: FCC1607059-01 Page 34 of 104

Date: 2016-07-30



Operation Mode: Transmitting under CH07 for 11n HT40 at 6.5Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4904	49.73 (PK)	Н	74(Peak)/ 54(AV)
4904	49.58 (PK)	V	74(Peak)/ 54(AV)
7356		H/V	74(Peak)/ 54(AV)
9808		H/V	74(Peak)/ 54(AV)
12260		H/V	74(Peak)/ 54(AV)
14712		H/V	74(Peak)/ 54(AV)
17164		H/V	74(Peak)/ 54(AV)
19616		H/V	74(Peak)/ 54(AV)
22068		H/V	74(Peak)/ 54(AV)
24520		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured


3. For 802.11n (HT40) mode 6.5Mbps

Date: 2016-07-30




Please refer to the following test plots for details:

CH01 for 11n HT40 at 6.5Mbps: Horizontal



CH01 for 11n HT40 at 6.5Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report

discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 36 of 104

Report No.: FCC1607059-01


Date: 2016-07-30



CH04 for 11n HT40 at 6.5Mbps: Vertical



CH04 for 11n HT40 at 6.5Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


adopt any other remedies which may be appropriate.

Report No.: FCC1607059-01


Date: 2016-07-30



CH07 for 11n HT40 at 6.5Mbps: Vertical



CH07 for 11n HT40 at 6.5Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.


Report No.: FCC1607059-01 Page 38 of 104

Date: 2016-07-30



7.0 6dB Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW) \geq 3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 Test Result

Page 39 of 104 Report No.: FCC1607059-01

Date: 2016-07-30



6dB Occupied Bandwidth


EUT		WiFi Speaker			Model		X10		
Mode		802.11b			Input Voltage		DC13.5V		
Temperati	ure	24 d	leg. C,		Humidity		569	% RH	
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)		N	Iinimum Limit (MHz)	Pass/ Fail	
1		2412		10.04			0.5	Pass	
6	2437		1	10.04			0.5	Pass	
11		2462	1		10.04		0.5	Pass	
1		2412	11		10.16		0.5	Pass	
6		2437	11	10.16			0.5	Pass	
11		2462	11	10.16			0.5	Pass	

Report No.: FCC1607059-01 Page 40 of 104

Date: 2016-07-30



1. 802.11b at 1Mbps of CH01




Report No.: FCC1607059-01 Page 41 of 104

Date: 2016-07-30



2. 802.11b at 1Mbps of CH06




Report No.: FCC1607059-01 Page 42 of 104

Date: 2016-07-30



3. 802.11b at 1Mbps of CH11




Report No.: FCC1607059-01 Page 43 of 104

Date: 2016-07-30



4. 802.11b at 11Mbps of CH01




Report No.: FCC1607059-01 Page 44 of 104

Date: 2016-07-30



5. 802.11b at 11Mbps of CH06




Report No.: FCC1607059-01 Page 45 of 104

Date: 2016-07-30



6. 802.11b at 11Mbps of CH11



Page 46 of 104 Report No.: FCC1607059-01

Date: 2016-07-30



6dB Occupied Bandwidth

EUT		WiFi Speaker			Model		X10	
Mode		80.	2.11g		Input Voltage		DC13.5V	
Temperat	ure	24 deg. C,			Humidity	umidity 56%		% RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)	6 dF	Bandwidth (MHz)	М	Iinimum Limit (MHz)	Pass/ Fail
1		2412	54		16.41		0.5	Pass
6		2437	54		16.41		0.5	Pass
11		2462	54		16.41		0.5	Pass


Report No.: FCC1607059-01 Page 47 of 104

Date: 2016-07-30



Test Plots:

1. 802.11g at 54Mbps of CH01




Report No.: FCC1607059-01 Page 48 of 104

Date: 2016-07-30



2. 802.11g at 54Mbps of CH06




Report No.: FCC1607059-01 Page 49 of 104

Date: 2016-07-30



3. 802.11g at 54Mbps of CH11



Page 50 of 104 Report No.: FCC1607059-01

Date: 2016-07-30



6dB Occupied Bandwidth

EUT		WiFi Speaker			Model		X10	
Mode		802.111	n HT20		Input Voltage		DC13.5V	
Temperat	ure	24 de	leg. C,		Humidity		56% RH	
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)		Minimum Limit (MHz)		Pass/ Fail
1		2412	6.5M		17.56		0.5	Pass
6		2437	6.5M		17.56		0.5	Pass
11		2462	6.5M		17.56		0.5	Pass


Report No.: FCC1607059-01 Page 51 of 104

Date: 2016-07-30



Test Plots:

1. 802.11n at HT20 of CH01




Report No.: FCC1607059-01 Page 52 of 104

Date: 2016-07-30



2. 802.11n at HT20 of CH06




Report No.: FCC1607059-01 Page 53 of 104

Date: 2016-07-30



3. 802.11n at HT20 of CH11



Page 54 of 104 Report No.: FCC1607059-01

Date: 2016-07-30



6dB Occupied Bandwidth

EUT		WiFi Speaker			Model	X1	0
Mode		802.111	n HT40		Input Voltage	DC13	3.5V
Temperat	ure	24 de	eg. C,		Humidity	56%	RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)	6	dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
1		2422	6.5M		36.17	0.5	Pass
4		2437	6.5M		36.17	0.5	Pass
7		2452	6.5M		36.17	0.5	Pass


Report No.: FCC1607059-01 Page 55 of 104

Date: 2016-07-30



Test Plots:

1. 802.11n at HT40 of CH01




Report No.: FCC1607059-01 Page 56 of 104

Date: 2016-07-30



2. 802.11n at HT40 of CH04




Report No.: FCC1607059-01 Page 57 of 104

Date: 2016-07-30



3. 802.11n at HT40 of CH07



Report No.: FCC1607059-01


Date: 2016-07-30



Page 58 of 104

8. Maximum Output Power

8.1 Test Setup



8.2 Limits of Maximum Output Power

The Maximum Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the Peak power were measured.

Date: 2016-07-30



8.4Test Results

EUT		WiFi Speaker		Model		X10			
Mode		802.11b		Input Voltage		DC13.5V			
Temperati	ure	24 deg. C	·,	Humidity	Humidity		56% RH		
Channel	Channel Frequency (MHz)		Max. Power Output (dBm)		Power Limit (dBm)		Pass/ Fail		
	11Mbps								
1		2412		7.74		30	Pass		
6		2437		8.64		30	Pass		
11		2462	2462		8.60		Pass		
1Mbps									
1		2412		5.32		30	Pass		
6	·	2437	6.26			30	Pass		
11	·	2462		6.15		30	Pass		

Note: 1. The result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

2. The worse case was recorded

EUT		WiFi Speaker		Model		X10		
Mode		802.11g		Input Voltage		DC13.5V		
Temperat	ure	24 deg. C,		Humidity		5	56% RH	
Channel	Ch	Channel Frequency (MHz)		Max. Power Output (dBm)		ower Limit (dBm)	Pass/ Fail	
1	2412		5.17			30	Pass	
6		2437		6.21		30	Pass	
11	2462			6.14		30	Pass	

Note: 1. At finial test to get the worst-case emission at 54Mbps for CH01, CH06 and CH11

- 2. The result basic equation calculation as follow:
 - Max. Power Output = Power Reading + Cable loss + Attenuator
- 3. The worse case was recorded

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 60 of 104

Report No.: FCC1607059-01

Date: 2016-07-30



EUT		WiFi Speaker		Model		X10	
Mode		802.11n (HT20)		Input Voltage		DC13.5V	
Temperature		24 deg. C,		Humidity		4	56% RH
Channel	Cha	Channel Frequency Max. (MHz)		Power Output (dBm)		Power Limit (dBm)	Pass/ Fail
1	2412		5.37			30	Pass
6		2437		6.34		30	Pass
11	2462			6.34		30	Pass

Note: 1. At finial test to get the worst-case emission at 6.5Mbps of 11n HT20 for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT		WiFi Speaker		Model		X10	
Mode 802.		802.11n (HT ²	10)	Input Voltage		DC13.5V	
Temperature		24 deg. C,	Humidi			56% RH	
Channel	Cha	annel Frequency	el Frequency Max.		I	Power Limit	Pass/ Fail
Chamici	(MHz)		(dBm)			(dBm)	
1	2422		6.24			30	Pass
4		2437		6.65		30	Pass
7	2452			6.70		30	Pass

Note: 1. At finial test to get the worst-case emission at 6.5Mbps of 11n HT40 for CH01, CH04 and CH7

2. The result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded