

Analysis Report

Report No.: 19031422HKG-001

The Equipment Under Test (EUT) is portable controller for a RC car set which operates at 49.860MHz. The EUT is powered by 2 x 1.5V AAA batteries.

After switch on the EUT, the car will be moved forward or backward, turned left or right based on the joystick control in the controller.

Antenna Type: Internal, Integral

Antenna Type: Internal integral antenna

Antenna Gain: 0dBi

Nominal rated field strength: 74.3dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 77.3dB μ V/m at 3m in frequency 49.860MHz, thus;

The worst case of SAR Exclusion Threshold Level for 49.860MHz when the minimum test separation distance is < 50mm:

$$= [474 * (1 + \log_{10}(f(\text{MHz}))) / 2]$$
$$= 308.6\text{mW}$$

According to the KDB 412172 D01:

$$\text{EIRP} = [(\text{FS} * \text{D})^2 * 1000 / 30]$$

Calculated Field Strength for 308.6mW is 120.1dB μ V/m @3m

Since maximum field strength plus production tolerance <= 120.1dB μ V/m @3m and antenna gain is >= 0.0dBi, it is concluded that maximum Conducted Power and Field Strength are well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.