

# TEST REPORT

**Applicant:** SHENZHEN GIEC DIGITAL CO., LTD

**Address of Applicant:** 1st&3rd Building, No.26 Puzai Road, Pingdi, Longgang District, Shenzhen, China

**Manufacturer/Factory:** SHENZHEN GIEC DIGITAL CO., LTD

**Address of Manufacturer/Factory:** 1st&3rd Building, No.26 Puzai Road, Pingdi, Longgang District, Shenzhen, China

**Equipment Under Test (EUT)**

Product Name: Hubitat Elevation Hub

Model No.: Model C-8

**FCC ID:** 2AHYK-2212C8

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.247

**Date of sample receipt:** November 15, 2022

**Date of Test:** November 16, 2022-December 20, 2022

**Date of report issued:** December 20, 2022

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



**Robinson Luo**


**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

Version No.	Date	Description
00	December 20, 2022	Original

Prepared By:



Date:

December 20, 2022

Project Engineer

Check By:



Date:

December 20 2022

Reviewer

## 3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS .....	3
4 TEST SUMMARY .....	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT .....	5
5.2 TEST MODE .....	7
5.3 DESCRIPTION OF SUPPORT UNITS .....	7
5.4 DEVIATION FROM STANDARDS.....	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS .....	7
5.6 TEST FACILITY.....	7
5.7 TEST LOCATION .....	7
5.8 ADDITIONAL INSTRUCTIONS.....	7
6 TEST INSTRUMENTS LIST .....	8
7 TEST RESULTS AND MEASUREMENT DATA.....	10
7.1 ANTENNA REQUIREMENT .....	10
7.2 CONDUCTED EMISSIONS .....	11
7.3 CONDUCTED PEAK OUTPUT POWER .....	14
7.4 CHANNEL BANDWIDTH .....	15
7.5 POWER SPECTRAL DENSITY .....	16
7.6 SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS .....	17
7.6.1 Conducted Emission Method.....	17
7.6.2 Radiated Emission Method.....	18
8 TEST SETUP PHOTO .....	39
9 EUT CONSTRUCTIONAL DETAILS .....	39

## 4 Test Summary

Test Item	Section	Result
Antenna requirement	FCC part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	FCC part 15.207	Pass
Conducted Peak Output Power	FCC part 15.247 (b)(3)	Pass
Channel Bandwidth & 99% OCB	FCC part 15.247 (a)(2)	Pass
Power Spectral Density	FCC part 15.247 (e)	Pass
Band Edge	FCC part 15.247(d)	Pass
Spurious Emission	FCC part 15.205/15.209	Pass

*Remark: Test according to ANSI C63.10:2013*

*Pass: The EUT complies with the essential requirements in the standard.*

### Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz-30MHz	3.1dB	(1)
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 5 General Information

### 5.1 General Description of EUT

Product Name:	Hubitat Elevation Hub
Model No.:	Model C-8
Test sample(s) ID:	GTS202211000133-1
Sample(s) Status	Engineer sample
S/N:	C-8112200001
Operation Frequency:	802.11b/802.11g/802.11n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
Channel numbers:	802.11b/802.11g /802.11n(HT20): 11 802.11n(HT40):7
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(HT20) /802.11n(HT40): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	Integral Antenna
Antenna gain:	2.33dBi
Power supply:	TRAVEL CHARGER Model: TPA-46B050100UU Input: AC100-240v 50/60Hz 0.15A Output:DC5.0V 1.1A 5.0W

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	X	

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/802.11g/802.11n(HT20)	802.11n(HT40)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

## 5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:				
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.				
Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	13Mbps

## 5.3 Description of Support Units

None.
-------

## 5.4 Deviation from Standards

None.
-------

## 5.5 Abnormalities from Standard Conditions

None.
-------

## 5.6 Test Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> <li>● <b>FCC —Registration No.: 381383</b> Designation Number: CN5029 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.</li> <li>● <b>IC —Registration No.: 9079A</b> CAB identifier: CN0091 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.</li> <li>● <b>NVLAP (LAB CODE:600179-0)</b> Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).</li> </ul>
--

## 5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

## 5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

## 6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July 02, 2020	July 01, 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	April 22, 2022	April 21, 2023
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	March 21, 2022	March 20, 2023
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June 12, 2022	June 11, 2023
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June 23, 2022	June 22, 2023
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	April 22, 2022	April 21, 2023
9	Coaxial Cable	GTS	N/A	GTS211	April 22, 2022	April 21, 2023
10	Coaxial cable	GTS	N/A	GTS210	April 22, 2022	April 21, 2023
11	Coaxial Cable	GTS	N/A	GTS212	April 22, 2022	April 21, 2023
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	April 22, 2022	April 21, 2023
13	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 23, 2022	June 22, 2023
14	Band filter	Amindeon	82346	GTS219	June 23, 2022	June 22, 2023
15	Power Meter	Anritsu	ML2495A	GTS540	June 23, 2022	June 22, 2023
16	Power Sensor	Anritsu	MA2411B	GTS541	June 23, 2022	June 22, 2023
17	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	April 22, 2022	April 21, 2023
18	Splitter	Agilent	11636B	GTS237	June 23, 2022	June 22, 2023
19	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov. 29, 2022	Nov. 28, 2023
20	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	April 22, 2022	April 21, 2023
21	Breitband hornantenna	SCHWARZBECK	BBHA 9170	GTS579	Oct. 16, 2022	Oct. 15, 2023
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 16, 2022	Oct. 15, 2023
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 16, 2022	Oct. 15, 2023
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June 23, 2022	June 22, 2023
25	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	April 22, 2022	April 21, 2023



Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May 14, 2022	May 13, 2025
2	EMI Test Receiver	R&S	ESCI 7	GTS552	April 24, 2022	April 23, 2023
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 23, 2022	June 22, 2023
4	ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	GTS226	April 22, 2022	April 21, 2023
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	JINCHUANG	GSP-8A	GTS639	April 28, 2022	April 27, 2023
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	April 15, 2022	April 14, 2023
9	ISN	SCHWARZBECK	NTFM 8158	GTS565	April 22, 2022	April 21, 2023
10	High voltage probe	SCHWARZBECK	TK9420	GTS537	April 22, 2022	April 21, 2023

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	April 22, 2022	April 21, 2023
2	EMI Test Receiver	R&S	ESCI 7	GTS552	April 22, 2022	April 21, 2023
3	Spectrum Analyzer	Agilent	E4440A	GTS536	April 22, 2022	April 21, 2023
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	April 22, 2022	April 21, 2023
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	April 22, 2022	April 21, 2023
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	April 22, 2022	April 21, 2023
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	April 22, 2022	April 21, 2023
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	April 22, 2022	April 21, 2023

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	April 25, 2022	April 24, 2023
2	Barometer	KUMAO	SF132	GTS647	July 26, 2022	July 25, 2023

## 7 Test results and Measurement Data

### 7.1 Antenna requirement

<b>Standard requirement:</b>	FCC Part15 C Section 15.203 /247(c)
<p><b>15.203 requirement:</b></p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p><b>15.247(c) (1)(i) requirement:</b></p> <p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
<b>EUT Antenna:</b>	
The antenna is integral antenna, reference to the appendix II for details.	


## 7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	<p>Remark:  E.U.T: Equipment Under Test  LISN: Line Impedance Stabilization Network  Test table height=0.8m</p>					
Test procedure:	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.</li> </ol>					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V					
Test results:	Pass					

**Measurement Data:**


Pre-scan all test modes, found worst case at 802.11b 2462MHz, and so only show the test result of 802.11b 2462MHz

Line:



Freq	Reading level	LISN/ISN factor	Cable loss	Level	Limit level	Over limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.17	24.98	10.10	0.01	35.09	64.99	-29.90	QP
0.17	13.63	10.10	0.01	23.74	54.99	-31.25	Average
0.49	36.71	9.96	0.01	46.68	56.19	-9.51	QP
0.49	27.98	9.96	0.01	37.95	46.19	-8.24	Average
0.78	26.90	9.96	0.02	36.88	56.00	-19.12	QP
0.78	18.18	9.96	0.02	28.16	46.00	-17.84	Average
2.07	28.57	9.83	0.04	38.44	56.00	-17.56	QP
2.07	17.69	9.83	0.04	27.56	46.00	-18.44	Average
10.79	37.16	9.57	0.12	46.85	60.00	-13.15	QP
10.79	28.85	9.57	0.12	38.54	50.00	-11.46	Average
21.60	31.74	9.44	0.19	41.37	60.00	-18.63	QP
21.60	22.04	9.44	0.19	31.67	50.00	-18.33	Average


Neutral:



Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

## 7.3 Conducted Peak Output Power

Test Requirement :	FCC Part15 C Section 15.247 (b)(3)
Test Method :	KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	30dBm
Test setup:	 <p>The diagram illustrates the test setup. A Power Meter is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


**Measurement Data:** The detailed test data see Appendix for WIFI 2.4G.

## 7.4 Channel Bandwidth

Test Requirement :	FCC Part15 C Section 15.247 (a)(2)
Test Method :	KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	>500KHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

**Measurement Data:** The detailed test data see Appendix for WIFI 2.4G.

## 7.5 Power Spectral Density


Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	8dBm/3kHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

**Measurement Data:** The detailed test data see Appendix for WIFI 2.4G.




## 7.6 Spurious Emission in Non-restricted & restricted Bands



### 7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

**Measurement Data:** The detailed test data see Appendix for WIFI 2.4G.

## 7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit:	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	PK/AV/QP	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	30m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
5000		Peak			
Test setup:	For radiated emissions from 9kHz to 30MHz				
	 <p>The diagram illustrates the test setup for radiated emissions from 9kHz to 30MHz. It shows an Equipment Under Test (EUT) placed on a turn table. A test antenna is positioned 3m away from the EUT. The antenna is mounted on a stand that is 1m high. A receiver is connected to the antenna. The turn table has a diameter of less than 80cm. The entire setup is on a ground plane.</p>				
For radiated emissions from 30MHz to 1GHz					

	 <p>For radiated emissions above 1GHz</p> 
<p>Test Procedure:</p>	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>
<p>Test Instruments:</p>	<p>Refer to section 6.0 for details</p>

Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V					
Test results:	Pass					

*Remarks:*

1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

**Measurement data:**


■ **9kHz~30MHz**

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.


■ **Below 1GHz**

Pre-scan all test modes, found worst case at 802.11b 2462MHz, and so only show the test result of 802.11b 2462MHz

**Horizontal:**



Vertical:



- Unwanted Emissions in non-restricted Frequency Bands
- Above 1GHz

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	37.10	31.79	8.62	32.10	45.41	74.00	-28.59	Vertical
7236.00	32.20	36.19	11.68	31.97	48.10	74.00	-25.90	Vertical
9648.00	31.27	38.07	14.16	31.56	51.94	74.00	-22.06	Vertical
4824.00	36.26	31.79	8.62	32.10	44.57	74.00	-29.43	Horizontal
7236.00	32.20	36.19	11.68	31.97	48.10	74.00	-25.90	Horizontal
9648.00	30.96	38.07	14.16	31.56	51.63	74.00	-22.37	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	26.43	31.79	8.62	32.10	34.74	54.00	-19.26	Vertical
7236.00	21.14	36.19	11.68	31.97	37.04	54.00	-16.96	Vertical
9648.00	21.67	38.07	14.16	31.56	42.34	54.00	-11.66	Vertical
4824.00	25.97	31.79	8.62	32.10	34.28	54.00	-19.72	Horizontal
7236.00	20.84	36.19	11.68	31.97	36.74	54.00	-17.26	Horizontal
9648.00	20.76	38.07	14.16	31.56	41.43	54.00	-12.57	Horizontal

Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	36.71	31.85	8.66	32.12	45.10	74.00	-28.90	Vertical
7311.00	32.62	36.37	11.71	31.91	48.79	74.00	-25.21	Vertical
9748.00	32.54	38.27	14.25	31.56	53.50	74.00	-20.50	Vertical
4874.00	37.60	31.85	8.66	32.12	45.99	74.00	-28.01	Horizontal
7311.00	31.47	36.37	11.71	31.91	47.64	74.00	-26.36	Horizontal
9748.00	32.52	38.27	14.25	31.56	53.48	74.00	-20.52	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	27.77	31.85	8.66	32.12	36.16	54.00	-17.84	Vertical
7311.00	20.99	36.37	11.71	31.91	37.16	54.00	-16.84	Vertical
9748.00	21.84	38.27	14.25	31.56	42.80	54.00	-11.20	Vertical
4874.00	27.85	31.85	8.66	32.12	36.24	54.00	-17.76	Horizontal
7311.00	20.60	36.37	11.71	31.91	36.77	54.00	-17.23	Horizontal
9748.00	22.27	38.27	14.25	31.56	43.23	54.00	-10.77	Horizontal



Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	40.33	31.90	8.70	32.15	48.78	74.00	-25.22	Vertical
7386.00	32.08	36.49	11.76	31.83	48.50	74.00	-25.50	Vertical
9848.00	34.97	38.62	14.31	31.77	56.13	74.00	-17.87	Vertical
4924.00	40.34	31.90	8.70	32.15	48.79	74.00	-25.21	Horizontal
7386.00	31.35	36.49	11.76	31.83	47.77	74.00	-26.23	Horizontal
9848.00	31.30	38.62	14.31	31.77	52.46	74.00	-21.54	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	31.60	31.90	8.70	32.15	40.05	54.00	-13.95	Vertical
7386.00	22.10	36.49	11.76	31.83	38.52	54.00	-15.48	Vertical
9848.00	23.55	38.62	14.31	31.77	44.71	54.00	-9.29	Vertical
4924.00	30.94	31.90	8.70	32.15	39.39	54.00	-14.61	Horizontal
7386.00	20.81	36.49	11.76	31.83	37.23	54.00	-16.77	Horizontal
9848.00	20.63	38.62	14.31	31.77	41.79	54.00	-12.21	Horizontal

Test mode:	802.11g	Test channel:	lowest
------------	---------	---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	37.33	31.79	8.62	32.10	45.64	74.00	-28.36	Vertical
7236.00	32.35	36.19	11.68	31.97	48.25	74.00	-25.75	Vertical
9648.00	31.38	38.07	14.16	31.56	52.05	74.00	-21.95	Vertical
4824.00	36.46	31.79	8.62	32.10	44.77	74.00	-29.23	Horizontal
7236.00	32.33	36.19	11.68	31.97	48.23	74.00	-25.77	Horizontal
9648.00	31.06	38.07	14.16	31.56	51.73	74.00	-22.27	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	26.65	31.79	8.62	32.10	34.96	54.00	-19.04	Vertical
7236.00	21.28	36.19	11.68	31.97	37.18	54.00	-16.82	Vertical
9648.00	21.78	38.07	14.16	31.56	42.45	54.00	-11.55	Vertical
4824.00	26.16	31.79	8.62	32.10	34.47	54.00	-19.53	Horizontal
7236.00	20.96	36.19	11.68	31.97	36.86	54.00	-17.14	Horizontal
9648.00	20.85	38.07	14.16	31.56	41.52	54.00	-12.48	Horizontal

Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	36.90	31.85	8.66	32.12	45.29	74.00	-28.71	Vertical
7311.00	32.74	36.37	11.71	31.91	48.91	74.00	-25.09	Vertical
9748.00	32.63	38.27	14.25	31.56	53.59	74.00	-20.41	Vertical
4874.00	37.76	31.85	8.66	32.12	46.15	74.00	-27.85	Horizontal
7311.00	31.58	36.37	11.71	31.91	47.75	74.00	-26.25	Horizontal
9748.00	32.60	38.27	14.25	31.56	53.56	74.00	-20.44	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	27.95	31.85	8.66	32.12	36.34	54.00	-17.66	Vertical
7311.00	21.11	36.37	11.71	31.91	37.28	54.00	-16.72	Vertical
9748.00	21.92	38.27	14.25	31.56	42.88	54.00	-11.12	Vertical
4874.00	20.71	36.37	11.71	31.91	36.88	54.00	-17.12	Horizontal
7311.00	22.35	38.27	14.25	31.56	43.31	54.00	-10.69	Horizontal
9748.00	27.95	31.85	8.66	32.12	36.34	54.00	-17.66	Horizontal

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	40.66	31.90	8.70	32.15	49.11	74.00	-24.89	Vertical
7386.00	32.30	36.49	11.76	31.83	48.72	74.00	-25.28	Vertical
9848.00	35.12	38.62	14.31	31.77	56.28	74.00	-17.72	Vertical
4924.00	40.62	31.90	8.70	32.15	49.07	74.00	-24.93	Horizontal
7386.00	31.53	36.49	11.76	31.83	47.95	74.00	-26.05	Horizontal
9848.00	31.44	38.62	14.31	31.77	52.60	74.00	-21.40	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	31.91	31.90	8.70	32.15	40.36	54.00	-13.64	Vertical
7386.00	22.31	36.49	11.76	31.83	38.73	54.00	-15.27	Vertical
9848.00	23.70	38.62	14.31	31.77	44.86	54.00	-9.14	Vertical
4924.00	31.21	31.90	8.70	32.15	39.66	54.00	-14.34	Horizontal
7386.00	20.99	36.49	11.76	31.83	37.41	54.00	-16.59	Horizontal
9848.00	20.76	38.62	14.31	31.77	41.92	54.00	-12.08	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	37.31	31.79	8.62	32.10	45.62	74.00	-28.38	Vertical
7236.00	32.33	36.19	11.68	31.97	48.23	74.00	-25.77	Vertical
9648.00	31.36	38.07	14.16	31.56	52.03	74.00	-21.97	Vertical
4824.00	36.44	31.79	8.62	32.10	44.75	74.00	-29.25	Horizontal
7236.00	32.32	36.19	11.68	31.97	48.22	74.00	-25.78	Horizontal
9648.00	31.05	38.07	14.16	31.56	51.72	74.00	-22.28	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	26.63	31.79	8.62	32.10	34.94	54.00	-19.06	Vertical
7236.00	21.26	36.19	11.68	31.97	37.16	54.00	-16.84	Vertical
9648.00	21.76	38.07	14.16	31.56	42.43	54.00	-11.57	Vertical
4824.00	26.14	31.79	8.62	32.10	34.45	54.00	-19.55	Horizontal
7236.00	20.95	36.19	11.68	31.97	36.85	54.00	-17.15	Horizontal
9648.00	20.84	38.07	14.16	31.56	41.51	54.00	-12.49	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	36.88	31.85	8.66	32.12	45.27	74.00	-28.73	Vertical
7311.00	32.73	36.37	11.71	31.91	48.90	74.00	-25.10	Vertical
9748.00	32.62	38.27	14.25	31.56	53.58	74.00	-20.42	Vertical
4874.00	37.74	31.85	8.66	32.12	46.13	74.00	-27.87	Horizontal
7311.00	31.57	36.37	11.71	31.91	47.74	74.00	-26.26	Horizontal
9748.00	32.59	38.27	14.25	31.56	53.55	74.00	-20.45	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	27.93	31.85	8.66	32.12	36.32	54.00	-17.68	Vertical
7311.00	21.10	36.37	11.71	31.91	37.27	54.00	-16.73	Vertical
9748.00	21.91	38.27	14.25	31.56	42.87	54.00	-11.13	Vertical
4874.00	27.98	31.85	8.66	32.12	36.37	54.00	-17.63	Horizontal
7311.00	20.69	36.37	11.71	31.91	36.86	54.00	-17.14	Horizontal
9748.00	22.34	38.27	14.25	31.56	43.30	54.00	-10.70	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	40.62	31.90	8.70	32.15	49.07	74.00	-24.93	Vertical
7386.00	32.27	36.49	11.76	31.83	48.69	74.00	-25.31	Vertical
9848.00	35.10	38.62	14.31	31.77	56.26	74.00	-17.74	Vertical
4924.00	40.59	31.90	8.70	32.15	49.04	74.00	-24.96	Horizontal
7386.00	31.51	36.49	11.76	31.83	47.93	74.00	-26.07	Horizontal
9848.00	31.42	38.62	14.31	31.77	52.58	74.00	-21.42	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	31.87	31.90	8.70	32.15	40.32	54.00	-13.68	Vertical
7386.00	22.28	36.49	11.76	31.83	38.70	54.00	-15.30	Vertical
9848.00	23.68	38.62	14.31	31.77	44.84	54.00	-9.16	Vertical
4924.00	31.18	31.90	8.70	32.15	39.63	54.00	-14.37	Horizontal
7386.00	20.97	36.49	11.76	31.83	37.39	54.00	-16.61	Horizontal
9848.00	20.75	38.62	14.31	31.77	41.91	54.00	-12.09	Horizontal

Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	36.92	31.81	8.63	32.11	45.25	74.00	-28.75	Vertical
7266.00	32.08	36.28	11.69	31.94	48.11	74.00	-25.89	Vertical
9688.00	31.19	38.13	14.21	31.52	52.01	74.00	-21.99	Vertical
4844.00	36.11	31.81	8.63	32.11	44.44	74.00	-29.56	Horizontal
7266.00	32.10	36.28	11.69	31.94	48.13	74.00	-25.87	Horizontal
9688.00	30.88	38.13	14.21	31.52	51.70	74.00	-22.30	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	26.27	31.81	8.63	32.11	34.60	54.00	-19.40	Vertical
7266.00	21.03	36.28	11.69	31.94	37.06	54.00	-16.94	Vertical
9688.00	21.60	38.13	14.21	31.52	42.42	54.00	-11.58	Vertical
4844.00	25.83	31.81	8.63	32.11	34.16	54.00	-19.84	Horizontal
7266.00	20.74	36.28	11.69	31.94	36.77	54.00	-17.23	Horizontal
9688.00	20.68	38.13	14.21	31.52	41.50	54.00	-12.50	Horizontal



Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	36.56	31.85	8.66	32.12	44.95	74.00	-29.05	Vertical
7311.00	32.52	36.37	11.71	31.91	48.69	74.00	-25.31	Vertical
9748.00	32.47	38.27	14.25	31.56	53.43	74.00	-20.57	Vertical
4874.00	37.47	31.85	8.66	32.12	45.86	74.00	-28.14	Horizontal
7311.00	31.39	36.37	11.71	31.91	47.56	74.00	-26.44	Horizontal
9748.00	32.46	38.27	14.25	31.56	53.42	74.00	-20.58	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	27.63	31.85	8.66	32.12	36.02	54.00	-17.98	Vertical
7311.00	20.90	36.37	11.71	31.91	37.07	54.00	-16.93	Vertical
9748.00	21.77	38.27	14.25	31.56	42.73	54.00	-11.27	Vertical
4874.00	27.73	31.85	8.66	32.12	36.12	54.00	-17.88	Horizontal
7311.00	20.52	36.37	11.71	31.91	36.69	54.00	-17.31	Horizontal
9748.00	22.22	38.27	14.25	31.56	43.18	54.00	-10.82	Horizontal

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	40.07	31.88	8.68	32.13	48.50	74.00	-25.50	Vertical
7356.00	31.92	36.45	11.75	31.86	48.26	74.00	-25.74	Vertical
9808.00	34.85	38.43	14.29	31.68	55.89	74.00	-18.11	Vertical
4904.00	40.12	31.88	8.68	32.13	48.55	74.00	-25.45	Horizontal
7356.00	31.21	36.45	11.75	31.86	47.55	74.00	-26.45	Horizontal
9808.00	31.19	38.43	14.29	31.68	52.23	74.00	-21.77	Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	31.36	31.88	8.68	32.13	39.79	54.00	-14.21	Vertical
7356.00	21.94	36.45	11.75	31.86	38.28	54.00	-15.72	Vertical
9808.00	23.44	38.43	14.29	31.68	44.48	54.00	-9.52	Vertical
4904.00	30.74	31.88	8.68	32.13	39.17	54.00	-14.83	Horizontal
7356.00	20.68	36.45	11.75	31.86	37.02	54.00	-16.98	Horizontal
9808.00	20.53	38.43	14.29	31.68	41.57	54.00	-12.43	Horizontal

Notes:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

■ **Unwanted Emissions in restricted Frequency Bands**

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	42.50	27.14	6.19	42.04	33.79	74.00	-40.21	Horizontal
2390.00	51.80	27.37	6.31	42.11	43.37	74.00	-30.63	Horizontal
2310.00	41.24	27.14	6.19	42.04	32.53	74.00	-41.47	Vertical
2390.00	53.82	27.37	6.31	42.11	45.39	74.00	-28.61	Vertical

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	32.02	27.14	6.19	42.04	23.31	54.00	-30.69	Horizontal
2390.00	39.40	27.37	6.31	42.11	30.97	54.00	-23.03	Horizontal
2310.00	30.90	27.14	6.19	42.04	22.19	54.00	-31.81	Vertical
2390.00	41.59	27.37	6.31	42.11	33.16	54.00	-20.84	Vertical

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	52.52	27.66	6.45	42.01	44.62	74.00	-29.38	Horizontal
2500.00	44.08	27.70	6.47	42.00	36.25	74.00	-37.75	Horizontal
2483.50	52.95	27.66	6.45	42.01	45.05	74.00	-28.95	Vertical
2500.00	45.78	27.70	6.47	42.00	37.95	74.00	-36.05	Vertical

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	39.51	27.66	6.45	42.01	31.61	54.00	-22.39	Horizontal
2500.00	35.45	27.70	6.47	42.00	27.62	54.00	-26.38	Horizontal
2483.50	40.53	27.66	6.45	42.01	32.63	54.00	-21.37	Vertical
2500.00	34.36	27.70	6.47	42.00	26.53	54.00	-27.47	Vertical

Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	41.38	27.14	6.19	42.04	32.67	74.00	-41.33	Horizontal
2390.00	50.30	27.37	6.31	42.11	41.87	74.00	-32.13	Horizontal
2310.00	40.04	27.14	6.19	42.04	31.33	74.00	-42.67	Vertical
2390.00	52.03	27.37	6.31	42.11	43.60	74.00	-30.40	Vertical

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	31.22	27.14	6.19	42.04	22.51	54.00	-31.49	Horizontal
2390.00	38.48	27.37	6.31	42.11	30.05	54.00	-23.95	Horizontal
2310.00	30.02	27.14	6.19	42.04	21.31	54.00	-32.69	Vertical
2390.00	40.59	27.37	6.31	42.11	32.16	54.00	-21.84	Vertical

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	50.92	27.66	6.45	42.01	43.02	74.00	-30.98	Horizontal
2500.00	42.84	27.70	6.47	42.00	35.01	74.00	-38.99	Horizontal
2483.50	51.13	27.66	6.45	42.01	43.23	74.00	-30.77	Vertical
2500.00	44.33	27.70	6.47	42.00	36.50	74.00	-37.50	Vertical

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	38.54	27.66	6.45	42.01	30.64	54.00	-23.36	Horizontal
2500.00	34.70	27.70	6.47	42.00	26.87	54.00	-27.13	Horizontal
2483.50	39.47	27.66	6.45	42.01	31.57	54.00	-22.43	Vertical
2500.00	33.57	27.70	6.47	42.00	25.74	54.00	-28.26	Vertical

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	41.15	27.14	6.19	42.04	32.44	74.00	-41.56	Horizontal
2390.00	49.99	27.37	6.31	42.11	41.56	74.00	-32.44	Horizontal
2310.00	39.80	27.14	6.19	42.04	31.09	74.00	-42.91	Vertical
2390.00	51.65	27.37	6.31	42.11	43.22	74.00	-30.78	Vertical

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	31.05	27.14	6.19	42.04	22.34	54.00	-31.66	Horizontal
2390.00	38.29	27.37	6.31	42.11	29.86	54.00	-24.14	Horizontal
2310.00	29.83	27.14	6.19	42.04	21.12	54.00	-32.88	Vertical
2390.00	40.38	27.37	6.31	42.11	31.95	54.00	-22.05	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	50.59	27.66	6.45	42.01	42.69	74.00	-31.31	Horizontal
2500.00	42.58	27.70	6.47	42.00	34.75	74.00	-39.25	Horizontal
2483.50	50.75	27.66	6.45	42.01	42.85	74.00	-31.15	Vertical
2500.00	44.02	27.70	6.47	42.00	36.19	74.00	-37.81	Vertical

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	38.34	27.66	6.45	42.01	30.44	54.00	-23.56	Horizontal
2500.00	34.54	27.70	6.47	42.00	26.71	54.00	-27.29	Horizontal
2483.50	39.24	27.66	6.45	42.01	31.34	54.00	-22.66	Vertical
2500.00	33.40	27.70	6.47	42.00	25.57	54.00	-28.43	Vertical

Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	40.33	27.14	6.19	42.04	31.62	74.00	-42.38	Horizontal
2390.00	48.89	27.37	6.31	42.11	40.46	74.00	-33.54	Horizontal
2310.00	38.92	27.14	6.19	42.04	30.21	74.00	-43.79	Vertical
2390.00	50.33	27.37	6.31	42.11	41.90	74.00	-32.10	Vertical

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	30.47	27.14	6.19	42.04	21.76	54.00	-32.24	Horizontal
2390.00	37.62	27.37	6.31	42.11	29.19	54.00	-24.81	Horizontal
2310.00	29.18	27.14	6.19	42.04	20.47	54.00	-33.53	Vertical
2390.00	39.64	27.37	6.31	42.11	31.21	54.00	-22.79	Vertical

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	49.41	27.66	6.45	42.01	41.51	74.00	-32.49	Horizontal
2500.00	41.67	27.70	6.47	42.00	33.84	74.00	-40.16	Horizontal
2483.50	49.40	27.66	6.45	42.01	41.50	74.00	-32.50	Vertical
2500.00	42.96	27.70	6.47	42.00	35.13	74.00	-38.87	Vertical

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.63	27.66	6.45	42.01	29.73	54.00	-24.27	Horizontal
2500.00	33.99	27.70	6.47	42.00	26.16	54.00	-27.84	Horizontal
2483.50	38.46	27.66	6.45	42.01	30.56	54.00	-23.44	Vertical
2500.00	32.82	27.70	6.47	42.00	24.99	54.00	-29.01	Vertical

*Remarks:*

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

## 8 Test Setup Photo

Reference to the **appendix I** for details.

## 9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----