

TEST REPORT

Reference No...... : WTH24X11256458W001
FCC ID..... : 2AHYK-GKIPC20AA
Applicant..... : SHENZHEN GIEC DIGITAL CO.,LTD
Address..... : 1st&3rd Building,No.26 Puzai Road,Pingdi,Longgang District,Shenzhen,
China
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : Smart Camera
Model No...... : GK-IPC2034
Standards..... : FCC Part 15.407
Date of Receipt sample..... : 2024-11-04
Date of Test..... : 2024-11-04 to 2024-11-19
Date of Issue..... : 2024-11-19
Test Report Form No...... : WTX_Part 15_407W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.


Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Gala Wang

Approved by:



Jason Su

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 TEST STANDARDS	6
1.3 TEST METHODOLOGY	6
1.4 TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING	6
1.5 EUT OPERATING DURING TEST	8
1.6 TEST FACILITY	8
1.7 EUT SETUP AND TEST MODE	9
1.8 MEASUREMENT UNCERTAINTY	10
1.9 TEST EQUIPMENT LIST AND DETAILS	11
2. SUMMARY OF TEST RESULTS	15
3. ANTENNA REQUIREMENT	16
3.1 STANDARD APPLICABLE	16
3.2 EVALUATION INFORMATION	16
4. AUTOMATICALLY DISCONTINUE TRANSMISSION	17
4.1 STANDARD APPLICABLE	17
4.2 SUMMARY OF TEST RESULTS	17
5. POWER SPECTRAL DENSITY	18
5.1 STANDARD APPLICABLE	18
5.2 TEST PROCEDURE	18
5.3 SUMMARY OF TEST RESULTS/PLOTS	19
6. EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH	20
6.1 STANDARD APPLICABLE	20
6.2 TEST PROCEDURE	20
6.3 SUMMARY OF TEST RESULTS/PLOTS	22
7. MAXIMUM CONDUCTED OUTPUT POWER	23
7.1 STANDARD APPLICABLE	23
7.2 TEST PROCEDURE	23
7.3 SUMMARY OF TEST RESULTS/PLOTS	24
8. RADIATED SPURIOUS EMISSIONS	25
8.1 STANDARD APPLICABLE	25
8.2 TEST PROCEDURE	25
8.3 TEST RECEIVER SETUP	27
8.4 CORRECTED AMPLITUDE & MARGIN CALCULATION	27
8.5 SUMMARY OF TEST RESULTS/PLOTS	27
9. FREQUENCY STABILITY	88
9.1 STANDARD APPLICABLE	88
9.2 TEST PROCEDURE	88
9.3 SUMMARY OF TEST RESULTS/PLOTS	88
10. CONDUCTED EMISSIONS	89
10.1 TEST PROCEDURE	89
10.2 BASIC TEST SETUP BLOCK DIAGRAM	89
10.3 TEST RECEIVER SETUP	89
10.4 SUMMARY OF TEST RESULTS/PLOTS	89
APPENDIX SUMMARY	92
APPENDIX A	93
APPENDIX B	107
APPENDIX C	133
APPENDIX D	147

APPENDIX PHOTOGRAPHS 149

Report version

Version No.	Date of issue	Description
Rev.00	2024-11-19	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Smart Camera
Trade Name:	/
Model No.:	GK-IPC2034
Adding Model(s):	GK-IPC2032, GK-IPC2033, GK-IPC2035, AD-CAM-OUT-WH-001
Rated Voltage:	DC 12V
Battery Capacity:	/
Power Adapter:	Model: JYSY1501-1201000U Input: 100-240V~50/60Hz 0.5A Output: 12.0V-1.0A 12.0W
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model GK-IPC2034, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11a, 802.11n(HT20), 802.11n-HT40, 802.11ac-VHT20/40, 802.11ax-HE20/40
Frequency Range:	5180-5240MHz, 5745-5825MHz
Max. RF Output Power:	Band 1: 16.83dBm (Conducted) Band 4: 14.48dBm (Conducted)
Type of Modulation:	QPSK, 16QAM, 64QAM, 256QAM
Type of Antenna:	PCB Antenna
Antenna Gain:	Band 1: 1.45dBi Band 4: 1.31dBi
<i>Note The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.407: General technical requirements.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

KDB789033 D02 v02r01: Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-Nii) Devices Part 15, Subparte.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB789033 D02 v02r01. The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Table for parameters of Test Software setting

Run commands and follow the instructions given by the manufacturer, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Mode	Test Frequency (MHz)												
	NCB: 20MHz												
	5180	5200	5240	5260	5280	5320	5500	5580	5700	5720	5745	5785	5825
802.11a 6Mbps	87	87	87	/	/	/	/	/	/	/	80	75	75
802.11n-HT20 MCS0	87	85	80	/	/	/	/	/	/	/	75	70	70
802.11ac-VHT20 MCS0	87	85	80	/	/	/	/	/	/	/	75	70	70
802.11ax-HE20 MCS0	87	85	80	/	/	/	/	/	/	/	75	70	70
Mode	NCB: 40MHz												
	5190	5230	5270	5310	5510	5550	5670	5710	5755	5795			
802.11ac-VHT40 MCS0	87	85	/	/	/	/	/	/	75	70			
802.11n-HT40 MCS0	87	85	/	/	/	/	/	/	75	70			

Reference No.: WTH24X11256458W001

802.11ax -HE40 MCS0	87	85	/	/	/	/	/	/	75	70
------------------------	----	----	---	---	---	---	---	---	----	----

1.5 EUT Operating during test

EUT was programmed to be in continuously transmitting mode. During the test, EUT operation to normal function and programs under Android were executed.

1.6 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.7 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11a	5180MHz,5200MHz,5240MHz,5745MHz, 5785MHz,5825MHz
TM2	802.11n-HT20	5180MHz,5200MHz,5240MHz,5745MHz, 5785MHz,5825MHz
TM3	802.11ac-VHT20	5180MHz,5200MHz,5240MHz,5745MHz, 5785MHz,5825MHz
TM4	802.11ax-HE20	5180MHz,5200MHz,5240MHz,5745MHz, 5785MHz,5825MHz
TM5	802.11n-HT40	5190MHz,5230MHz,5755MHz,5795MHz
TM6	802.11ac-VHT40	5190MHz,5230MHz,5755MHz,5795MHz
TM7	802.11ax-HE40	5190MHz,5230MHz,5755MHz,5795MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	45~75 %
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
DC Cable	1.5	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Network Cable	1.0	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.8 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.9 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2024-02-24	2025-02-23
WTXE1005A 1005	Spectrum Analyzer	Agilent	N9020A	US471401 02	2024-03-19	2025-03-18
WTXE1084A 1001	Spectrum Analyzer	Agilent	N9020A	MY543205 48	2024-02-24	2025-02-23
WTXE1004A 1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2024-02-27	2025-02-26
WTXE1103A 1003	Attenuator	Pasternack	PE4007-4	/	2024-02-24	2025-02-23
WTXE1003A 1-005	Coaxial Cable	/	0M4RFC	/	2024-07-03	2025-01-03
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2024-02-24	2025-02-23
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
WTXE1007A 1001	Amplifier	HP	8447F	2805A034 75	2024-02-24	2025-02-23
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2024-02-24	2025-02-23
WTXE1104A 1032-1	Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-14
WTXE1104A 1032-2	Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-14
WTXE1104A 1032-3	Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-14
☒ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2024-02-24	2025-02-23
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
WTXE1065A 1001	Amplifier	C&D	PAP-1G18	2002	2024-02-27	2025-02-26
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2024-02-26	2025-02-25

WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-14
WTXE1104A 1033-2	Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-14
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-14
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2024-02-24	2025-02-23
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2024-02-24	2025-02-23
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2024-07-03	2025-07-02
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02
☒ Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1007A 1002	Amplifier	HP	8447F	2944A038 69	2024-02-24	2025-02-23
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-02
WTXE1104A 1034-2	Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-02
WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-02
☒ Chamber C: Above 1GHz						
WTXE1093A	EMI Test	Rohde &	ESIB 26	100401	2024-02-27	2025-02-26

1001	Receiver	Schwarz				
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2023-03-10	2026-03-09
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2024-02-27	2025-02-26
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2024-07-03	2025-07-02
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2024-07-03	2025-07-02
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2024-07-03	2025-07-02
☐ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2023-12-12	2024-12-11
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2024-02-24	2025-02-23
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2024-02-24	2025-02-23
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2024-07-03	2025-07-02
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2024-02-24	2025-02-23
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2024-02-24	2025-02-23
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission A)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission B)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission C)	Farad	EZ-EMC	RA-03A1-2 (1.1.4.2)
EMI Test Software (Conducted Emission Room 1#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3
EMI Test Software (Conducted Emission Room 2#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.405	Antenna Requirement	Compliant
15.407 (c)	Automatically Discontinue Transmission	Compliant
§15.207; §15.407(b)(6)	Conducted Emission	Compliant
§15.407(a)(1),(2)	Power Spectral Density	Compliant
§15.407(e)	Emission Bandwidth and Occupied Bandwidth	Compliant
§15.407(a)(1),(2)	Maximum Conducted Output Power	Compliant
§15.407(b)(1),(2),(3),(4)	Undesirable emission	Compliant
§15.205; §15.407(b)(1),(2),(3)	Radiated Emission	Compliant
§15.407(g)	Frequency Stability	Compliant
§15.407(h)	Dynamic Frequency Selection (DFS)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information

This product has a PCB antenna, fulfill the requirement of this section.

4. Automatically Discontinue Transmission

4.1 Standard Applicable

According to FCC Part 15.407(c), the device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

4.2 Summary of Test Results

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

5. Power Spectral Density

5.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11 \text{ dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

5.2 Test Procedure

According to 789033 D02 v02r01 General UNII Test Procedures New Rules v02, the following is the measurement procedure.

For devices operating in the bands 5.15-5.25GHz, 5.25-5.35GHz, and 5.47-5.725GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85GHz, the rules specify a measurement bandwidth of 500kHz. Many spectrum analyzers do not have 500kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500kHz, "provided that the measured power is integrated over the full

reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1MHz, or 500kHz). If measurements are performed using a reduced resolution bandwidth ($< 1\text{MHz}$, or $< 500\text{kHz}$) and integrated over 1 MHz, or 500kHz bandwidth, the following adjustments to the procedures apply:

- a) Set $\text{RBW} \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $\text{VBW} \geq 3 \text{ RBW}$.
- c) If measurement bandwidth of Maximum PSD is specified in 500kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 500\text{kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 1\text{MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100kHz for the sections 5.c) and 5.d) above, since $\text{RBW}=100\text{kHz}$ is available on nearly all spectrum analyzers.

5.3 Summary of Test Results/Plots

Please refer to Appendix A

6. Emission Bandwidth and Occupied Bandwidth

6.1 Standard Applicable

According to 15.407(a) and (e):

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(e) Within the 5.725-5.85GHz band, the minimum 6dB bandwidth of U-NII devices shall be at least 500kHz.

6.2 Test Procedure

According to 789033 D02 v02r0r section C&D, the following is the measurement procedure.

1. Emission Bandwidth (EBW)

a) Set RBW = approximately 1% of the emission bandwidth.

b) Set the VBW > RBW.

- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85GHz Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

D. 99 Percent Occupied Bandwidth

The 99-percent occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission. Measurement of the 99-percent occupied bandwidth is required only as a condition for using the optional band-edge measurement techniques described in section II.G.3.d). Measurements of 99-percent occupied bandwidth may also optionally be used in lieu of the EBW to 789033 D02 v02r01 General UNII Test Procedures New Rules v01 define the minimum frequency range over which the spectrum is integrated when measuring maximum conducted output power as described in section II.E. However, the EBW must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with 15.407(a).

The following procedure shall be used for measuring (99 %) power bandwidth:

- 1. Set center frequency to the nominal EUT channel center frequency.
- 2. Set span = 1.5 times to 5.0 times the OBW.
- 3. Set RBW = 1 % to 5 % of the OBW
- 4. Set VBW $\geq 3 \times$ RBW
- 5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- 6. Use the 99 % power bandwidth function of the instrument (if available).
- 7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency.

Reference No.: WTH24X11256458W001

The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6.3 Summary of Test Results/Plots

Please refer to Appendix B

7. Maximum Conducted Output Power

7.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

7.2 Test Procedure

According to KDB789033 D02 v02r01 section E, the following is the measurement procedure.

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1MHz.
- (iii) Set VBW $\geq$ 3MHz.
- (iv) Number of points in sweep $\geq$ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that

narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq$ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

7.3 Summary of Test Results/Plots

Please refer to Appendix C

8. Radiated Spurious Emissions

8.1 Standard Applicable

According to §15.407(b), undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725GHz band: All emissions outside of the 5.47-5.725GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85GHz band:
 - (i) All emissions shall be limited to a level of -27dBm/MHz at 75MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6dBm/MHz at 5MHz above or below the band edge, and from 5MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

According to §15.407(b)(6), Unwanted emissions below 1GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

According to §15.407(b)(7), The provisions of §15.205 apply to intentional radiators operating under this section.

789033 D02 v02r01 General UNII Test Procedures New Rules v01

If radiated measurements are performed, field strength is then converted to EIRP as follows:

$$\text{EIRP} = ((E \cdot d)^2) / 30$$

where:


- E is the field strength in V/m;
- d is the measurement distance in meters;
- EIRP is the equivalent isotropically radiated power in watts.

8.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.407(b)(6) and FCC Part 15.209 Limit..

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



8.3 Test Receiver Setup

During the radiated emission test for above 1GHz, the test receiver was set with the following configurations:

For peak detector:

RBW = 1000kHz, VBW = 3000kHz, Sweep Time = Auto

For average detector:

RBW = 1000kHz, VBW = 10Hz, Sweep Time = Auto

8.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.5 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


- Spurious Emission From 30MHz to 1GHz
- 5150-5250MHz

802.11a			
Test Channel	5180MHz(Worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	100.4712	39.48	-11.95	27.53	43.50	-15.97	-	-	peak
2	149.9676	36.10	-8.04	28.06	43.50	-15.44	-	-	peak
3	175.0404	42.22	-9.03	33.19	43.50	-10.31	-	-	peak
4	200.0432	48.98	-11.38	37.60	43.50	-5.90	-	-	peak
5	300.6988	46.22	-7.85	38.37	46.00	-7.63	-	-	peak
6	350.9722	38.13	-7.05	31.08	46.00	-14.92	-	-	peak

802.11a			
Test Channel	5180MHz(Worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.4588	38.91	-8.07	30.84	40.00	-9.16	-	-	peak
2	84.8783	36.97	-12.51	24.46	40.00	-15.54	-	-	peak
3	100.4712	51.05	-11.95	39.10	43.50	-4.40	-	-	peak
4	149.9676	41.96	-8.04	33.92	43.50	-9.58	-	-	peak
5	175.0404	39.45	-9.03	30.42	43.50	-13.08	-	-	peak
6	200.0432	50.91	-11.38	39.53	43.50	-3.97	-	-	peak

802.11n-HT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	100.4712	39.07	-11.95	27.12	43.50	-16.38	-	-	peak
2	149.9676	37.06	-8.04	29.02	43.50	-14.48	-	-	peak
3	175.0404	42.07	-9.03	33.04	43.50	-10.46	-	-	peak
4	200.0432	48.84	-11.38	37.46	43.50	-6.04	-	-	peak
5	300.6988	45.87	-7.85	38.02	46.00	-7.98	-	-	peak
6	804.2523	37.02	1.05	38.07	46.00	-7.93	-	-	peak

802.11n-HT20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.7371	32.44	-8.01	24.43	40.00	-15.57	-	-	peak
2	53.0056	28.76	-7.91	20.85	40.00	-19.15	-	-	peak
3	100.4712	50.80	-11.95	38.85	43.50	-4.65	-	-	peak
4	149.9676	41.48	-8.04	33.44	43.50	-10.06	-	-	peak
5	200.0432	50.89	-11.38	39.51	43.50	-3.99	-	-	peak
6	300.6988	35.34	-7.85	27.49	46.00	-18.51	-	-	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	100.4712	39.09	-11.95	27.14	43.50	-16.36	-	-	peak
2	175.0404	41.98	-9.03	32.95	43.50	-10.55	-	-	peak
3	200.0432	49.47	-11.38	38.09	43.50	-5.41	-	-	peak
4	250.4859	41.08	-9.68	31.40	46.00	-14.60	-	-	peak
5	300.6988	46.16	-7.85	38.31	46.00	-7.69	-	-	peak
6	350.9722	38.80	-7.05	31.75	46.00	-14.25	-	-	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.1825	38.05	-8.12	29.93	40.00	-10.07	-	-	peak
2	100.4712	51.06	-11.95	39.11	43.50	-4.39	-	-	peak
3	149.9676	43.79	-8.04	35.75	43.50	-7.75	-	-	peak
4	175.0404	40.05	-9.03	31.02	43.50	-12.48	-	-	peak
5	200.0432	50.83	-11.38	39.45	43.50	-4.05	-	-	peak
6	300.6988	34.26	-7.85	26.41	46.00	-19.59	-	-	peak

802.11ax-HE20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	100.4712	39.60	-11.95	27.65	43.50	-15.85	-	-	peak
2	149.9676	37.03	-8.04	28.99	43.50	-14.51	-	-	peak
3	175.0404	41.95	-9.03	32.92	43.50	-10.58	-	-	peak
4	200.0432	48.90	-11.38	37.52	43.50	-5.98	-	-	peak
5	300.6988	46.19	-7.85	38.34	46.00	-7.66	-	-	peak
6	734.0373	36.01	-0.23	35.78	46.00	-10.22	-	-	peak

802.11ax-HE20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.7371	36.38	-8.01	28.37	40.00	-11.63	-	-	peak
2	100.4712	51.10	-11.95	39.15	43.50	-4.35	-	-	peak
3	149.9676	43.88	-8.04	35.84	43.50	-7.66	-	-	peak
4	175.0404	39.59	-9.03	30.56	43.50	-12.94	-	-	peak
5	200.0432	50.97	-11.38	39.59	43.50	-3.91	-	-	peak
6	300.6988	34.68	-7.85	26.83	46.00	-19.17	-	-	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	175.0404	41.53	-9.03	32.50	43.50	-11.00	-	-	peak
2	200.0432	48.78	-11.38	37.40	43.50	-6.10	-	-	peak
3	250.4859	39.78	-9.68	30.10	46.00	-15.90	-	-	peak
4	300.6988	46.11	-7.85	38.26	46.00	-7.74	-	-	peak
5	350.9722	38.84	-7.05	31.79	46.00	-14.21	-	-	peak
6	445.6932	32.80	-5.28	27.52	46.00	-18.48	-	-	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.5837	32.76	-7.96	24.80	40.00	-15.20	-	-	peak
2	100.4712	50.75	-11.95	38.80	43.50	-4.70	-	-	peak
3	149.9676	43.30	-8.04	35.26	43.50	-8.24	-	-	peak
4	175.0404	40.13	-9.03	31.10	43.50	-12.40	-	-	peak
5	200.0432	51.17	-11.38	39.79	43.50	-3.71	-	-	peak
6	300.6988	34.54	-7.85	26.69	46.00	-19.31	-	-	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	149.9676	37.43	-8.04	29.39	43.50	-14.11	-	-	peak
2	175.0404	41.63	-9.03	32.60	43.50	-10.90	-	-	peak
3	200.0432	48.80	-11.38	37.42	43.50	-6.08	-	-	peak
4	250.4859	41.04	-9.68	31.36	46.00	-14.64	-	-	peak
5	300.6988	45.95	-7.85	38.10	46.00	-7.90	-	-	peak
6	350.9722	39.21	-7.05	32.16	46.00	-13.84	-	-	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.1581	33.00	-7.96	25.04	40.00	-14.96	-	-	peak
2	74.2696	36.31	-11.18	25.13	40.00	-14.87	-	-	peak
3	100.4712	51.01	-11.95	39.06	43.50	-4.44	-	-	peak
4	149.9676	42.01	-8.04	33.97	43.50	-9.53	-	-	peak
5	175.0404	39.61	-9.03	30.58	43.50	-12.92	-	-	peak
6	200.0432	51.05	-11.38	39.67	43.50	-3.83	-	-	peak

802.11ax-HE40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	100.4712	38.54	-11.95	26.59	43.50	-16.91	-	-	peak
2	149.9676	36.79	-8.04	28.75	43.50	-14.75	-	-	peak
3	175.0404	42.27	-9.03	33.24	43.50	-10.26	-	-	peak
4	200.0432	48.97	-11.38	37.59	43.50	-5.91	-	-	peak
5	250.4859	41.30	-9.68	31.62	46.00	-14.38	-	-	peak
6	300.6988	46.09	-7.85	38.24	46.00	-7.76	-	-	peak


802.11ax-HE40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.4588	38.40	-8.07	30.33	40.00	-9.67	-	-	peak
2	74.2696	35.20	-11.18	24.02	40.00	-15.98	-	-	peak
3	100.4712	51.09	-11.95	39.14	43.50	-4.36	-	-	peak
4	149.9676	43.90	-8.04	35.86	43.50	-7.64	-	-	peak
5	175.0404	39.47	-9.03	30.44	43.50	-13.06	-	-	peak
6	200.0432	50.89	-11.38	39.51	43.50	-3.99	-	-	peak


➤ 5725-5850MHz

802.11a			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	175.0404	41.68	-9.03	32.65	43.50	-10.85	-	-	peak
2	200.0432	49.17	-11.38	37.79	43.50	-5.71	-	-	peak
3	250.4859	40.86	-9.68	31.18	46.00	-14.82	-	-	peak
4	300.6988	46.24	-7.85	38.39	46.00	-7.61	-	-	peak
5	350.9722	38.69	-7.05	31.64	46.00	-14.36	-	-	peak
6	938.7139	39.29	3.03	42.32	46.00	-3.68	-	-	peak

802.11a			
Test Channel	5745MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.4588	38.01	-8.07	29.94	40.00	-10.06	-	-	peak
2	100.4712	51.07	-11.95	39.12	43.50	-4.38	-	-	peak
3	149.9676	43.50	-8.04	35.46	43.50	-8.04	-	-	peak
4	175.0404	39.60	-9.03	30.57	43.50	-12.93	-	-	peak
5	200.0432	51.04	-11.38	39.66	43.50	-3.84	-	-	peak
6	300.6988	34.82	-7.85	26.97	46.00	-19.03	-	-	peak

802.11n-HT20			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	100.4712	39.18	-11.95	27.23	43.50	-16.27	-	-	peak
2	149.9676	37.31	-8.04	29.27	43.50	-14.23	-	-	peak
3	175.0404	41.49	-9.03	32.46	43.50	-11.04	-	-	peak
4	200.0432	49.11	-11.38	37.73	43.50	-5.77	-	-	peak
5	250.4859	40.84	-9.68	31.16	46.00	-14.84	-	-	peak
6	300.6988	46.00	-7.85	38.15	46.00	-7.85	-	-	peak

802.11n-HT20			
Test Channel	5745MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.7371	38.21	-8.01	30.20	40.00	-9.80	-	-	peak
2	74.2696	38.06	-11.18	26.88	40.00	-13.12	-	-	peak
3	100.4712	51.02	-11.95	39.07	43.50	-4.43	-	-	peak
4	149.9676	42.95	-8.04	34.91	43.50	-8.59	-	-	peak
5	200.0432	50.81	-11.38	39.43	43.50	-4.07	-	-	peak
6	300.6988	35.09	-7.85	27.24	46.00	-18.76	-	-	peak

802.11ac-VHT20			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	100.4712	38.67	-11.95	26.72	43.50	-16.78	-	-	peak
2	149.9676	36.98	-8.04	28.94	43.50	-14.56	-	-	peak
3	175.0404	42.12	-9.03	33.09	43.50	-10.41	-	-	peak
4	200.0432	49.16	-11.38	37.78	43.50	-5.72	-	-	peak
5	250.4859	40.51	-9.68	30.83	46.00	-15.17	-	-	peak
6	300.6988	45.96	-7.85	38.11	46.00	-7.89	-	-	peak

802.11ac-VHT20			
Test Channel	5745MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.7371	34.19	-8.01	26.18	40.00	-13.82	-	-	peak
2	58.4855	27.80	-8.34	19.46	40.00	-20.54	-	-	peak
3	100.4712	50.79	-11.95	38.84	43.50	-4.66	-	-	peak
4	149.9676	43.16	-8.04	35.12	43.50	-8.38	-	-	peak
5	175.0404	39.21	-9.03	30.18	43.50	-13.32	-	-	peak
6	200.0432	51.10	-11.38	39.72	43.50	-3.78	-	-	peak

802.11ax-HE20			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	149.9676	36.19	-8.04	28.15	43.50	-15.35	-	-	peak
2	175.0404	41.84	-9.03	32.81	43.50	-10.69	-	-	peak
3	200.0432	48.98	-11.38	37.60	43.50	-5.90	-	-	peak
4	250.4859	40.63	-9.68	30.95	46.00	-15.05	-	-	peak
5	300.6988	46.02	-7.85	38.17	46.00	-7.83	-	-	peak
6	350.9722	39.45	-7.05	32.40	46.00	-13.60	-	-	peak

802.11ax-HE20			
Test Channel	5745MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.1825	32.06	-8.12	23.94	40.00	-16.06	-	-	peak
2	74.7934	36.61	-11.30	25.31	40.00	-14.69	-	-	peak
3	100.4712	51.29	-11.95	39.34	43.50	-4.16	-	-	peak
4	149.9676	40.99	-8.04	32.95	43.50	-10.55	-	-	peak
5	175.0404	39.31	-9.03	30.28	43.50	-13.22	-	-	peak
6	200.0432	50.81	-11.38	39.43	43.50	-4.07	-	-	peak

802.11n-HT40			
Test Channel	5755MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	149.9676	36.79	-8.04	28.75	43.50	-14.75	-	-	peak
2	175.0404	41.75	-9.03	32.72	43.50	-10.78	-	-	peak
3	200.0432	48.85	-11.38	37.47	43.50	-6.03	-	-	peak
4	250.4859	41.39	-9.68	31.71	46.00	-14.29	-	-	peak
5	300.6988	46.19	-7.85	38.34	46.00	-7.66	-	-	peak
6	350.9722	39.26	-7.05	32.21	46.00	-13.79	-	-	peak

802.11n-HT40			
Test Channel	5755MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.0173	38.77	-7.95	30.82	40.00	-9.18	-	-	peak
2	100.4712	48.94	-11.95	36.99	43.50	-6.51	-	-	peak
3	149.9676	43.48	-8.04	35.44	43.50	-8.06	-	-	peak
4	200.0432	48.45	-11.38	37.07	43.50	-6.43	-	-	peak
5	250.4859	41.77	-9.68	32.09	46.00	-13.91	-	-	peak
6	734.0373	41.30	-0.23	41.07	46.00	-4.93	-	-	peak

802.11ac-VHT40			
Test Channel	5755MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	100.4712	38.85	-11.95	26.90	43.50	-16.60	-	-	peak
2	175.0404	41.85	-9.03	32.82	43.50	-10.68	-	-	peak
3	200.0432	49.10	-11.38	37.72	43.50	-5.78	-	-	peak
4	250.4859	40.41	-9.68	30.73	46.00	-15.27	-	-	peak
5	300.6988	45.96	-7.85	38.11	46.00	-7.89	-	-	peak
6	938.7139	39.81	3.03	42.84	46.00	-3.16	-	-	peak

802.11ac-VHT40			
Test Channel	5755MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.0173	32.37	-7.95	24.42	40.00	-15.58	-	-	peak
2	74.7934	35.28	-11.30	23.98	40.00	-16.02	-	-	peak
3	100.4712	51.00	-11.95	39.05	43.50	-4.45	-	-	peak
4	149.9676	43.71	-8.04	35.67	43.50	-7.83	-	-	peak
5	175.0404	39.35	-9.03	30.32	43.50	-13.18	-	-	peak
6	200.0432	51.21	-11.38	39.83	43.50	-3.67	-	-	peak

802.11ax-HE40			
Test Channel	5755MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	100.4712	38.83	-11.95	26.88	43.50	-16.62	-	-	peak
2	124.9249	33.49	-9.67	23.82	43.50	-19.68	-	-	peak
3	175.0404	41.96	-9.03	32.93	43.50	-10.57	-	-	peak
4	200.0432	49.13	-11.38	37.75	43.50	-5.75	-	-	peak
5	250.4859	40.71	-9.68	31.03	46.00	-14.97	-	-	peak
6	300.6988	45.82	-7.85	37.97	46.00	-8.03	-	-	peak

802.11ax-HE40			
Test Channel	5755MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.7371	38.46	-8.01	30.45	40.00	-9.55	-	-	peak
2	74.7934	37.90	-11.30	26.60	40.00	-13.40	-	-	peak
3	100.4712	51.12	-11.95	39.17	43.50	-4.33	-	-	peak
4	149.9676	42.30	-8.04	34.26	43.50	-9.24	-	-	peak
5	200.0432	50.77	-11.38	39.39	43.50	-4.11	-	-	peak
6	300.6988	35.04	-7.85	27.19	46.00	-18.81	-	-	peak

Remark: '-'Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.


➤ Spurious Emission above 1GHz

802.11a- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	67.67	-12.53	55.14	74.00	-18.86	-	-	peak

802.11a- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5147.395	47.19	-12.54	34.65	54.00	-19.35	-	-	AVG

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5146.092	69.95	-12.55	57.40	74.00	-16.60	-	-	peak

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	48.05	-12.53	35.52	54.00	-18.48	-	-	AVG

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	70.87	-12.53	58.34	74.00	-15.66	-	-	peak

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5147.395	48.34	-12.54	35.80	54.00	-18.20	-	-	AVG

802.11ax-HE20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5148.697	71.48	-12.53	58.95	74.00	-15.05	-	-	peak

802.11ax-HE20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	47.59	-12.53	35.06	54.00	-18.94	-	-	AVG

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5148.697	75.91	-12.53	63.38	74.00	-10.62	-	-	peak

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	51.05	-12.53	38.52	54.00	-15.48	-	-	AVG

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5148.697	81.03	-12.53	68.50	74.00	-5.50	-	-	peak

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5148.697	52.35	-12.53	39.82	54.00	-14.18	-	-	AVG

802.11ax-HE40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5147.395	81.33	-12.54	68.79	74.00	-5.21	-	-	peak

802.11ax-HE40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5148.697	54.14	-12.53	41.61	54.00	-12.39	-	-	AVG

Note: The Restricted Bandedge was tested in Horizontal /Vertical and the worst case position data was reported.

Remark: ‘-’Means’ the test Degree and Height is not recorded by the test software and only show the worst case in the test report.

- For the frequency band 5.150-5.250GHz, 5.725-5.850GHz (802.11a)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5180MHz)							
10360	61.93	-6.13	55.8	74	-18.2	H	PK
10360	41.28	-6.13	35.15	54	-18.85	H	AV
15540	57.92	-1.64	56.28	74	-17.72	H	PK
15540	38.75	-1.64	37.11	54	-16.89	H	AV
10360	58.38	-6.13	52.25	74	-21.75	V	PK
10360	41.11	-6.13	34.98	54	-19.02	V	AV
15540	57.53	-1.64	55.89	74	-18.11	V	PK
15540	40.69	-1.64	39.05	54	-14.95	V	AV
Middle Channel (5200MHz)							
10400	58.48	-5.93	52.55	74	-21.45	H	PK
10400	41.95	-5.93	36.02	54	-17.98	H	AV
15600	60.71	-1.58	59.13	74	-14.87	H	PK
15600	38.55	-1.58	36.97	54	-17.03	H	AV
10400	61.25	-5.93	55.32	74	-18.68	V	PK
10400	39.71	-5.93	33.78	54	-20.22	V	AV
15600	60.07	-1.58	58.49	74	-15.51	V	PK
15600	38.98	-1.58	37.4	54	-16.6	V	AV
High Channel (5240MHz)							
10480	59.16	-5.71	53.45	74	-20.55	H	PK
10480	41.94	-5.71	36.23	54	-17.77	H	AV
15720	58.96	-1.52	57.44	74	-16.56	H	PK
15720	38.78	-1.52	37.26	54	-16.74	H	AV
10480	58.26	-5.71	52.55	74	-21.45	V	PK
10480	38.05	-5.71	32.34	54	-21.66	V	AV
15720	60.75	-1.52	59.23	74	-14.77	V	PK
15720	41.25	-1.52	39.73	54	-14.27	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5745MHz)							
11490	60.01	-6.13	53.88	74	-20.12	H	PK
11490	43.3	-6.13	37.17	54	-16.83	H	AV
17235	55.99	-1.64	54.35	74	-19.65	H	PK
17235	40.86	-1.64	39.22	54	-14.78	H	AV
11490	58.78	-6.13	52.65	74	-21.35	V	PK
11490	40.77	-6.13	34.64	54	-19.36	V	AV
17235	55.31	-1.64	53.67	74	-20.33	V	PK
17235	38.02	-1.64	36.38	54	-17.62	V	AV
Middle Channel (5785MHz)							
11570	60.62	-5.93	54.69	74	-19.31	H	PK
11570	41.11	-5.93	35.18	54	-18.82	H	AV
17355	60.13	-1.58	58.55	74	-15.45	H	PK
17355	38.03	-1.58	36.45	54	-17.55	H	AV
11570	61.55	-5.93	55.62	74	-18.38	V	PK
11570	39.4	-5.93	33.47	54	-20.53	V	AV
17355	61.35	-1.58	59.77	74	-14.23	V	PK
17355	39.78	-1.58	38.2	54	-15.8	V	AV
High Channel (5825MHz)							
11650	58.6	-5.71	52.89	74	-21.11	H	PK
11650	39.59	-5.71	33.88	54	-20.12	H	AV
17475	60.9	-1.52	59.38	74	-14.62	H	PK
17475	40.82	-1.52	39.3	54	-14.7	H	AV
11650	60.07	-5.71	54.36	74	-19.64	V	PK
11650	39.14	-5.71	33.43	54	-20.57	V	AV
17475	61.56	-1.52	60.04	74	-13.96	V	PK
17475	38.96	-1.52	37.44	54	-16.56	V	AV

➤ Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-31.56	-27
Highest	Above 5350	-32.63	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-33.21	-27
	5650 to 5700	-26.51	-27 to -17
	5700 to 5720	-24.23	-17 to 15.6
	5720 to 5725	-36.25	15.6 to 27
Highest	5850 to 5855	-38.21	27 to 15.6
	5855 to 5875	-38.69	15.6 to -17
	5875 to 5925	-29.19	-17 to -27
	Above 5925	-30.24	-27
Note: the data just list the worst cases			

- For the frequency band 5.150-5.250GHz, 5.725-5.850GHz (802.11n HT20)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5180MHz)							
10360	58.61	-6.13	52.48	74	-21.52	H	PK
10360	42.95	-6.13	36.82	54	-17.18	H	AV
15540	58.49	-1.64	56.85	74	-17.15	H	PK
15540	41.33	-1.64	39.69	54	-14.31	H	AV
10360	56.53	-6.13	50.4	74	-23.6	V	PK
10360	40.09	-6.13	33.96	54	-20.04	V	AV
15540	56.59	-1.64	54.95	74	-19.05	V	PK
15540	40.89	-1.64	39.25	54	-14.75	V	AV
Middle Channel (5200MHz)							
10400	60.39	-5.93	54.46	74	-19.54	H	PK
10400	41.88	-5.93	35.95	54	-18.05	H	AV
15600	60.13	-1.58	58.55	74	-15.45	H	PK
15600	39.09	-1.58	37.51	54	-16.49	H	AV
10400	61.77	-5.93	55.84	74	-18.16	V	PK
10400	38.38	-5.93	32.45	54	-21.55	V	AV
15600	61.04	-1.58	59.46	74	-14.54	V	PK
15600	38.06	-1.58	36.48	54	-17.52	V	AV
High Channel (5240MHz)							
10480	59.52	-5.71	53.81	74	-20.19	H	PK
10480	41.08	-5.71	35.37	54	-18.63	H	AV
15720	59.37	-1.52	57.85	74	-16.15	H	PK
15720	39.56	-1.52	38.04	54	-15.96	H	AV
10480	61.37	-5.71	55.66	74	-18.34	V	PK
10480	38.54	-5.71	32.83	54	-21.17	V	AV
15720	60.01	-1.52	58.49	74	-15.51	V	PK
15720	38.86	-1.52	37.34	54	-16.66	V	AV

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5745MHz)							
11490	59.81	-6.13	53.68	74	-20.32	H	PK
11490	41.87	-6.13	35.74	54	-18.26	H	AV
17235	55.25	-1.64	53.61	74	-20.39	H	PK
17235	40.3	-1.64	38.66	54	-15.34	H	AV
11490	56.78	-6.13	50.65	74	-23.35	V	PK

11490	38.85	-6.13	32.72	54	-21.28	V	AV
17235	57.3	-1.64	55.66	74	-18.34	V	PK
17235	38.9	-1.64	37.26	54	-16.74	V	AV
Middle Channel (5785MHz)							
11570	60.64	-5.93	54.71	74	-19.29	H	PK
11570	38.87	-5.93	32.94	54	-21.06	H	AV
17355	59.1	-1.58	57.52	74	-16.48	H	PK
17355	40.25	-1.58	38.67	54	-15.33	H	AV
11570	58.02	-5.93	52.09	74	-21.91	V	PK
11570	39.11	-5.93	33.18	54	-20.82	V	AV
17355	60.43	-1.58	58.85	74	-15.15	V	PK
17355	38.02	-1.58	36.44	54	-17.56	V	AV
High Channel (5825MHz)							
11650	59.38	-5.71	53.67	74	-20.33	H	PK
11650	39.13	-5.71	33.42	54	-20.58	H	AV
17475	61.06	-1.52	59.54	74	-14.46	H	PK
17475	39.32	-1.52	37.8	54	-16.2	H	AV
11650	59.33	-5.71	53.62	74	-20.38	V	PK
11650	40.21	-5.71	34.5	54	-19.5	V	AV
17475	58.61	-1.52	57.09	74	-16.91	V	PK
17475	40.74	-1.52	39.22	54	-14.78	V	AV

➤ Out of Band edge 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-29.24	-27
Highest	Above 5350	-38.65	-27

Note: the data just list the worst cases

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-34.56	-27
	5650 to 5700	-32.14	-27 to -17
	5700 to 5720	-25.54	-17 to 15.6
	5720 to 5725	-36.18	15.6 to 27
Highest	5850 to 5855	-38.25	27 to 15.6
	5855 to 5875	-26.23	15.6 to -17
	5875 to 5925	-24.16	-17 to -27
	Above 5925	-32.98	-27

Note: the data just list the worst cases

- For the frequency band 5.150-5.250GHz, 5.725-5.850GHz (802.11ac-VHT20)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5180MHz)							
10360	58.72	-6.13	52.59	74	-21.41	H	PK
10360	42.41	-6.13	36.28	54	-17.72	H	AV
15540	56.24	-1.64	54.6	74	-19.4	H	PK
15540	38.25	-1.64	36.61	54	-17.39	H	AV
10360	56.35	-6.13	50.22	74	-23.78	V	PK
10360	38.17	-6.13	32.04	54	-21.96	V	AV
15540	57.31	-1.64	55.67	74	-18.33	V	PK
15540	40.82	-1.64	39.18	54	-14.82	V	PK
Middle Channel (5200MHz)							
10400	59.9	-5.93	53.97	74	-20.03	H	PK
10400	41.14	-5.93	35.21	54	-18.79	H	AV
15600	58.06	-1.58	56.48	74	-17.52	H	PK
15600	41.75	-1.58	40.17	54	-13.83	H	AV
10400	60.28	-5.93	54.35	74	-19.65	V	PK
10400	39.58	-5.93	33.65	54	-20.35	V	AV
15600	60.26	-1.58	58.68	74	-15.32	V	PK
15600	38.92	-1.58	37.34	54	-16.66	V	PK
High Channel (5240MHz)							
10480	60.71	-5.71	55	74	-19	H	PK
10480	40.72	-5.71	35.01	54	-18.99	H	AV
15720	60.88	-1.52	59.36	74	-14.64	H	PK
15720	40.95	-1.52	39.43	54	-14.57	H	AV
10480	58.57	-5.71	52.86	74	-21.14	V	PK
10480	38.78	-5.71	33.07	54	-20.93	V	AV
15720	60.11	-1.52	58.59	74	-15.41	V	PK
15720	38.75	-1.52	37.23	54	-16.77	V	PK

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5745MHz)							
11490	58.69	-6.13	52.56	74	-21.44	H	PK
11490	41.21	-6.13	35.08	54	-18.92	H	AV
17235	57.11	-1.64	55.47	74	-18.53	H	PK
17235	38.28	-1.64	36.64	54	-17.36	H	AV
11490	57.31	-6.13	51.18	74	-22.82	V	PK
11490	39.56	-6.13	33.43	54	-20.57	V	AV
11490	57.26	-1.64	55.62	74	-18.38	V	PK
17235	40.29	-1.64	38.65	54	-15.35	V	PK
Middle Channel (5785MHz)							
11570	61.17	-5.93	55.24	74	-18.76	H	PK
11570	38.64	-5.93	32.71	54	-21.29	H	AV
17355	61.38	-1.58	59.8	74	-14.2	H	PK
17355	40.73	-1.58	39.15	54	-14.85	H	AV
11570	61.13	-5.93	55.2	74	-18.8	V	PK
11570	39.51	-5.93	33.58	54	-20.42	V	AV
17355	61.21	-1.58	59.63	74	-14.37	V	PK
17355	38.95	-1.58	37.37	54	-16.63	V	PK
High Channel (5825MHz)							
11650	59.6	-5.71	53.89	74	-20.11	H	PK
11650	38.85	-5.71	33.14	54	-20.86	H	AV
17475	61.02	-1.52	59.5	74	-14.5	H	PK
17475	40.39	-1.52	38.87	54	-15.13	H	AV
11650	60.8	-5.71	55.09	74	-18.91	V	PK
11650	41.79	-5.71	36.08	54	-17.92	V	AV
17475	61.94	-1.52	60.42	74	-13.58	V	PK
17475	38.82	-1.52	37.3	54	-16.7	V	PK

➤ Out of Band edge 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-29.25	-27
Highest	Above 5350	-33.36	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-41.22	-27
	5650 to 5700	-23.62	-27 to -17
	5700 to 5720	-24.17	-17 to 15.6
	5720 to 5725	-36.10	15.6 to 27
Highest	5850 to 5855	-36.52	27 to 15.6
	5855 to 5875	-29.18	15.6 to -17
	5875 to 5925	-26.33	-17 to -27
	Above 5925	-39.15	-27
Note: the data just list the worst cases			

- For the frequency band 5.150-5.250GHz, 5.725-5.850GHz (802.11ax HE20)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5180MHz)							
10360	58.57	-6.13	52.44	74	-21.56	H	PK
10360	42.11	-6.13	35.98	54	-18.02	H	AV
15540	57.88	-1.64	56.24	74	-17.76	H	PK
15540	40.11	-1.64	38.47	54	-15.53	H	AV
10360	58.32	-6.13	52.19	74	-21.81	V	PK
10360	38.02	-6.13	31.89	54	-22.11	V	AV
15540	57.52	-1.64	55.88	74	-18.12	V	PK
15540	39.1	-1.64	37.46	54	-16.54	V	PK
Middle Channel (5200MHz)							
10400	59.21	-5.93	53.28	74	-20.72	H	PK
10400	41.16	-5.93	35.23	54	-18.77	H	AV
15600	58.73	-1.58	57.15	74	-16.85	H	PK
15600	38.97	-1.58	37.39	54	-16.61	H	AV
10400	60.04	-5.93	54.11	74	-19.89	V	PK
10400	39.27	-5.93	33.34	54	-20.66	V	AV
15600	59.92	-1.58	58.34	74	-15.66	V	PK
15600	39.97	-1.58	38.39	54	-15.61	V	PK
High Channel (5240MHz)							
10480	59.22	-5.71	53.51	74	-20.49	H	PK
10480	40.83	-5.71	35.12	54	-18.88	H	AV
15720	61.15	-1.52	59.63	74	-14.37	H	PK
15720	41.01	-1.52	39.49	54	-14.51	H	AV
10480	60.52	-5.71	54.81	74	-19.19	V	PK
10480	39.53	-5.71	33.82	54	-20.18	V	AV
15720	59.64	-1.52	58.12	74	-15.88	V	PK
15720	40.12	-1.52	38.6	54	-15.4	V	PK

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5745MHz)							
11490	60.92	-6.13	54.79	74	-19.21	H	PK
11490	42.03	-6.13	35.9	54	-18.1	H	AV
17235	55.6	-1.64	53.96	74	-20.04	H	PK
17235	40.63	-1.64	38.99	54	-15.01	H	AV
11490	58.08	-6.13	51.95	74	-22.05	V	PK
11490	39.8	-6.13	33.67	54	-20.33	V	AV
11490	57.81	-1.64	56.17	74	-17.83	V	PK
17235	41.08	-1.64	39.44	54	-14.56	V	PK
Middle Channel (5785MHz)							
11570	61.74	-5.93	55.81	74	-18.19	H	PK
11570	39.54	-5.93	33.61	54	-20.39	H	AV
17355	61.53	-1.58	59.95	74	-14.05	H	PK
17355	41.32	-1.58	39.74	54	-14.26	H	AV
11570	60.82	-5.93	54.89	74	-19.11	V	PK
11570	40.62	-5.93	34.69	54	-19.31	V	AV
17355	59.5	-1.58	57.92	74	-16.08	V	PK
17355	39.85	-1.58	38.27	54	-15.73	V	PK
High Channel (5825MHz)							
11650	60.4	-5.71	54.69	74	-19.31	H	PK
11650	39.97	-5.71	34.26	54	-19.74	H	AV
17475	60.55	-1.52	59.03	74	-14.97	H	PK
17475	41.91	-1.52	40.39	54	-13.61	H	AV
11650	60.87	-5.71	55.16	74	-18.84	V	PK
11650	40.47	-5.71	34.76	54	-19.24	V	AV
17475	60.65	-1.52	59.13	74	-14.87	V	PK
17475	40.28	-1.52	38.76	54	-15.24	V	PK

➤ Out of Band edge 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-31.58	-27
Highest	Above 5350	-31.66	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-38.33	-27
	5650 to 5700	-36.22	-27 to -17
	5700 to 5720	-21.03	-17 to 15.6
	5720 to 5725	-21.66	15.6 to 27
Highest	5850 to 5855	-34.65	27 to 15.6
	5855 to 5875	-21.17	15.6 to -17
	5875 to 5925	-23.46	-17 to -27
	Above 5925	-33.38	-27
Note: the data just list the worst cases			

- For the frequency band 5.150-5.250GHz, 5.725-5.850GHz (802.11n HT40)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5190MHz)							
10380	61.41	-6.07	55.34	74	-18.66	H	PK
10380	42.66	-6.07	36.59	54	-17.41	H	AV
15570	53.9	-1.63	52.27	74	-21.73	H	PK
15570	40.84	-1.63	39.21	54	-14.79	H	AV
10380	59.76	-6.07	53.69	74	-20.31	V	PK
10380	41.44	-6.07	35.37	54	-18.63	V	AV
15570	54.27	-1.63	52.64	74	-21.36	V	PK
15570	40.12	-1.63	38.49	54	-15.51	V	PK
High Channel (5230MHz)							
10460	61.44	-5.94	55.5	74	-18.5	H	PK
10460	42.49	-5.94	36.55	54	-17.45	H	AV
15690	52.95	-1.59	51.36	74	-22.64	H	PK
15690	39.58	-1.59	37.99	54	-16.01	H	AV
10460	61.84	-5.94	55.9	74	-18.1	V	PK
10460	43.36	-5.94	37.42	54	-16.58	V	AV
15690	55.08	-1.59	53.49	74	-20.51	V	PK
15690	38.25	-1.59	36.66	54	-17.34	V	PK

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5755MHz)							
11510	58.06	-6.07	51.99	74	-22.01	H	PK
11510	42.95	-6.07	36.88	54	-17.12	H	AV
17265	54.92	-1.63	53.29	74	-20.71	H	PK
17265	38.14	-1.63	36.51	54	-17.49	H	AV
11510	61.39	-6.07	55.32	74	-18.68	V	PK
11510	41.65	-6.07	35.58	54	-18.42	V	AV
17265	53.15	-1.63	51.52	74	-22.48	V	PK
17265	40.86	-1.63	39.23	54	-14.77	V	AV
High Channel (5795MHz)							
11590	61.94	-5.94	56	74	-18	H	PK
11590	43.16	-5.94	37.22	54	-16.78	H	AV
17385	53.24	-1.59	51.65	74	-22.35	H	PK
17385	40.49	-1.59	38.9	54	-15.1	H	AV
11590	61.13	-5.94	55.19	74	-18.81	V	PK
11590	42.53	-5.94	36.59	54	-17.41	V	AV
17385	55.44	-1.59	53.85	74	-20.15	V	PK
17385	39.32	-1.59	37.73	54	-16.27	V	AV

➤ Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-36.32	-27
Highest	Above 5350	-34.12	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-36.25	-27
	5650 to 5700	-27.11	-27 to -17
	5700 to 5720	-28.23	-17 to 15.6
	5720 to 5725	-34.70	15.6 to 27
Highest	5850 to 5855	-39.16	27 to 15.6
	5855 to 5875	-23.39	15.6 to -17
	5875 to 5925	-29.56	-17 to -27
	Above 5925	-34.22	-27
Note: the data just list the worst cases			

- For the frequency band 5.150-5.250GHz, 5.725-5.850GHz (802.11ac-VHT40)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5190MHz)							
10380	61.71	-6.07	55.64	74	-18.36	H	PK
10380	43.79	-6.07	37.72	54	-16.28	H	AV
15570	54.85	-1.63	53.22	74	-20.78	H	PK
15570	38.75	-1.63	37.12	54	-16.88	H	AV
10380	61.37	-6.07	55.3	74	-18.7	V	PK
10380	42.46	-6.07	36.39	54	-17.61	V	AV
15570	53.55	-1.63	51.92	74	-22.08	V	PK
15570	39.4	-1.63	37.77	54	-16.23	V	AV
High Channel (5230MHz)							
10460	58.07	-5.94	52.13	74	-21.87	H	PK
10460	42.37	-5.94	36.43	54	-17.57	H	AV
15690	52.42	-1.59	50.83	74	-23.17	H	PK
15690	39.31	-1.59	37.72	54	-16.28	H	AV
10460	58.89	-5.94	52.95	74	-21.05	V	PK
10460	43.77	-5.94	37.83	54	-16.17	V	AV
15690	53.38	-1.59	51.79	74	-22.21	V	PK
15690	38.69	-1.59	37.1	54	-16.9	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5755MHz)							
11510	61.05	-6.07	54.98	74	-19.02	H	PK
11510	41.06	-6.07	34.99	54	-19.01	H	AV
17265	53.74	-1.63	52.11	74	-21.89	H	PK
17265	38.33	-1.63	36.7	54	-17.3	H	AV
11510	60.07	-6.07	54	74	-20	V	PK
11510	41.85	-6.07	35.78	54	-18.22	V	AV
17265	52.78	-1.63	51.15	74	-22.85	V	PK
17265	40.11	-1.63	38.48	54	-15.52	V	AV
High Channel (5795MHz)							
11590	61.73	-5.94	55.79	74	-18.21	H	PK
11590	43.45	-5.94	37.51	54	-16.49	H	AV
17385	54.03	-1.59	52.44	74	-21.56	H	PK
17385	40.34	-1.59	38.75	54	-15.25	H	AV
11590	61.21	-5.94	55.27	74	-18.73	V	PK
11590	43.2	-5.94	37.26	54	-16.74	V	AV
17385	53.9	-1.59	52.31	74	-21.69	V	PK
17385	40.65	-1.59	39.06	54	-14.94	V	AV

➤ Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-31.26	-27
Highest	Above 5350	-35.63	-27

Note: the data just list the worst cases

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-38.28	-27
	5650 to 5700	-27.12	-27 to -17
	5700 to 5720	-24.19	-17 to 15.6
	5720 to 5725	-36.34	15.6 to 27
Highest	5850 to 5855	-32.14	27 to 15.6
	5855 to 5875	-31.23	15.6 to -17
	5875 to 5925	-26.39	-17 to -27
	Above 5925	-33.62	-27

Note: the data just list the worst cases

- For the frequency band 5.150-5.250GHz, 5.725-5.850GHz (802.11ax HE40)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5190MHz)							
10380	61.01	-6.07	54.94	74	-19.06	H	PK
10380	41.42	-6.07	35.35	54	-18.65	H	AV
15570	53.53	-1.63	51.9	74	-22.1	H	PK
15570	38.02	-1.63	36.39	54	-17.61	H	AV
10380	60.55	-6.07	54.48	74	-19.52	V	PK
10380	43.71	-6.07	37.64	54	-16.36	V	AV
15570	53.14	-1.63	51.51	74	-22.49	V	PK
15570	39.16	-1.63	37.53	54	-16.47	V	AV
High Channel (5230MHz)							
10460	58.89	-5.94	52.95	74	-21.05	H	PK
10460	42.55	-5.94	36.61	54	-17.39	H	AV
15690	52.37	-1.59	50.78	74	-23.22	H	PK
15690	40.04	-1.59	38.45	54	-15.55	H	AV
10460	60.24	-5.94	54.3	74	-19.7	V	PK
10460	41.19	-5.94	35.25	54	-18.75	V	AV
15690	52.28	-1.59	50.69	74	-23.31	V	PK
15690	38.72	-1.59	37.13	54	-16.87	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5755MHz)							
11510	59.66	-6.07	53.59	74	-20.41	H	PK
11510	42.67	-6.07	36.6	54	-17.4	H	AV
17265	55.81	-1.63	54.18	74	-19.82	H	PK
17265	40.39	-1.63	38.76	54	-15.24	H	AV
11510	58.29	-6.07	52.22	74	-21.78	V	PK
11510	43.3	-6.07	37.23	54	-16.77	V	AV
17265	53.65	-1.63	52.02	74	-21.98	V	PK
17265	40.77	-1.63	39.14	54	-14.86	V	AV
High Channel (5795MHz)							
11590	61	-5.94	55.06	74	-18.94	H	PK
11590	41.04	-5.94	35.1	54	-18.9	H	AV
17385	52.57	-1.59	50.98	74	-23.02	H	PK
17385	38.21	-1.59	36.62	54	-17.38	H	AV
11590	59.35	-5.94	53.41	74	-20.59	V	PK
11590	43.14	-5.94	37.2	54	-16.8	V	AV
17385	52.88	-1.59	51.29	74	-22.71	V	PK
17385	39.09	-1.59	37.5	54	-16.5	V	AV

➤ Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-31.21	-27
Highest	Above 5350	-36.66	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-37.63	-27
	5650 to 5700	-26.59	-27 to -17
	5700 to 5720	-28.21	-17 to 15.6
	5720 to 5725	-37.39	15.6 to 27
Highest	5850 to 5855	-39.12	27 to 15.6
	5855 to 5875	-31.32	15.6 to -17
	5875 to 5925	-27.36	-17 to -27
	Above 5925	-39.21	-27
Note: the data just list the worst cases			

Note: Testing is carried out with frequency rang 9kHz to 40Ghz, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Frequency Stability

9.1 Standard Applicable

According to §15.407(g), manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

9.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode.

9.3 Summary of Test Results/Plots

Please refer to Appendix D


10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

10.2 Basic Test Setup Block Diagram




10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150kHz
Stop Frequency.....	30MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth.....	9kHz
Quasi-Peak Adapter Mode.....	Normal


10.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	37.10	9.76	46.86	65.99	-19.13	QP
2	0.1539	18.91	9.75	28.66	55.78	-27.12	AVG
3	0.4980	30.68	9.74	40.42	56.03	-15.61	QP
4*	0.4980	24.53	9.74	34.27	46.03	-11.76	AVG
5	1.3660	13.92	9.65	23.57	46.00	-22.43	AVG
6	1.3700	22.78	9.65	32.43	56.00	-23.57	QP
7	2.0500	11.20	9.62	20.82	46.00	-25.18	AVG
8	2.4539	16.74	9.62	26.36	56.00	-29.64	QP
9	6.1460	18.40	9.75	28.15	60.00	-31.85	QP
10	6.1460	14.94	9.75	24.69	50.00	-25.31	AVG
11	21.4660	19.61	10.19	29.80	60.00	-30.20	QP
12	22.5260	12.01	10.16	22.17	50.00	-27.83	AVG

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	38.45	9.76	48.21	65.99	-17.78	QP
2	0.1500	20.55	9.76	30.31	55.99	-25.68	AVG
3	0.4980	26.39	9.74	36.13	56.03	-19.90	QP
4*	0.4980	19.33	9.74	29.07	46.03	-16.96	AVG
5	1.3940	23.60	9.65	33.25	56.00	-22.75	QP
6	1.3940	13.33	9.65	22.98	46.00	-23.02	AVG
7	1.9740	22.15	9.62	31.77	56.00	-24.23	QP
8	2.0500	11.54	9.62	21.16	46.00	-24.84	AVG
9	6.1460	18.19	9.75	27.94	60.00	-32.06	QP
10	6.1460	13.49	9.75	23.24	50.00	-26.76	AVG
11	18.4340	13.83	10.15	23.98	50.00	-26.02	AVG
12	22.5300	25.14	10.16	35.30	60.00	-24.70	QP

APPENDIX SUMMARY

Project No.	WTH24X11256458W	Test Engineer	Timi Huang
Start date	2024/11/13	Finish date	2024/11/13
Temperature	22.5℃	Humidity	62%
RF specifications	U-NII		

APPENDIX	Description of Test Item	Result
A	Power Spectral Density	Compliant
B	Emission Bandwidth and Occupied Bandwidth	Compliant
C	Maximum Conducted Output Power	Compliant
D	Frequency Stability	Compliant



APPENDIX A

Power Spectral Density			
U-NII-1:5150-5250MHz			
Operating mode	Test Channel	Power Spectral Density dBm/MHz	Limit (dBm/MHz)
802.11a	5180	-4.20	11
	5200	-3.89	11
	5240	-3.34	11
802.11n-HT20	5180	-6.93	11
	5200	-6.56	11
	5240	-5.91	11
802.11n-HT40	5190	-12.88	11
	5230	-12.18	11
802.11ac-VHT20	5180	-6.74	11
	5200	-6.66	11
	5240	-5.94	11
802.11ac-VHT40	5190	-14.42	11
	5230	-13.58	11
802.11ax-HE20	5180	-8.77	11
	5200	-8.23	11
	5240	-7.48	11
802.11ax-HE40	5190	-13.78	11
	5230	-13.02	11



U-NII-3: 5725-5850MHz					
Operating mode	Test Channel	Power Spectral Density dBm/300kHz	Factor	Power Spectral Density* dBm/500kHz	Limit dBm/500kHz
802.11a	5745	-10.86	2.22	-8.64	30
	5785	-10.67	2.22	-8.45	30
	5825	-10.73	2.22	-8.51	30
802.11n-HT20	5745	-12.37	2.22	-10.15	30
	5785	-12.43	2.22	-10.21	30
	5825	-12.28	2.22	-10.06	30
802.11n HT40	5755	-18.22	2.22	-16	30
	5795	-18.04	2.22	-15.82	30

802.11ac-VHT20	5745	-13.74	2.22	-11.52	30
	5785	-14.19	2.22	-11.97	30
	5825	-14.27	2.22	-12.05	30
802.11ac-VHT40	5755	-18.63	2.22	-16.41	30
	5795	-19.00	2.22	-16.78	30
802.11ax-HE20	5745	-15.10	2.22	-12.88	30
	5785	-15.76	2.22	-13.54	30
	5825	-15.83	2.22	-13.61	30
802.11ax-HE40	5755	-19.55	2.22	-17.33	30
	5795	-19.85	2.22	-17.63	30
*Note: Maximum PSD=PSD(dBm/300kHz)+10log(500kHz/300kHz)=2.22					



5150-5250MHz






Date: 13.NOV.2024 14:27:15






Date: 13.NOV.2024 14:28:02









Date: 13.NOV.2024 14:29:09

802.11n-HT20-Low	 Ref: 20 dBm, Att: 30 dB, RBW: 1 MHz, VSW: 3 MHz, SWT: 1 s, Marker 1 [T1]: -6.93 dBm, 5.183120000 GHz Center: 5.18 GHz, Span: 40 MHz Date: 13.NOV.2024 14:26:15
802.11n-HT20-Middle	 Ref: 20 dBm, Att: 30 dB, RBW: 1 MHz, VSW: 3 MHz, SWT: 1 s, Marker 1 [T1]: -6.56 dBm, 5.197600000 GHz Center: 5.2 GHz, Span: 40 MHz Date: 13.NOV.2024 14:25:25
802.11n-HT20-High	 Ref: 20 dBm, Att: 30 dB, RBW: 1 MHz, VSW: 3 MHz, SWT: 1 s, Marker 1 [T1]: -5.91 dBm, 5.238960000 GHz Center: 5.24 GHz, Span: 40 MHz Date: 13.NOV.2024 14:24:49

Configuration	Plot Type	Frequency (GHz)	Power (dBm)	Bandwidth (MHz)	Span (MHz)	Resolution (MHz)	Marker 1 [T1]
802.11n-HT40-Low	Power Spectral Density (PSD)	5.19	-12.88	40	80	1	5.192880000 GHz
802.11n-HT40-High	Power Spectral Density (PSD)	5.23	-12.18	40	80	1	5.232880000 GHz
802.11ac-VHT20-Low	Power Spectral Density (PSD)	5.19	-6.74	20	40	1	5.192000000 GHz




802.11ac-VHT20-Middle	 Date: 13.NOV.2024 14:21:48
802.11ac-VHT20-High	 Date: 13.NOV.2024 14:22:22
802.11ac-VHT40-Low	 Date: 13.NOV.2024 14:09:35




802.11ac-VHT40-High	 Date: 13.NOV.2024 14:11:41
802.11ax-HE20-Low	 Date: 13.NOV.2024 14:20:33
802.11ax-HE20-Middle	 Date: 13.NOV.2024 14:19:57




802.11ax-HE20-High	 Date: 13.NOV.2024 14:19:13
802.11ax-HE40-Low	 Date: 13.NOV.2024 14:08:48
802.11ax-HE40-High	 Date: 13.NOV.2024 14:08:00




5725-5850MHz

802.11a-Low	Date: 13.NOV.2024 16:48:25
802.11a-Middle	Date: 13.NOV.2024 16:49:38
802.11a-High	Date: 13.NOV.2024 16:50:14

802.11n-HT20-Low	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -12.37 dBm *VSW 1 MHz *SWT 1 s 5.752520000 GHz 20 Offset 1 dB Center 5.745 GHz 4 MHz/ Span 40 MHz Date: 13.NOV.2024 16:47:29
802.11n-HT20-Middle	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -12.43 dBm *VSW 1 MHz *SWT 1 s 5.791240000 GHz 20 Offset 1 dB Center 5.785 GHz 4 MHz/ Span 40 MHz Date: 13.NOV.2024 16:46:49
802.11n-HT20-High	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -12.28 dBm *VSW 1 MHz *SWT 1 s 5.821320000 GHz 20 Offset 1 dB Center 5.825 GHz 4 MHz/ Span 40 MHz Date: 13.NOV.2024 16:46:13

802.11n-HT40-Low	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -18.22 dBm *VBW 1 MHz *SWT 1 s 5.770040000 GHz Offset 1 dB Center 5.755 GHz 8 MHz/ Span 80 MHz Date: 13.NOV.2024 16:38:43
802.11n-HT40-High	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -18.04 dBm *VBW 1 MHz *SWT 1 s 5.810040000 GHz Offset 1 dB Center 5.795 GHz 8 MHz/ Span 80 MHz Date: 13.NOV.2024 16:37:38
802.11ac-VHT20-Low	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -13.74 dBm *VBW 1 MHz *SWT 1 s 5.741240000 GHz Offset 1 dB Center 5.745 GHz 4 MHz/ Span 40 MHz Date: 13.NOV.2024 16:43:44

802.11ac-VHT20-Middle	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -14.19 dBm *VSW 1 MHz *SWT 1 s 5.777480000 GHz 20 Offset 1 dB Center 5.785 GHz 4 MHz/ Span 40 MHz Date: 13.NOV.2024 16:44:19
802.11ac-VHT20-High	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -14.27 dBm *VSW 1 MHz *SWT 1 s 5.822520000 GHz 20 Offset 1 dB Center 5.825 GHz 4 MHz/ Span 40 MHz Date: 13.NOV.2024 16:45:39
802.11ac-VHT40-Low	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -18.63 dBm *VSW 1 MHz *SWT 1 s 5.743640000 GHz 20 Offset 1 dB Center 5.755 GHz 8 MHz/ Span 80 MHz Date: 13.NOV.2024 16:35:18

802.11ac-VHT40-High	 Date: 13.NOV.2024 16:36:33
802.11ax-HE20-Low	 Date: 13.NOV.2024 16:42:25
802.11ax-HE20-Middle	 Date: 13.NOV.2024 16:40:22




Configuration	Plot Type	Frequency (GHz)	Span (MHz)	Resolution Bandwidth (kHz)	Marker 1 [T1] (dBm)	Date
802.11ax-HE20-High	Power Spectral Density (PSD)	5.825	40	300	-15.83	13.NOV.2024 16:39:29
802.11ax-HE40-Low	Power Spectral Density (PSD)	5.755	80	300	-19.55	13.NOV.2024 16:33:12
802.11ax-HE40-High	Power Spectral Density (PSD)	5.795	80	300	-19.85	13.NOV.2024 16:32:28




APPENDIX B

Emission Bandwidth and Occupied Bandwidth

U-NII-1:5150-5250MHz				
Test Mode	Test Channel MHz	26 dB Bandwidth MHz	99% Bandwidth MHz	Limit MHz
802.11a	5180	22.80	17.04	Pass
	5200	22.40	17.04	Pass
	5240	24.20	17.12	Pass
802.11n-HT20	5180	24.00	18.24	Pass
	5200	24.24	18.24	Pass
	5240	24.60	18.16	Pass
802.11n-HT40	5190	42.60	37.60	Pass
	5230	42.40	37.60	Pass
802.11ac-VHT20	5180	25.08	18.24	Pass
	5200	25.44	18.24	Pass
	5240	24.84	18.24	Pass
802.11ac-VHT40	5190	42.80	37.44	Pass
	5230	42.00	37.28	Pass
802.11ax-HE20	5180	27.24	19.36	Pass
	5200	26.64	19.36	Pass
	5240	26.40	19.36	Pass
802.11ax-HE40	5190	43.80	38.88	Pass
	5230	43.20	38.88	Pass

U-NII-3: 5725-5850MHz				
Test Mode	Test Channel MHz	6 dB Bandwidth MHz	99% Bandwidth MHz	Limit MHz
802.11a	5745	16.64	17.28	≥500
	5785	16.64	17.20	≥500
	5825	16.64	17.28	≥500
802.11n-HT20	5745	17.84	18.40	≥500
	5785	17.84	18.40	≥500
	5825	17.84	18.32	≥500
802.11n-HT40	5755	36.80	37.92	≥500
	5795	36.80	37.76	≥500
802.11ac-VHT20	5745	17.92	18.40	≥500
	5785	17.84	18.40	≥500
	5825	17.84	18.48	≥500
802.11ac-VHT40	5755	36.64	38.08	≥500
	5795	36.80	37.76	≥500
802.11ax-HE20	5745	19.12	19.44	≥500
	5785	19.12	19.52	≥500
	5825	19.12	19.44	≥500
802.11ax-HE40	5755	38.24	39.36	≥500
	5795	38.40	39.20	≥500

802.11n-HT20-Low	 Ref 20 dBm *Att 30 dB SWT 20 ms Marker 1 [T1] 5.183360000 GHz 6.46 dBm ndB [T1] 26.00 dB BW 24.00000000 MHz Temp 1 [T1] ndB -19.03 dBm 5.168000000 GHz -19.69 dBm 5.192000000 GHz Center 5.18 GHz 6 MHz/ Span 60 MHz Date: 13.NOV.2024 15:41:56
802.11n-HT20-Middle	 Ref 20 dBm *Att 30 dB SWT 20 ms Marker 1 [T1] 5.202520000 GHz 6.78 dBm ndB [T1] 26.00 dB BW 24.24000000 MHz Temp 1 [T1] ndB -19.73 dBm 5.188000000 GHz -19.39 dBm 5.212240000 GHz Center 5.2 GHz 6 MHz/ Span 60 MHz Date: 13.NOV.2024 15:40:50
802.11n-HT20-High	 Ref 20 dBm *Att 30 dB SWT 20 ms Marker 1 [T1] 5.240840000 GHz 7.22 dBm ndB [T1] 26.00 dB BW 24.60000000 MHz Temp 1 [T1] ndB -18.26 dBm 5.227640000 GHz -18.80 dBm 5.252240000 GHz Center 5.24 GHz 6 MHz/ Span 60 MHz Date: 13.NOV.2024 15:40:04

802.11n-HT40-Low	 Ref: 20 dBm Att: 30 dB BW: 1 MHz SWT: 20 ms Center: 5.19 GHz Span: 100 MHz Marker 1 [T1]: -23.55 dBm Level: -24.94 dBm Span: 1.71 MHz Date: 13.NOV.2024 15:19:25
802.11n-HT40-High	 Ref: 20 dBm Att: 30 dB BW: 1 MHz SWT: 20 ms Center: 5.23 GHz Span: 100 MHz Marker 1 [T1]: -23.78 dBm Level: -24.02 dBm Span: 1.71 MHz Date: 13.NOV.2024 15:18:24
802.11ac-VHT20-Low	 Ref: 20 dBm Att: 30 dB BW: 1 MHz SWT: 20 ms Center: 5.18 GHz Span: 60 MHz Marker 1 [T1]: -18.34 dBm Level: -19.18 dBm Span: 1.71 MHz Date: 13.NOV.2024 15:33:48

[illegible]

802.11ac-VHT40-High

Ref: 20 dBm, Att: 30 dB, RBW: 300 kHz, VBW: 1 MHz, SWT: 20 ms, Marker 1 [T1]: 5.22580000 GHz, 2.26 dBm

ndB [T1]: 26.00 dB, BW: 42.00000000 MHz, Span: 100.0000 MHz, Level: -23.57 dBm, 5.20940000 GHz, -23.76 dBm, 5.25140000 GHz

Center: 5.23 GHz, 10 MHz/, Span: 100 MHz

802.11ax-HE20-Low

Ref: 20 dBm, Att: 30 dB, RBW: 300 kHz, VBW: 1 MHz, SWT: 20 ms, Marker 1 [T1]: 5.18120000 GHz, 7.02 dBm

ndB [T1]: 26.00 dB, BW: 27.24000000 MHz, Span: 60.0000 MHz, Level: -18.95 dBm, 5.16740000 GHz, -18.95 dBm, 5.19460000 GHz

Center: 5.18 GHz, 6 MHz/, Span: 60 MHz

802.11ax-HE20-Middle




Ref: 20 dBm, Att: 30 dB, RBW: 300 kHz, VBW: 1 MHz, SWT: 20 ms, Marker 1 [T1]: 5.20120000 GHz, 7.61 dBm




ndB [T1]: 26.00 dB, BW: 26.64000000 MHz, Span: 60.0000 MHz, Level: -18.54 dBm, 5.18780000 GHz, -18.54 dBm, 5.21450000 GHz




Center: 5.2 GHz, 6 MHz/, Span: 60 MHz




802.11ax-HE20-High	Date: 13.NOV.2024 15:21:37
802.11ax-HE40-Low	Date: 13.NOV.2024 15:14:59
802.11ax-HE40-High	Date: 13.NOV.2024 15:11:34




6 dB Bandwidth
5725-5850MHz



802.11a-Low	 Ref 20 dBm *Att 30 dB RBW 100 kHz Delta 1 [T1] -0.58 dB VBW 300 kHz SWT 20 ms 16.640000000 MHz Marker 1 [T1] -0.20 dBm Marker 2 [T1] 2.43 dBm D1 -3.57 dBm Center 5.745 GHz 4 MHz/ Span 40 MHz Date: 13.NOV.2024 17:36:48
802.11a-Middle	 Ref 20 dBm *Att 30 dB RBW 100 kHz Delta 1 [T1] -0.87 dB VBW 300 kHz SWT 20 ms 16.640000000 MHz Marker 1 [T1] -4.53 dBm Marker 2 [T1] 2.48 dBm D1 -3.52 dBm Center 5.785 GHz 4 MHz/ Span 40 MHz Date: 13.NOV.2024 17:37:45
802.11a-High	 Ref 20 dBm *Att 30 dB RBW 100 kHz Delta 1 [T1] 1.82 dB VBW 300 kHz SWT 20 ms 16.640000000 MHz Marker 1 [T1] -7.11 dBm Marker 2 [T1] 2.74 dBm D1 -3.25 dBm Center 5.825 GHz 4 MHz/ Span 40 MHz Date: 13.NOV.2024 17:38:53

802.11n-HT20-Low	 Date: 13.NOV.2024 17:35:43
802.11n-HT20-Middle	 Date: 13.NOV.2024 17:34:36
802.11n-HT20-High	 Date: 13.NOV.2024 17:33:44



802.11n-HT40-Low	 Date: 13.NOV.2024 17:25:03
802.11n-HT40-High	 Date: 13.NOV.2024 17:23:48
802.11ac-VHT20-Low	 Date: 13.NOV.2024 17:30:53

802.11ac-VHT20-Middle	 Date: 13.NOV.2024 17:31:54
802.11ac-VHT20-High	 Date: 13.NOV.2024 17:32:47
802.11ac-VHT40-Low	 Date: 13.NOV.2024 17:21:29



802.11ac-VHT40-High	 Ref 20 dBm *Att 30 dB RBW 100 kHz VSW 300 kHz SWT 20 ms Delta 1 [T1] 2.27 dB 36.80000000 MHz Marker 1 [T1] -14.92 dBm 5.79500000 GHz LVL 30n Marker 2 [T1] -5.02 dBm 5.79500000 GHz LVL 30n Center 5.795 GHz 8 MHz Span 80 MHz Date: 13.NOV.2024 17:22:42
802.11ax-HE20-Low	 Ref 20 dBm *Att 30 dB RBW 100 kHz VSW 300 kHz SWT 20 ms Delta 1 [T1] 2.69 dB 19.12000000 MHz Marker 1 [T1] -8.92 dBm 5.74500000 GHz LVL 30n Marker 2 [T1] -5.65 dBm 5.74500000 GHz LVL 30n Center 5.745 GHz 4 MHz Span 40 MHz Date: 13.NOV.2024 17:29:32
802.11ax-HE20-Middle	 Ref 20 dBm *Att 30 dB RBW 100 kHz VSW 300 kHz SWT 20 ms Delta 1 [T1] 1.89 dB 19.12000000 MHz Marker 1 [T1] -7.49 dBm 5.78500000 GHz LVL 30n Marker 2 [T1] -5.85 dBm 5.78500000 GHz LVL 30n Center 5.785 GHz 4 MHz Span 40 MHz Date: 13.NOV.2024 17:28:33





99% Bandwidth
5150-5250MHz



Date: 13.NOV.2024 14:42:09




Date: 13.NOV.2024 14:41:29




Date: 13.NOV.2024 14:39:52


802.11n-HT20-Low






802.11n-HT20-Middle





802.11n-HT20-High




802.11n-HT40-Low	 Ref: 20 dBm Att: 30 dB RBW 1 MHz VBW 3 MHz SWT 20 ms Marker 1 [T1] 7.88 dBm OSW 37.60000000 MHz Temp 1 [T1] 0.00 dBm 5.171280000 GHz 5.208880000 GHz Center 5.19 GHz 8 MHz/ Span 80 MHz
802.11n-HT40-High	 Ref: 20 dBm Att: 30 dB RBW 1 MHz VBW 3 MHz SWT 20 ms Marker 1 [T1] 8.95 dBm OSW 37.60000000 MHz Temp 1 [T1] 0.00 dBm 5.211280000 GHz 5.248880000 GHz Center 5.23 GHz 8 MHz/ Span 80 MHz
802.11ac-VHT20-Low	 Ref: 20 dBm Att: 30 dB RBW 300 kHz VBW 1 MHz SWT 20 ms Marker 1 [T1] 6.08 dBm OSW 18.24000000 MHz Temp 1 [T1] 0.00 dBm 5.170880000 GHz 5.189120000 GHz Center 5.18 GHz 4 MHz/ Span 40 MHz

[illegible]







99% dB Bandwidth
5725-5850MHz



Date: 13.NOV.2024 16:52:46




Date: 13.NOV.2024 16:52:13




Date: 13.NOV.2024 16:51:29


802.11n-HT20-Low




802.11n-HT20-Middle




802.11n-HT20-High




802.11n-HT40-Low









802.11n-HT40-High



802.11ac-VHT20-Low



802.11ac-VHT20-Middle	 Date: 13.NOV.2024 16:56:21
802.11ac-VHT20-High	 Date: 13.NOV.2024 16:55:43
802.11ac-VHT40-Low	 Date: 13.NOV.2024 17:06:48

802.11ac-VHT40-High	 Date: 13.NOV.2024 17:05:22
802.11ax-HE20-Low	 Date: 13.NOV.2024 16:58:03
802.11ax-HE20-Middle	 Date: 13.NOV.2024 17:00:04



APPENDIX C



Maximum Conducted Output Power




U-NII-1:5150-5250MHz			
Test mode	Frequency MHz	Output Power dBm	Limit dBm
802.11a	5180	15.90	23.98
	5200	16.34	23.98
	5240	16.83	23.98
802.11n-HT20	5180	14.12	23.98
	5200	14.39	23.98
	5240	14.89	23.98
802.11n-HT40	5190	13.12	23.98
	5230	13.96	23.98
802.11ac-VHT20	5180	14.29	23.98
	5200	14.70	23.98
	5240	15.44	23.98
802.11ac-VHT40	5190	12.62	23.98
	5230	13.28	23.98
802.11ax-HE20	5180	14.24	23.98
	5200	14.76	23.98
	5240	15.36	23.98
802.11ax-HE40	5190	13.51	23.98
	5230	14.14	23.98

U-NII-3: 5725-5850MHz			
Test mode	Frequency MHz	Output Power dBm	Limit dBm
802.11a	5745	14.48	30.00
	5785	14.27	30.00
	5825	14.47	30.00
802.11n-HT20	5745	13.27	30.00
	5785	13.33	30.00
	5825	13.45	30.00
802.11n-HT40	5755	12.13	30.00
	5795	12.16	30.00




802.11ac-VHT20	5745	12.60	30.00
	5785	12.04	30.00
	5825	11.76	30.00
802.11ac-VHT40	5755	12.17	30.00
	5795	11.60	30.00
802.11ax-HE20	5745	12.23	30.00
	5785	11.72	30.00
	5825	11.64	30.00
802.11ax-HE40	5755	12.18	30.00
	5795	11.80	30.00




5150-5250MHz




802.11a-Low	 Date: 13.NOV.2024 11:48:17
802.11a-Middle	 Date: 13.NOV.2024 11:48:58

802.11a-High	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.24 GHz Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 16.83 dBm Date: 13.NOV.2024 11:49:31
802.11n-HT20-Low	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.18 GHz Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 14.12 dBm Date: 13.NOV.2024 11:52:50
802.11n-HT20-Middle	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.2 GHz Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 14.39 dBm Date: 13.NOV.2024 13:41:40


802.11n-HT20-High	Date: 13.NOV.2024 13:42:22
802.11n-HT40-Low	Date: 13.NOV.2024 13:48:34
802.11n-HT40-High	Date: 13.NOV.2024 13:50:40

802.11ac-VHT20-Low	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.18 GHz Span: 40 MHz 4 MHz/div Tx Channel Bandwidth: 20 MHz Power: 14.29 dBm Date: 13.NOV.2024 13:43:09
802.11ac-VHT20-Middle	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.2 GHz Span: 40 MHz 4 MHz/div Tx Channel Bandwidth: 20 MHz Power: 14.70 dBm Date: 13.NOV.2024 13:43:40
802.11ac-VHT20-High	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.24 GHz Span: 40 MHz 4 MHz/div Tx Channel Bandwidth: 20 MHz Power: 15.44 dBm Date: 13.NOV.2024 13:44:17

802.11ac-VHT40-Low	 Date: 13.NOV.2024 13:56:49
802.11ac-VHT40-High	 Date: 13.NOV.2024 13:58:35
802.11ax-HE20-Low	 Date: 13.NOV.2024 13:45:14

802.11ax-HE20-Middle	 Date: 13.NOV.2024 13:46:18
802.11ax-HE20-High	 Date: 13.NOV.2024 13:47:20
802.11ax-HE40-Low	 Date: 13.NOV.2024 14:00:04


802.11ax-HE40-High



Date: 13.NOV.2024 14:01:07


5725-5850MHz

802.11a-Low




Date: 13.NOV.2024 16:14:32

802.11a-Middle






Date: 13.NOV.2024 16:15:13




802.11a-High






Date: 13.NOV.2024 16:15:43

802.11n-HT20-Low	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.745 GHz Span: 40 MHz Bandwidth: 20 MHz Power: 13.27 dBm Date: 13.NOV.2024 16:17:25
802.11n-HT20-Middle	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.785 GHz Span: 40 MHz Bandwidth: 20 MHz Power: 13.33 dBm Date: 13.NOV.2024 16:16:52
802.11n-HT20-High	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.825 GHz Span: 40 MHz Bandwidth: 20 MHz Power: 13.45 dBm Date: 13.NOV.2024 16:16:18

802.11n-HT40-Low	Date: 13.NOV.2024 16:23:54
802.11n-HT40-High	Date: 13.NOV.2024 16:24:40
802.11ac-VHT20-Low	Date: 13.NOV.2024 16:18:47

802.11ac-VHT20-Middle	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.755 GHz Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 12.04 dBm Date: 13.NOV.2024 16:19:48
802.11ac-VHT20-High	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.825 GHz Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 11.76 dBm Date: 13.NOV.2024 16:20:46
802.11ac-VHT40-Low	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.755 GHz Span: 80 MHz Tx Channel Bandwidth: 40 MHz Power: 12.17 dBm Date: 13.NOV.2024 16:27:27

802.11ac-VHT40-High	 Date: 13.NOV.2024 16:25:27
802.11ax-HE20-Low	 Date: 13.NOV.2024 16:22:48
802.11ax-HE20-Middle	 Date: 13.NOV.2024 16:22:06

802.11ax-HE20-High	Date: 13.NOV.2024 16:21:33
802.11ax-HE40-Low	Date: 13.NOV.2024 16:28:36
802.11ax-HE40-High	Date: 13.NOV.2024 16:29:45

APPENDIX D

Frequency Stability

U-NII-1:5150-5250MHz worst case at 802.11a middle channel				
Voltage(%)	Power(VDC)	TEMP(°C)	Freq.Dev(Hz)	Deviation
100%	12	-30	501	0.096
100%		-20	503	0.097
100%		-10	496	0.095
100%		0	503	0.097
100%		+10	497	0.095
100%		+20	501	0.096
100%		+30	496	0.095
100%		+40	502	0.097
100%		+50	502	0.097
Low Battery power	10.8	+20	498	0.096
High Battery power	13.2	+20	498	0.096

U-NII-1:5725-5850MHz worst case at 802.11a middle channel				
Voltage(%)	Power(VDC)	TEMP(°C)	Freq.Dev(Hz)	Deviation
100%	12	-30	496	0.086
100%		-20	504	0.087
100%		-10	497	0.086
100%		0	500	0.086
100%		+10	500	0.086
100%		+20	502	0.087
100%		+30	499	0.086
100%		+40	505	0.087
100%		+50	501	0.087
Low Battery power	10.8	+20	497	0.086
High Battery power	13.2	+20	503	0.087

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****