

# RF EXPOSURE REPORT

## FOR

|                             |   |   |
|-----------------------------|---|---|
| <b>Applicant</b>            | : | PEAG, LLC dba JLab Audio  |
| <b>Address</b>              | : | 5927 Landau Ct. Carlsbad, CA 92008, USA   |
| <b>Equipment under Test</b> | : | TWS Earbuds   |
| <b>Model No.</b>            | : | Epic Lab Edition  |
| <b>Trade Mark</b>           | : | JLAB  |
| <b>FCC ID</b>               | : | 2AHYV-EPLEDG  |
| <b>Manufacturer</b>         | : | GuangDong Simpreal Intelligent Technology Co., Ltd  |
| <b>Address</b>              | : | Room 2408, JiaHong ZhenXing DaSha, DongGuan Avenue #13, DongCheng District, DongGuan City, GuangDong Province, P.R. China |

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add.:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,  
Dongguan City, Guangdong Province, China, 523808

**Tel.:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

### Table of Contents

|  |   |
|--|---|
| Test report declares.....              | 3 |
| 1. General Information .....           | 5 |
| 1.1. Description of equipment .....    | 5 |
| 1.2. Assess laboratory.....            | 5 |
| 2. RF Exposure evaluation for FCC..... | 6 |

## Test Report Declare

|                             |   |   |
|-----------------------------|---|---|
| <b>Applicant</b>            | : | PEAG, LLC dba JLab Audio  |
| <b>Address</b>              | : | 5927 Landau Ct. Carlsbad, CA 92008, USA   |
| <b>Equipment under Test</b> | : | TWS Earbuds   |
| <b>Model No.</b>            | : | Epic Lab Edition  |
| <b>Trade mark</b>           | : | JLAB  |
| <b>Manufacturer</b>         | : | GuangDong Simpreal Intelligent Technology Co., Ltd  |
| <b>Address</b>              | : | Room 2408, JiaHong ZhenXing DaSha, DongGuan Avenue #13,<br>DongCheng District, DongGuan City, Guangdong Province, P.R.<br>China |

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above.

The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

|                         |                     |                      |                               |
|-------------------------|---------------------|----------------------|-------------------------------|
| <b>Report No:</b>       | DDT-RE23071128-2E18 |                      |                               |
| <b>Date of Receipt:</b> | Jul. 19, 2023       | <b>Date of Test:</b> | Jul. 19, 2023 ~ Aug. 09, 2023 |

**Prepared By:**

*Johnny Wang*

**Johnny Wang/Engineer**

**Approved By:**

*Damon Hu*

**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

### Revision History

| Rev. | Revisions     | Issue Date    | Revised By |
|------|---------------|---------------|------------|
| ---  | Initial issue | Aug. 09, 2023 |            |
|      |               |               |            |

## 1. General Information

### 1.1. Description of equipment

|                          |  |
|--------------------------|--|
| EUT Name                 | : Dongle   |
| Model Number             | : Epic Lab Edition-Dongle                                    |
| EUT Function Description | : Please reference user manual of this device                |
| Power Supply             | : DC 5V  |
| Radio Specification      | : Bluetooth V5.3   |
| Operation Frequency      | : 2402 MHz - 2480 MHz  |
| Modulation               | : GFSK   |
| Data Rate                | : 1 Mbps, 2 Mbps   |
| Antenna                  | : 3.59 dBi   |
| Sample Number            | : S23071128-10 for conductive,<br>S23071128-11 for radiation |

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com).

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

## 2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

### Manufacturing Tolerance

#### BLE

Left side:

| GFSK 1M (Peak)       |           |            |            |
|----------------------|-----------|------------|------------|
| Channel              | Channel 0 | Channel 19 | Channel 39 |
| Target (dBm)         | 2         | 2          | 2          |
| Tolerance $\pm$ (dB) | 1         | 1          | 1          |

| GFSK 2M (Peak)       |           |            |            |
|----------------------|-----------|------------|------------|
| Channel              | Channel 1 | Channel 19 | Channel 38 |
| Target (dBm)         | 2         | 2          | 2          |
| Tolerance $\pm$ (dB) | 1         | 1          | 1          |

### Estimation Result

Worse case is as below: [2480 MHz, 3 dBm, (1.9953 mW) output power]

$(1.9953 / 5) \cdot [\sqrt{2.480(\text{GHz})}] = 0.6284 < 3.0$  for 1-g SAR

Then SAR evaluation is not required.

**END OF REPORT**