



## RF Exposure Evaluation

FCC ID: 2AHYV-GMOUSE

### Applicable Standard

According to FCC part 2.1093 and part 1.1307(b)(3), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline

KDB447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.3 SAR-Based Exemption:

A more comprehensive exemption, considering a variable power threshold that depends on both the separation distance and power, is provided in 1.1307(b)(3) (i)(B). This exemption is applicable to the frequency range between 300 MHz and 6 GHz, with test separation distances between 0.5 cm and 40 cm, and for all RF sources in fixed, mobile, and portable device exposure conditions

Accordingly, a RF source is considered an RF exempt device if its available maximum time averaged (matched conducted) power or its effective radiated power(ERP), whichever is greater, are below a specified threshold.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

### TEST RESULT

**Passed**

**Not Applicable**



# KSIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,  
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China  
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website: www.gdkesign.com

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain		ERP		Exemption Limit (mW)
				(dBi)	(dBd)	dBm	mw	
BDR/EDR	2402-2480	-1.35	-0.35	2.97	0.82	-0.35	0.92	1



# KSIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,  
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China  
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website: www.gdkesign.com

## BLE

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Maximum Output Power (mW)	Calculating data	Limit	Results
GFSK_1M	2402	-1.24	-1±1	0	1	0.3100	3.00	Pass
	2440	-1.23	-1±1	0	1	0.3100		
	2480	-1.14	-1±1	0	1	0.3100		

### Note:

- The tune-up power was declared by the applicant
- The maximum antenna gain is 2.97dBi.
- To maintain compliance with the RF exposure guidelines, place the equipment at least 20cm from nearby persons
- This device does not support simultaneous Transmitter.
- The BLEI and BT can not be transmit simultaneously.

**Result:Compliant**

**--THE END--**