

RF Exposure evaluation

Product Description: TRUE WIRELESS SPORT EARBUDS
Model Number: EPIC AIR ELITE
FCC ID: 2AHYVEPICELITER

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

According to the follow transmitter output power (P_t) formula :

$$P_t = (E \times d)^2 / (30 \times g_t)$$

P_t =transmitter output power in watts

g_t =numeric gain of the transmitting antenna (unitless)

E =electric field strength in V/m

d =measurement distance in meters (m)

According to the above test data,

$$P_t = 8.59 \text{ dBm} = 7.23 \text{ mW}$$

The result is rounded to one decimal place for comparison

Worse case is as below: [2441MHz -3.0mW output power]

$$(7.23 \text{ mW} / 5 \text{ mm}) \cdot \sqrt{2.441 (\text{GHz})} = 2.26 < 3.0 \text{ for 1-g SAR}$$

Then SAR evaluation is not required

NOTE: For the maximum power, you can refer FCC test report.