

RF Test Report

Project Number: 4942239 **Proposal:** SUW-202112002041
Report Number: 4942239EMC05 **Revision Level:** 1
Client: Risk Band LLC

Equipment Under Test: LTE Module in Wearable Emergency Device

Module Model Number: TOBY-R200

Host Model Name: ARIES

Host Model Number: RBD30060

Module FCC ID: 2AHZ7-R20082B00

Module IC: 21986-R20082B00

Host FCC ID: 2AHZ7-300602022

Host IC: 21986-300602022

Test Standard: ANSI C63.26:2015

FCC Rule Parts: Part 2, Part 22(H), Part 24(E), Part 27

ISED Specifications: RSS-130 Issue 2; RSS-132 Issue 3; RSS-133 Issue 6
RSS-139 Issue 4; RSS-GEN Issue 5

Report issued on: 25 January 2023

Test Result: Compliant



FOR THE SCOPE OF ACCREDITATION UNDER CERTIFICATE NUMBER: 3212.01

Report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the Federal Government.

Prepared by:

Brandon E. Osborn

Brandon Osborn, EMC/RF Project Engineer

Reviewed by:

Martin Taylor

Martin Taylor, EMC/RF Project Engineer

Remarks: This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>. And for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/terms-e-document.aspx>.

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for a maximum of 30 days only.

TABLE OF CONTENTS

1	SUMMARY OF TEST RESULTS	3
1.1	MODIFICATIONS REQUIRED TO COMPLIANCE	3
2	GENERAL INFORMATION	4
2.1	CLIENT INFORMATION	4
2.2	TEST LABORATORY	4
2.3	GENERAL INFORMATION OF EUT	4
2.4	OPERATING MODES AND CONDITIONS	4
2.5	EUT CONNECTION BLOCK DIAGRAM.....	5
2.6	SYSTEM CONFIGURATIONS	5
3	RADIATED SPURIOUS EMISSIONS	6
3.1	TEST RESULT.....	6
3.2	TEST METHOD.....	6
3.3	TEST SETUP DIAGRAMS.....	6
3.4	TEST SITE.....	7
3.5	TEST EQUIPMENT	7
3.6	TEST DATA.....	8
4	MEASUREMENT UNCERTAINTY	23
5	REVISION HISTORY	24

1 Summary of Test Results

Reference Sections		Test Description	Test Condition	Test Result
FCC	ISED			
2.1046	RSS-GEN (6.12)	Conducted Output Power	Conducted	N/S ¹
24.232(d) 27.50(d)(5)	RSS-130 (4.6.1) RSS-132 (5.4) RSS-133 (6.4) RSS-139 (5.5)	Peak-to-Average Ratio		N/S ¹
2.1049 22.917(b) 24.238(b) 27.53(h)(3)	RSS-GEN (6.7) RSS-133 (2.3)	Occupied / Emission Bandwidth		N/S ¹
2.1051 22.917(a) 24.238(a) 27.53(g)/(h)	RSS-130 (4.7) RSS-132 (5.5) RSS-133 (6.5) RSS-139 (5.6)	Band Edge / Conducted Spurious Emissions		N/S ¹
22.913(a)(5) 24.232(c) 27.50(c)(10) 27.50(d)(4)	RSS-130 (4.6.3) RSS-132 (5.4) RSS-133 (6.4) RSS-139 (5.5)	Effective Radiated Power / Effective Isotropic Radiated Power		N/S ¹
2.1053 22.917(a) 24.238(a) 27.53(g)/(h)	RSS-GEN (6.13) RSS-130 (4.7) RSS-132 (5.5) RSS-133 (6.5) RSS-139 (5.6)	Radiated Spurious Emissions	Radiated	Compliant
2.1055 22.355 24.235 27.54	RSS-GEN (6.11) RSS-130 (4.5) RSS-132 (5.3) RSS-133 (6.3) RSS-139 (5.4)	Frequency Stability		N/S ¹

Note:

- 1) Not in the scope of evaluation. The EUT is a certified cellular module. Only radiated spurious emissions was performed with the module installed in the new host per FCC KDB 996369 D04 Module Integration Guide v02.

1.1 Modifications Required to Compliance

None

2 General Information

2.1 Client Information

Name: Risk Band LLC
 Address: 1000 Johnnie Dobbs Blvd., Suite 103-312
 City, State, Zip, Country: Mount Pleasant, SC, 29464, USA

2.2 Test Laboratory

Name: SGS North America, Inc.
 Address: 620 Old Peachtree Road NW, Suite 100
 City, State, Zip, Country: Suwanee, GA 30024, USA

Accrediting Body: A2LA
 Type of lab: Testing Laboratory
 Certificate Number: 3212.01
 Designation Number: US1126
 CAB Identifier: US0186


2.3 General Information of EUT

Equipment Under Test: LTE Module in Wearable Emergency Device
 Module Model Number: TOBY-R200
 Host Model Name: ARIES
 Host Model Number: RBD30060
 Serial Number: 221003-00004
 IMEI Number: 359947100951077
 Frequencies of Operation: 1850 – 1910 MHz (LTE Band 2)
 1710 – 1755 MHz (LTE Band 4)
 824 – 849 MHz (LTE Band 5)
 699 – 716 MHz (LTE Band 12)
 Radio Technology: LTE Cat 1
 Channel Bandwidth tested: 1.4 MHz
 Modulation tested: QPSK
 RB allocation: 1 RBs allocated, RB start = 0
 Antenna Type/Gain: SMT, Ethertronics P822601, 698-2200MHz, 2.6 to 4.4dBi
 Rated Voltage: 3.7 VDC
 Test Voltage: 3.7 VDC
 Sample Received Date: 26 July 2022
 Dates of testing: 28-31 October 2022

2.4 Operating Modes and Conditions

The EUT was tested with normal operating firmware, but with a Rohde & Schwarz test SIM installed. Once powered on by USB and AT commands were sent, the cellular modem connected with the R&S Wideband Radio Communication Tester (CMW500). The CMW500 was used to control the EUT to operate with maximum transmit (uplink) power in LTE Bands 2 and 12. Low, middle and high channels were tested in each band using a cell bandwidth of 1.4MHz with 1 Resource Block.

2.5 EUT Connection Block Diagram



2.6 System Configurations

Device Reference	Manufacturer	Description	Model Number	Serial Number
A	Risk Band LLC	Wearable Emergency Device containing LTE Module (EUT)	RBD30060	221003-00004

3 Radiated Spurious Emissions

3.1 Test Result

Test Description	Specification	Test Result
Transmitter Spurious Emissions	ANSI C63.26:2015	Compliant


3.2 Test Method

The levels of the carrier and the various conducted spurious and harmonics frequencies are measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB.

A radio link was established between EUT and Radio Communications Tester. The output power of the EUT was set to maximum value by using the maximum power setting on the Radio Communications Tester.

The measurements were performed at the lowest, middle, and highest channels of the lowest and highest frequency bands (Bands 2 and 12).

3.3 Test Setup Diagrams



3.4 Test Site

3m Absorber Lined Shielded Enclosure (ALSE), Suwanee, GA

Environmental Conditions	28-Oct-2022	31-Oct-2022
Temperature:	21.82 °C	21.01°C
Relative Humidity:	40.2 %	51.1 %
Atmospheric Pressure:	97.9 kPa	97.7 kPa

3.5 Test Equipment

30-1000MHz

Test End Date: 28-Oct-2022

Tester: PL

Equipment	Model	Manufacturer	Asset	Cal Date	Cal Due Date
ANTENNA, BILOG	JB6	SUNOL	B079689	26-May-2022	26-May-2024
RF CABLE NM TO NM, 0.01-18GHZ	90-195-079	TELEDYNE STORM MICROWAVE	20124	14-Feb-2022	14-Feb-2023
RF CABLE NM TO NF, 0.01-18GHZ	90-213-118	TELEDYNE STORM MICROWAVE	20117	17-Feb-2022	17-Feb-2023
RF CABLE RIGHT ANGLE NM TO NM, 0.01- N to N RF Cable	90-076-020 NC12-N1N1-276	TELEDYNE STORM MICROWAVE MEGAPHASE	20131 22001	16-Mar-2022 10-Jan-2022	16-Mar-2023 10-Jan-2023
EMI TEST RECEIVER	ESW44	ROHDE & SCHWARZ	22027	13-Sep-2022	13-Sep-2023
LOW NOISE AMPLIFIER	ZKL-2+	MINI-CIRCUITS	B079800	14-Sep-2022	14-Sep-2023

>1GHz

Test End Date: 31-Oct-2022


Tester: PL

Equipment	Model	Manufacturer	Asset	Cal Date	Cal Due Date
ANTENNA, DRG HORN (MEDIUM)	3117	ETS LINDGREN	B079691	15-Aug-2022	15-Aug-2024
RF CABLE NM TO NF, 0.01-18GHZ	90-213-118	TELEDYNE STORM MICROWAVE	20118	16-Mar-2022	16-Mar-2023
RF CABLE NM TO NM, 0.01-18GHZ	90-195-118	TELEDYNE STORM MICROWAVE	20126	14-Feb-2022	14-Feb-2023
RF CABLE	104PE	HUBER & SUHNER	B079793	25-Aug-2022	25-Aug-2023
EMI TEST RECEIVER	ESW44	ROHDE & SCHWARZ	22027	13-Sep-2022	13-Sep-2023
LOW NOISE AMPLIFIER	TS-PR18	ROHDE & SCHWARZ	15003	3-Oct-2022	3-Oct-2023
EMI TEST RECEIVER	ESU8	ROHDE & SCHWARZ	B085759	8-Sep-2022	8-Sep-2023
FILTER, HIGH PASS, >2800MHZ	HPM50110	MICRO-TRONICS	B079792	11-Jul-2022	11-Jul-2023
RF CABLE RIGHT ANGLE NM TO NM, 0.01-	90-076-020	TELEDYNE STORM MICROWAVE	20131	16-Mar-2022	16-Mar-2023
FILTER, HIGH PASS, >1000MHZ	HPM50108	MICRO-TRONICS	B079802	5-Jul-2022	5-Jul-2023

Note: Refer to equipment list for calibration intervals.


3.6 Test Data

3.6.1 30-1000MHz




LTE Band 2, QPSK modulation
Mid Channel (1880MHz)

Vertical Plot (30-1000MHz)




Horizontal Plot (30-1000MHz)




LTE Band 2, QPSK modulation
High Channel (1909.3MHz)

Vertical Plot (30-1000MHz)




Horizontal Plot (30-1000MHz)




LTE Band 12, QPSK modulation
Low channel (699.7MHz)

Vertical Plot (30-1000MHz)




Horizontal Plot (30-1000MHz)




LTE Band 12, QPSK modulation
Mid channel (707.5MHz)

Vertical Plot (30-1000MHz)




Horizontal Plot (30-1000MHz)




LTE Band 12, QPSK modulation
High channel (715.3MHz)


Vertical Plot (30-1000MHz)



Horizontal Plot (30-1000MHz)




3.6.2 Above 1GHz




LTE Band 2, QPSK modulation
Mid Channel (1880MHz)

Vertical Plot (1-3GHz)




Horizontal Plot (1-3GHz)




LTE Band 2, QPSK modulation
High Channel (1909.3MHz)

Vertical Plot (1-3GHz)




Horizontal Plot (1-3GHz)




LTE Band 2, QPSK modulation
Low Channel (1850.7MHz)

Vertical Plot (3-18GHz)




Horizontal Plot (3-18GHz)




LTE Band 2, QPSK modulation
Mid Channel (1880MHz)

Vertical Plot (3-18GHz)




Horizontal Plot (3-18GHz)




LTE Band 2, QPSK modulation
High Channel (1909.3MHz)

Vertical Plot (3-18GHz)




Horizontal Plot (3-18GHz)




LTE Band 12, QPSK modulation
Low Channel (699.7 MHz)

Vertical Plot (1-8GHz)




Horizontal Plot (1-8GHz)





LTE Band 12, QPSK modulation
Mid Channel (707.5 MHz)

Vertical Plot (1-8GHz)



Horizontal Plot Mid (1-8GHz)





Regardless of channel or band, no spurious emissions associated with the radio were within 20dB of the limit.

4 Measurement Uncertainty

The measurement uncertainty figures are be calculated in accordance with TR 100 028-1 [2] and correspond to an expansion factor (coverage factor) $k = 2$ (which provide confidence levels of 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Parameter	Expanded Uncertainty for Normal k factor equal to 2	
	Required	Laboratory Actual
Radio Frequency	$\pm 1 \times 10^{-5}$	$\pm 9.8 \times 10^{-8}$
total RF power, conducted	± 1.5 dB	± 1.2 dB
RF power density, conducted	± 3 dB	± 0.7 dB
spurious emissions, conducted	± 3 dB	± 2.1 dB
all emissions, radiated	± 6 dB	± 4.8 dB
temperature	$\pm 1^{\circ}\text{C}$	$\pm 0.5^{\circ}\text{C}$
humidity	± 5 %	± 3.5 %
DC and low frequency voltages	± 3 %	± 0.4 %

5 Revision History

Revision Level	Description of changes	Revision Date
0	Initial release	12 January 2023
1	<ul style="list-style-type: none"> - Clarified that EUT is LTE Module on title page and in section 2.3 - Added Measurement Uncertainty (new section 4) 	25 January 2023