



# TEST REPORT

**APPLICANT** : Shenzhen Xhorse Electronics Co., Ltd.  
**PRODUCT NAME** : KEY TOOL MAX PRO  
**MODEL NAME** : XDKMP0  
**BRAND NAME** : Xhorse  
**FCC ID** : 2A14T-XDKMP0  
**STANDARD(S)** : 47 CFR Part 15 Subpart C  
**RECEIPT DATE** : 2022-07-20  
**TEST DATE** : 2022-07-26 to 2022-08-09  
**ISSUE DATE** : 2024-07-01



Edited by:

*Peng Mi*

Peng Mi (Rapporteur)

Approved by:

*Shen Junsheng*

Shen Junsheng (Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





# DIRECTORY

- 1. Technical Information** ..... 3
- 1.1. Applicant and Manufacturer Information** ..... 3
- 1.2. Equipment Under Test (EUT) Description** ..... 3
- 1.3. Test Standards and Results** ..... 5
- 1.4. Environmental Conditions** ..... 5
- 2. 47 CFR Part 15C Requirements** ..... 6
- 2.1. Antenna Requirement** ..... 6
- 2.2. Conducted Emission** ..... 7
- 2.3. Radiated Emission** ..... 11
- 2.4. Frequency Tolerance** ..... 18
- 2.5. 20 dB Bandwidth** ..... 20
- Annex A Test Uncertainty** ..... 22
- Annex B Testing Laboratory Information** ..... 23

Change History		
Version	Date	Reason for change
1.0	2024-07-01	First edition



# 1. Technical Information

**Note:** Provide by applicant.

## 1.1. Applicant and Manufacturer Information

<b>Applicant:</b>	Shenzhen Xhorse Electronics Co., Ltd.
<b>Applicant Address:</b>	Floor 28, Block A, Building NO.6, international innovation Valley, Nanshan District, Shenzhen
<b>Manufacturer:</b>	Shenzhen Xhorse Electronics Co., Ltd.
<b>Manufacturer Address:</b>	Floor 28, Block A, Building NO.6, international innovation Valley, Nanshan District, Shenzhen

## 1.2. Equipment Under Test (EUT) Description

<b>Product Name:</b>	KEY TOOL MAX PRO	
<b>Sample No.:</b>	2#	
<b>Hardware Version:</b>	V3.0	
<b>Software Version:</b>	V1.5.1	
<b>Operating Frequency:</b>	13.56 MHz	
<b>Modulation Type:</b>	AM	
<b>Antenna Type:</b>	Loop Antenna	
<b>Accessory Information:</b>	Battery	
	<b>Brand Name:</b>	BAK
	<b>Model No.:</b>	G795260P
	<b>Serial No.:</b>	N/A
	<b>Capacity:</b>	3375 mAh
	<b>Rated Voltage:</b>	3.7 V
	<b>Charge Limit:</b>	4.2 V
	<b>Manufacturer:</b>	Zhengzhou BAK Battery Co., Ltd.



**Note 1:** This test report is variant from the original report (Report No.: SZ22070187W04, Model: XDKMP0), based on the similarity between before, the differences with before as below:

1. Some optocoupler devices are reduced, their position is U803, U806, U810, U804, U808, U809, and added 0 ohm resistance. Their modifications are only related to OBD-related functionality, it has nothing to do with wireless functions.

2. Modified the logic device U704 is added in the 125 kHz acquisition and receiving part, and some devices are not welded (U701, C724, C725), and the corresponding principle is modified.

3. Update the software version and hardware version.

There is no other change. The appearance, all RF parameters and circuits remain the same as before.

**Note 2:** For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

### 1.3. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-15 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS <sub>Note1</sub>	No deviation
2	15.207	Conducted Emission	Aug. 01, 2022	Wu Zhaoling	PASS <sub>Note1</sub>	No deviation
3	15.209 15.225(a) (b) (c)(d)	Radiated Emission	Aug. 04, 2022	Gao Jianrou	PASS <sub>Note1</sub>	No deviation
4	15.225(e)	Frequency Tolerance	Aug. 09, 2022	He Yuyang	PASS <sub>Note1</sub>	No deviation
5	15.215(c)	20dB Bandwidth	Aug. 07, 2022	Gao Jianrou	PASS <sub>Note1</sub>	No deviation

**Note 1:** The test results of these test items in this report refer to the test report (Report No.: SZ22070187W04).

**Note 2:** The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013. The EUT has been tested under continuous operating condition.

**Note 3:** Additions to, deviation, or exclusions from the method shall be judged in the “method determination” column of add, deviate or exclude from the specific method shall be explained in the “Remark” of the above table.

**Note 4:** When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

### 1.4. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15–35
Relative Humidity (%):	30–60
Atmospheric Pressure (kPa):	86–106



## 2. 47 CFR Part 15C Requirements

### 2.1. Antenna Requirement

#### 2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 2.1.2. Test Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

## 2.2. Conducted Emission

### 2.2.1. Test Requirement


According to FCC section 15.207, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50  $\Omega$  line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15–0.50	66 to 56	56 to 46
0.50–5	56	46
5–30	60	50

NOTE:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15–0.50 MHz.

### 2.2.2. Test Setup



The EUT is placed on a 0.8 m high insulating table, which stands on the grounded conducting floor, and keeps 0.4 m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides 50  $\Omega$ /50  $\mu$ H of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.



### 2.2.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW = 9kHz, VBW = 30kHz. Refer to recorded points and plots below.

**Note:** Both of the test voltage AC 120 V/60 Hz and AC 230 V/50 Hz were considered and tested respectively, only the results of the worst case AC 120 V/60 Hz were recorded in this report.

#### A. Test Setup:

Test Mode: EUT + Adapter + 13.56 MHz TX

Test voltage: AC 120 V/60 Hz

The measurement results are obtained as below:


$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

$U_R$ : Receiver Reading

$A_{\text{Factor}}$ : Voltage division factor of LISN




**B.Test Plot:**



(L Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1779	57.57	32.38	64.58	54.58	Line	PASS
2	0.2853	50.05	31.39	60.66	50.66		PASS
3	0.3396	47.68	29.27	59.21	49.21		PASS
4	0.4384	43.70	30.00	57.09	47.09		PASS
5	1.2864	35.11	24.40	56.00	46.00		PASS
6	13.5603	35.07	29.49	60.00	50.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1511	59.11	36.90	65.94	55.94	Neutral	PASS
2	0.2489	51.86	31.89	61.79	51.79		PASS
3	0.3349	47.60	32.47	59.33	49.33		PASS
4	0.5489	39.47	26.19	56.00	46.00		PASS
5	1.4439	35.07	25.89	56.00	46.00		PASS
6	13.5589	30.11	26.07	60.00	50.00		PASS



## 2.3. Radiated Emission

### 2.3.1. Test Requirement

#### Radiated Emission <30 MHz (9 kHz–30 MHz, E-field)

According to FCC section 15.225, for <30 MHz, Radiated emissions were measured according to ANSIC63.4. The EUT was set to transmit at the highest output power. The EUT was set 30 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10 KHz. (Note: During testing the receive antenna was rotated about its axis to maximize the emission from the EUT)

There was no detected Restricted bands and Radiated Spurious emission below 30 MHz. The 30 m limit was converted to 3 m Limit using square factor(x) as it was found by measurements as follows;

$$3 \text{ m Limit (dB}\mu\text{V/m)} = 20\log(X) + 40\log(30/3) = 20\log(15848) + 40\log(30/3) = 124 \text{ dB}\mu\text{V}$$

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency Range (MHz)	Field Strength@30 m		Field Strength@3 m
	$\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$
Below 13.110	30	29.5	69.5
13.110–13.410	106	40.5	80.5
13.410–13.553	334	50.5	90.5
13.553–13.567	15.848	84	124
13.567–13.710	334	50.5	90.5
13.710–14.010	106	40.5	80.5
Above 14.010	30	29.5	69.5

NOTE: a) Field Strength ( $\text{dB}\mu\text{V/m}$ ) =  $20 * \log[\text{Field Strength } (\mu\text{V/m})]$ .

b) In the emission tables above, the tighter limit applies at the band edges.

#### Radiated Emission >30 MHz (30 MHz–1 GHz, E-field)

According to FCC section 15.205, the field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:


Frequency Range (MHz)	Field Strength	
	$\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$
30–88	100	40
88–216	150	43.5
216–960	200	46
Above 960	500	54

NOTE: a) Field Strength ( $\text{dB}\mu\text{V/m}$ ) =  $20 * \log[\text{Field Strength } (\mu\text{V/m})]$ .


b) In the emission tables above, the tighter limit applies at the band edges.

**2.3.2. Test Setup**

1) For radiated emissions below 30 MHz



2) For radiated emissions from 30 MHz to 1 GHz



The test is performed in a 3 m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8 m high insulating Turn Table, and keeps 3 m away from the Test Antenna, which is mounted on a variable-height antenna master tower.



For the test Antenna:

In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1 m distance from the EUT. The center of the Loop Test Antenna is 1 m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

In the frequency range above 30 MHz, Bi-Log Test Antenna (30 MHz to 1 GHz) was used. Test Antenna is 3 m away from the EUT. Test Antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.


For measurements frequency range from 0.009 MHz to 0.15 MHz, the resolution bandwidth is set to 200 kHz.

For measurements frequency range from 0.15 MHz to 30 MHz, the resolution bandwidth is set to 9 kHz.

The emission limits shown in the above are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz and 110–490 kHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

2.3.3. Test Result

A.Radiated Emission <30 MHz (9 kHz–30 MHz, opened)




No.	Frequency (MHz)	Detector Type	Level at 3 m (dB $\mu$ V/m)	Limit at 3 m (dB $\mu$ V/m)
1	0.0092	Quasi Peak	55.26	108.33
2	0.015	Quasi Peak	58.11	104.08
3	0.0822	Quasi Peak	55.49	89.31
4	0.165	Quasi Peak	59.14	83.25
5	0.265	Quasi Peak	57.18	79.14
6	13.56	Quasi Peak	77.80	124.0

**B. Radiated Emission <30 MHz (9 kHz–30 MHz, closed)**



No.	Frequency (MHz)	Detector Type	Level at 3 m (dBμV/m)	Limit at 3 m (dBμV/m)
1	0.0149	Quasi Peak	58.22	104.14
2	0.0822	Quasi Peak	55.38	89.31
3	0.175	Quasi Peak	58.79	82.74
4	0.26	Quasi Peak	59.58	79.30
5	0.62	Quasi Peak	54.93	71.76
6	13.56	Quasi Peak	62.06	124.0


**C.Radiated Emission >30 MHz (30 MHz–1 GHz)**



(30 MHz–1 GHz, Test Antenna Horizontal)

No.	Fre. MHz	Pk dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	32.2312	31.37	N/A	N/A	N/A	40.00	N/A	H	PASS
2	48.7229	31.93	N/A	N/A	N/A	40.00	N/A	H	PASS
3	106.5407	25.53	N/A	N/A	N/A	43.50	N/A	H	PASS
4	227.9968	26.64	N/A	N/A	N/A	46.00	N/A	H	PASS
5	360.0270	34.87	N/A	N/A	N/A	46.00	N/A	H	PASS
6	737.0067	35.52	N/A	N/A	N/A	46.00	N/A	H	PASS





(30 MH –1 GHz, Test Antenna Vertical)


No.	Fre. MHz	Pk dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	47.4617	32.01	N/A	N/A	N/A	40.00	N/A	V	PASS
2	107.3167	25.78	N/A	N/A	N/A	43.50	N/A	V	PASS
3	215.9676	26.82	N/A	N/A	N/A	43.50	N/A	V	PASS
4	359.9300	30.63	N/A	N/A	N/A	46.00	N/A	V	PASS
5	633.6914	35.07	N/A	N/A	N/A	46.00	N/A	V	PASS
6	785.9966	35.65	N/A	N/A	N/A	46.00	N/A	V	PASS

## 2.4. Frequency Tolerance

### 2.4.1. Test Requirement

According to FCC section 15.225, the devices operating in the 13.553–13.567 MHz shall maintain the carrier frequency within 0.01% of the operating frequency over the temperature variation of -20°C to +50°C using an environmental chamber. The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

### 2.4.2. Test Setup



The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT was measured by transmitter mode continuously.



**2.4.3. Test Result**

Operating Frequency: 13,560,000 Hz

Deference Voltage: 3.80 V

Deviant Limit:  $\pm 0.01\%$


VOLTAGE (%)	Test Conditions		Fre. Dev. (Hz)	Deviation (%)	Verdict
	Power (VDC)	Temperature (°C)			
100	3.80	-20	256	0.00189	PASS
100		-10	245	0.00181	
100		0	196	0.00145	
100		+10	184	0.00136	
100		+20	199	0.00147	
100		+25	173	0.00128	
100		+30	185	0.00136	
100		+40	192	0.00142	
100		+50	168	0.00124	
85		3.23	+20	169	
115	4.37	+20	191	0.00141	

## 2.5. 20 dB Bandwidth

### 2.5.1. Standard Applicable

According to FCC section 15.215(c), the 20 dB bandwidth should be contained within the frequency band designated in the rule section under which the EUT is operated, it was measured with a spectrum analyzer connected the EUT while the EUT is operating in transmission mode.


### 2.5.2. Test Setup





2.5.3. Test Result

Centre Frequency	Measurement		Limit		Verdict
	20 dB Bandwidth (kHz)	Frequency Range (MHz)	20 dB Bandwidth (kHz)	Frequency Range (MHz)	
13.56 MHz	0.95	13.55993 to 13.56088	14	13.553 to 13.567	PASS





## Annex A Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Radiated Emission:	$\pm 3.1$ dB
Conducted Emission:	$\pm 1.8$ dB
Bandwidth:	$\pm 5\%$
Frequency Tolerance:	$\pm 5\%$



## Annex B Testing Laboratory Information

### 1. Identification of the Responsible Testing Laboratory

<b>Laboratory Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd.
<b>Laboratory Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
<b>Telephone:</b>	+86 755 36698555
<b>Facsimile:</b>	+86 755 36698525

### 2. Identification of the Responsible Testing Location

<b>Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd.
<b>Address:</b>	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



#### 4. Test Equipment Utilized

##### 4.1 Test Equipment

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY54130016	N9038A	Agilent	2022.07.06	2023.07.05
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2022.05.25	2025.05.24
Test Antenna - Loop	1520-022	FMZB1519	Schwarzbeck	2022.02.11	2025.02.10
Anechoic Chamber	N/A	9m*6m*6m	CRT	2020.01.06	2023.01.05
DC Power Supply	1709D361010	IV3610	IVYTECH	2021.10.20	2022.10.19
Temperature Chamber	12108015	DTL-003S101	YOMA	2021.10.20	2022.10.19

##### 4.2 Conducted Emission Test Equipment

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2022.03.03	2023.03.02
LISN	812744	NSLK 8127	Schwarzbeck	2022.03.03	2023.03.02
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2022.07.06	2023.07.05
Coaxial Cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A

##### 4.3 Test Software Utilized

Model	Software Version	Manufacturer
TS+ -[JS32-RE]	Version 2.5.0.6	Tonscend
TS+ -[JS32-CE]	Version 2.5.0.0	Tonscend
PMM Emission Suite	Version 2.02	narda

————— END OF REPORT —————