



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No. :** CQASZ20210100002EX-03  
**Applicant:** SHENZHEN AMEDIATECH TECHNOLOGY CO.,LTD  
**Address of Applicant:** No.01, 2/F, A Plant, Block B, Minsheng Industrial Park, Longmei Road, Gaofeng community, Dalang office, Longhua District, Shenzhen, China

### Equipment Under Test (EUT):

**Product:** Set Top Box  
**Model No.:** X96 mini+  
**Brand Name:** N/A  
**FCC ID:** 2AI6D-X96MINI  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 1.1310  
KDB447498D01 General RF Exposure Guidance v06

**Date of Receipt:** Jan. 04, 2021  
**Date of Test:** Jan. 04, 2021 – Jan. 31, 2021  
**Date of Issue:** Jan. 31, 2021  
**Test Result :** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:** Jun Li  
(Jun Li)

**Reviewed By:** Ares Liu  
(Ares Liu)

**Approved By:** Sheek Luo  
( Sheek Luo)



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210100002EX-03	Rev.01	Initial report	Jan. 31, 2021

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION .....	4
3.1 CLIENT INFORMATION .....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
3.3 GENERAL DESCRIPTION OF 2.4G WIFI .....	4
3.4 GENERAL DESCRIPTION OF 5G WIFI .....	4
4 RF EXPOSURE EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Limits</i> .....	5
4.1.2 <i>Test Procedure</i> .....	5
4.1.3 <i>EUT RF Exposure Evaluation standalone operations</i> .....	6
4.1.4 <i>EUT RF Exposure Evaluation simultaneous transmission operations</i> .....	10

### 3 General Information

#### 3.1 Client Information

Applicant:	SHENZHEN AMEDIATECH TECHNOLOGY CO.,LTD
Address of Applicant:	No.01, 2/F, A Plant, Block B, Minsheng Industrial Park, Longmei Road, Gaofeng community, Dalang office, Longhua District, Shenzhen, China
Manufacturer:	SHENZHEN AMEDIATECH TECHNOLOGY CO.,LTD
Address of Manufacturer:	No.01, 2/F, A Plant, Block B, Minsheng Industrial Park, Longmei Road, Gaofeng community, Dalang office, Longhua District, Shenzhen, China

#### 3.2 General Description of EUT

Product Name:	Set Top Box
Model No.:	X96 mini+
Trade Mark:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Sample Type:	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location
Power Supply:	100-240V 50/60Hz

#### 3.3 General Description of 2.4G WIFI

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(H40): 2422MHz~2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM IEEE for 802.11n(HT20): OFDM IEEE for 802.11n(HT40): OFDM
Antenna Type:	IPEX Antenna
Antenna Gain:	0dBi

#### 3.4 General Description of 5G WIFI

Operation Frequency:	5180 ~ 5240 MHz, 5745 ~ 5825 MHz
Channel Numbers:	5180 ~ 5240 MHz:4 for 802.11n, 802.11ac, 2 for 802.11n40 , 802.11ac 40 5745 ~ 5825 MHz:5 for, 802.11n , 802.11ac, 2 for 802.11n40, 802.11ac40
Type of Modulation:	IEEE 802.11n/IEEE 802.11ac: OFDM
Antenna Type:	IPEX Antenna
Antenna Gain:	0dBi

## 4 RF Exposure Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 4.1.3 EUT RF Exposure Evaluation standalone operations

#### 1) For 2.4G WIFI

Antenna Gain: 0dB

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

#### Measurement Data

802.11b mode					
Test channel	Antenna	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	Ant1	11.67	11.0±1.0	12.0	15.849
Middle(2437MHz)	Ant1	9.63	9.0±1.0	10.0	10.000
Highest(2462MHz)	Ant1	10.75	10.0±1.0	11.0	12.589
802.11g mode					
Test channel	Antenna	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	Ant1	8.07	7±1.0	8.0	6.310
Middle(2437MHz)	Ant1	7.95	7±1.0	8.0	6.310
Highest(2462MHz)	Ant1	8.75	8±1.0	9.0	7.943
802.11n(HT20) SISO mode					
Test channel	Antenna	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	Ant1	6.67	6±1.0	7.0	5.012
Middle(2437MHz)	Ant1	6.71	6±1.0	7.0	5.012
Highest(2462MHz)	Ant1	6.53	6±1.0	7.0	5.012
802.11n(HT40) SISO mode					
Test channel	Antenna	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2422MHz)	Ant1	5.97	5±1.0	6.0	3.981
Middle(2437MHz)	Ant1	5.13	5±1.0	6.0	3.981
Highest(2452MHz)	Ant1	5.28	5±1.0	6.0	3.981

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
15.849	0	0.0032	1.0	PASS

Note: 1) Refer to report No. CQASZ20210100002EX-01 for EUT test Max Conducted average Output Power value.

2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (15.849 * 1.0) / (4 * 3.1416 * 20^2) = 0.0032$

**2) For 5G WIFI**

Antenna Gain: 0dB

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

**Measurement Data**

802.11n(HT20) SISO mode					
Test channel	Antenna	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
5180	Ant1	9.01	8±1.0	9.0	7.943
5200	Ant1	8.94	8±1.0	9.0	7.943
5240	Ant1	8.07	8±1.0	9.0	7.943
5745	Ant1	3.37	3±1.0	4.0	2.512
5785	Ant1	3.83	3±1.0	4.0	2.512
5825	Ant1	3.12	3±1.0	4.0	2.512
802.11n(HT40) SISO mode					
Test channel	Antenna	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
5190	Ant1	10.36	10±1.0	11.0	12.589
5230	Ant1	10.18	10±1.0	11.0	12.589
5755	Ant1	3.35	3±1.0	4.0	2.512
5795	Ant1	2.99	2±1.0	3.0	1.995



802.11ac(VHT20) SISO mode					
Test channel	Antenna	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
5180	Ant1	9.21	9±1.0	10.0	10.000
5200	Ant1	10.34	10±1.0	11.0	12.589
5240	Ant1	9.68	9±1.0	10.0	10.000
5745	Ant1	2.67	2±1.0	3.0	1.995
5785	Ant1	2.83	2±1.0	3.0	1.995
5825	Ant1	2.26	2±1.0	3.0	1.995
802.11ac(VHT40) SISO mode					
Test channel	Antenna	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
5190	Ant1	10.70	10±1.0	11.0	12.589
5230	Ant1	10.51	10±1.0	11.0	12.589
5755	Ant1	2.81	2±1.0	3.0	1.995
5795	Ant1	2.83	2±1.0	3.0	1.995

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
12.589	0	0.0025	1.0	PASS

Note: 1) Refer to report No. CQASZ20210100002EX-02 for EUT test Max Conducted average Output Power value.

$$2) P_d = (P_{out} * G) / (4 * \pi * R^2) = (12.589 * 1.0) / (4 * 3.1416 * 20^2) = 0.0025$$

#### 4.1.4 EUT RF Exposure Evaluation simultaneous transmission operations

According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits :

Simultaneous transmission mode	The sum of the ratios	Result
2.4G WIFI + 5G WIFI	$0.0032/1 + 0.0025/1$	$=0.0057 < 1$