

1 Version

Revision History Of Report

| Report No. | Version | Description | Issue Date |
|----------------------|---------|----------------|------------|
| CQASZ20240400664E-01 | Rev.01 | Initial report | 2024-04-24 |

2 Test Summary

| Test Item | Test Requirement | Test method | Result |
|---|--|------------------|--------|
| Antenna Requirement | 47 CFR Part 15.203 | / | PASS |
| AC Power Line Conducted Emission | 47 CFR Part 15, Subpart C Section 15.207 | ANSI C63.10-2013 | PASS |
| Conducted Peak Output Power | 47 CFR Part 15.247 | ANSI C63.10-2013 | PASS |
| 20dB Occupied Bandwidth | 47 CFR Part 15.247 | ANSI C63.10-2013 | PASS |
| Carrier Frequencies Separation | 47 CFR Part 15.247 | ANSI C63.10-2013 | PASS |
| Hopping Channel Number | 47 CFR Part 15.247 | ANSI C63.10-2013 | PASS |
| Dwell Time | 47 CFR Part 15.247 | ANSI C63.10-2013 | PASS |
| Pseudorandom Frequency Hopping Sequence | 47 CFR Part 15.247 | ANSI C63.10-2013 | PASS |
| Band-edge for RF Conducted Emissions | 47 CFR Part 15.247 | ANSI C63.10-2013 | PASS |
| RF Conducted Spurious Emissions | 47 CFR Part 15.247 | ANSI C63.10-2013 | PASS |
| Radiated Spurious emissions | 47 CFR Part 15.209 | ANSI C63.10-2013 | PASS |
| Restricted bands around fundamental frequency (Radiated Emission) | 47 CFR Part 15.205/15.209 | ANSI C63.10-2013 | PASS |

Remark:

The tested sample(s) and the sample information are provided by the client.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

CH: In this whole report CH means channel.

Volt: In this whole report Volt means Voltage.

Temp: In this whole report Temp means Temperature.

Humid: In this whole report Humid means humidity.

Press: In this whole report Press means Pressure.

N/A: In this whole report not application

3 Contents

| | Page |
|--|-----------|
| 1 VERSION | 2 |
| 2 TEST SUMMARY | 3 |
| 3 CONTENTS | 4 |
| 4 GENERAL INFORMATION | 5 |
| 4.1 CLIENT INFORMATION | 5 |
| 4.2 GENERAL DESCRIPTION OF EUT | 5 |
| 4.3 ADDITIONAL INSTRUCTIONS | 7 |
| 4.4 TEST ENVIRONMENT | 8 |
| 4.5 DESCRIPTION OF SUPPORT UNITS | 8 |
| 4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY | 9 |
| 4.7 TEST LOCATION | 10 |
| 4.8 TEST FACILITY | 10 |
| 4.9 ABNORMALITIES FROM STANDARD CONDITIONS | 10 |
| 4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER | 10 |
| 4.11 EQUIPMENT LIST | 11 |
| 5 TEST RESULTS AND MEASUREMENT DATA | 12 |
| 5.1 ANTENNA REQUIREMENT | 12 |
| 5.2 CONDUCTED EMISSIONS | 13 |
| 5.3 CONDUCTED PEAK OUTPUT POWER | 17 |
| 5.4 20dB OCCUPIED BANDWIDTH | 22 |
| 5.5 CARRIER FREQUENCIES SEPARATION | 26 |
| 5.6 HOPPING CHANNEL NUMBER | 29 |
| 5.7 DWELL TIME | 31 |
| 5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS | 38 |
| 5.9 SPURIOUS RF CONDUCTED EMISSIONS | 43 |
| 5.10 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM | 51 |
| 5.11 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS | 53 |
| 5.11.1 Radiated Emission below 1GHz | 56 |
| 5.11.2 Transmitter Emission above 1GHz | 58 |
| 6 PHOTOGRAPHS - EUT TEST SETUP | 60 |
| 6.1 RADIATED EMISSION | 60 |
| 6.2 CONDUCTED EMISSION | 61 |
| 7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS | 62 |

4 General Information

4.1 Client Information

| | |
|--------------------------|--|
| Applicant: | Guangzhou Havit Technology Co., Ltd. |
| Address of Applicant: | ROOM 1307, 13F, PHASE 2 B, C BUILDING OF POLY WORLD TRADE CENTER, NO.1000, XINGANG EAST ROAD, HAIZHU, GUANGDONG, China |
| Manufacturer: | Guangzhou Havit Technology Co., Ltd. |
| Address of Manufacturer: | ROOM 1307, 13F, PHASE 2 B, C BUILDING OF POLY WORLD TRADE CENTER, NO.1000, XINGANG EAST ROAD, HAIZHU, GUANGDONG, China |
| Factory: | Guangzhou Havit Technology Co., Ltd. |
| Address of Factory: | ROOM 1307, 13F, PHASE 2 B, C BUILDING OF POLY WORLD TRADE CENTER, NO.1000, XINGANG EAST ROAD, HAIZHU, GUANGDONG, China |

4.2 General Description of EUT

| | |
|---------------------------|--|
| Product Name: | OPEN-EAR CLIP HEADPHONES |
| Model No.: | TW980, Openbuds 1 |
| Test Model No.: | TW980 |
| Trade Mark: | HAVIT |
| Software Version: | V0.0.1 |
| Hardware Version: | V1.0 |
| Operation Frequency: | 2402MHz~2480MHz |
| Bluetooth Version: | V5.3 |
| Modulation Technique: | Frequency Hopping Spread Spectrum(FHSS) |
| Modulation Type: | GFSK, $\pi/4$ DQPSK |
| Transfer Rate: | 1Mbps/2Mbps |
| Number of Channel: | 79 |
| Hopping Channel Type: | Adaptive Frequency Hopping systems |
| Product Type: | <input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable |
| Test Software of EUT: | FCC Assist 1.0.1.1 |
| Antenna Type: | Chip antenna |
| Antenna Gain: | 1.7dBi |
| Power Supply: | Li-ion battery: DC 3.7V 40mAh, Charge by DC 5V for Charge box |
| Simultaneous Transmission | <input type="checkbox"/> Simultaneous TX is supported and evaluated in this report. <input checked="" type="checkbox"/> Simultaneous TX is not supported. |

| Operation Frequency each of channel | | | | | | | |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 0 | 2402MHz | 20 | 2422MHz | 40 | 2442MHz | 60 | 2462MHz |
| 1 | 2403MHz | 21 | 2423MHz | 41 | 2443MHz | 61 | 2463MHz |
| 2 | 2404MHz | 22 | 2424MHz | 42 | 2444MHz | 62 | 2464MHz |
| 3 | 2405MHz | 23 | 2425MHz | 43 | 2445MHz | 63 | 2465MHz |
| 4 | 2406MHz | 24 | 2426MHz | 44 | 2446MHz | 64 | 2466MHz |
| 5 | 2407MHz | 25 | 2427MHz | 45 | 2447MHz | 65 | 2467MHz |
| 6 | 2408MHz | 26 | 2428MHz | 46 | 2448MHz | 66 | 2468MHz |
| 7 | 2409MHz | 27 | 2429MHz | 47 | 2449MHz | 67 | 2469MHz |
| 8 | 2410MHz | 28 | 2430MHz | 48 | 2450MHz | 68 | 2470MHz |
| 9 | 2411MHz | 29 | 2431MHz | 49 | 2451MHz | 69 | 2471MHz |
| 10 | 2412MHz | 30 | 2432MHz | 50 | 2452MHz | 70 | 2472MHz |
| 11 | 2413MHz | 31 | 2433MHz | 51 | 2453MHz | 71 | 2473MHz |
| 12 | 2414MHz | 32 | 2434MHz | 52 | 2454MHz | 72 | 2474MHz |
| 13 | 2415MHz | 33 | 2435MHz | 53 | 2455MHz | 73 | 2475MHz |
| 14 | 2416MHz | 34 | 2436MHz | 54 | 2456MHz | 74 | 2476MHz |
| 15 | 2417MHz | 35 | 2437MHz | 55 | 2457MHz | 75 | 2477MHz |
| 16 | 2418MHz | 36 | 2438MHz | 56 | 2458MHz | 76 | 2478MHz |
| 17 | 2419MHz | 37 | 2439MHz | 57 | 2459MHz | 77 | 2479MHz |
| 18 | 2420MHz | 38 | 2440MHz | 58 | 2460MHz | 78 | 2480MHz |
| 19 | 2421MHz | 39 | 2441MHz | 59 | 2461MHz | | |

Note:


In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel | Frequency |
|---------------------|-----------|
| The Lowest channel | 2402MHz |
| The Middle channel | 2441MHz |
| The Highest channel | 2480MHz |

4.3 Additional Instructions

| EUT Test Software Settings: | | |
|---|--|----------------|
| Mode: | <input checked="" type="checkbox"/> Special software is used. <input type="checkbox"/> Through engineering command into the engineering mode. engineering command: <code>***#3646633#**</code> | |
| EUT Power level: | (Power level is built-in set parameters and cannot be changed and selected) | |
| Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT. | | |
| Mode | Channel | Frequency(MHz) |
| DH1/DH3/DH5 | CH0 | 2402 |
| | CH39 | 2441 |
| | CH78 | 2480 |
| 2DH1/2DH3/2DH5 | CH0 | 2402 |
| | CH39 | 2441 |
| | CH78 | 2480 |

Run Software:



4.4 Test Environment

| Operating Environment: | |
|------------------------|---|
| Temperature: | 25 °C |
| Humidity: | 54% RH |
| Atmospheric Pressure: | 1009mbar |
| Test Mode: | Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT. |

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

| Description | Manufacturer | Model No. | Remark | Supplied |
|-------------|--------------|-----------|--------|----------|
| Adapter | MI | / | / | CQA |

4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

| No. | Item | Uncertainty |
|-----|------------------------------------|--------------------|
| 1 | Radiated Emission (Below 1GHz) | 5.12dB |
| 2 | Radiated Emission (Above 1GHz) | 4.60dB |
| 3 | Conducted Disturbance (0.15~30MHz) | 3.34dB |
| 4 | Radio Frequency | 3×10^{-8} |
| 5 | Duty cycle | 0.6 % |
| 6 | Occupied Bandwidth | 1.1% |
| 7 | RF conducted power | 0.86dB |
| 8 | RF power density | 0.74 |
| 9 | Conducted Spurious emissions | 0.86dB |
| 10 | Temperature test | 0.8°C |
| 11 | Humidity test | 2.0% |
| 12 | Supply voltages | 0.5 % |
| 13 | Frequency Error | 5.5 Hz |

4.7 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

4.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 22984-1

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L5785)**

CNAS has accredited Shenzhen Huaxia Testing Technology Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.9 Abnormalities from Standard Conditions

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List


| Test Equipment | Manufacturer | Model No. | Instrument No. | Calibration Date | Calibration Due Date |
|---|--------------|------------------------|----------------|------------------|----------------------|
| EMI Test Receiver | R&S | ESR7 | CQA-005 | 2023/09/08 | 2024/09/07 |
| Spectrum analyzer | R&S | FSU26 | CQA-038 | 2023/09/08 | 2024/09/07 |
| Spectrum analyzer | R&S | FSU40 | CQA-075 | 2023/09/08 | 2024/09/07 |
| Preamplifier | MITEQ | AFS4-00010300-18-10P-4 | CQA-035 | 2023/09/08 | 2024/09/07 |
| Preamplifier | MITEQ | AMF-6D-02001800-29-20P | CQA-036 | 2023/09/08 | 2024/09/07 |
| Preamplifier | EMCI | EMC184055SE | CQA-089 | 2023/09/08 | 2024/09/07 |
| Loop antenna | Schwarzbeck | FMZB1516 | CQA-060 | 2021/09/16 | 2024/09/15 |
| Bilog Antenna | R&S | HL562 | CQA-011 | 2021/09/16 | 2024/09/15 |
| Horn Antenna | R&S | HF906 | CQA-012 | 2021/09/16 | 2024/09/15 |
| Horn Antenna | Schwarzbeck | BBHA 9170 | CQA-088 | 2021/09/16 | 2024/09/15 |
| Coaxial Cable (Above 1GHz) | CQA | N/A | C007 | 2023/09/08 | 2024/09/07 |
| Coaxial Cable (Below 1GHz) | CQA | N/A | C013 | 2023/09/08 | 2024/09/07 |
| RF cable(9KHz~40GHz) | CQA | RF-01 | CQA-079 | 2023/09/08 | 2024/09/07 |
| Antenna Connector | CQA | RFC-01 | CQA-080 | 2023/09/08 | 2024/09/07 |
| Power Sensor | KEYSIGHT | U2021XA | CQA-30 | 2023/09/08 | 2024/09/07 |
| N1918A Power Analysis Manager Power Panel | Agilent | N1918A | CQA-074 | 2023/09/08 | 2024/09/07 |
| Power meter | R&S | NRVD | CQA-029 | 2023/09/08 | 2024/09/07 |
| Power divider | MIDWEST | PWD-2533-02-SMA-79 | CQA-067 | 2023/09/08 | 2024/09/07 |
| EMI Test Receiver | R&S | ESR7 | CQA-005 | 2023/09/08 | 2024/09/07 |
| LISN | R&S | ENV216 | CQA-003 | 2023/09/08 | 2024/09/07 |
| Coaxial cable | CQA | N/A | CQA-C009 | 2023/09/08 | 2024/09/07 |
| DC power | KEYSIGHT | E3631A | CQA-028 | 2023/09/08 | 2024/09/07 |

Note:


The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data

5.1 Antenna Requirement

| | |
|--|--|
| Standard requirement: | 47 CFR Part 15C Section 15.203 /247(c) |
| <p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> | |
| EUT Antenna: |  |
| <p>The antenna is Chip antenna. The connection/connection type between the antenna to the EUT's antenna port is: permanently attachment. This is either permanently attachment or a unique coupling that satisfies the requirement.</p> | |


5.2 Conducted Emissions

| | | | |
|-----------------------|---|--------------|-----------|
| Test Requirement: | 47 CFR Part 15C Section 15.207 | | |
| Test Method: | ANSI C63.10: 2013 | | |
| Test Frequency Range: | 150kHz to 30MHz | | |
| Limit: | Frequency range (MHz) | Limit (dBuV) | |
| | | Quasi-peak | Average |
| | 0.15-0.5 | 66 to 56* | 56 to 46* |
| | 0.5-5 | 56 | 46 |
| | 5-30 | 60 | 50 |
| | * Decreases with the logarithm of the frequency. | | |
| Test Procedure: | <ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. | | |
| Test Setup: |  | | |

| | |
|---------------|---------------|
| Test Mode: | Charging mode |
| Test Voltage: | AC 120V/60Hz |
| Test Results: | Pass |

Measurement Data

Live line:




| | | Read | | Limit | Over | | | | |
|----|------|-------|--------|-------|-------|-------|-----------|---------|------|
| | Freq | Level | Factor | Level | Line | Limit | Remark | | |
| | MHz | dBuV | dB | dBuV | dBuV | dB | Pol/Phase | | |
| 1 | PP | 0.565 | 25.77 | 9.64 | 35.41 | 46.00 | -10.59 | Average | Line |
| 2 | QP | 0.565 | 34.09 | 9.64 | 43.73 | 56.00 | -12.27 | QP | Line |
| 3 | | 0.775 | 20.16 | 9.78 | 29.94 | 46.00 | -16.06 | Average | Line |
| 4 | | 0.775 | 25.58 | 9.78 | 35.36 | 56.00 | -20.64 | QP | Line |
| 5 | | 0.915 | 20.08 | 9.62 | 29.70 | 46.00 | -16.30 | Average | Line |
| 6 | | 0.915 | 25.70 | 9.62 | 35.32 | 56.00 | -20.68 | QP | Line |
| 7 | | 1.000 | 19.42 | 9.53 | 28.95 | 46.00 | -17.05 | Average | Line |
| 8 | | 1.000 | 24.91 | 9.53 | 34.44 | 56.00 | -21.56 | QP | Line |
| 9 | | 1.210 | 20.27 | 9.53 | 29.80 | 46.00 | -16.20 | Average | Line |
| 10 | | 1.210 | 25.95 | 9.53 | 35.48 | 56.00 | -20.52 | QP | Line |
| 11 | | 1.390 | 18.32 | 9.53 | 27.85 | 46.00 | -18.15 | Average | Line |
| 12 | | 1.390 | 24.03 | 9.53 | 33.56 | 56.00 | -22.44 | QP | Line |

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:





| | Read | | | Limit | Over | | | | |
|------|-------|--------|-------|-------|-------|--------|-----------|---------|---------|
| Freq | Level | Factor | Level | Line | Limit | Remark | Pol/Phase | | |
| MHz | dBuV | dB | dBuV | dBuV | dB | | | | |
| 1 | 0.210 | 21.14 | 9.59 | 30.73 | 53.21 | -22.48 | Average | Neutral | |
| 2 | 0.210 | 26.59 | 9.59 | 36.18 | 63.21 | -27.03 | QP | Neutral | |
| 3 | 0.310 | 19.86 | 9.49 | 29.35 | 49.97 | -20.62 | Average | Neutral | |
| 4 | 0.310 | 25.19 | 9.49 | 34.68 | 59.97 | -25.29 | QP | Neutral | |
| 5 | PP | 0.555 | 26.44 | 9.76 | 36.20 | 46.00 | -9.80 | Average | Neutral |
| 6 | QP | 0.555 | 32.06 | 9.76 | 41.82 | 56.00 | -14.18 | QP | Neutral |
| 7 | | 0.840 | 18.74 | 9.81 | 28.55 | 46.00 | -17.45 | Average | Neutral |
| 8 | | 0.840 | 24.43 | 9.81 | 34.24 | 56.00 | -21.76 | QP | Neutral |
| 9 | | 1.350 | 18.90 | 9.72 | 28.62 | 46.00 | -17.38 | Average | Neutral |
| 10 | | 1.350 | 24.35 | 9.72 | 34.07 | 56.00 | -21.93 | QP | Neutral |
| 11 | | 1.620 | 17.70 | 9.73 | 27.43 | 46.00 | -18.57 | Average | Neutral |
| 12 | | 1.620 | 22.91 | 9.73 | 32.64 | 56.00 | -23.36 | QP | Neutral |

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


5.3 Conducted Peak Output Power


| | |
|------------------------|---|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (b)(1) |
| Test Method: | ANSI C63.10:2013 |
| Test Setup: | <p>Setup for Power meter measurement method</p>  <p>Setup for Spectrum analyser measurement method</p>  <p><i>Remark: Offset=Cable loss+ attenuation factor.</i></p> |
| Limit: | 21dBm |
| Exploratory Test Mode: | Non-hopping transmitting with all kind of modulation and all kind of data type |
| Final Test Mode: | Only the worst case is recorded in the report. |
| Test Results: | Pass |

Measurement Data


| GFSK mode | | | |
|--------------------|-------------------------|-------------|--------|
| Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest | -0.08 | 21.00 | Pass |
| Middle | 0 | 21.00 | Pass |
| Highest | 0.47 | 21.00 | Pass |
| $\pi/4$ DQPSK mode | | | |
| Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest | -0.15 | 21.00 | Pass |
| Middle | -0.06 | 21.00 | Pass |
| Highest | 0.53 | 21.00 | Pass |

Test plot as follows:







2DH5_Ant1_2402




2DH5_Ant1_2441



2DH5_Ant1_2480




5.4 20dB Occupied Bandwidth


| | |
|------------------------|--|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (a)(1) |
| Test Method: | ANSI C63.10:2013 |
| Test Setup: |  <p>Remark: Offset=Cable loss+ attenuation factor.</p> |
| Limit: | NA |
| Exploratory Test Mode: | Non-hopping transmitting with all kind of modulation and all kind of data type |
| Final Test Mode: | Only the worst case is recorded in the report. |
| Test Results: | Pass |

Measurement Data

| Test channel | 20dB Occupy Bandwidth (MHz) | |
|--------------|-----------------------------|---------------|
| | GFSK | $\pi/4$ DQPSK |
| Lowest | 0.94 | 1.21 |
| Middle | 0.94 | 1.21 |
| Highest | 0.94 | 1.21 |


Test plot as follows:






Date: 18.APR 2024 15:03:18

2DH5_Ant1_2402




Date: 18.APR 2024 15:06:47

2DH5_Ant1_2441




Date: 18.APR 2024 15:13:28

2DH5_Ant1_2480



5.5 Carrier Frequencies Separation

| | |
|------------------------|--|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (a)(1) |
| Test Method: | ANSI C63.10:2013 |
| Test Setup: |  <p>Remark: Offset=Cable loss+ attenuation factor.</p> |
| Limit: | 2/3 of the 20dB bandwidth |
| | Remark: the transmission power is less than 0.125W. |
| Exploratory Test Mode: | Hopping transmitting with all kind of modulation and all kind of data type |
| Final Test Mode: | Only the worst case is recorded in the report. |
| Test Results: | Pass |

Measurement Data


| TestMode | Freq(MHz) | Result[MHz] | Limit[MHz] | Verdict |
|----------|-----------|-------------|------------|---------|
| DH5 | Hop | 1.003 | ≥0.627 | PASS |
| 2DH5 | Hop | 1.003 | ≥0.807 | PASS |

| Mode | 20dB bandwidth (MHz) (worse case) | Limit (MHz) (Carrier Frequencies Separation) |
|---------------|--------------------------------------|---|
| GFSK | 0.94 | ≥0.627 |
| $\pi/4$ DQPSK | 1.21 | ≥0.807 |

Test plot as follows:




5.6 Hopping Channel Number

| | |
|------------------------|---|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (a)(1) |
| Test Method: | ANSI C63.10:2013 |
| Test Setup: |  <p style="text-align: center;"><i>Remark: Offset=Cable loss+ attenuation factor.</i></p> |
| Limit: | At least 15 channels |
| Exploratory Test Mode: | hopping transmitting with all kind of modulation and all kind of data type |
| Final Test Mode: | Only the worst case is recorded in the report. |
| Test Results: | Pass |


Measurement Data

| Mode | Hopping channel numbers | Limit |
|---------------|-------------------------|-------|
| GFSK | 79 | ≥15 |
| $\pi/4$ DQPSK | 79 | ≥15 |

Test plot as follows:



5.7 Dwell Time

| | |
|-------------------|---|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (a)(1) |
| Test Method: | ANSI C63.10:2013 |
| Test Setup: |  <p style="text-align: center;"><i>Remark: Offset=Cable loss+ attenuation factor.</i></p> |
| Test Mode: | Hopping transmitting with all kind of modulation and all kind of data type. |
| Limit: | 0.4 Second |
| Test Results: | Pass |


Measurement Data


| TestMode | Freq(MHz) | BurstWidth [ms] | TotalHops [Num] | Result[s] | Limit[s] | Verdict |
|----------|-----------|--------------------|--------------------|-----------|----------|---------|
| DH1 | Hop | 0.368 | 320 | 0.118 | ≤0.4 | PASS |
| DH3 | Hop | 1.609 | 160 | 0.257 | ≤0.4 | PASS |
| DH5 | Hop | 2.850 | 110 | 0.314 | ≤0.4 | PASS |
| 2DH1 | Hop | 0.376 | 320 | 0.12 | ≤0.4 | PASS |
| 2DH3 | Hop | 1.621 | 160 | 0.259 | ≤0.4 | PASS |
| 2DH5 | Hop | 2.867 | 110 | 0.315 | ≤0.4 | PASS |

Remark:


The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test plot as follows:






Date: 18.APR 2024 15:38:53




Date: 18.APR 2024 15:38:59



DH5_Ant1_Hop




Date: 18.APR 2024 15:34:27




2DH1_Ant1_Hop



2DH3_Ant1_Hop




Date: 18.APR 2024 15:46:50




Date: 18.APR 2024 15:46:55


2DH5_Ant1_Hop



Date: 18.APR 2024 15:45:15




5.8 Band-edge for RF Conducted Emissions

| | |
|------------------------|---|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (d) |
| Test Method: | ANSI C63.10:2013 |
| Test Setup: |  <p style="text-align: center;"><i>Remark: Offset=cable loss+ attenuation factor.</i></p> |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Exploratory Test Mode: | Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type |
| Final Test Mode: | Only the worst case is recorded in the report. |
| Test Results: | Pass |


Measurement Data

| TestMode | ChName | Freq(MHz) | RefLevel [dBm] | Result [dBm] | Limit [dBm] | Verdict |
|----------|--------|-----------|-------------------|-----------------|----------------|---------|
| DH5 | Low | 2402 | -0.56 | -54.11 | ≤-20.56 | PASS |
| | High | 2480 | 0.23 | -54.77 | ≤-19.77 | PASS |
| | Low | Hop_2402 | -1.39 | -55.67 | ≤-21.39 | PASS |
| | High | Hop_2480 | -0.11 | -54.74 | ≤-20.11 | PASS |
| 2DH5 | Low | 2402 | -0.74 | -54.89 | ≤-20.74 | PASS |
| | High | 2480 | -0.48 | -54.74 | ≤-20.48 | PASS |
| | Low | Hop_2402 | -5.44 | -55.77 | ≤-25.44 | PASS |
| | High | Hop_2480 | -2.10 | -54.78 | ≤-22.1 | PASS |

Test plot as follows:




DH5_Ant1_Low_Hop_2402




Date: 18.APR 2024 15:30:43

DH5_Ant1_High_Hop_2480




Date: 18.APR 2024 15:39:14

2DH5_Ant1_Low_2402




Date: 18.APR 2024 15:07:04


2DH5_Ant1_High_2480




2DH5 Ant1 Low Hop 2402



2DH5 Ant1 High Hop 2480



5.9 Spurious RF Conducted Emissions


| | |
|------------------------|---|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (d) |
| Test Method: | ANSI C63.10:2013 |
| Test Setup: |  <p style="text-align: center;"><i>Remark: Offset=cable loss+ attenuation factor.</i></p> |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Exploratory Test Mode: | Non-hopping transmitting with all kind of modulation and all kind of data type |
| Final Test Mode: | Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type. |
| Test Results: | Pass |

DH5_Ant1_2402_0~Reference




Date: 18.APR.2024 14:57:30

DH5_Ant1_2402_30~1000




Date: 18.APR.2024 14:57:36

DH5_Ant1_2402_1000~26500




Date: 18.APR.2024 14:57:58

DH5_Ant1_2441_0~Reference




Date: 18.APR.2024 14:59:32

DH5_Ant1_2441_30~1000



Date: 18.APR.2024 14:59:39


DH5_Ant1_2441_1000~26500




DH5_Ant1_2480_0~Reference




DH5_Ant1_2480_30~1000




DH5_Ant1_2480_1000~26500




2DH5_Ant1_2402_0~Reference



2DH5_Ant1_2402_30~1000




2DH5_Ant1_2402_1000~26500




Date: 18.APR.2024 15:09:11

2DH5_Ant1_2441_0~Reference




Date: 18.APR.2024 15:13:43

2DH5_Ant1_2441_30~1000




Date: 18.APR.2024 15:13:50

2DH5_Ant1_2441_1000~26500




Date: 18.APR 2024 15:14:12

2DH5_Ant1_2480_0~Reference




Date: 18.APR 2024 15:17:32

2DH5_Ant1_2480_30~1000



Date: 18.APR 2024 15:17:39



2DH5_Ant1_2480_1000~26500



Remark:

Pre test 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o), The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.10 Other requirements Frequency Hopping Spread Spectrum System

| Test Requirement: | 47 CFR Part 15C Section 15.247 (a)(1), (h) requirement: |
|---|---|
| <p>The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.</p> <p>Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.</p> <p>The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.</p> | |
| <p>Compliance for section 15.247(a)(1)</p> | |
| <p>According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.</p> <ul style="list-style-type: none"> • Number of shift register stages: 9 • Length of pseudo-random sequence: $2^9 - 1 = 511$ bits • Longest sequence of zeros: 8 (non-inverted signal) <div data-bbox="300 1373 1353 1523" style="text-align: center;">  </div> <p style="text-align: center;"><i>Linear Feedback Shift Register for Generation of the PRBS sequence</i></p> <p>An example of Pseudorandom Frequency Hopping Sequence as follow:</p> <div data-bbox="276 1621 1262 1767" style="text-align: center;">  </div> <p>Each frequency used equally on the average by each transmitter.</p> <p>According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.</p> | |
| <p>Compliance for section 15.247(g)</p> | |
| <p>According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.</p> | |

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

5.11 Radiated Spurious Emission & Restricted bands

| | | | | | |
|--|--|----------------------------------|----------------|------------|--------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.209 and 15.205 | | | | |
| Test Method: | ANSI C63.10: 2013 | | | | |
| Test Site: | Measurement Distance: 3m (Semi-Anechoic Chamber) | | | | |
| Receiver Setup: | Frequency | Detector | RBW | VBW | Remark |
| | 0.009MHz-0.090MHz | Peak | 10kHz | 30kHz | Peak |
| | 0.009MHz-0.090MHz | Average | 10kHz | 30kHz | Average |
| | 0.090MHz-0.110MHz | Quasi-peak | 10kHz | 30kHz | Quasi-peak |
| | 0.110MHz-0.490MHz | Peak | 10kHz | 30kHz | Peak |
| | 0.110MHz-0.490MHz | Average | 10kHz | 30kHz | Average |
| | 0.490MHz -30MHz | Quasi-peak | 10kHz | 30kHz | Quasi-peak |
| | 30MHz-1GHz | Peak | 120 kHz | 300kHz | Peak |
| | Above 1GHz | Peak | 1MHz | 3MHz | Peak |
| Peak | | 1MHz | 10Hz | Average | |
| Limit: | Frequency | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark | Measurement distance (m) |
| | 0.009MHz-0.490MHz | 2400/F(kHz) | - | - | 300 |
| | 0.490MHz-1.705MHz | 24000/F(kHz) | - | - | 30 |
| | 1.705MHz-30MHz | 30 | - | - | 30 |
| | 30MHz-88MHz | 100 | 40.0 | Quasi-peak | 3 |
| | 88MHz-216MHz | 150 | 43.5 | Quasi-peak | 3 |
| | 216MHz-960MHz | 200 | 46.0 | Quasi-peak | 3 |
| | 960MHz-1GHz | 500 | 54.0 | Quasi-peak | 3 |
| | Above 1GHz | 500 | 54.0 | Average | 3 |
| <p>Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.</p> | | | | | |

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz


Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

| | |
|------------------------|---|
| | <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz)</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> |
| Exploratory Test Mode: | Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode |
| Final Test Mode: | Only the worst case is recorded in the report. |
| Test Results: | Pass |

5.11.1 Radiated Emission below 1GHz

| | | |
|------------|--------------|----------|
| 30MHz~1GHz | | |
| Test mode: | Transmitting | Vertical |



| | Read Freq | Read Level | Factor | Limit Level | Over Limit | Remark | Pol/Phase | | |
|---|-----------|------------|--------|-------------|------------|--------|-----------|------|----------|
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | | |
| 1 | pp | 37.42 | 15.45 | 13.73 | 29.18 | 40.00 | -10.82 | Peak | VERTICAL |
| 2 | | 44.12 | 14.32 | 10.86 | 25.18 | 40.00 | -14.82 | Peak | VERTICAL |
| 3 | | 129.47 | 9.38 | 10.34 | 19.72 | 43.50 | -23.78 | Peak | VERTICAL |
| 4 | | 501.18 | 12.93 | 18.29 | 31.22 | 46.00 | -14.78 | Peak | VERTICAL |
| 5 | | 836.24 | 9.52 | 24.12 | 33.64 | 46.00 | -12.36 | Peak | VERTICAL |
| 6 | | 982.62 | 9.84 | 24.65 | 34.49 | 54.00 | -19.51 | Peak | VERTICAL |

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

| | | |
|------------|--------------|------------|
| Test mode: | Transmitting | Horizontal |
|------------|--------------|------------|



| | Read Freq | Read Level | Factor | Limit Level | Over Limit | Remark | Pol/Phase |
|------|-----------|------------|--------|-------------|------------|--------|-----------------|
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | |
| 1 | 34.04 | 10.09 | 14.86 | 24.95 | 40.00 | -15.05 | Peak HORIZONTAL |
| 2 | 102.72 | 10.08 | 10.52 | 20.60 | 43.50 | -22.90 | Peak HORIZONTAL |
| 3 | 354.18 | 9.48 | 15.05 | 24.53 | 46.00 | -21.47 | Peak HORIZONTAL |
| 4 | 501.18 | 10.99 | 18.29 | 29.28 | 46.00 | -16.72 | Peak HORIZONTAL |
| 5 | 726.81 | 11.24 | 21.27 | 32.51 | 46.00 | -13.49 | Peak HORIZONTAL |
| 6 pp | 845.09 | 9.45 | 24.08 | 33.53 | 46.00 | -12.47 | Peak HORIZONTAL |

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

5.11.2 Transmitter Emission above 1GHz

| Worse case mode: | | GFSK(DH5) | | Test channel: | | Lowest | |
|------------------|---------------|-----------|----------------|----------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | | H/V |
| 2390 | 54.25 | -9.2 | 45.05 | 74 | -28.95 | Peak | H |
| 2400 | 54.83 | -9.39 | 45.44 | 74 | -28.56 | Peak | H |
| 4804 | 52.90 | -4.33 | 48.57 | 74 | -25.43 | Peak | H |
| 7206 | 49.92 | 1.01 | 50.93 | 74 | -23.07 | Peak | H |
| 2390 | 53.62 | -9.2 | 44.42 | 74 | -29.58 | Peak | V |
| 2400 | 56.83 | -9.39 | 47.44 | 74 | -26.56 | Peak | V |
| 4804 | 54.17 | -4.33 | 49.84 | 74 | -24.16 | Peak | V |
| 7206 | 48.63 | 1.01 | 49.64 | 74 | -24.36 | Peak | V |

| Worse case mode: | | GFSK(DH5) | | Test channel: | | Middle | |
|------------------|---------------|-----------|----------------|----------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | | H/V |
| 4882 | 54.25 | -9.2 | 45.05 | 74 | -28.95 | peak | H |
| 7323 | 54.83 | -9.39 | 45.44 | 74 | -28.56 | peak | H |
| 4882 | 52.90 | -4.33 | 48.57 | 74 | -25.43 | peak | V |
| 7323 | 49.92 | 1.01 | 50.93 | 74 | -23.07 | peak | V |

| Worse case mode: | | GFSK(DH5) | | Test channel: | | Highest | |
|------------------|---------------|-----------|----------------|----------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | | H/V |
| 2483.5 | 55.95 | -9.29 | 46.66 | 74 | -27.34 | Peak | H |
| 4960 | 51.19 | -4.04 | 47.15 | 74 | -26.85 | Peak | H |
| 7440 | 48.59 | 1.57 | 50.16 | 74 | -23.84 | Peak | H |
| 2483.5 | 55.31 | -9.29 | 46.02 | 74 | -27.98 | Peak | V |
| 4960 | 49.59 | -4.04 | 45.55 | 74 | -28.45 | Peak | V |
| 7440 | 49.50 | 1.57 | 51.07 | 74 | -22.93 | Peak | V |

| Worse case mode: | | π /4DQPSK (2DH5) | | Test channel: | | Lowest | |
|------------------|---------------|----------------------|----------------|----------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | | H/V |
| 2390 | 53.78 | -9.2 | 44.58 | 74 | -29.42 | Peak | H |
| 2400 | 54.35 | -9.39 | 44.96 | 74 | -29.04 | Peak | H |
| 4804 | 52.08 | -4.33 | 47.75 | 74 | -26.25 | Peak | H |
| 7206 | 49.49 | 1.01 | 50.50 | 74 | -23.50 | Peak | H |
| 2390 | 56.02 | -9.2 | 46.82 | 74 | -27.18 | Peak | V |
| 2400 | 54.64 | -9.39 | 45.25 | 74 | -28.75 | Peak | V |
| 4804 | 52.72 | -4.33 | 48.39 | 74 | -25.61 | Peak | V |
| 7206 | 49.88 | 1.01 | 50.89 | 74 | -23.11 | Peak | V |

| Worse case mode: | | π /4DQPSK (2DH5) | | Test channel: | | Middle | |
|------------------|---------------|----------------------|----------------|----------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | | H/V |
| 4882 | 52.88 | -4.11 | 48.77 | 74 | -25.23 | peak | H |
| 7323 | 49.13 | 1.51 | 50.64 | 74 | -23.36 | peak | H |
| 4882 | 52.27 | -4.11 | 48.16 | 74 | -25.84 | peak | V |
| 7323 | 48.62 | 1.51 | 50.13 | 74 | -23.87 | peak | V |

| Worse case mode: | | π /4DQPSK (2DH5) | | Test channel: | | Highest | |
|------------------|---------------|----------------------|----------------|----------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | | H/V |
| 2483.5 | 56.69 | -9.29 | 47.40 | 74 | -26.60 | Peak | H |
| 4960 | 52.28 | -4.04 | 48.24 | 74 | -25.76 | Peak | H |
| 7440 | 50.09 | 1.57 | 51.66 | 74 | -22.34 | Peak | H |
| 2483.5 | 53.56 | -9.29 | 44.27 | 74 | -29.73 | Peak | V |
| 4960 | 49.05 | -4.04 | 45.01 | 74 | -28.99 | Peak | V |
| 7440 | 48.81 | 1.57 | 50.38 | 74 | -23.62 | Peak | V |

Remark:

- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6 Photographs - EUT Test Setup

6.1 Radiated Emission

9KHz~30MHz:



30MHz~1GHz:

