



**Microtest**  
微 测 检 测

# Test Report

**Report No.:** MTi240408008-01E2  
**Date of issue:** 2024-05-28  
**Applicant:** Guangzhou Havit Technology Co., Ltd.  
**Product:** 3 IN 1 WIRELESS CHARGER  
**Model(s):** W3037 kit  
**FCC ID:** 2A16I-W3037KIT

Shenzhen Microtest Co., Ltd.

[http:// Web: www.mtitest.cn](http://www.mtitest.cn)

## Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

# Contents

<b>1</b>	<b>General Description .....</b>	<b>5</b>
1.1	Description of the EUT .....	5
1.2	Description of test modes .....	6
1.3	Description of support units .....	7
<b>2</b>	<b>Measurement uncertainty .....</b>	<b>7</b>
<b>3</b>	<b>Test facilities and accreditations.....</b>	<b>8</b>
3.1	Test laboratory .....	8
<b>4</b>	<b>List of test equipment .....</b>	<b>9</b>
<b>5</b>	<b>Test result .....</b>	<b>10</b>
5.2	Test setup .....	11
5.3	Test Procedures.....	11
5.4	Information of test equipment .....	12
5.5	Test results .....	13
	<b>Photographs of the Test Setup.....</b>	<b>14</b>
	<b>Photographs of the EUT.....</b>	<b>14</b>

<b>Test Result Certification</b>	
<b>Applicant:</b>	Guangzhou Havit Technology Co., Ltd.
<b>Address:</b>	ROOM 1307, 13F, PHASE 2 B, C BUILDING OF POLY WORLD TRADE CENTER, NO.1000, XINGANG EAST ROAD, HAIZHU GUANGDONG China
<b>Manufacturer:</b>	Guangzhou Havit Technology Co., Ltd.
<b>Address:</b>	ROOM 1307, 13F, PHASE 2 B, C BUILDING OF POLY WORLD TRADE CENTER, NO.1000, XINGANG EAST ROAD, HAIZHU GUANGDONG China
<b>Product description</b>	
<b>Product name:</b>	3 IN 1 WIRELESS CHARGER
<b>Trademark:</b>	HAVIT
<b>Model name:</b>	W3037 kit
<b>Series Model:</b>	N/A
<b>Standards:</b>	FCC CFR 47 PART 1, § 1.1310
<b>Test method:</b>	KDB 680106 D01 Wireless Power Transfer v04
<b>Date of Test</b>	
<b>Date of test:</b>	2024-05-22 to 2024-05-24
<b>Test result:</b>	Pass

<b>Test Engineer</b>	:	<i>Letter Lan.</i>
		(Letter Lan)
<b>Reviewed By</b>	:	<i>David. Lee</i>
		(David Lee)
<b>Approved By</b>	:	<i>Leon Chen</i>
		(Leon Chen)

## 1 General Description

### 1.1 Description of the EUT

Product name:	3 IN 1 WIRELESS CHARGER
Model name:	W3037 kit
Series Model(s):	N/A
Model difference:	N/A
Electrical rating:	Input: 9VDC 3A Wireless Output: Phone: 5W,7.5W,10W,15W; Earphone: 3W; Watch: 2.5W
Accessories:	Type-c to Type-c cable 1m
Hardware version:	V1.0
Software version:	V1.0
Test sample(s) number:	MTi240408008-01S1001
<b>RF specification</b>	
Operating frequency range:	Transmitter1 (Phone): 115-205 kHz Transmitter2 (Earphone): 115-205 kHz Transmitter3 (Watch): 300-350 kHz
Modulation type:	ASK
Antenna(s) type:	Coil

## 1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode1	Wireless output(5W)+Earphone(3W)+Watch(2.5W)+lighting
Mode2	Wireless output(7.5W)+Earphone(3W)+Watch(2.5W)+lighting
Mode3	Wireless output(10W)+Earphone(3W)+Watch(2.5W)+lighting
Mode4	Wireless output(15W)+Earphone(3W)+Watch(2.5W)+lighting
Mode5	Wireless output(5W)+Earphone(3W)+lighting
Mode6	Wireless output(7.5W)+Earphone(3W)+lighting
Mode7	Wireless output(10W)+Earphone(3W)+lighting
Mode8	Wireless output(15W)+Earphone(3W)+lighting
Mode9	Wireless output(5W)+Watch(2.5W)+lighting
Mode10	Wireless output(7.5W)+Watch(2.5W)+lighting
Mode11	Wireless output(10W)+Watch(2.5W)+lighting
Mode12	Wireless output(15W)+Watch(2.5W)+lighting
Mode13	Earphone(3W)+Watch(2.5W)+lighting
Mode14	Wireless output(5W)+lighting
Mode15	Wireless output(7.5W)+lighting
Mode16	Wireless output(10W)+lighting
Mode17	Wireless output(15W)+lighting
Mode18	Watch(2.5W)+lighting
Mode19	Earphone(3W)+lighting
Mode20	stand by

### 1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list			
Description	Model	Serial No.	Manufacturer
MI CHARGE(33W)	MDY-11-EX	SA623116200029J	MI
Phone	Find X3	/	OPPO
iWatch	iWatch S7	M0JVGQG1VP	Apple
Air Pods	MQD83CH/A	/	Apple
Support cable list			
Description	Length (m)	From	To
/	/	/	/

## 2 Measurement uncertainty

Parameter	Expanded Uncertainty
Magnetic field measurement (3kHz~10MHz)	± 14.8%
Electric field measurements (3kHz~10MHz)	± 17.5%

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3 Test facilities and accreditations

#### 3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573



#### 4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E143	Near-field Electric and Magnetic Field Sensor System	Speag	MAGPy-8H3D +ED3 V2	3101	2024/3/12	2027/3/11

No.	Equipment	Manufacturer	Model	Software version:	Cal. date	Cal. Due
MTI-E016S	MPE test software	SPEAG	MAGPY 2.4	2.4.1	/	/

## 5 Test result

### 5.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

**Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(i) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
<b>(ii) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30


f = frequency in MHz

\* = Plane-wave equivalent power density

**Note 1:** Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

**Note 2:** General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

## 5.2 Test setup




## 5.3 Test Procedures

- The RF exposure test was performed in anechoic chamber.
- E and H-field measurements should be made with these devices considered to meet the § 2.1091-Mobile conditions (“generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and [the nearest person]”).
- The highest emission level was recorded and compared with limit.
- The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.

#### 5.4 Information of test equipment

Test equipment: MAGPy-8H3D+ED3	
Diameter	60mm
8 isotropic H-field sensors	Concentric loops of 1cm <sup>2</sup> arranged at the corner of a cube of 22mm side length
1 isotropic E-field sensor	Orthogonal dipole/monopole (arm length: 50mm)
Measurement center	18.5mm from the probe tip
Dimensions	110*635*35mm (MAGPy-8H3D+E3D V2 & MAGPy-DAS V2)



Test probe, without the casing

## 5.5 Test results

### Test condition 1: Mode 4 operating mode with client device (1 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	11.13	614	1.81%	0.14	1.63	25.15%
Left	4.25			0.40		
Right	7.37			0.26		
Front	6.19			0.41		
Rear	3.19			0.25		
bottom	6.02			0.27		

### Test condition 2: Mode 4 operating mode with client device (50 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
Z axis	11.01	614	1.79%	0.13	1.63	23.31%
Left	4.20			0.37		
Right	7.18			0.24		
Front	6.10			0.38		
Rear	3.17			0.23		
Bottom	5.80			0.25		

### Test condition 3: Mode 4 operating mode with client device (99 % battery status of client device)

Probe Position	E -field (V/m)			H-field (A/m)		
	Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
Z axis	10.84	614	1.77%	0.12	1.63	22.09%
Left	4.17			0.35		
Right	7.15			0.23		
Front	6.07			0.36		
Rear	3.15			0.24		
bottom	5.74			0.26		

## **Photographs of the Test Setup**

See the Appendix - Test Setup Photos.

## **Photographs of the EUT**

See the Appendix - EUT Photos.

**----End of Report----**