

RF MEASUREMENT REPORT

FCC ID: 2A19TOAW-AP151X
Applicant: ALE USA Inc.
Product: OmniAccess Stellar
Model No.: OAW-AP1511
Brand Name: Alcatel-Lucent Enterprise
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part 15 Subpart C (Section 15.247)
Result: Complies
Received Date: 2024-04-29
Test Date: 2024-05-24 ~ 2024-08-16

Reviewed By:

Vincent Yu

Approved By:

Robin Wu



The test results relate only to the samples tested.
This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.
The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2404RSU054-U1	V01	Initial Report	2024-08-29	Valid

CONTENTS

Description	Page
1. General Information	5
1.1. Applicant	5
1.2. Manufacturer	5
1.3. Testing Facility	5
1.4. Product Information.....	6
1.5. Radio Specification under Test	6
1.6. Working Frequencies	7
2. Test Configuration	8
2.1. Test Mode.....	8
2.2. Test System Connection Diagram.....	8
2.3. Test Software	9
2.4. Applied Standards.....	9
2.5. Test Environment Condition	9
3. Antenna Requirements	10
4. Measuring Instrument	11
5. Decision Rules and Measurement Uncertainty	12
5.1. Decision Rules	12
5.2. Measurement Uncertainty	12
6. Test Result.....	13
6.1. Summary.....	13
6.2. 6dB Bandwidth Measurement.....	14
6.2.1. Test Limit	14
6.2.2. Test Procedure.....	14
6.2.3. Test Setting	14
6.2.4. Test Setup	14
6.2.5. Test Result	14
6.3. Output Power Measurement	15
6.3.1. Test Limit	15
6.3.2. Test Procedure.....	15
6.3.3. Test Setting	15
6.3.4. Test Setup	15
6.3.5. Test Result	15
6.4. Power Spectral Density Measurement	16
6.4.1. Test Limit	16
6.4.2. Test Procedure.....	16

6.4.3.	Test Setting	16
6.4.4.	Test Setup	16
6.4.5.	Test Result	16
6.5.	Conducted Band Edge and Out-of-Band Emissions Measurement	17
6.5.1.	Test Limit	17
6.5.2.	Test Procedure	17
6.5.3.	Test Settintg	17
6.5.4.	Test Setup	18
6.5.5.	Test Result	18
6.6.	Radiated Spurious Emission Measurement.....	19
6.6.1.	Test Limit	19
6.6.2.	Test Procedure	19
6.6.3.	Test Setting	19
6.6.4.	Test Setup	21
6.6.5.	Test Result	22
6.7.	Radiated Restricted Band Edge Measurement	23
6.7.1.	Test Limit	23
6.7.2.	Test Procedure	24
6.7.3.	Test Setting	24
6.7.4.	Test Setup	25
6.7.5.	Test Result	26
6.8.	AC Conducted Emissions Measurement	27
6.8.1.	Test Limit	27
6.8.2.	Test Setup	27
6.8.3.	Test Result	27
Appendix A - Test Result.....		28
A.1	Duty Cycle Test Result	28
A.2	6dB Bandwidth Test Result	29
A.3	Output Power Test Result	31
A.4	Power Spectral Density Test Result.....	32
A.5	Conducted Band Edge and Out-of-Band Emissions Test Result.....	34
A.6	Radiated Spurious Emission Test Result.....	38
A.7	Radiated Restricted Band Edge Test Result.....	42
A.8	AC Conducted Emissions Test Result	58
Appendix B - Test Setup Photograph		60
Appendix C - EUT Photograph		61



1. General Information

1.1. Applicant

ALE USA Inc.
2000 Corporate Center Drive Thousand Oaks, CA 91320

1.2. Manufacturer

ALE USA Inc.
2000 Corporate Center Drive Thousand Oaks, CA 91320

1.3. Testing Facility

<input checked="" type="checkbox"/>	<p>Test Site – MRT Suzhou Laboratory</p> <hr/> <p>Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China</p> <p>Laboratory Location (Suzhou - SIP) 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China</p> <p>Laboratory Location (Suzhou - Wujiang) Building 1, No.1 Xingdong Road, Wujiang, Suzhou, Jiangsu, People's Republic of China</p> <hr/> <p>Laboratory Accreditations</p> <p>A2LA: 3628.01 CNAS: L10551 FCC: CN1166 ISED: CN0001</p> <p>VCCI: <input type="checkbox"/>R-20025 <input type="checkbox"/>G-20034 <input type="checkbox"/>C-20020 <input type="checkbox"/>T-20020 <input type="checkbox"/>R-20141 <input type="checkbox"/>G-20134 <input type="checkbox"/>C-20103 <input type="checkbox"/>T-20104</p>
<input type="checkbox"/>	<p>Test Site – MRT Shenzhen Laboratory</p> <hr/> <p>Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China</p> <hr/> <p>Laboratory Accreditations</p> <p>A2LA: 3628.02 CNAS: L10551 FCC: CN1284 ISED: CN0105</p>
<input type="checkbox"/>	<p>Test Site – MRT Taiwan Laboratory</p> <hr/> <p>Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)</p> <hr/> <p>Laboratory Accreditations</p> <p>TAF: 3261 FCC: 291082, TW3261 ISED: TW3261</p>

1.4. Product Information

Product Name	OmniAccess Stellar
Model No.	OAW-AP1511
EUT Identification No.	20240604Sample#02
Wi-Fi Specification	802.11a/b/g/n/ac/ax/be
Bluetooth Specification	V5.4 single mode, BLE only
ZigBee Specification	802.15.4
Antenna Information	Refer to Section 1.5
Power Type	AC Adapter Input or PoE Input
Operating Environment	Indoor Use
Accessories	
Adapter	Model No.: ADP-50GR B Input Power: 100 - 240V ~ 50/60Hz, 1.3A Output Power: 48V, 1.042A
PoE Injector	Model: POE60U-1BT-X (ALE P/N: POE60U-1BT-X-R) Input: 100-240V ~ 1.5A, 50/60Hz Output: 56.0V, 0.535A, 30W PIN 3, 6+ PIN 1, 2 Return Output: 56.0V, 0.535A, 30W PIN 4, 5+ PIN 7, 8 Return
Remark: 1. The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer. 2. AC Power Adapter and PoE Injector are not sold with Product. For this report, we select AC Adapter for testing.	

1.5. Radio Specification under Test

Bluetooth Frequency	2402 ~ 2480MHz
Channel Number	40
Type of modulation	GFSK
Data Rate	1Mbps & 2Mbps
Antenna Type	Dipole
Antenna Gain	4.3 dBi

1.6. Working Frequencies

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz
03	2408 MHz	04	2410 MHz	05	2412 MHz
06	2414 MHz	07	2416 MHz	08	2418 MHz
09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz
15	2432 MHz	16	2434 MHz	17	2436 MHz
18	2438 MHz	19	2440 MHz	20	2442 MHz
21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz
27	2456 MHz	28	2458 MHz	29	2460 MHz
30	2462 MHz	31	2464 MHz	32	2466 MHz
33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz
39	2480 MHz	--	--	--	--


2. Test Configuration

2.1. Test Mode

Mode 1: Transmit by BLE-1Mbps
Mode 2: Transmit by BLE-2Mbps

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram			
 <p>The diagram shows a test setup within a large rectangular frame. On the left is a box labeled 'EUT'. To its right is a box labeled 'Adapter'. Further right is a box labeled '1' (representing a notebook). Cable 'A' connects the EUT to the Adapter. Cable 'B' connects the Adapter to the notebook '1'.</p>			
Cable Type		Cable Description	Length
A	Power Cable	Non-Shielded	1.5m
B	LAN Cable	Non-Shielded	> 10m
Product		Manufacturer	Model No.
1	Notebook	Lenovo	E430C

2.3. Test Software

The test utility software used during testing was “IPOP” and commands were provided by the manufacturer.

2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 558074 D01v05r02
- ANSI C63.10-2013

2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~75%RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Signal Generator	Agilent	E4438C	MRTSUE06081	1 year	2025-02-03	WZ-SR5
Signal Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2025-02-03	WZ-SR5
Thermohygrometer	testo	608-H1	MRTSUE06402	1 year	2025-05-12	WZ-SR5
Signal Analyzer	Keysight	N9010B	MRTSUE06457	1 year	2025-05-08	WZ-SR5
Shielding Room	HUAMING	WZ-SR5	MRTSUE06442	N/A	N/A	WZ-SR5
TRILOG Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2025-04-17	WZ-AC2
EMI Test Receiver	Agilent	N9038A	MRTSUE06125	1 year	2025-05-08	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06171	1 year	2024-10-11	WZ-AC2
Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2025-05-06	WZ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11263	1 year	2024-11-07	WZ-AC2
Anechoic Chamber	RIKEN	WZ-AC2	MRTSUE06213	1 year	2025-04-18	WZ-AC2
Active Loop Antenna	Schwarzbeck	FMZB 1519-60 D	MRTSUE07076	1 year	2024-12-04	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2024-11-04	WZ-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE06640	1 year	2025-01-11	WZ-AC2
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2025-05-08	WZ-SR2
Shielding Room	MIX-BEP	WZ-SR2	MRTSUE06215	5 years	2026-12-20	WZ-SR2
Thermohygrometer	testo	608-H1	MRTSUE06404	1 year	2025-05-12	WZ-SR2
Four-Line V-Network	R&S	ENV432	MRTSUE06615	1 year	2024-09-27	WZ-SR2
EMI Test Receiver	R&S	ESR3	MRTSUE06909	1 year	2024-09-27	WZ-SR2

Software	Version	Function
EMI Software	V3.0.0	EMI Test Software
e3	230711	EMI Test Software
Controller_MF 7802	1.02	RE Antenna & Turntable
BenchVue Power Meter	2018.1	Power

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
The maximum measurement uncertainty is evaluated as: 9kHz~150kHz: 3.58dB 150kHz~30MHz: 3.20dB
Radiated Emission Measurement
The maximum measurement uncertainty is evaluated as: Coaxial: 9kHz~30MHz: 2.61dB Coplanar: 9kHz~30MHz: 2.62dB Horizontal: 30MHz~200MHz: 3.79dB 200MHz~1GHz: 3.91dB 1GHz~40GHz: 4.99dB Vertical: 30MHz~200MHz: 4.06dB 200MHz~1GHz: 5.21dB 1GHz~40GHz: 4.90dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 2.2dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 1.4dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 2.2dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 2.7%

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	6dB Bandwidth	Conducted	Pass
15.247(b)(3)	Output Power		Pass
15.247(e)	Power Spectral Density		Pass
15.247(d)	Band Edge / Out-of-Band Emissions		Pass
15.205 15.209	General Field Strength (Restricted Bands and Radiated Emission)	Radiated	Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Notes:

- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

6.2. 6dB Bandwidth Measurement

6.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


6.2.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.8

6.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

6.2.4. Test Setup



6.2.5. Test Result

Refer to Appendix A.2.

6.3. Output Power Measurement

6.3.1. Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.9.1.3

ANSI C63.10 - 2013 - Section 11.9.2.3.2

6.3.3. Test Setting


Method PKPM1 (Peak Power Measurement of Signals with DTS BW ≤ 50MHz)

Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The pulse sensor employs a VBW = 50MHz so this method was only used for signals whose DTS bandwidth was less than or equal to 50MHz.

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.3.

6.4. Power Spectral Density Measurement

6.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.


6.4.2. Test Procedure

ANSI C63.10-2013 Section 11.10.2

6.4.3. Test Setting

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 10kHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. Conducted Band Edge and Out-of-Band Emissions Measurement

6.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

6.5.2. Test Procedure

ANSI C63.10-2013 - Section 11.11

6.5.3. Test Setting

Reference level measurement


1. Set instrument center frequency to DTS channel center frequency
2. Set the span to ≥ 1.5 times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW $\geq 3 \times$ RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

6.5.4. Test Setup

Spectrum Analyzer



DC Block
&
Attenuator



6.5.5. Test Result

Refer to Appendix A.5.

6.6. Radiated Spurious Emission Measurement

6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.6.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.11 & 11.12

ANSI C63.10 - 2013 - Section 6.3 (General Requirements)

ANSI C63.10 - 2013 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - 2013 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - 2013 - Section 6.6 (Standard test method above 1GHz)

6.6.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; if the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10Hz
If the EUT duty cycle is $< 98\%$, set $VBW \geq 1/T$. T is the minimum transmission duration.
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

6.6.4. Test Setup


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.6.5. Test Result

Refer to Appendix A.6.

6.7. Radiated Restricted Band Edge Measurement

6.7.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.7.2. Test Procedure

ANSI C63.10-2013 Section 6.3 & 6.6 & 11.13

6.7.3. Test Setting


Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz.
If the EUT duty cycle is $< 98\%$, set VBW $\geq 1/T$. T is the minimum transmission duration.
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

6.7.4. Test Setup



6.7.5. Test Result

Refer to Appendix A.7.

6.8. AC Conducted Emissions Measurement


6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dB μ V)	AV (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

6.8.2. Test Setup



6.8.3. Test Result

Refer to Appendix A.8.

Appendix A - Test Result

A.1 Duty Cycle Test Result

Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2024-05-24		

Test Mode	Duty Cycle
BLE-1Mbps	86.69%
BLE-2Mbps	59.05%
Duty Cycle (T = Transmission Duration)	
BLE-1Mbps (T = 2.169ms)	BLE-2Mbps (T = 1.106ms)


Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	Δ	1	2.169 ms (Δ)	-5.07 dB			
2	F	1	6.494 ms	2.099 dBm			
3	Δ	1	2.502 ms (Δ)	2.24 dB			
4	F	1	6.494 ms	2.099 dBm			


Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	Δ	1	1.106 ms (Δ)	-1.339 dB			
2	F	1	2.842 ms	2.520 dBm			
3	Δ	1	1.873 ms (Δ)	-3.884 dB			
4	F	1	2.842 ms	2.520 dBm			

A.2 6dB Bandwidth Test Result

Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2024-05-24		

Test Mode	Data Rate	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
BLE	1Mbps	00	2402	0.6781	≥ 0.5
BLE	1Mbps	19	2440	0.6796	≥ 0.5
BLE	1Mbps	39	2480	0.6845	≥ 0.5
BLE	2Mbps	00	2402	1.0940	≥ 0.5
BLE	2Mbps	19	2440	1.0930	≥ 0.5
BLE	2Mbps	39	2480	1.1150	≥ 0.5





A.3 Output Power Test Result

Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2024-06-13		

Test Result of Peak Output Power

Test Mode	Data Rate	Channel No.	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Result
BLE	1Mbps	00	2402	10.41	≤ 30.00	Pass
BLE	1Mbps	19	2440	10.10	≤ 30.00	Pass
BLE	1Mbps	39	2480	10.47	≤ 30.00	Pass
BLE	2Mbps	00	2402	10.04	≤ 30.00	Pass
BLE	2Mbps	19	2440	10.14	≤ 30.00	Pass
BLE	2Mbps	39	2480	10.10	≤ 30.00	Pass


Test Result of Average Output Power (Reporting Only)

Test Mode	Data Rate	Channel No.	Frequency (MHz)	Average Power (dBm)	Limit (dBm)	Result
BLE	1Mbps	00	2402	9.84	≤ 30.00	Pass
BLE	1Mbps	19	2440	9.62	≤ 30.00	Pass
BLE	1Mbps	39	2480	9.85	≤ 30.00	Pass
BLE	2Mbps	00	2402	9.60	≤ 30.00	Pass
BLE	2Mbps	19	2440	9.71	≤ 30.00	Pass
BLE	2Mbps	39	2480	9.71	≤ 30.00	Pass

A.4 Power Spectral Density Test Result


Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2024-06-13		

Test Mode	Data Rate	Channel No.	Frequency (MHz)	PSD Result (dBm / 3kHz)	Limit (dBm / 3kHz)	Result
BLE	1Mbps	00	2402	-5.97	≤ 8.00	Pass
BLE	1Mbps	19	2440	-6.46	≤ 8.00	Pass
BLE	1Mbps	39	2480	-5.80	≤ 8.00	Pass
BLE	2Mbps	00	2402	-6.62	≤ 8.00	Pass
BLE	2Mbps	19	2440	-6.66	≤ 8.00	Pass
BLE	2Mbps	39	2480	-6.35	≤ 8.00	Pass



BLE-2Mbps PSD


Channel 00 (2402MHz)



Channel 19 (2440MHz)




Channel 39 (2480MHz)



A.5 Conducted Band Edge and Out-of-Band Emissions Test Result


Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2024-06-13 ~ 2024-08-16		

Test Mode	Data Rate / Mbps	Channel No.	Frequency (MHz)	Limit	Result
BLE	1	00	2402	20	Pass
BLE	1	19	2440	20	Pass
BLE	1	39	2480	20	Pass
BLE	2	00	2402	20	Pass
BLE	2	19	2440	20	Pass
BLE	2	39	2480	20	Pass




Channel 19 (2440MHz)

100kHz PSD Reference Level




Spurious Emission 30MHz ~ 25GHz




Channel 39 (2480MHz)


100kHz PSD Reference Level



High Band Edge




Spurious Emission 30MHz ~ 25GHz




BLE-2Mbps Out-of-Band Emissions

Channel 00 (2402MHz)


100kHz PSD Reference Level



Low Band Edge




Spurious Emission 30MHz ~ 25GHz




Channel 19 (2440MHz)

100kHz PSD Reference Level




Spurious Emission 30MHz ~ 25GHz




Channel 39 (2480MHz)


100kHz PSD Reference Level



High Band Edge



Spurious Emission 30MHz ~ 25GHz



A.6 Radiated Spurious Emission Test Result

Test Site	WZ-AC2	Test Engineer	Bob Zhang
Test Date	2024-06-14	Test Mode	BLE-1Mbps
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Test Channel	Frequency (MHz)	Reading Level (dB μ V)	Factor (dB/m)	Measure Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Polarization
00	3949.5	35.2	0.3	35.5	74.0	-38.5	Peak	Horizontal
	4799.5	47.7	3.7	51.4	74.0	-22.6	Peak	Horizontal
	4799.5	43.2	3.7	46.9	54.0	-7.1	Average	Horizontal
	11353.0	31.3	17.1	48.4	74.0	-25.6	Peak	Horizontal
	3592.5	39.8	-0.2	39.6	68.2	-28.6	Peak	Vertical
	4808.0	52.3	3.7	56.0	74.0	-18.0	Peak	Vertical
	4808.0	48.6	3.7	52.3	54.0	-1.7	Average	Vertical
	11557.0	30.8	17.4	48.2	74.0	-25.8	Peak	Vertical
19	3592.5	41.0	-0.2	40.8	68.2	-27.4	Peak	Horizontal
	4876.0	45.9	3.3	49.2	74.0	-24.8	Peak	Horizontal
	11565.5	30.7	17.4	48.1	74.0	-25.9	Peak	Horizontal
	4153.5	34.5	1.1	35.6	74.0	-38.4	Peak	Vertical
	4876.0	49.8	3.3	53.1	74.0	-20.9	Peak	Vertical
	4876.0	45.3	3.3	48.6	54.0	-5.4	Average	Vertical
	11650.5	31.0	17.6	48.6	74.0	-25.4	Peak	Vertical
39	4961.0	41.9	3.4	45.3	74.0	-28.7	Peak	Horizontal
	7443.0	35.4	11.4	46.8	74.0	-27.2	Peak	Horizontal
	11472.0	31.1	17.4	48.5	74.0	-25.5	Peak	Horizontal
	3830.5	37.7	0.2	37.9	74.0	-36.1	Peak	Vertical
	4961.0	47.1	3.4	50.5	74.0	-23.5	Peak	Vertical
	11548.5	31.5	17.3	48.8	74.0	-25.2	Peak	Vertical

Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Site	WZ-AC2	Test Engineer	Bob Zhang
Test Date	2024-06-14	Test Mode	BLE-2Mbps
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		


Test Channel	Frequency (MHz)	Reading Level (dBμV)	Factor (dB/m)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
00	4077.0	34.6	0.8	35.4	74.0	-38.6	Peak	Horizontal
	4799.5	47.0	3.7	50.7	74.0	-23.3	Peak	Horizontal
	11548.5	30.9	17.3	48.2	74.0	-25.8	Peak	Horizontal
	3949.5	36.0	0.3	36.3	74.0	-37.7	Peak	Vertical
	4799.5	51.0	3.7	54.7	74.0	-19.3	Peak	Vertical
	4799.5	46.2	3.7	49.9	54.0	-4.1	Average	Vertical
	11659.0	31.0	17.6	48.6	74.0	-25.4	Peak	Vertical
19	4102.5	36.3	1.0	37.3	74.0	-36.7	Peak	Horizontal
	4876.0	43.7	3.3	47.0	74.0	-27.0	Peak	Horizontal
	11531.5	30.2	17.3	47.5	74.0	-26.5	Peak	Horizontal
	4196.0	38.4	1.4	39.8	74.0	-34.2	Peak	Vertical
	4876.0	45.9	3.3	49.2	74.0	-24.8	Peak	Vertical
	11081.0	30.7	16.7	47.4	74.0	-26.6	Peak	Vertical
39	3847.5	37.2	0.2	37.4	74.0	-36.6	Peak	Horizontal
	4961.0	41.9	3.4	45.3	74.0	-28.7	Peak	Horizontal
	10987.5	31.2	16.4	47.6	74.0	-26.4	Peak	Horizontal
	3847.5	34.8	0.2	35.0	74.0	-39.0	Peak	Vertical
	4961.0	46.3	3.4	49.7	74.0	-24.3	Peak	Vertical
	11633.5	30.5	17.4	47.9	74.0	-26.1	Peak	Vertical

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

The Result of Radiated Emission below 1GHz:

Site	WZ-AC2	Test Date	2024-08-07
Test Engineer	Bob Zhang	Temp./Humidity	25.4°C /61.0%
Factor	VULB 9162_30-7000MHz	Polarity	Horizontal
EUT	OmniAccess Stellar (OAW-AP1511)	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 1Mbps at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		47.169	2.60	20.42	23.02	-16.98	40.00	QP
2		227.880	3.40	19.42	22.82	-23.18	46.00	QP
3		391.422	1.10	23.54	24.64	-21.36	46.00	QP
4		521.208	2.40	25.58	27.98	-18.02	46.00	QP
5		624.513	1.20	27.69	28.89	-17.11	46.00	QP
6	*	932.682	1.10	32.11	33.21	-12.79	46.00	QP

Notes:

1. " *", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WZ-AC2	Test Date	2024-08-07
Test Engineer	Bob Zhang	Temp./Humidity	25.4°C /61.0%
Factor	VULB 9162_30-7000MHz	Polarity	Vertical
EUT	OmniAccess Stellar (OAW-AP1511)	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 1Mbps at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dB μ V)	C.F (dB/m)	Measurement (dB μ V/m)	Margin (dB)	Limit (dB μ V/m)	Detector
1		50.370	2.60	20.49	23.09	-16.91	40.00	QP
2		152.414	3.50	15.45	18.95	-24.55	43.50	QP
3		229.917	3.80	19.51	23.31	-22.69	46.00	QP
4		342.243	2.10	22.68	24.78	-21.22	46.00	QP
5		500.062	2.89	25.76	28.65	-17.35	46.00	QP
6		856.925	1.20	31.79	32.99	-13.01	46.00	QP
7	*	856.925	2.10	31.79	33.89	-12.11	46.00	QP

Notes:

1. " *", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dB μ V/m) = Reading (dB μ V) + C.F (dB/m).

A.7 Radiated Restricted Band Edge Test Result

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Horizontal
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 1Mbps at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2345.815	56.669	23.890	-17.331	74.000	32.778	PK
2		2390.000	52.565	20.039	-21.435	74.000	32.527	PK
3		2401.675	106.592	74.103	N/A	N/A	32.489	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Horizontal
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 1Mbps at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2390.000	38.902	6.376	-15.098	54.000	32.527	AV
2		2401.960	105.681	73.193	N/A	N/A	32.488	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Vertical
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 1Mbps at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2341.350	57.253	24.478	-16.747	74.000	32.775	PK
2		2390.000	54.019	21.493	-19.981	74.000	32.527	PK
3		2401.675	102.157	69.668	N/A	N/A	32.489	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Vertical
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 1Mbps at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2333.702	39.504	6.734	-14.496	54.000	32.770	AV
2		2390.000	38.199	5.673	-15.801	54.000	32.527	AV
3		2401.913	101.536	69.047	N/A	N/A	32.488	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Horizontal
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 1Mbps at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2479.727	105.285	72.901	N/A	N/A	32.384	PK
2		2483.500	59.967	27.585	-14.033	74.000	32.382	PK
3	*	2483.610	62.210	29.828	-11.790	74.000	32.382	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Horizontal
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 1Mbps at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2479.947	104.360	71.976	N/A	N/A	32.384	AV
2	*	2483.500	46.221	13.839	-7.779	54.000	32.382	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Vertical
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 1Mbps at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2480.244	102.309	69.925	N/A	N/A	32.384	PK
2		2483.500	54.965	22.583	-19.035	74.000	32.382	PK
3	*	2484.996	58.229	25.847	-15.771	74.000	32.382	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Vertical
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 1Mbps at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2479.980	101.219	68.835	N/A	N/A	32.384	AV
2	*	2483.500	43.100	10.718	-10.900	54.000	32.382	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Horizontal
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 2Mbps at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1	*	2354.270	58.254	25.515	-15.746	74.000	32.740	PK
2		2390.000	53.084	20.558	-20.916	74.000	32.527	PK
3		2401.960	106.594	74.106	N/A	N/A	32.488	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Horizontal
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 2Mbps at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2363.722	40.760	8.090	-13.240	54.000	32.670	AV
2		2390.000	39.524	6.998	-14.476	54.000	32.527	AV
3		2402.008	104.389	71.901	N/A	N/A	32.488	AV
4	*	2483.500	56.741	24.359	2.741	54.000	32.382	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Vertical
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 2Mbps at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1	*	2353.510	56.785	24.041	-17.215	74.000	32.744	PK
2		2390.000	55.286	22.760	-18.714	74.000	32.527	PK
3		2401.485	102.256	69.766	N/A	N/A	32.490	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Vertical
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 2Mbps at 2402MHz	




No	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1	*	2374.363	40.471	7.872	-13.529	54.000	32.599	AV
2		2390.000	39.859	7.333	-14.141	54.000	32.527	AV
3		2401.913	99.727	67.238	N/A	N/A	32.488	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Horizontal
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 2Mbps at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2479.463	105.275	72.891	N/A	N/A	32.385	PK
2		2483.500	61.794	29.412	-12.206	74.000	32.382	PK
3	*	2483.720	63.398	31.016	-10.602	74.000	32.382	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Horizontal
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 2Mbps at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2480.057	102.823	70.439	N/A	N/A	32.384	AV
2	*	2483.500	49.335	16.953	-4.665	54.000	32.382	AV

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Vertical
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 2Mbps at 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2480.442	96.554	64.170	N/A	N/A	32.384	PK
2		2483.500	55.312	22.930	-18.688	74.000	32.382	PK
3	*	2484.655	57.908	25.526	-16.092	74.000	32.381	PK

Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: WZ-AC2	Test Date: 2024-06-14
Limit: FCC_2.4G_RE(3m)	Engineer: Bob Zhang
Probe: BBHA9120D_1457_1-18GHz	Polarity: Vertical
EUT: OmniAccess Stellar (OAW-AP1511)	Power: AC 120V/60Hz
Test Mode: Transmit by BLE 2Mbps at 2480MHz	



No	Mark	Frequency (MHz)	Measure Level (dB μ V/m)	Reading Level (dB μ V)	Margin (dB)	Limit (dB μ V/m)	Factor (dB/m)	Type
1		2479.936	99.983	67.599	N/A	N/A	32.384	AV
2		2483.500	46.465	14.083	-7.535	54.000	32.382	AV
3	*	2483.522	46.676	14.294	-7.324	54.000	32.382	AV


Note 1: " * ", means this data is the worst emission level.

Note 2: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB/m).

Note 3: Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

A.8 AC Conducted Emissions Test Result

Site	WZ-SR2	Test Date	2024-08-09
Test Engineer	Linda Wei	Temp./Humidity	24.3°C/52.6%
Factor	ENV216_101683_L1_Filter Off_C	Polarity	Line
EUT	OmniAccess Stellar (OAW-AP1511)	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 1Mbps at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB)	Measurement (dBμV)	Margin (dB)	Limit (dBμV)	Detector
1		0.158	29.70	9.82	39.52	-16.05	55.57	Average
2	*	0.158	43.30	9.82	53.12	-12.45	65.57	QP
3		0.186	24.00	9.82	33.82	-20.40	54.21	Average
4		0.186	38.60	9.82	48.42	-15.80	64.21	QP
5		0.375	24.50	9.87	34.37	-14.02	48.39	Average
6		0.375	28.50	9.87	38.37	-20.02	58.39	QP
7		1.220	13.10	10.12	23.22	-22.78	46.00	Average
8		1.220	18.20	10.12	28.32	-27.68	56.00	QP
9		2.590	12.60	10.15	22.75	-23.25	46.00	Average
10		2.590	18.10	10.15	28.25	-27.75	56.00	QP
11		9.140	12.40	10.33	22.73	-27.27	50.00	Average
12		9.140	18.10	10.33	28.43	-31.57	60.00	QP

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB) = LISN Factor (dB) + Cable Loss (dB).
3. Measurement (dBμV) = Reading (dBμV) + C.F (dB).

Site	WZ-SR2	Test Date	2024-08-09
Test Engineer	Linda Wei	Temp./Humidity	24.3°C/52.6%
Factor	ENV216_101683_N_Filter Off_C	Polarity	Neutral
EUT	OmniAccess Stellar (OAW-AP1511)	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 1Mbps at 2402MHz		



No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB)	Measurement (dBμV)	Margin (dB)	Limit (dBμV)	Detector
1		0.160	29.20	10.12	39.32	-16.14	55.46	Average
2	*	0.160	43.30	10.12	53.42	-12.04	65.46	QP
3		0.187	23.20	10.11	33.31	-20.86	54.17	Average
4		0.187	38.30	10.11	48.41	-15.76	64.17	QP
5		0.374	24.60	10.13	34.73	-13.68	48.41	Average
6		0.374	28.90	10.13	39.03	-19.38	58.41	QP
7		1.158	9.20	10.38	19.58	-26.42	46.00	Average
8		1.158	12.90	10.38	23.28	-32.72	56.00	QP
9		3.510	13.40	10.42	23.82	-22.18	46.00	Average
10		3.510	18.30	10.42	28.72	-27.28	56.00	QP
11		8.290	13.50	10.56	24.06	-25.94	50.00	Average
12		8.290	19.40	10.56	29.96	-30.04	60.00	QP

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB) = LISN Factor (dB) + Cable Loss (dB).
3. Measurement (dBμV) = Reading (dBμV) + C.F (dB).

Appendix B - Test Setup Photograph

Refer to "2404RSU054-UT" file.

Appendix C - EUT Photograph

Refer to "2404RSU054-UE" file.

_____ The End _____