

FCC Test Report

Report No: WD-RF-R-240116-D0

Product Name : Furbo 3.5 Camera
Model Name : Furbo 3.5 Dog
Series Model Name : Furbo 3.5 Cat
FCC ID : 2AIBVTFFBV5
Applicant : Tomofun Co., Ltd.
Received Date : Mar. 19, 2024
Tested Date : Mar. 17, 2024 ~ May 31, 2024
Applicable Standard : 47 CFR FCC Part 15, Subpart C (Section 15.31)
47 CFR FCC Part 2, Subpart J (Section 2.947(f))
ANSI C63.10 : 2013



Wendell Industrial Co., Ltd
Wendell EMC & RF Laboratory

Caution:

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment.

Please note that the measurement uncertainty are provided for informational purpose only and are not used in determining the Pass/Fail results.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of Wendell Industrial Co., Ltd..

Test Report

Issued Date: June 03, 2024

Project No.: 24Q031902


Product Name	Furbo 3.5 Camera
Trade Name	Furbo
Model Name	Furbo 3.5 Dog
Series Model Name	Furbo 3.5 Cat
FCC ID	2AIBVTFFBV5
Applicant	Tomofun Co., Ltd.
Manufacturer 1	Primax Electronics Ltd.
Manufacturer 2	Primax Electronics (Thailand) Co., Ltd
EUT Rated Voltage	DC 5V2A
EUT Test Voltage	AC 110V / 60Hz 、DC 5V
EUT Supports Radios Application	WLAN 802.11b/g 、WLAN 802.11n (HT20/HT40) Bluetooth LE
Applicable Standard	47 CFR FCC Part 15, Subpart C (Section 15.31) 47 CFR FCC Part 2, Subpart J (Section 2.947(f)) ANSI C63.10 : 2013
Test Result	Complied

Documented :




(Specialist / Emma Lu)

Technical Engineer :



(Section Manager / Jack Chang)

Approved :



(Project Manager / Gary Wu)

Table of Contents

Document Revision History	4
Summary of Test Result	5
1 Generation Information	6
1.1 Applicant	6
1.2 Manufacturer	6
1.3 Description of Equipment under Test	6
1.4 Test Mode Applicability	8
1.5 Configuration of Tested System	9
1.6 EUT Exercise Software	9
1.7 Tested System Details	10
1.8 Test Facility	11
1.9 Measurement Uncertainty	12
1.10 List of Test Equipment	13
2 Test Result	16
2.1 Spurious Emission Measurement	16
2.1.1 Limit	16
2.1.2 Test Setup	16
2.1.3 Test Procedure	18
2.1.4 Test Result of Radiated Spurious Emission Measurement	19
2.2 AC Conducted Emissions Measurement	24
2.2.1 Limit	24
2.2.2 Test Setup	24
2.2.3 Test Procedure	25
2.2.4 Test Result	26

Document Revision History

Report No.	Issue date	Description
WD-RF-R-240116-D0	June 03, 2024	Initial report

Summary of Test Result

Ref. Std. Clause	Test Items	Result
15.247(d)	Radiated Spurious Emission	Pass
15.207	AC Conducted Emission	Pass

1 Generation Information

1.1 Applicant

Tomofun Co., Ltd.
4F, No.178, Sec. 3, Minquan E. Rd., SongShan Dist., Taipei City, Taiwan

1.2 Manufacturer

Primax Electronics Ltd.
No. 669, Ruiguang Rd., Neihu Dist., Taipei City 114, Taiwan

Primax Electronics (Thailand) Co., Ltd
888/8 Moo.7, Klongkiew Sub-district, Banbueng District, Chonburi, Thailand

1.3 Description of Equipment under Test

Product Name	Furbo 3.5 Camera
Model No.	Furbo 3.5 Dog
Series Model No.	Furbo 3.5 Cat
Model Difference	Refer to the table “Series Difference List”
FCC ID	2AIBVTFFBV5
Frequency Range	802.11b/g/n-20MHz: 2412~2462MHz 802.11n-40MHz: 2422~2452MHz Bluetooth: 2402-2480MHz
Data Rate	802.11b: 1-11Mbps, 802.11g: 6-54Mbps, 802.11n: up to 150Mbps
Type of Modulation	802.11b:DSSS (DBPSK, DQPSK, CCK) 802.11g/n:OFDM (BPSK, QPSK, 16QAM, 64QAM) Bluetooth: GFSK(1Mbps)
Antenna Information	Refer to the table “Antenna List”
EUT Supports Radios Application	WLAN 802.11b/g WLAN 802.11n (HT20/HT40) Bluetooth LE
EUT Rated Voltage	DC 5V2A
EUT Test Voltage	AC 110V / 60Hz 、DC 5V

Series Difference List

Model Difference	Main Model Furbo 3.5 Dog	Series Model Furbo 3.5 Cat
Circuit design, printed circuit boards	O	O
Antenna specifications, RF modules	O	O
Use components, wires, and materials	O	O
Use component location, routing, and structure	O	O
Product appearance	White	1. black 2. Add a holder for cat teaser
Other differences	--	Accessories include cat teaser

Note: The laboratory determines based on series differences. The differences are only in appearance color and shape, so there is no need to evaluate the output power/electric field strength +/-2dB requirements. The Furbo 2.5 Dog model is used as the main test.

Antenna List

No.	Manufacturer	Model No.	Antenna Type	Peak Gain
1	INPAQ TECHNOLOGY CO., LTD	RFFPA272206IMAB301	FPC antenna	2.71 dBi for 2.4GHz

1.4 Test Mode Applicability


1. These tests were performed on equipment samples to demonstrate compliance with the 15.31(k) chapter simultaneous launch requirements.
2. Select the combination of the highest power transmission mode, only the worst case is shown in the report.
3. The worst case was found when positioned on X axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report.

Test Mode


Mode 1: Bluetooth LE + WIFI 2.4GHz

1.5 Configuration of Tested System

Radiation



AC Conduction



Test Table

Test Table

1.6 EUT Exercise Software

1. Setup the EUT as shown in Section 1.6
2. Configure the test mode, the test channel, and the data rate.
3. Press “OK” to start the continuous transmit.
4. Verify that the EUT works properly.

1.7 Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

No.	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook PC	acer	N16Q1	NXVD4TA023742254707600	N/A
2	Fixture	FTDI	FT2232RL	N/A	N/A
3	Adapter	DEEVAN	DSA-10PF06-05FUS 052200	N/A	N/A

No.	Signal Cable Type	Signal cable Description
A	USB Cable	Non-shielded, Non-Core, 1.8m
B	Data Cable	Non-shielded, Non-Core, 0.95m
C	USB Cable	Shielded, Non-Core, 1.0m

1.8 Test Facility

Items	Required (IEC 60068-1)
Temperature (°C)	15-35
Humidity (% RH)	25-75
Barometric pressure (mbar)	860-1060

Description: Accredited by TAF
Accredited Number: 2965

Issued by: Wendell Industrial Co., Ltd

Company Address: 6F/6F-1, No.188, Baoqiao Rd., Xindian Dist.,
New Taipei City 23145, Taiwan R.O.C

Test Lab: Wendell EMC & RF Laboratory

Lab Address: 5F-1, No.188, Baoqiao Rd., Xindian Dist.,
New Taipei City 23145, Taiwan R.O.C

Test Location: No. 119, Wugong 3rd Rd., Wugu Dist.,
New Taipei City 248, Taiwan (R.O.C.)

Designation Number: TW0025

Test Firm Registration Number: 665221

1.9 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence (level based on a coverage factor K=2)

Measurement Project	Condition	Expended Uncertainty
AC Conducted Emission	0.150 ~ 30 MHz	± 2.64 dB
Radiated Emission	0.009 ~ 30 MHz	± 3.7 dB
	30 ~ 1000 MHz	± 3.9 dB
	1000 ~ 18000 MHz	± 4.5 dB
	18000 ~ 40000 MHz	± 4.3 dB
RF Power, Conducted	Conducted Measuring	± 0.75 dB
Occupied Bandwidth	Conducted Measuring	± 2.4 %
Power Density	Conducted Measuring	± 1.2 dB
Duty Cycle and Dwell Time	Conducted Measuring	± 0.9 %
Conducted Unwanted Emission Strength	Conducted Measuring	± 1.4 dB
DC Power Supply	--	± 0.062 ppm
Temperature	--	± 2.0 %
Humidity	--	± 0.55 °C

Note: Please note that the measurement uncertainty are provided for informational purpose only and are not used in determining the Pass/Fail results.

1.10 List of Test Equipment

For AC Conduction measurements / Conducted Room

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
✓	EMI Test Receiver	R&S	ESR3	102309	2023/06/19	2024/06/18
✓	2-Line V-Network LISN	R&S	ENV216	101185	2023/06/16	2024/06/15
✓	LISN	SCHWARZBECK	NSLK 8127RC	05028	2023/06/16	2024/06/15
✓	Transient Limiter	EM Electronics Corporation	EM-7600	857	2023/06/17	2024/06/16
✓	50ohm Cable	EMCI	EMCCFD300-BM-BM-5000	170612	2023/06/17	2024/06/16
✓	50 ohm terminal impedance	HUBER+SUHNER	50 ohm terminal impedance	CT-1-109-1	2023/06/16	2024/06/15

Remark:

1. All equipments are calibrated every one year.
2. The test instruments marked with “✓” are used to measure the final test results.
3. Test Software version: FARAD EZ-EMC Ver.EMC-CON 3A1

For Radiated measurements / 9x6x6 Semi Anechoic Room

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
✓	EMI Receiver	Keysight	N9038A	MY51210173	2023/08/18	2024/08/17
✓	Spectrum Analyzer	Keysight	N9010A	MY52220228	2023/08/18	2024/08/17
✓	Active Loop Antenna	Schwarzbeck	FMZB 1513-60B	00033	2024/05/02	2025/05/01
✓	TRILOG super broad Antenna	Schwarzbeck	VULB 9168	VULB 9168-700 & 20E03	2023/07/31	2024/07/30
✓	Horn Antenna	Schwarzbeck	BBHA 9120D	01767	2023/08/17	2024/08/16
✓	Horn Antenna	Schwarzbeck	BBHA 9170	703	2023/08/21	2024/08/20
✓	Pre-Amplifier	EMEC	EMC330	060774	2023/08/22	2024/08/21
✓	Pre-Amplifier	EMEC	EM01G18G	060648	2023/08/22	2024/08/21
✓	Pre-Amplifier	JPT	JPA0118-55-303K	1910001800055003	2023/08/22	2024/08/21
✓	Pre-Amplifier	EMCI	EMC184045SE	980515	2023/08/22	2024/08/21
✓	Cable	EMEC	EM-CB400	105060103	2023/08/22	2024/08/21
✓	Cable	EMEC	EM-CB400	105060102	2023/08/22	2024/08/21
✓	Cable	EMEC	EM-CB400	105060101	2023/08/22	2024/08/21
✓	RF Cable	HUBER+SUHNER	SF102	MY2752/2	2023/08/22	2024/08/21
✓	RF Cable	MVE	280280.LL266.1200	B60028C	2023/08/22	2024/08/21
✓	RF Cable	EMCI	EMC102-KM-KM-600	190646	2023/08/22	2024/08/21
✓	RF Cable	MVE	140140.LL404.700	B90014C	2023/08/22	2024/08/21
✓	RF Cable	MVE	140140.LL404.300	B90006C	2023/08/22	2024/08/21
✓	RF Filter	EMEC	BRF-2400-2500	002	2022/08/17	2024/08/16
✓	RF Filter	EMEC	BRF-5150-5350	104	2022/08/17	2024/08/16
✓	RF Filter	EMEC	BRF-5470-5725	092	2022/08/17	2024/08/16
✓	RF Filter	EMEC	BRF-5725-5875	091	2022/08/17	2024/08/16
✓	RF Filter	EMEC	HPF-2800	002	2022/08/17	2024/08/16
✓	RF Filter	EMEC	HPF-5850	059	2022/08/17	2024/08/16
	SMA Notch Filter	MVE	MFN-902.928.S1	190604001	2022/08/17	2024/08/16

Remark:

1. The equipments are calibrated every one year.
2. The Filter calibrated every two year.
3. The test instruments marked with “✓” are used to measure the final test results.
4. Test Software version: FARAD EZ-EMC Ver.WD-03A1-1

2 Test Result

2.1 Spurious Emission Measurement

2.1.1 Limit


Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 – 0.490	$2400/F(\text{kHz})$	300
0.490 – 1.705	$24000/F(\text{kHz})$	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Remarks:


1. RF Voltage (dBuV) = $20 \log \text{RF Voltage}(\mu\text{V})$
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system

2.1.2 Test Setup


Below 30MHz



30MHz~1GHz



Above 1GHz



2.1.3 Test Procedure

The EUT was setup according to ANSI C63.10, 2013 and tested according test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

For Radiated emission below 30MHz

- (1) The EUT was placed on the top of a rotating table 0.8 meters above the ground in a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- (3) Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- (4) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- (5) The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

For Radiated emission Above 30MHz


- (1) The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for the test. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The EUT was set 3 meters away from the interference-receiving antenna, the height of the antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength.
- (3) Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- (4) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- (5) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- (6) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets the average limit, measurement with the average detector is unnecessary.

2.1.4 Test Result of Radiated Spurious Emission Measurement

- (1) The radiation measurement frequency is 9kHz ~ 30MHz. The interference value of this frequency range is less than the limit value of 20 dB. It is considered that the background noise value is not recorded.
- (2) The following table shows the radiation measurement frequency from 30MHz to 26.5G/40GHz, pre-scanning in the X, Y and Z axes. The worst case (X-axis) is documented in this report.

Above 1GHz Data

Test Mode :	Mode 1: Bluetooth LE + WIFI 2.4GHz	Test Date :	2024/05/11
Test Voltage :	AC 120V/60Hz	Temperature :	22.6 °C
Polarization :	Horizontal	Relative Humidity :	52 %




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.000	66.09	-19.00	47.09	74.00	-26.91	peak
2	7311.000	62.49	-12.53	49.96	74.00	-24.04	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Mode 1: Bluetooth LE + WIFI 2.4GHz	Test Date :	2024/05/11
Test Voltage :	AC 120V/60Hz	Temperature :	22.6 °C
Polarization :	Vertical	Relative Humidity :	52 %




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.000	65.61	-19.00	46.61	74.00	-27.39	peak
2	7311.000	60.79	-12.53	48.26	74.00	-25.74	peak

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Below 1GHz Data

Test Mode :	Mode 1: Bluetooth LE + WIFI 2.4GHz	Test Date :	2024/05/10
Test Voltage :	AC 120V/60Hz	Temperature :	22.6 °C
Polarization :	Horizontal	Relative Humidity :	52 %




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	167.7400	43.85	-11.28	32.57	43.50	-10.93	QP
2	263.7700	44.67	-11.49	33.18	46.00	-12.82	QP
3	314.2100	44.85	-9.77	35.08	46.00	-10.92	QP
4	340.4000	42.92	-8.99	33.93	46.00	-12.07	QP
5	515.9700	36.64	-4.28	32.36	46.00	-13.64	QP
6	904.9400	32.64	3.37	36.01	46.00	-9.99	QP

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit

Test Mode :	Mode 1: Bluetooth LE + WIFI 2.4GHz	Test Date :	2024/05/10
Test Voltage :	AC 120V/60Hz	Temperature :	22.6 °C
Polarization :	Vertical	Relative Humidity :	52 %



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	294.8100	40.73	-10.37	30.36	46.00	-15.64	QP
2	357.8600	42.73	-8.83	33.90	46.00	-12.10	QP
3	406.3600	41.38	-6.97	34.41	46.00	-11.59	QP
4	532.4600	37.65	-4.00	33.65	46.00	-12.35	QP
5	795.3300	31.22	1.66	32.88	46.00	-13.12	QP
6	904.9400	31.49	3.37	34.86	46.00	-11.14	QP

Remark :

1. Correction Factor = Antenna factor + Cable loss – Amplifier gain
2. Result Value = Reading Level + Correct Factor
3. Margin Level = Result Value – Limit Value
4. The other emission levels were very low against the limit


2.2 AC Conducted Emissions Measurement

2.2.1 Limit

Frequency (MHz)	FCC Part 15 Subpart C Paragraph 15.207 (dBμV) Limit	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.50 to 5.0	56	46
5.0 to 30.0	60	50

*Decreases with the logarithm of the frequency

2.2.2 Test Setup




2.2.3 Test Procedure

1. The EUT was placed 0.8 meter height wooden table from the horizontal ground plane with EUT being connected to power source through a line impedance stabilization network (LISN). The LISN at least be 80 cm from nearest chassis of EUT.
2. The line impedance stabilization network (LISN) provides 50 ohm/50uH of coupling impedance for the measuring instrument. All other support equipments powered from additional LISN(s).
3. Interrelating cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle. All I/O cables were positioned to simulate typical usage.
4. All I/O cables that are not connected to a peripheral shall be bundle in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
5. The EMI test receiver connected to LISN powering the EUT. The actual test configuration, please refer to EUT test photos.
6. The receiver scanned from 150kHz to 30MHz for emissions in each of test modes. Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz. A scan was taken on both power lines, Line and Neutral, recording at least six highest emissions.
7. The EUT and cable configuration of the above highest emission levels were recorded. The test data of the worst case was recorded.

2.2.4 Test Result

Test Voltage :	120Vac, 60Hz	Frequency Range:	0.15-30 MHz
Test Mode :	Mode 1: Bluetooth LE + WIFI 2.4GHz	6dB Bandwidth :	9 kHz
Test Date :	2024/04/25	Phase :	L
Temperature :	21.7°C	Humidity :	48 %




No.	Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measurement (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1521	24.93	9.84	34.77	65.88	-31.11	QP
2	0.1521	9.58	9.84	19.42	55.88	-36.46	AVG
3	0.1726	21.99	9.84	31.83	64.83	-33	QP
4	0.1726	6.25	9.84	16.09	54.83	-38.74	AVG
5	0.2076	17.38	9.83	27.21	63.3	-36.09	QP
6	0.2076	3.46	9.83	13.29	53.3	-40.01	AVG
7	0.6156	24.58	9.84	34.42	56	-21.58	QP
8	0.6156	8.82	9.84	18.66	46	-27.34	AVG
9	1.2383	18.61	9.87	28.48	56	-27.52	QP
10	1.2383	3.13	9.87	13	46	-33	AVG
11	24.0122	17.43	10.43	27.86	60	-32.14	QP
12	24.0122	6.98	10.43	17.41	50	-32.59	AVG

Remark:

1. QP = Quasi Peak, AVG = Average
2. Correction Factor = Insertion loss of LISN + Cable loss
3. Measurement Value = Reading Level + Correct Factor
4. Margin Level = Measurement Value – Limit Value

Test Voltage :	120Vac, 60Hz	Frequency Range:	0.15-30 MHz
Test Mode :	Mode 1: Bluetooth LE + WIFI 2.4GHz	6dB Bandwidth :	9 kHz
Test Date :	2024/04/25	Phase :	N
Temperature :	21.7°C	Humidity :	48 %



No.	Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measurement (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1522	25.4	9.84	35.24	65.88	-30.64	QP
2	0.1522	13.97	9.84	23.81	55.88	-32.07	AVG
3	0.1545	24.88	9.84	34.72	65.75	-31.03	QP
4	0.1545	12.82	9.84	22.66	55.75	-33.09	AVG
5	0.2112	19.27	9.83	29.1	63.16	-34.06	QP
6	0.2112	12.96	9.83	22.79	53.16	-30.37	AVG
7	0.4632	18.69	9.84	28.53	56.63	-28.1	QP
8	0.4632	15.56	9.84	25.4	46.63	-21.23	AVG
9	0.6221	29.64	9.84	39.48	56	-16.52	QP
10	0.6221	24.77	9.84	34.61	46	-11.39	AVG
11	23.9938	18.84	10.43	29.27	60	-30.73	QP
12	23.9938	6.69	10.43	17.12	50	-32.88	AVG

Remark:

1. QP = Quasi Peak, AVG = Average
2. Correction Factor = Insertion loss of LISN + Cable loss
3. Measurement Value = Reading Level + Correct Factor
4. Margin Level = Measurement Value – Limit Value

--- END ---