



**RF Exposure Analysis – SAR Test Exemption – XP9200, XP9201, XP9202, XP9203, XP9204, XP9205, XP9206, XP9207, XP9208, XP9209, XP9210, XP9212, XP9213, XP9214, XP9215 and XP9216**

**FCC ID: 2AICSP92**

The XP9200, XP9201, XP9202, XP9203, XP9204, XP9205, XP9206, XP9207, XP9208, XP9209, XP9210, XP9212, XP9213, XP9214, XP9215 and XP9216 contain a Bluetooth LE transceiver that operates in the 2402 -2480 MHz frequency band.

**The following FCC Rule Parts are applicable:**

Part 2.1093 – Radiofrequency radiation exposure evaluation: portable devices (i)

Part 1.1307(b)(3)(i)(C) - MPE test exemption (ii)

Part 1.1307(b)(3)(i)(B) - SAR test exemption (iii)

**For FCC ID: 2AICSP92**

Transmitter frequency range = 2402 MHz to 2480 MHz

Maximum Conducted Power = 1.0 dBm (including tune-up tolerance)

Antenna gain: 2.5 dBi

EIRP = 1.0 dBm + 2.5 dBi = 3.5 dBm

ERP = EIRP-2.15 dBm = 1.35 dBm (**1.36 mW**)

Minimum separation distance (d) = 5 mm (0.005 m)

**Evaluation**

From Part 2.1093(c)(1). RF exemption applies if the maximum transmitted power is less than the maximum of the following three criteria:

- i) No more than 1 mw Blanket exemption.  $P_{TH} = 0.001 W$  – (**not met**)
- ii) determination of exemption under the MPE-based §1.1307(b)(3)(i)(C), if i) not met
- iii) determination of exemption under the SAR-based §1.1307(b)(3)(i)(B) if both i) and ii) are not met;

Determination of threshold power ( $P_{TH}$ ) under the MPE-based §1.1307(b)(3)(i)(C) :

This is only applicable at a separation distance greater than  $\lambda/2\pi$

**For FCC ID: 2AICSP92**

2402 MHz operation -  $\lambda/2\pi = 0.02$  m

Separation distance equals 0.005 m therefore this clause is not applicable.

Determination of threshold power ( $P_{th}$ ) under §1.1307(b)(3)(i)(B) as the transmitter power threshold for SAR test exemption:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

### For 2402 MHz operation:

For SAR test exemption (iii):

§1.1307(b)(3)(B) :

$$ERP_{20 \text{ cm}} = 3060 \text{ mW}$$

$$\begin{aligned} x &= -\log_{10} (60 / (3060 \sqrt{2.402})) \\ &= -\log_{10} (0.0127) = 1.899 \end{aligned}$$


$$\begin{aligned} \text{Threshold Power } P_{th} &= ERP_{20 \text{ cm}} (d/20 \text{ cm})^x \\ &= 3060 (0.5/20)^{1.899} \\ &= 2.79 \text{ mW (4.4 dBm)} \end{aligned}$$

( $P_{th}$  = device transmitter power ERP or conducted time averaged, whichever is greater)

FCC ID: 2AICSXP92 maximum ERP is 1.35 dBm (**1.36 mW**)

**Conclusion:**

The maximum ERP is below the applicable 2.79 mW threshold for operation at 2402 MHz and, therefore, RF Exposure Evaluation is not required for FCC ID: 2AICSXP92, as it is exempt from evaluation in accordance with §1.1307(b)(3).

A handwritten signature in blue ink, appearing to read 'Klaas Kloosterman', is written over a solid black horizontal line.

Date: 10-10-2024  
Name: Klaas Kloosterman  
Job Title: Safety & Compliance Engineer  
Company Name: Philips Consumer Lifestyle B.V.