

FCC RF Exposure

EUT Description: 4 INCH LED FLAME LIGHT SPEAKER

Model No.: BX214

FCC ID: **2AIDL-BX214**

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max power of channel, including tune - up tolerance, mW}}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1 - g SAR and ≤ 7.5 for 10 - g extremity SAR,

Where:

$$\text{Result} = P/D^2 \cdot \sqrt{F}$$

F= the RF channel transmit frequency in GHz

P=Maximum turn - up power in mw

D=Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

| Frequency (MHz) | Output power (dBm) | Tune Up Power (dBm) | Max Tune Up power dBm/mW | Min test separation distance mm | Result | Limit (mW/cm ²) | SAR Test Exclusion |
|-----------------|--------------------|---------------------|--------------------------|---------------------------------|--------|-----------------------------|--------------------|
| 2480 | 1.93 | 1 ± 1 | 2/1.585 | 5 | 0.499 | 3.0 | Pass |

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2306052287-E**, antenna gain= -0.58dBi

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.499 which is ≤ 3 , RF Exposure testing is not required.

Note: Exclusion Thresholds Results= $\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})}$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance=5mm