



# TEST REPORT

No.I23N00229-MPE

For

**Guilin Zhishen Information Technology Co., Ltd.**

**CRANE-M 3S**

**Model Name: CR127**

**With**

**Hardware Version: V1.0**

**Software Version: V1.54**

**FCC ID: 2AIHFZYCR127**

**Issued Date: 2023-04-18**

**Designation Number: CN1210**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

**Test Laboratory:**

**SAICT, Shenzhen Academy of Information and Communications Technology**

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518000.

Tel:+86(0)755-33322000, Fax:+86(0)755-33322001

Email: yewu@caict.ac.cn. www.saict.ac.cn



## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I23N00229-MPE	Rev.0	1st edition	2023-04-18



## CONTENTS

<b>1. SUMMARY OF TEST REPORT</b> .....	<b>4</b>
1.1. TEST ITEMS .....	4
1.2. TEST STANDARDS .....	4
1.3. TEST RESULT .....	4
1.4. TESTING LOCATION .....	4
1.5. PROJECT DATA .....	4
1.6. SIGNATURE .....	4
<b>2. CLIENT INFORMATION</b> .....	<b>5</b>
2.1. APPLICANT INFORMATION .....	5
2.2. MANUFACTURER INFORMATION .....	5
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)</b> .....	<b>5</b>
3.1. ABOUT EUT .....	5
<b>4. TEST METHODOLOGY</b> .....	<b>5</b>
<b>5. RESULT</b> .....	<b>6</b>

## 1. Summary of Test Report

### 1.1. Test Items

Description: CRANE-M 3S  
Model Name: CR127  
Applicant's Name: Guilin Zhishen Information Technology Co., Ltd.  
Manufacturer's Name: Guilin Zhishen Information Technology Co., Ltd.

### 1.2. Test Standards

KDB 447498 D01 General RF Exposure Guidance v06

### 1.3. Test Result

Pass

### 1.4. Testing Location


Address: Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China

### 1.5. Project Data

Testing Start Date: 2023-04-17


Testing End Date: 2023-04-17

### 1.6. Signature




---

Li Yongfu  
(Prepared this test report)



---

LiuJian  
(Reviewed this test report)



---

Cao Junfei  
(Approved this test report)

## 2. Client Information

### 2.1. Applicant Information

Company Name:	Guilin Zhishen Information Technology Co., Ltd.
Address:	09 Huangtong Road, Tieshan Industrial Zone, Qixing District, Guilin, Guangxi, China.
City:	Guilin
Country:	China
Telephone:	+86 13066932837

### 2.2. Manufacturer Information

Company Name:	Guilin Zhishen Information Technology Co., Ltd.
Address:	09 Huangtong Road, Tieshan Industrial Zone, Qixing District, Guilin, Guangxi, China.
City:	Guilin
Country:	China
Telephone:	+86 13066932837

## 3. Equipment under Test (EUT) and Ancillary Equipment (AE)

### 3.1. About EUT

Description:	CRANE-M 3S
Model name:	CR127
Condition of EUT as received:	No obvious damage in appearance
Frequency Bands:	Bluetooth
Tx Frequency:	2402 – 2480MHz (Bluetooth)

## 4. Test Methodology

**KDB 447498 D01 General RF Exposure Guidance v06** RF exposure procedures and equipment authorization policies for mobile and portable devices

## 5. Result

Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

Where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

If the test separation distance (antenna-user) is  $< 5$ mm, 5mm is used for excluded SAR calculation

Evaluation Mode	Maximum Tune-up Power		Test Distance (mm)	Frequency (GHz)	Exclusion Thresholds
	(dBm)	(mW)			
Bluetooth	-6.50	0.22	0	2.48	0.07

### Conclusion:

Per KDB 447498 D01v06, exclusion thresholds is less than 3, RF exposure evaluation is not required.

**\*\*\*END OF REPORT\*\*\***