Appendix C

RF Test Data for 5.2G WLAN (Conducted Measurement)

Product Name: LAPTOP
Trade Mark: FUSION5
Test Model: A90B+ Pro

Environmental Conditions

Temperature:	25.5 ° C
Relative Humidity:	51.3%
ATM Pressure:	100.0 kPa
Test Engineer:	Ken He
Supervised by:	Li Huan

C.1 Duty Cycle

Ant0

Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW(KHz)
11A	5200	100	0.00	0.01
11N20 SISO	5200	100	0.00	0.01
11N40 SISO	5190	100	0.00	0.01
11AC20 SISO	5200	100	0.00	0.01
11AC40 SISO	5190	100	0.00	0.01
11AC80 SISO	5210	100	0.00	0.01

Ant1

Test Mode	Test Frequency (MHz)	Duty Cycle (%)	10log(1/x) Factor (dB)	1/B Minimum VBW(KHz)
11A	5200	100	0.00	0.01
11N20 SISO	5200	100	0.00	0.01
11N40 SISO	5190	100	0.00	0.01
11AC20 SISO	5200	100	0.00	0.01
11AC40 SISO	5190	100	0.00	0.01
11AC80 SISO	5210	100	0.00	0.01

On Time and Duty Cycle_Ant0



IEEE 802.11a



IEEE 802.11n HT20



IEEE 802.11n HT40



IEEE 802.11AC20



IEEE 802.11 AC40



IEEE 802.11AC80

On Time and Duty Cycle_ Ant1



IEEE 802.11a



IEEE 802.11n HT20



IEEE 802.11n HT40



IEEE 802.11AC20



IEEE 802.11 AC40



IEEE 802.11AC80

C.2 Maximum Conduct Output Power

Ant0

Test Mode	Channel	Frequency (MHz)	Peak Conducted Power (dBm)	Duty Cycle Factor(dB)	Report Conducted Power(dBm)	Limit (dBm)	Verdict
11A	36	5180	5.30	0	5.30	24	Pass
	40	5200	5.42	0	5.42		Pass
	48	5240	5.80	0	5.80		Pass
11N20 SISO	36	5180	4.89	0	4.89	24	Pass
	40	5200	4.64	0	4.64		Pass
	48	5240	4.51	0	4.51		Pass
11N40 SISO	38	5190	4.56	0	4.56	24	Pass
	46	5230	4.47	0	4.47		Pass
11AC20 SISO	36	5180	4.33	0	4.33	24	Pass
	40	5200	4.90	0	4.90		Pass
	48	5240	4.48	0	4.48		Pass
11AC40 SISO	38	5190	4.88	0	4.88	24	Pass
	46	5230	4.88	0	4.88		Pass
11AC80 SISO	42	5210	4.34	0	4.34	24	Pass

Ant1

Test Mode	Channel	Frequency (MHz)	Peak Conducted Power (dBm)	Duty Cycle Factor(dB)	Report Conducted Power(dBm)	Limit (dBm)	Verdict
11A	36	5180	5.69	0	5.69	24	Pass
	40	5200	5.79	0	5.79		Pass
	48	5240	5.67	0	5.67		Pass
11N20 SISO	36	5180	4.30	0	4.30	24	Pass
	40	5200	4.93	0	4.93		Pass
	48	5240	4.94	0	4.94		Pass
11N40 SISO	38	5190	4.85	0	4.85	24	Pass
	46	5230	4.22	0	4.22		Pass
11AC20 SISO	36	5180	4.88	0	4.88	24	Pass
	40	5200	4.56	0	4.56		Pass
	48	5240	4.49	0	4.49		Pass
11AC40 SISO	38	5190	4.86	0	4.86	24	Pass
	46	5230	4.79	0	4.79		Pass
11AC80 SISO	42	5210	4.46	0	4.46	24	Pass

Combined Ant0 and Ant1

Test Mode	Channel	Frequency (MHz)	Report Conducted Power (dBm)			Limit (dBm)
			Ant_0	Ant_1	Sum	
11N20	36	5180	4.89	4.30	7.62	24
	40	5200	4.64	4.93	7.80	
	48	5240	4.51	4.94	7.74	
11N40	38	5190	4.56	4.85	7.72	24
	46	5230	4.47	4.22	7.36	
11AC20	36	5180	4.33	4.88	7.62	24
	40	5200	4.90	4.56	7.74	
	48	5240	4.48	4.49	7.50	
11AC40	38	5190	4.88	4.86	7.88	24
	46	5230	4.88	4.79	7.85	
11AC80	42	5210	4.34	4.46	7.41	24

C.3 Power Spectral Density

Ant0

Test Mode	Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Cycle Factor(dB)	Report Power Density (dBm/MHz)	Limit (dBm/MHz)	Verdict
11A	36	5180	-2.23	0	-2.23	11	Pass
	40	5200	-2.26	0	-2.26		Pass
	48	5240	-0.98	0	-0.98		Pass
11N20 SISO	36	5180	-3.49	0	-3.49	11	Pass
	40	5200	-2.33	0	-2.33		Pass
	48	5240	-1.49	0	-1.49		Pass
11N40 SISO	38	5190	-5.88	0	-5.88	11	Pass
	46	5230	-5.38	0	-5.38		Pass
11AC20 SISO	36	5180	-3.53	0	-3.53	11	Pass
	40	5200	-3.07	0	-3.07		Pass
	48	5240	-2.54	0	-2.54		Pass
11AC40 SISO	38	5190	-5.90	0	-5.90	11	Pass
	46	5230	-4.53	0	-4.53		Pass
11AC80 SISO	42	5210	-7.13	0	-7.13	11	Pass

Ant1

Test Mode	Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Cycle Factor(dB)	Report Power Density (dBm/MHz)	Limit (dBm/MHz)	Verdict
11A	36	5180	-2.09	0	-2.09	11	Pass
	40	5200	-1.71	0	-1.71		Pass
	48	5240	-0.76	0	-0.76		Pass
11N20 SISO	36	5180	-1.93	0	-1.93	11	Pass
	40	5200	-1.52	0	-1.52		Pass
	48	5240	-0.38	0	-0.38		Pass
11N40 SISO	38	5190	-4.05	0	-4.05	11	Pass
	46	5230	-4.35	0	-4.35		Pass
11AC20 SISO	36	5180	-0.55	0	-0.55	11	Pass
	40	5200	-0.72	0	-0.72		Pass
	48	5240	-1.26	0	-1.26		Pass
11AC40 SISO	38	5190	-4.42	0	-4.42	11	Pass
	46	5230	-3.79	0	-3.79		Pass
11AC80 SISO	42	5210	-6.43	0	-6.43	11	Pass

Combined Ant0 and Ant1

Test Mode	Channel	Frequency (MHz)	Report Power Density (dBm/MHz)			Limit (dBm/MHz)
			Ant_0	Ant_1	Sum	
11N20	36	5180	-3.49	-1.93	0.37	11
	40	5200	-2.33	-1.52	1.10	
	48	5240	-1.49	-0.38	2.11	
11N40	38	5190	-5.88	-4.05	-1.86	11
	46	5230	-5.38	-4.35	-1.82	
11AC20	36	5180	-3.53	-0.55	1.22	11
	40	5200	-3.07	-0.72	1.27	
	48	5240	-2.54	-1.26	1.16	
11AC40	38	5190	-5.90	-4.42	-2.09	11
	46	5230	-4.53	-3.79	-1.13	
11AC80	42	5210	-7.13	-6.43	-3.76	11

Ant0

Power Spectral Density

IEEE 802.11a / Channel 36 / 5180MHz

IEEE 802.11na / Channel 40 / 5200MHz



IEEE 802.11na / Channel 48 / 5240MHz

Power Spectral Density



IEEE 802.11n20 / Channel 36 / 5180MHz



IEEE 802.11n20 / Channel 40 / 5200MHz



IEEE 802.11n20 / Channel 48 / 5240MHz

Power Spectral Density

IEEE 802.11n40 / Channel 38 / 5190MHz

IEEE 802.11n40 / Channel 46 / 5230MHz



IEEE 802.11ac20 / Channel 36 / 5180MHz



IEEE 802.11ac20 / Channel 40 / 5200MHz



IEEE 802.11ac20 / Channel 48 / 5240MHz



IEEE 802.11ac40 / Channel 38 / 5190MHz



IEEE 802.11ac40 / Channel 46 / 5230MHz



IEEE 802.11ac80 / Channel 42 / 5210MHz

Ant1

Power Spectral Density

IEEE 802.11a / Channel 36 / 5180MHz

IEEE 802.11na / Channel 40 / 5200MHz



IEEE 802.11na / Channel 48 / 5240MHz

Power Spectral Density



IEEE 802.11n20 / Channel 36 / 5180MHz



IEEE 802.11n20 / Channel 40 / 5200MHz



IEEE 802.11n20 / Channel 48 / 5240MHz

Power Spectral Density



IEEE 802.11n40 / Channel 38 / 5190MHz



IEEE 802.11n40 / Channel 46 / 5230MHz



IEEE 802.11ac20 / Channel 36 / 5180MHz



IEEE 802.11ac20 / Channel 40 / 5200MHz



IEEE 802.11ac20 / Channel 48 / 5240MHz



IEEE 802.11ac40 / Channel 38 / 5190MHz



IEEE 802.11ac40 / Channel 46 / 5230MHz



IEEE 802.11ac80 / Channel 42 / 5210MHz

C.4 Emission Bandwidth

Ant0

Test Mode	Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
11A	36	5180	20.13	No Limit	Pass
	40	5200	20.27		Pass
	48	5240	19.94		Pass
11N20 SISO	36	5180	20.88	No Limit	Pass
	40	5200	20.91		Pass
	48	5240	20.78		Pass
11N40 SISO	38	5190	42.49	No Limit	Pass
	46	5230	41.96		Pass
11AC20 SISO	36	5180	20.98	No Limi	Pass
	40	5200	20.86		Pass
	48	5240	20.68		Pass
11AC40 SISO	38	5190	42.46	No Limi	Pass
	46	5230	42.00		Pass
11AC80 SISO	42	5210	81.60	No Limi	Pass

Ant1

Test Mode	Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
11A	36	5180	20.63	No Limit	Pass
	40	5200	20.57		Pass
	48	5240	20.34		Pass
11N20 SISO	36	5180	21.41	No Limit	Pass
	40	5200	20.92		Pass
	48	5240	21.23		Pass
11N40 SISO	38	5190	42.85	No Limit	Pass
	46	5230	42.77		Pass
11AC20 SISO	36	5180	20.78	No Limi	Pass
	40	5200	20.79		Pass
	48	5240	20.93		Pass
11AC40 SISO	38	5190	42.01	No Limi	Pass
	46	5230	42.72		Pass
11AC80 SISO	42	5210	81.15	No Limi	Pass

Ant0

26dB Bandwidth

IEEE 802.11a / Channel 36 / 5180MHz

IEEE 802.11a / Channel 40 / 5200MHz



IEEE 802.11a / Channel 48 / 5240MHz

26dB Bandwidth



IEEE 802.11n20 / Channel 36 / 5180MHz



IEEE 802.11n20 / Channel 40 / 5200MHz



IEEE 802.11n20 / Channel 48 / 5240MHz

26dB Bandwidth



IEEE 802.11n40 / Channel 38 / 5190MHz



IEEE 802.11n40 / Channel 46 / 5230MHz



IEEE 802.11ac20 / Channel 36 / 5180MHz



IEEE 802.11ac20 / Channel 40 / 5200MHz



IEEE 802.11ac20 / Channel 48 / 5240MHz



IEEE 802.11ac40 / Channel 38 / 5190MHz



IEEE 802.11ac40 / Channel 46 / 5230MHz



IEEE 802.11ac80 / Channel 42 / 5210MHz

Ant1

26dB Bandwidth

IEEE 802.11a / Channel 36 / 5180MHz

IEEE 802.11a / Channel 40 / 5200MHz



IEEE 802.11a / Channel 48 / 5240MHz

26dB Bandwidth



IEEE 802.11n20 / Channel 36 / 5180MHz



IEEE 802.11n20 / Channel 40 / 5200MHz



IEEE 802.11n20 / Channel 48 / 5240MHz

26dB Bandwidth



IEEE 802.11n40 / Channel 38 / 5190MHz



IEEE 802.11n40 / Channel 46 / 5230MHz



IEEE 802.11ac20 / Channel 36 / 5180MHz



IEEE 802.11ac20 / Channel 40 / 5200MHz



IEEE 802.11ac20 / Channel 48 / 5240MHz



IEEE 802.11ac40 / Channel 38 / 5190MHz



IEEE 802.11ac40 / Channel 46 / 5230MHz



IEEE 802.11ac80 / Channel 42 / 5210MHz

C.5 Undesirable Emissions Measurement

Ant0

Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
11A	36	4500.0	-50.49	2.00	0	46.74	Peak	68.20	Pass
		4500.0	-60.28	2.00	0	36.95	Average	54.00	Pass
		5150.0	-48.57	2.00	0	48.66	Peak	68.20	Pass
		5150.0	-58.08	2.00	0	39.15	Average	54.00	Pass
	48	5350.0	-48.44	2.00	0	48.79	Peak	68.20	Pass
		5350.0	-58.70	2.00	0	38.53	Average	54.00	Pass
		5460.0	-47.74	2.00	0	49.49	Peak	68.20	Pass
		5460.0	-58.50	2.00	0	38.73	Average	54.00	Pass
11N20 SISO	36	4500.0	-50.68	2.00	0	46.55	Peak	68.20	Pass
		4500.0	-60.32	2.00	0	36.91	Average	54.00	Pass
		5150.0	-47.60	2.00	0	49.63	Peak	68.20	Pass
		5150.0	-58.08	2.00	0	39.15	Average	54.00	Pass
	48	5350.0	-48.54	2.00	0	48.69	Peak	68.20	Pass
		5350.0	-58.77	2.00	0	38.46	Average	54.00	Pass
		5460.0	-48.11	2.00	0	49.12	Peak	68.20	Pass
		5460.0	-58.47	2.00	0	38.76	Average	54.00	Pass
11N40 SISO	38	4500.0	-49.94	2.00	0	47.29	Peak	68.20	Pass
		4500.0	-60.32	2.00	0	36.91	Average	54.00	Pass
		5150.0	-46.20	2.00	0	51.03	Peak	68.20	Pass
		5150.0	-57.88	2.00	0	39.35	Average	54.00	Pass
	46	5350.0	-47.35	2.00	0	49.88	Peak	68.20	Pass
		5350.0	-58.60	2.00	0	38.63	Average	54.00	Pass
		5460.0	-48.14	2.00	0	49.09	Peak	68.20	Pass
		5460.0	-58.33	2.00	0	38.90	Average	54.00	Pass
11AC20 SISO	36	4500.0	-51.01	2.00	0	46.22	Peak	68.20	Pass
		4500.0	-60.35	2.00	0	36.88	Average	54.00	Pass
		5150.0	-47.75	2.00	0	49.48	Peak	68.20	Pass
		5150.0	-58.08	2.00	0	39.15	Average	54.00	Pass
	48	4500.0	-51.01	2.00	0	46.22	Peak	68.20	Pass
		4500.0	-60.35	2.00	0	36.88	Average	54.00	Pass
		5150.0	-47.75	2.00	0	49.48	Peak	68.20	Pass
		5150.0	-58.08	2.00	0	39.15	Average	54.00	Pass
11AC40 SISO	38	4500.0	-49.50	2.00	0	47.73	Peak	68.20	Pass
		4500.0	-60.39	2.00	0	36.84	Average	54.00	Pass
		5150.0	-47.41	2.00	0	49.82	Peak	68.20	Pass
		5150.0	-57.86	2.00	0	39.37	Average	54.00	Pass
	46	5350.0	-47.42	2.00	0	49.81	Peak	68.20	Pass
		5350.0	-58.51	2.00	0	38.72	Average	54.00	Pass
		5460.0	-47.92	2.00	0	49.31	Peak	68.20	Pass
		5460.0	-58.27	2.00	0	38.96	Average	54.00	Pass
11AC80 SISO	42	4500.0	-48.36	2.00	0	48.87	Peak	68.20	Pass
		5150.0	-58.05	2.00	0	39.18	Average	54.00	Pass
		4500.0	-47.16	2.00	0	50.07	Peak	68.20	Pass
		5150.0	-57.87	2.00	0	39.36	Average	54.00	Pass
		5350.0	-48.36	2.00	0	48.87	Peak	68.20	Pass
		5460.0	-58.05	2.00	0	39.18	Average	54.00	Pass
		5350.0	-47.16	2.00	0	50.07	Peak	68.20	Pass
		5460.0	-57.87	2.00	0	39.36	Average	54.00	Pass

Ant1

Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
11A	36	4500.0	-50.22	2.00	0	47.01	Peak	68.20	Pass
		4500.0	-59.63	2.00	0	37.60	Average	54.00	Pass
		5150.0	-47.92	2.00	0	49.31	Peak	68.20	Pass
		5150.0	-57.52	2.00	0	39.71	Average	54.00	Pass
	48	5350.0	-48.01	2.00	0	49.22	Peak	68.20	Pass
		5350.0	-58.74	2.00	0	38.49	Average	54.00	Pass
		5460.0	-47.21	2.00	0	50.02	Peak	68.20	Pass
		5460.0	-58.39	2.00	0	38.84	Average	54.00	Pass
11N20 SISO	36	4500.0	-50.12	2.00	0	47.11	Peak	68.20	Pass
		4500.0	-60.42	2.00	0	36.81	Average	54.00	Pass
		5150.0	-47.93	2.00	0	49.30	Peak	68.20	Pass
		5150.0	-58.11	2.00	0	39.12	Average	54.00	Pass
	48	5350.0	-48.15	2.00	0	49.08	Peak	68.20	Pass
		5350.0	-58.70	2.00	0	38.53	Average	54.00	Pass
		5460.0	-47.54	2.00	0	49.69	Peak	68.20	Pass
		5460.0	-58.35	2.00	0	38.88	Average	54.00	Pass
11N40 SISO	38	4500.0	-50.49	2.00	0	46.74	Peak	68.20	Pass
		4500.0	-60.40	2.00	0	36.83	Average	54.00	Pass
		5150.0	-47.29	2.00	0	49.94	Peak	68.20	Pass
		5150.0	-57.81	2.00	0	39.42	Average	54.00	Pass
	46	5350.0	-48.89	2.00	0	48.34	Peak	68.20	Pass
		5350.0	-58.51	2.00	0	38.72	Average	54.00	Pass
		5460.0	-48.45	2.00	0	48.78	Peak	68.20	Pass
		5460.0	-58.25	2.00	0	38.98	Average	54.00	Pass
11AC20 SISO	36	4500.0	-50.68	2.00	0	46.55	Peak	68.20	Pass
		4500.0	-60.40	2.00	0	36.83	Average	54.00	Pass
		5150.0	-49.29	2.00	0	47.94	Peak	68.20	Pass
		5150.0	-58.21	2.00	0	39.02	Average	54.00	Pass
	48	4500.0	-50.68	2.00	0	46.55	Peak	68.20	Pass
		4500.0	-60.40	2.00	0	36.83	Average	54.00	Pass
		5150.0	-49.29	2.00	0	47.94	Peak	68.20	Pass
		5150.0	-58.21	2.00	0	39.02	Average	54.00	Pass
11AC40 SISO	38	4500.0	-50.65	2.00	0	46.58	Peak	68.20	Pass
		4500.0	-60.42	2.00	0	36.81	Average	54.00	Pass
		5150.0	-47.17	2.00	0	50.06	Peak	68.20	Pass
		5150.0	-57.73	2.00	0	39.50	Average	54.00	Pass
	46	5350.0	-48.48	2.00	0	48.75	Peak	68.20	Pass
		5350.0	-58.42	2.00	0	38.81	Average	54.00	Pass
		5460.0	-48.72	2.00	0	48.51	Peak	68.20	Pass
		5460.0	-58.26	2.00	0	38.97	Average	54.00	Pass
11AC80 SISO	42	4500.0	-47.44	2.00	0	49.79	Peak	68.20	Pass
		5150.0	-58.04	2.00	0	39.19	Average	54.00	Pass
		4500.0	-47.35	2.00	0	49.88	Peak	68.20	Pass
		5150.0	-57.85	2.00	0	39.38	Average	54.00	Pass
		5350.0	-47.44	2.00	0	49.79	Peak	68.20	Pass
		5460.0	-58.04	2.00	0	39.19	Average	54.00	Pass
		5350.0	-47.35	2.00	0	49.88	Peak	68.20	Pass
		5460.0	-57.85	2.00	0	39.38	Average	54.00	Pass

Combined Ant_0 and Ant_1

Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)			Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
			Ant0	Ant1	Sum						
11N20 SISO	36	4500.0	-50.68	-50.12	-47.38	3.01	0	50.86	Peak	68.20	Pass
		4500.0	-60.32	-60.42	-57.36	3.01	0	40.88	Average	54.00	Pass
		5150.0	-47.60	-47.93	-44.75	3.01	0	53.49	Peak	68.20	Pass
		5150.0	-58.08	-58.11	-55.08	3.01	0	43.16	Average	54.00	Pass
	48	5350.0	-48.54	-48.15	-45.33	3.01	0	52.91	Peak	68.20	Pass
		5350.0	-58.77	-58.70	-55.72	3.01	0	42.52	Average	54.00	Pass
		5460.0	-48.11	-47.54	-44.81	3.01	0	53.43	Peak	68.20	Pass
		5460.0	-58.47	-58.35	-55.40	3.01	0	42.84	Average	54.00	Pass
11N40 SISO	38	4500.0	-49.94	-50.49	-47.20	3.01	0	51.04	Peak	68.20	Pass
		4500.0	-60.32	-60.40	-57.35	3.01	0	40.89	Average	54.00	Pass
		5150.0	-46.20	-47.29	-43.70	3.01	0	54.54	Peak	68.20	Pass
		5150.0	-57.88	-57.81	-54.83	3.01	0	43.41	Average	54.00	Pass
	46	5350.0	-47.35	-48.89	-45.04	3.01	0	53.20	Peak	68.20	Pass
		5350.0	-58.60	-58.51	-55.54	3.01	0	42.70	Average	54.00	Pass
		5460.0	-48.14	-48.45	-45.28	3.01	0	52.96	Peak	68.20	Pass
		5460.0	-58.33	-58.25	-55.28	3.01	0	42.96	Average	54.00	Pass
11AC20 SISO	36	4500.0	-51.01	-50.68	-47.83	3.01	0	50.41	Peak	68.20	Pass
		4500.0	-60.35	-60.40	-57.36	3.01	0	40.88	Average	54.00	Pass
		5150.0	-47.75	-49.29	-45.44	3.01	0	52.80	Peak	68.20	Pass
		5150.0	-58.08	-58.21	-55.13	3.01	0	43.11	Average	54.00	Pass
	48	5350.0	-51.01	-50.68	-47.83	3.01	0	50.41	Peak	68.20	Pass
		5350.0	-60.35	-60.40	-57.36	3.01	0	40.88	Average	54.00	Pass
		5460.0	-47.75	-49.29	-45.44	3.01	0	52.80	Peak	68.20	Pass
		5460.0	-58.08	-58.21	-55.13	3.01	0	43.11	Average	54.00	Pass
11AC40 SISO	38	4500.0	-49.50	-50.65	-47.03	3.01	0	51.21	Peak	68.20	Pass
		4500.0	-60.39	-60.42	-57.39	3.01	0	40.85	Average	54.00	Pass
		5150.0	-47.41	-47.17	-44.28	3.01	0	53.96	Peak	68.20	Pass
		5150.0	-57.86	-57.73	-54.78	3.01	0	43.46	Average	54.00	Pass
	46	5350.0	-47.42	-48.48	-44.91	3.01	0	53.33	Peak	68.20	Pass
		5350.0	-58.51	-58.42	-55.45	3.01	0	42.79	Average	54.00	Pass
		5460.0	-47.92	-48.72	-45.29	3.01	0	52.95	Peak	68.20	Pass
		5460.0	-58.27	-58.26	-55.25	3.01	0	42.99	Average	54.00	Pass
11AC80 SISO	42	4500.0	-48.36	-47.44	-44.87	3.01	0	53.37	Peak	68.20	Pass
		5150.0	-58.05	-58.04	-55.03	3.01	0	43.21	Average	54.00	Pass
		4500.0	-47.16	-47.35	-44.24	3.01	0	54.00	Peak	68.20	Pass
		5150.0	-57.87	-57.85	-54.85	3.01	0	43.39	Average	54.00	Pass
		5350.0	-48.36	-47.44	-44.87	3.01	0	53.37	Peak	68.20	Pass
		5460.0	-58.05	-58.04	-55.03	3.01	0	43.21	Average	54.00	Pass
		5350.0	-47.16	-47.35	-44.24	3.01	0	54.00	Peak	68.20	Pass
		5460.0	-57.87	-57.85	-54.85	3.01	0	43.39	Average	54.00	Pass

Ant0

Undesirable Emissions Measurement

IEEE 802.11a / Channel 36 / 5180MHz / Peak

IEEE 802.11a / Channel 36 / 5180MHz / Average

Undesirable Emissions Measurement



IEEE 802.11a / Channel 48 / 5240MHz / Peak



IEEE 802.11a / Channel 48 / 5240MHz / Average

Undesirable Emissions Measurement



IEEE 802.11n20 / Channel 36 / 5180MHz / Peak



IEEE 802.11n20 / Channel 36 / 5180MHz / Average

Undesirable Emissions Measurement



IEEE 802.11n20 / Channel 48 / 5240MHz / Peak



IEEE 802.11n20 / Channel 48 / 5240MHz / Average

Undesirable Emissions Measurement



IEEE 802.11n40 / Channel 38 / 5190MHz / Peak



IEEE 802.11n40 / Channel 38 / 5190MHz / Average

Undesirable Emissions Measurement



IEEE 802.11n40 / Channel 46 / 5230MHz / Peak



IEEE 802.11n40 / Channel 46 / 5230MHz / Average



IEEE 802.11ac20 / Channel 36 / 5180MHz / Peak



IEEE 802.11ac20 / Channel 36 / 5180MHz / Average



IEEE 802.11ac20 / Channel 48 / 5240MHz / Peak



IEEE 802.11ac20 / Channel 48 / 5240MHz / Average



IEEE 802.11ac40 / Channel 38/ 5190MHz / Peak



IEEE 802.11ac40 / Channel 38 / 5190MHz / Average



IEEE 802.11ac40 / Channel 46/ 5230MHz / Peak



IEEE 802.11ac40 / Channel 46 / 5230MHz / Average



IEEE 802.11ac80 / Channel 42 / 5210MHz / Peak



IEEE 802.11ac80 / Channel 42 / 5210MHz / Average

Ant1

Undesirable Emissions Measurement

IEEE 802.11a / Channel 36 / 5180MHz / Peak

IEEE 802.11a / Channel 36 / 5180MHz / Average

Undesirable Emissions Measurement



IEEE 802.11a / Channel 48 / 5240MHz / Peak



IEEE 802.11a / Channel 48 / 5240MHz / Average

Undesirable Emissions Measurement



IEEE 802.11n20 / Channel 36 / 5180MHz / Peak



IEEE 802.11n20 / Channel 36 / 5180MHz / Average

Undesirable Emissions Measurement



IEEE 802.11n20 / Channel 48 / 5240MHz / Peak



IEEE 802.11n20 / Channel 48 / 5240MHz / Average

Undesirable Emissions Measurement



IEEE 802.11n40 / Channel 38 / 5190MHz / Peak



IEEE 802.11n40 / Channel 38 / 5190MHz / Average

Undesirable Emissions Measurement



IEEE 802.11n40 / Channel 46 / 5230MHz / Peak



IEEE 802.11n40 / Channel 46 / 5230MHz / Average



IEEE 802.11ac20 / Channel 36 / 5180MHz / Peak



IEEE 802.11ac20 / Channel 36 / 5180MHz / Average



IEEE 802.11ac20 / Channel 48 / 5240MHz / Peak



IEEE 802.11ac20 / Channel 48 / 5240MHz / Average



IEEE 802.11ac40 / Channel 38/ 5190MHz / Peak



IEEE 802.11ac40 / Channel 38 / 5190MHz / Average



IEEE 802.11ac40 / Channel 46/ 5230MHz / Peak



IEEE 802.11ac40 / Channel 46 / 5230MHz / Average



IEEE 802.11ac80 / Channel 42 / 5210MHz / Peak



IEEE 802.11ac80 / Channel 42 / 5210MHz / Average