



FCC Test Report

Report No: FCS202008035W01

Issued for

Applicant:	VTIN TECHNOLOGY Co.,Limited
Address:	UNIT D 16/F ONE CAPITAL PLACE 21 LUARD ROAD WAN CHAI HK
Product Name:	Wireless Presenter
Brand Name:	victsing
Model Name:	PC276A
Series Model:	PC276B, PC276C
FCC ID:	2AIL4-PC276A
Issued By: Flux Compliance Service Laboratory Add: Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan Tel: 769-27280901 Fax:769-27280901 http://www.fcs-lab.com	

TEST RESULT CERTIFICATION

Applicant's Name: VTIN TECHNOLOGY Co.,Limited
Address.....: UNIT D 16/F ONE CAPITAL PLACE 21 LUARD ROAD WAN CHAI HK
Manufacture's Name: VTIN TECHNOLOGY Co.,Limited
Address.....: UNIT D 16/F ONE CAPITAL PLACE 21 LUARD ROAD WAN CHAI HK

Product Description

Product Name: Wireless Presenter
Brand Name: victsing
Model Name.....: PC276A
Series Model: PC276B, PC276C
Test Standards: FCC Rules and Regulations Part 15 Subpart C, Section 249
Test Procedure: ANSI C63.10:2013

This device described above has been tested FCS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of FCS, this document may be altered or revised by FCS, personal only, and shall be noted in the revision of the document..

Date of Test

Date (s) of performance of tests : Septemper 01, 2020 ~ Septemper 28, 2020

Date of Issue: Septemper 28, 2020

Test Result.....: Pass

Tested by

:

Scott Shen

(Scott Shen)

Reviewed by

:

Duke Qian

(Duke Qian)

Approved by

:

Kait Chen

(Kait Chen)

Table of Contents	Page
1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACTORY.....	6
1.2 MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION.....	7
2.1 GENERAL DESCRIPTION OF THE EUT.....	7
2.2 DESCRIPTION OF THE TEST MODES.....	9
2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS.....	10
2.4 EQUIPMENTS LIST.....	11
3. RADIATED EMISSION MEASUREMENT	12
3.1 LIMIT	12
3.2 TEST PROCEDURE.....	13
3.3 TEST SETUP.....	14
3.4 TEST RESULTS	15
4. BAND EDGE TEST	22
4.1 LIMIT	22
4.2 TEST PROCEDURE.....	22
4.3 TEST SETUP.....	23
4.4 TEST RESULTS	24
5. 20 DB BANDWIDTH TEST	28
5.1 LIMIT	28
5.2 TEST PROCEDURE.....	28
5.3 TEST SETUP.....	28
5.4 TEST RESULTS	29
6. ANTENNA REQUIREMENT.....	31
6.1 STANDARD REQUIREMENT	31
6.2 EUT ANTENNA.....	31

Revision History

Rev.	Issue Date	Effect Page	Contents
00	Septemper 28, 2020	All	Initial Issue

1. SUMMARY OF TEST RESULTS

FCC Part 15.249,Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	NA	--
15.205(a), 15.209(a), 15.249(a), 15.249(c)	Radiated Spurious Emission	PASS	--
15.209	Field strength of fundamental	PASS	
15.249(d)	Band Edge Emission	PASS	--
15.215(c)	20dB Bandwidth	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report
- (2) All tests are according to ANSI C63.10-2013

1.1 TEST FACTORY

Company Name:	Flux Compliance Service Laboratory
Address:	Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan
Telephone:	+86-769-27280901
Fax:	+86-769-27280901
FCC Test Firm Registration Number: 514908 Designation number: CN0127 A2LA accreditation number: 5545.01	

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	± 0.71 dB
2	Unwanted Emissions, conducted	± 2.98 dB
3	Conducted Emission (9KHz-150KHz)	± 4.13 dB
4	Conducted Emission (150KHz-30MHz)	± 4.74 dB
5	All emissions, radiated (<1G) 30MHz-1000MHz	± 3.2 dB
6	All emissions, radiated (1GHz -18GHz)	± 3.66 dB
7	All emissions, radiated (18GHz -40GHz)	± 4.31 dB

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Wireless Presenter
Trade Name	victsing
Model Name	PC276A
Series Model	PC276B, PC276C
Model Difference	The above product with same circuit, PCB layout, electrical parts, materials and wiring structures, Appearance shape, the materials of decorative accessories is same, only different color
Channel List	Please refer to the Note 2.
Operational Frequency	Frequency:2404-2479MHz
Channel number:	16CH
Modulation:	GFSK
Power Supply	DC 1.5V
Hardware version number	V1.0
Software version number	V1.0
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. Channel List

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2404MHz	5	2424MHz	9	2444MHz	13	2464MHz
2	2409MHz	6	2429MHz	10	2449MHz	14	2469MHz
3	2414MHz	7	2434MHz	11	2454MHz	15	2474MHz
4	2419MHz	8	2439MHz	12	2459MHz	16	2479MHz

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	Integral Antenna	N/A	1.00dBi	Antenna

2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test software: FCC tool


The test software was used to control EUT work in continuous TX mode, and select test channel, Wireless mode as below table

No.	Test model descrption
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK

Note:

1. All the test modes can be supply by batter , only the result of the worst case recorded in the report..
2. For radiated emission, 3 axis were chosen for testing for each applicable mode.
3. The EUT used fully charge battery when tested.

Configuration and peripherals



2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
1					
2					

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.4 EQUIPMENTS LIST

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESRP 3	FCS-E001	2019.10.11	2020.10.10
Signal Analyzer	R&S	FSV40-N	FCS-E012	2019.10.11	2020.10.10
Active loop Antenna	ZHINAN	ZN30900C	FCS-E013	2019.10.11	2020.10.10
Bilog Antenna	SCHWARZBECK	VULB 9168	FCS-E002	2019.10.26	2020.10.25
Horn Antenna	SCHWARZBECK	BBHA 9120D	FCS-E003	2019.10.11	2020.10.10
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	FCS-E018	2019.10.11	2020.10.10
Pre-Amplifier(0.1M-3G Hz)	EMCI	EM330N	FCS-E004	2019.10.11	2020.10.10
Pre-Amplifier (1G-18GHz)	N/A	TSAMP-0518SE	FCS-E014	2019.10.03	2020.10.02
Pre-Amplifier (18G-40GHz)	TERA-MW	TRLA-0400	FCS-E019	2019.10.08	2020.10.07
Temperature & Humidity	HTC-1	victor	FCS-E005	2019.10.11	2020.10.10

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	FCS-E020	2019.10.11	2020.10.10
LISN	R&S	ENV216	FCS-E007	2019.10.11	2020.10.10
LISN	ETS	3810/2NM	FCS-E009	2019.10.15	2020.10.14
Temperature & Humidity	HTC-1	victor	FCS-E008	2019.10.11	2020.10.10

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
Spectrum Analyzer	Keysight	N9020A	FCS-E015	2019.10.15	2020.10.14
Spectrum Analyzer	Agilent	E4447A	MY50180039	2019.11.08	2020.11.07
Spectrum Analyzer	R&S	FSV-40	101499	2019.10.10	2020.10.09

3. RADIATED EMISSION MEASUREMENT

3.1 LIMIT

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009mhz - 1000mhz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

LIMITS OF FIELD STRENGTH OF THE FUNDAMENTAL SIGNAL

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
2400-2483.5	114	94

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

3.2 TEST PROCEDURE

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz /10 Hz (PK detector is used)


- a. The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.4 TEST RESULTS

Temperature:	25°C	Relative Humidity:	60%
Test Mode:	GFSK	Test Voltage:	DC 1.5V

For field strength of the fundamental signal

Peak value

No.	Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2404	91.03	26.68	6.31	30.91	93.11	114	-20.89	Horizontal
2	2404	90.11	26.68	6.31	30.91	92.19	114	-21.81	Vertical
3	2444	91.04	26.38	6.43	30.68	93.18	114	-20.82	Horizontal
4	2444	90.66	26.38	6.43	30.68	92.79	114	-21.21	Vertical
5	2479	88.26	26.29	6.58	30.46	90.67	114	-23.33	Horizontal
6	2479	86.06	26.29	6.58	30.46	88.46	114	-25.54	Vertical

Average value

No.	Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2404	65.07	26.68	6.31	30.91	67.15	94	-26.85	Horizontal
2	2404	63.24	26.68	6.31	30.91	65.32	94	-28.58	Vertical
3	2444	62.06	26.38	6.43	30.68	67.19	94	-26.81	Horizontal
4	2444	66.36	26.38	6.43	30.68	68.49	94	-25.51	Vertical
5	2479	64.36	26.29	6.58	30.46	66.77	94	-27.23	Horizontal
6	2479	57.64	26.29	6.58	30.46	60.04	94	-33.96	Vertical

Note : RBW>20dB BW,VBW>RBW ,PK detector for PK value ,RMS detector for AV value

For spurious emission

(9KHz-30MHz)

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F	Test Result
--	--	--	--	--	
--	--	--	--	--	PASS

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

(30MHZ-1000MHZ)

Temperature:	23.7°C	Relative Humidity:	61%
Test Voltage:	DC 1.5V	Phase:	Horizontal
Test Mode:	GFSK		




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	43.6584	31.99	-18.44	13.55	40.00	-26.45	QP
2	49.3594	31.00	-18.14	12.86	40.00	-27.14	QP
3	96.7750	32.42	-20.87	11.55	43.50	-31.95	QP
4	224.5193	31.17	-19.54	11.63	46.00	-34.37	QP
5	517.2480	31.45	-14.53	16.92	46.00	-29.08	QP
6	830.4002	31.16	-10.53	20.63	46.00	-25.37	QP

Remarks:

1. Final Level =Receiver Read level + Factor
2. all of the modulations were tested, and only the data of worst case exhibited. gfsk is worst case

Temperature:	22.7°C	Relative Humidity:	61%
Test Voltage:	DC 1.5V	Phase:	Vertical
Test Mode:	GFSK		



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	50.2324	31.73	-18.12	13.61	40.00	-26.39	QP
2	98.8326	31.40	-20.49	10.91	43.50	-32.59	QP
3	199.2855	31.35	-19.79	11.56	43.50	-31.94	QP
4	286.9823	31.67	-18.12	13.55	46.00	-32.45	QP
5	454.3100	30.99	-15.61	15.38	46.00	-30.62	QP
6	860.0352	30.86	-10.13	20.73	46.00	-25.27	QP

Remarks:

1. Final Level =Receiver Read level + Factor
2. all of the modulations were tested, and only the data of worst case exhibited. gfsk is worst case

(1GHZ~25GHZ)

LOW CH

PEAK VALUE

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4808	51.23	26.89	7.59	31.68	54.03	74	-19.97	Vertical
7212	51.39	28.35	10.64	31.59	58.79	74	-15.21	Vertical
9616	50.54	32.65	11.24	30.56	63.87	74	-10.13	Vertical
12020	*					74		Vertical
14424	*					74		Vertical
4808	52.65	26.89	7.59	31.68	55.45	74	-18.55	Horizontal
7212	51.57	28.35	10.64	31.59	58.97	74	-15.03	Horizontal
9616	50.94	32.65	11.24	30.56	64.27	74	-9.73	Horizontal
12020	*					74		Horizontal
14424	*					74		Horizontal

AV VALUE

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4808	22.13	26.89	7.59	31.68	24.93	54	-29.07	Vertical
7212	21.38	28.35	10.64	31.59	18.78	54	-35.22	Vertical
9616	22.04	32.65	11.24	30.56	35.37	54	-18.63	Vertical
12020	*					54		Vertical
14424	*					54		Vertical
4808	22.65	26.89	7.59	31.68	25.45	54	-28.55	Horizontal
7212	20.56	28.35	10.64	31.59	27.96	54	-26.04	Horizontal
9616	22.44	32.65	11.24	30.56	35.77	54	-18.23	Horizontal
12020	*					54		Horizontal
14424	*					54		Horizontal

MIDDLE CH

PEAK VALUE

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4888	51.21	26.89	7.59	31.68	54.01	74	-19.99	Vertical
7332	51.35	28.35	10.64	31.59	58.75	74	-15.25	Vertical
9776	50.44	32.65	11.24	30.56	63.77	74	-10.23	Vertical
12220	*					74		Vertical
14664	*					74		Vertical
4888	52.61	26.89	7.59	31.68	55.41	74	-18.59	Horizontal
7332	51.23	28.35	10.64	31.59	58.63	74	-15.37	Horizontal
9776	50.51	32.65	11.24	30.56	63.84	74	-10.16	Horizontal
12220	*					74		Horizontal
14664	*					74		Horizontal

AV VALUE

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4888	29.23	26.89	7.59	31.68	32.03	54	-22.97	Vertical
7332	27.16	28.35	10.64	31.59	34.56	54	-19.44	Vertical
9776	25.26	32.65	11.24	30.56	38.56	54	-15.44	Vertical
12220	*					54		Vertical
14664	*					54		Vertical
4888	32.05	26.89	7.59	31.68	34.85	54	-19.15	Horizontal
7332	28.11	28.35	10.64	31.59	35.51	54	-18.49	Horizontal
9776	28.83	32.65	11.24	30.56	42.16	54	-11.84	Horizontal
12220	*					54		Horizontal
14664	*					54		Horizontal

HIGHT CH

PEAK VALUE

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4958	51.10	26.89	7.59	31.68	53.90	74	-20.10	Vertical
7437	51.13	28.35	10.64	31.59	58.53	74	-15.47	Vertical
9916	50.11	32.65	11.24	30.56	63.44	74	-10.56	Vertical
12395	*					74		Vertical
14874	*					74		Vertical
4958	52.41	26.89	7.59	31.68	55.21	74	-18.79	Horizontal
7437	51.43	28.35	10.64	31.59	58.83	74	-15.17	Horizontal
9916	50.74	32.65	11.24	30.56	64.07	74	-9.93	Horizontal
12395	*					74		Horizontal
14874	*					74		Horizontal

AV VALUE

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4958	25.03	26.89	7.59	31.68	27.83	54	-26.17	Vertical
7437	25.19	28.35	10.64	31.59	32.59	54	-21.41	Vertical
9916	24.21	32.65	11.24	30.56	37.54	54	-16.46	Vertical
12395	*					54		Vertical
14874	*					54		Vertical
4958	26.15	26.89	7.59	31.68	28.95	54	-25.05	Horizontal
7437	25.41	28.35	10.64	31.59	32.81	54	-21.19	Horizontal
9916	25.83	32.65	11.24	30.56	39.16	54	-14.84	Horizontal
12395	*					54		Horizontal
14874	*					54		Horizontal

4. BAND EDGE TEST

4.1 LIMIT


According to §15.249(d), Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

4.2 TEST PROCEDURE

- a. The EUT is placed on a turntable, which is 1.5m above ground plane.
- b. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
Use the following spectrum analyzer settings:
 - c. Span = wide enough to fully capture the emission being measured, RBW = 1 MHz, VBW \geq RBW, Sweep = auto, Detector function = peak, Trace = max hold
Follow the guidelines in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc.
- d. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. Set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the duty cycle per channel of the hopping signal is less than 100 ms, then the reading obtained with
- e. the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{duty cycle}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

4.3 TEST SETUP


Radiated Emission Test-Up Frequency Above 1GHz



4.4 TEST RESULTS


Low CH (GFSK)

Polarization: Horizontal



Freq.	Note	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBμV	dB	dBμV/m	dBμV/m	dB
2371.40	S	Peak	58.78	0.72	59.50	74	-14.50
2371.40	S	Average	39.49	0.72	40.21	54	-13.79
2390.00	E	Peak	54.82	0.92	55.74	74	-18.26
2390.00	E	Average	36.37	0.92	37.29	54	-16.71
2400.00	E	Peak	66.54	1.01	67.55	74	-6.45
2400.00	E	Average	41.11	1.01	42.12	54	-11.88


Polarization: Vertical



Freq. MHz	Note F/H/E/S	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2371.90	S	Peak	54.06	0.72	54.78	74	-19.22
2371.90	S	Average	38.18	0.72	38.90	54	-15.10
2390.00	E	Peak	48.29	0.92	49.21	74	-24.79
2390.00	E	Average	35.34	0.92	36.26	54	-17.74
2400.00	E	Peak	58.87	1.01	59.88	74	-14.12
2400.00	E	Average	38.88	1.01	39.89	54	-14.11


High CH(GFSK)

Polarization: Horizontal



Freq.	Note	Detector	Spectrum	Factor	Actual	Limit	Margin
MHz	F/H/E/S	Mode	Reading Level	dB	FS	@3m	dB
		PK/QP/AV	dBµV		dBµV/m	dBµV/m	
2483.50	E	Peak	66.43	1.16	67.59	74	-6.41
2483.50	E	Average	41.78	1.16	42.94	54	-11.06
2485.20	S	Peak	67.01	1.16	68.17	74	-5.83
2485.20	S	Average	42.59	1.16	43.75	54	-10.25

Polarization: Vertical



Freq. MHz	Note F/H/E/S	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2483.50	E	Peak	58.93	1.16	60.09	74	-13.91
2483.50	E	Average	40.16	1.16	41.32	54	-12.68
2485.40	S	Peak	59.61	1.15	60.77	74	-13.23
2485.40	S	Average	40.16	1.15	41.31	54	-12.69

5. 20 DB BANDWIDTH TEST


5.1 LIMIT

According to 15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation

5.2 TEST PROCEDURE

- Check the calibration of the measuring instrument using either an internal calibrator or a
- a. known signal from an external generator
 - b. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
 - c. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.


5.3 TEST SETUP





5.4 TEST RESULTS

Temperature:	25°C	Relative Humidity:	50%
Test Mode:	GFSK	Test Voltage:	DC 1.5V

Frequency	20dB Bandwidth (MHz)	Result
2404 MHz	2.207	PASS
2444 MHz	2.214	PASS
2479 MHz	2.236	PASS





6. ANTENNA REQUIREMENT

6.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2 EUT ANTENNA

The antennas used for this product are Integral antenna and other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 1.0dBi.

※※※※※END OF THE REPORT※※※※※