




# RF TEST REPORT



Report No.: 17070235-FCC-R1

Supersede Report No.: N/A

Applicant	SMT TELECOMM HK LIMITED	
Product Name	Mobile Phone	
Model No.	X4	
Serial No.	N/A	
Test Standard	FCC Part 22(H):2016 ;FCC Part 24(E):2016; ANSI/TIA-603-D: 2010	
Test Date	April 1 to April 12, 2017	
Issue Date	April 13, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	17070235-FCC-R1
Page	3 of 76

This page has been left blank intentionally.

# CONTENTS

<b>1. REPORT REVISION HISTORY .....</b>	<b>5</b>
<b>2. CUSTOMER INFORMATION .....</b>	<b>5</b>
<b>3. TEST SITE INFORMATION.....</b>	<b>5</b>
<b>4. EQUIPMENT UNDER TEST (EUT) INFORMATION.....</b>	<b>6</b>
<b>5. TEST SUMMARY .....</b>	<b>9</b>
<b>6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....</b>	<b>11</b>
6.1 RF EXPOSURE (SAR).....	11
6.2 RF OUTPUT POWER.....	12
6.3 PEAK-AVERAGE RATIO.....	23
6.4 OCCUPIED BANDWIDTH.....	26
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS .....	37
6.6 SPURIOUS RADIATED EMISSIONS.....	50
6.7 BAND EDGE.....	56
6.8 FREQUENCY STABILITY .....	66
<b>ANNEX A. TEST INSTRUMENT.....</b>	<b>70</b>
<b>ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....</b>	<b>72</b>
<b>ANNEX C.II. EUT OPERATING CONKITIONS.....</b>	<b>74</b>
<b>ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST .....</b>	<b>75</b>
<b>ANNEX E. DECLARATION OF SIMILARITY.....</b>	<b>76</b>

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070235-FCC-R1	NONE	Original	April 13, 2017

## 2. Customer information

Applicant Name	SMT TELECOMM HK LIMITED
Applicant Add	Unit C 8/F, CHARMHILL CTR 50 HILLWOOD RD TST KL
Manufacturer	SMT TELECOMM HK LIMITED
Manufacturer Add	Unit C 8/F, CHARMHILL CTR 50 HILLWOOD RD TST KL

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen(ICP-03A1)

## 4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	X4
Serial Model:	N/A
Date EUT received:	March 31, 2017
Test Date(s):	April 1 to April 12, 2017
Equipment Category :	PCE
Antenna Gain:	GSM850: 0.7dBi PCS1900: 0.5dBi UMTS-FDD Band V: 0.7dBi UMTS-FDD Band II: 0.5dBi Bluetooth/WIFI/BLE: 1.0dBi
Antenna Type:	PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK UMTS-FDD: QPSK 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, $\pi$ /4DQPSK, 8DPSK BLE: GFSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz

Test Report	17070235-FCC-R1
Page	7 of 76

	GSM Voice:GSM850: 32.31 dBm
	PCS1900: 30.98 dBm
	GPRS:GSM850: 32.27 dBm
	PCS1900: 30.95 dBm
	EGPRS(MCS1):GSM850: 32.24 dBm
Maximum Conducted	PCS1900:30.94 dBm
AV Power to Antenna:	RMC:UMTS-FDD Band 5: 23.49 dBm
	UMTS-FDD Band 2: 21.85 dBm
	HSUPA:UMTS-FDD Band 5: 22.63 dBm
	UMTS-FDD Band 2: 21.10 dBm
	HSDPA:UMTS-FDD Band 5: 22.63 dBm
	UMTS-FDD Band 2: 21.13 dBm
	GSM Voice:GSM850: 30.81 dBm / ERP
	PCS1900: 31.48 dBm / EIRP
	GPRS:GSM850: 30.77 dBm / ERP
	PCS1900: 31.45 dBm / EIRP
	EGPRS(MCS1):GSM850: 30.74 dBm / ERP
ERP/EIRP:	PCS1900: 31.44 dBm / EIRP
	RMC:UMTS-FDD Band 5: 21.99 dBm / ERP
	UMTS-FDD Band 2: 22.35 dBm / EIRP
	HSDPA:UMTS-FDD Band 5: 21.13 dBm / ERP
	UMTS-FDD Band 2: 21.63 dBm / EIRP
	HSUPA:UMTS-FDD Band 5: 21.13 dBm / ERP
	UMTS-FDD Band 2: 21.60 dBm / EIRP
	GSM 850: 124CH
	PCS1900: 299CH
	UMTS-FDD Band V: 102CH
	UMTS-FDD Band II: 277CH
Number of Channels:	WIFI :802.11b/g/n(20M): 11CH
	WIFI :802.11n(40M): 7CH
	Bluetooth: 79CH
	BLE: 40CH

Port: USB Port, Earphone Port

Adapter:  
Model: PCX4  
Input: AC100-240V~50/60Hz,0.15A  
Output: DC 5.0V,500mA  
Input Power:  
Battery:  
Model: BPX4  
Spec : 3.7V,1300mAh  
voltage: 4.2V

Trade Name : N/A

GPRS/ EGPRS Multi-slot class 8/10/12

FCC ID: 2AIMEX4



## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ;	RF Output Power	Compliance
§ 24.232 (d) ;	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238;	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a);	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a);	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a);	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235;	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

## Measurement Uncertainty

Parameter	Uncertainty
AC Power Line Conducted Emissions (150kHz~30MHz)	$\pm 3.11\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.12\text{dB}$
Radiated Emission(1GHz~6GHz)	$\pm 5.34\text{dB}$

## **6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS**

### 6.1 RF Exposure (SAR)

Test Result: Pass

The EUT is a portable device, thus requires SAR evaluation;


Please refer to RF Exposure Evaluation Report: 17070235-FCC-H.

## 6.2 RF Output Power

Temperature	23 °C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	April 06, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	<input checked="" type="checkbox"/>
§24.232 (c)	b)	EIRP:33dBm	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Base Station                      EUT</p>
------------	--

Test Procedure	<p>For Conducted Power:</p> <ul style="list-style-type: none"> <li>- The transmitter output port was connected to base station.</li> <li>- Set EUT at maximum power through base station.</li> <li>- Select lowest, middle, and highest channels for each band and different test mode.</li> </ul> <p>For ERP/EIRP:</p> <p>According with KDB 971168 v02r02</p> <ul style="list-style-type: none"> <li>- The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.</li> <li>- The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.</li> <li>- The frequency range up to tenth harmonic of the fundamental frequency was investigated.</li> </ul>
----------------	---

	<ul style="list-style-type: none"> <li>- Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.</li> <li>- Spurious emissions in dB = 10 log (TX power in Watts/0.001) – the absolute level</li> <li>- Spurious attenuation limit in dB = 43 + 10 Log10 (power out in Watts).</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

**Test Data**     Yes                       N/A  
**Test Plot**     Yes (See below)             N/A

## Conducted Power

### GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	<b>32.31</b>	32.22	31.96	32±1	<b>30.98</b>	30.49	30.11	30.5±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	<b>32.27</b>	32.21	31.94	32±1	<b>30.95</b>	30.44	30.09	30.5±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	31.66	31.49	31.5	31.5±1	30.43	30.05	29.81	30±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	29.63	29.27	28.95	29±1	28.59	28.64	28.63	28.5±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	<b>32.24</b>	32.15	31.93	32±1	<b>30.94</b>	30.42	30.08	30.5±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	31.48	31.48	31.46	31.5±1	30.41	30.03	29.81	30±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	29.53	29.1	28.78	29±1	28.56	28.61	28.58	28.5±1

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

## UMTS Mode:

### UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	<b>23.49</b>	23±1
	4175	835	22.54	23±1
	4233	846.6	22.95	23±1
HSDPA Subtest1	4132	826.4	22.35	22±1
	4175	835	21.95	22±1
	4233	846.6	22.14	22±1
HSDPA Subtest2	4132	826.4	22.36	22±1
	4175	835	21.87	22±1
	4233	846.6	21.96	22±1
HSDPA Subtest3	4132	826.4	22.03	22±1
	4175	835	21.53	22±1
	4233	846.6	21.85	22±1
HSDPA Subtest4	4132	826.4	<b>22.63</b>	22±1
	4175	835	21.90	22±1
	4233	846.6	22.34	22±1
HSUPA Subtest1	4132	826.4	22.18	22±1
	4175	835	21.73	22±1
	4233	846.6	21.99	22±1
HSUPA Subtest2	4132	826.4	22.38	22±1
	4175	835	21.96	22±1
	4233	846.6	22.11	22±1
HSUPA Subtest3	4132	826.4	22.54	22±1
	4175	835	21.90	22±1
	4233	846.6	22.28	22±1
HSUPA Subtest4	4132	826.4	<b>22.63</b>	22±1
	4175	835	22.05	22±1
	4233	846.6	22.38	22±1
HSUPA Subtest5	4132	826.4	22.16	22±1
	4175	835	21.59	22±1
	4233	846.6	21.83	22±1

## UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	<b>21.85</b>	21.3±1
	9400	1880	21.71	21.3±1
	9538	1907.6	21.83	21.3±1
HSDPA Subtest1	9262	1852.4	20.99	21.3±1
	9400	1880	20.98	21.3±1
	9538	1907.6	20.96	21.3±1
HSDPA Subtest2	9262	1852.4	21.05	21.3±1
	9400	1880	21.03	21.3±1
	9538	1907.6	21.00	21.3±1
HSDPA Subtest3	9262	1852.4	20.86	21.3±1
	9400	1880	20.88	21.3±1
	9538	1907.6	20.82	21.3±1
HSDPA Subtest4	9262	1852.4	21.01	21.3±1
	9400	1880	21.10	21.3±1
	9538	1907.6	<b>21.13</b>	21.3±1
HSUPA Subtest1	9262	1852.4	20.95	21.3±1
	9400	1880	20.99	21.3±1
	9538	1907.6	20.93	21.3±1
HSUPA Subtest2	9262	1852.4	21.06	21.3±1
	9400	1880	<b>21.10</b>	21.3±1
	9538	1907.6	21.05	21.3±1
HSUPA Subtest3	9262	1852.4	20.88	21.3±1
	9400	1880	20.85	21.3±1
	9538	1907.6	20.87	21.3±1
HSUPA Subtest4	9262	1852.4	21.05	21.3±1
	9400	1880	21.07	21.3±1
	9538	1907.6	21.06	21.3±1
HSUPA Subtest5	9262	1852.4	20.70	21.3±1
	9400	1880	20.75	21.3±1
	9538	1907.6	20.79	21.3±1



## ERP & EIRP

### GSM Voice

#### ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	24.54	V	6.8	0.53	<b>30.81</b>	38.45
824.2	22.97	H	6.8	0.53	29.24	38.45
836.6	24.45	V	6.8	0.53	30.72	38.45
836.6	22.88	H	6.8	0.53	29.15	38.45
848.8	24.09	V	6.9	0.53	30.46	38.45
848.8	22.41	H	6.9	0.53	28.78	38.45

#### EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	24.45	V	7.88	0.85	<b>31.48</b>	33
1850.2	22.84	H	7.88	0.85	29.87	33
1880	23.96	V	7.88	0.85	30.99	33
1880	22.4	H	7.88	0.85	29.43	33
1909.8	23.6	V	7.86	0.85	30.61	33
1909.8	22.14	H	7.86	0.85	29.15	33

**GPRS:**

**ERP for Cellular Band (Part 22H)**

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	24.5	V	6.8	0.53	<b>30.77</b>	38.45
824.2	22.9	H	6.8	0.53	29.17	38.45
836.6	24.44	V	6.8	0.53	30.71	38.45
836.6	22.83	H	6.8	0.53	29.10	38.45
848.8	24.07	V	6.9	0.53	30.44	38.45
848.8	22.32	H	6.9	0.53	28.69	38.45

**EIRP for PCS Band (Part 24E)**

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	24.42	V	7.88	0.85	<b>31.45</b>	33
1850.2	22.65	H	7.88	0.85	29.68	33
1880	23.91	V	7.88	0.85	30.94	33
1880	22.34	H	7.88	0.85	29.37	33
1909.8	23.58	V	7.86	0.85	30.59	33
1909.8	22.08	H	7.86	0.85	29.09	33

**EGPRS (MCS1):**

**ERP for Cellular Band (Part 22H)**

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	24.47	V	6.8	0.53	<b>30.74</b>	38.45
824.2	22.94	H	6.8	0.53	29.21	38.45
836.6	24.38	V	6.8	0.53	30.65	38.45
836.6	22.89	H	6.8	0.53	29.16	38.45
848.8	24.06	V	6.9	0.53	30.43	38.45
848.8	23.36	H	6.9	0.53	29.73	38.45

**EIRP for PCS Band (Part 24E)**

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	24.41	V	7.88	0.85	<b>31.44</b>	33
1850.2	22.68	H	7.88	0.85	29.71	33
1880	23.89	V	7.88	0.85	30.92	33
1880	22.43	H	7.88	0.85	29.46	33
1909.8	23.57	V	7.86	0.85	30.58	33
1909.8	21.93	H	7.86	0.85	28.94	33

## RMC

### ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	15.72	V	6.8	0.53	<b>21.99</b>	38.45
826.4	14.76	H	6.8	0.53	21.03	38.45
835	14.77	V	6.8	0.53	21.04	38.45
835	13.89	H	6.8	0.53	20.16	38.45
846.6	15.08	V	6.9	0.53	21.45	38.45
846.6	14.15	H	6.9	0.53	20.52	38.45

### EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	15.32	V	7.88	0.85	<b>22.35</b>	33
1852.4	14.4	H	7.88	0.85	21.43	33
1880	15.18	V	7.88	0.85	22.21	33
1880	14.32	H	7.88	0.85	21.35	33
1907.6	15.32	V	7.86	0.85	22.33	33
1907.6	14.39	H	7.86	0.85	21.40	33

## HSDPA

### ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	14.86	V	6.8	0.53	<b>21.13</b>	38.45
826.4	13.96	H	6.8	0.53	20.23	38.45
835	14.18	V	6.8	0.53	20.45	38.45
835	13.24	H	6.8	0.53	19.51	38.45
846.6	14.47	V	6.9	0.53	20.84	38.45
846.6	13.48	H	6.9	0.53	19.85	38.45

### EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	14.52	V	7.88	0.85	21.55	33
1852.4	13.58	H	7.88	0.85	20.61	33
1880	14.57	V	7.88	0.85	21.60	33
1880	13.7	H	7.88	0.85	20.73	33
1907.6	14.62	V	7.86	0.85	<b>21.63</b>	33
1907.6	13.74	H	7.86	0.85	20.75	33

## HSUPA

### ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	14.86	V	6.8	0.53	<b>21.13</b>	38.45
826.4	13.94	H	6.8	0.53	20.21	38.45
835	14.28	V	6.8	0.53	20.55	38.45
835	13.29	H	6.8	0.53	19.56	38.45
846.6	14.51	V	6.9	0.53	20.88	38.45
846.6	13.55	H	6.9	0.53	19.92	38.45

### EIRP for UMTS-FDD Band II (Part 24E)


Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	14.53	V	7.88	0.85	21.56	33
1852.4	13.58	H	7.88	0.85	20.61	33
1880	14.57	V	7.88	0.85	<b>21.60</b>	33
1880	13.65	H	7.88	0.85	20.68	33
1907.6	14.53	V	7.86	0.85	21.54	33
1907.6	13.57	H	7.86	0.85	20.58	33

### 6.3 Peak-Average Ratio

Temperature	23 °C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	April 06, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13dB.	<input checked="" type="checkbox"/>



Test Procedure	<p><b>According with KDB 971168 v02r02</b></p> <p><b>5.7.2 Alternate procedure for PAPR</b></p> <p><b>5.1.2 Peak power measurements with a peak power meter</b></p> <p>The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector.</p> <p><b>5.2.3 Average power measurement with average power meter</b></p> <p>As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions</p> <p>If the EUT can be configured to transmit continuously (i.e., the burst duty cycle <math>\geq 98\%</math>) and at all times the EUT is transmitting at its maximum output</p>
----------------	--

	<p>power level, then a conventional wide-band RF power meter can be used.</p> <p>If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle &lt; 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than <math>\pm 2</math> percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to <math>10\log(1/\text{duty cycle})</math></p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

**Test Data**     Yes                       N/A  
**Test Plot**     Yes (See below)             N/A



**GSM : GSM 1900 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	31.49	30.98	0.51
1880	30.96	30.49	0.47
1909.8	30.53	30.11	0.42

**GPRS 1900 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	31.42	30.95	0.47
1880	30.85	30.44	0.41
1909.8	30.45	30.19	0.26

**RMC : UMTS-FDD Band 2 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	22.48	21.85	0.63
1880	21.99	21.71	0.28
1907.6	22.26	21.83	0.43

**HSDPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	21.43	20.99	0.44
1880	21.45	20.98	0.47
1907.6	21.47	20.96	0.51


**HSUPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)**

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	21.32	20.95	0.37
1880	21.37	20.99	0.38
1907.6	21.35	20.93	0.42

## 6.4 Occupied Bandwidth

Temperature	23 °C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	April 06&11, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238	a)	99% Occupied Bandwidth(kHz)	<input checked="" type="checkbox"/>
	b)	26 dB Bandwidth(kHz)	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Base Station      Spectrum Analyzer      EUT</p>		
Test Procedure	<ul style="list-style-type: none"> <li>- The EUT was connected to Spectrum Analyzer and Base Station via power divider.</li> <li>- The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data     Yes       N/A

Test Plot     Yes (See below)       N/A

**GSM Voice:**

**Cellular Band (Part 22H) result**

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	245.8794	317.181
190	836.6	242.9834	317.990
251	848.8	246.0881	318.080

**PCS Band (Part 24E) result**

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	245.5327	320.151
661	1880.0	246.9922	318.919
810	1909.8	244.3045	318.017

**GPRS:**

**Cellular Band (Part 22H) result**

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	249.6972	317.694
190	836.6	247.7873	324.140
251	848.8	244.6700	318.118

**PCS Band (Part 24E) result**

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	247.2338	320.983
661	1880.0	248.2937	318.254
810	1909.8	246.9940	318.039

**EGPRS (MCS 1):**

**Cellular Band (Part 22H) result**

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	243.7581	320.819
190	836.6	250.0005	319.336
251	848.8	243.3378	319.207

**PCS Band (Part 24E) result**

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	246.7776	322.824
661	1880.0	245.7287	318.122
810	1909.8	251.5396	320.388

**RMC:**

**UMTS-FDD Band V (Part 22H)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1389	4.706
4175	835.0	4.1512	4.722
4233	846.6	4.1265	4.730

**UMTS-FDD Band II (Part 24E)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1530	4.725
9400	1880.0	4.1499	4.723
9538	1907.6	4.1614	4.705

**HSDPA:**

**UMTS-FDD Band V (Part 22H)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1286	4.707
4175	835.0	4.1498	4.703
4233	846.6	4.1332	4.722

**UMTS-FDD Band II (Part 24E)**

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1593	4.723
9400	1880.0	4.1580	4.723
9538	1907.6	4.1604	4.718

**HSUPA:**

**UMTS-FDD Band V (Part 22H)**


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1308	4.714
4175	835.0	4.1639	4.722
4233	846.6	4.1306	4.704

**UMTS-FDD Band II (Part 24E)**


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1429	4.703
9400	1880.0	4.1804	4.714
9538	1907.6	4.1594	4.715

### Test Plots


#### GSM Voice:




### GPRS:




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz




PCS 1900 BW - Mid CH 1880MHz




PCS 1900 BW - High CH 1909.8MHz




### EGPRS (MCS1):




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz




PCS 1900 BW - Mid CH 1880MHz




PCS 1900 BW - High CH 1909.8MHz


RMC:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz




Band V BW - High CH 846.4 MHz



Band II BW - Low CH 1852.4MHz




Band II BW - Mid CH 1880MHz




Band II BW - High CH 1907.6MHz


**HSDPA:**




**Band V BW - Low CH 826.6 MHz**




**Band V BW - Mid CH 835.0 MHz**




**Band V BW - High CH 846.4 MHz**



**Band II BW - Low CH 1852.4MHz**




**Band II BW - Mid CH 1880MHz**




**Band II BW - High CH 1907.6MHz**


HSUPA:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz




Band V BW - High CH 846.4 MHz



Band II BW - Low CH 1852.4MHz



Band II BW - Mid CH 1880MHz




Band II BW - High CH 1907.6MHz

## 6.5 Spurious Emissions at Antenna Terminals

Temperature	24 °C
Relative Humidity	53%
Atmospheric Pressure	1011mbar
Test date :	April 11, 2017
Tested By :	Loren Luo

### Requirement(s):


Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log(P)$ dB	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;"> <span style="margin-right: 100px;">Base Station</span> <span style="margin-right: 100px;">Spectrum Analyzer</span> <span>EUT</span> </p>		
Test Procedure	<ul style="list-style-type: none"> <li>- The EUT was connected to Spectrum Analyzer and Base Station via power divider.</li> <li>- The Band Edges of low and high channels for the highest RF powers were measured.</li> <li>- Setting RBW as roughly BW/100.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data     Yes       N/A  
 Test Plot     Yes (See below)       N/A


**Test Plots**

**GSM Voice:**


**Cellular Band (Part 22H) result**




**GSM 850 - Low Channel-1**




**GSM 850 - Low Channel-2**




**GSM 850 Middle Channel-1**



**GSM 850 Middle Channel-2**




**GSM 850 - High Channel-1**




**GSM 850 - High Channel-2**

### PCS Band (Part24E) result




**GPRS:**


**Cellular Band (Part 22H) result**




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2




### PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2




PCS1900 - High Channel-1




PCS 1900 - High Channel-2


**EGPRS (MCS 1):  
Cellular Band (Part 22H) result**




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2

### PCS Band (Part24E) result




RMC


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2


### UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

HSDPA:


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2


### UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

HSUPA:


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1



Band V - High Channel-2



### UMTS-FDD Band II (Part 24E)




## 6.6 Spurious Radiated Emissions

Temperature	24 °C
Relative Humidity	53%
Atmospheric Pressure	1011mbar
Test date :	April 11, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	<input checked="" type="checkbox"/>

Test setup	
------------	--

Test Procedure	<ol style="list-style-type: none"> <li>The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.</li> <li>The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.</li> <li>Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. Sample Calculation: EUT Field Strength = Raw Amplitude (dBµV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)</li> </ol>
----------------	---

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A  
Test Plot  Yes (See below)  N/A

## Cellular Band (Part 22H) result

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-44.21	V	7.95	0.78	-37.04	-13	-24.04
1648.4	-44.26	H	7.95	0.78	-37.09	-13	-24.09
327.6	-52.86	V	6.4	0.26	-46.72	-13	-33.72
604.3	-52.98	H	6.8	0.37	-46.55	-13	-33.55

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-43.65	V	7.95	0.78	-36.48	-13	-23.48
1673.2	-44.51	H	7.95	0.78	-37.34	-13	-24.34
326.9	-53.26	V	6.4	0.26	-47.12	-13	-34.12
607.3	-52.86	H	6.8	0.37	-46.43	-13	-33.43

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-43.59	V	7.95	0.78	-36.42	-13	-23.42
1697.6	-44.28	H	7.95	0.78	-37.11	-13	-24.11
325.4	-53.17	V	6.4	0.26	-47.03	-13	-34.03
605.2	-52.65	H	6.8	0.37	-46.22	-13	-33.22

#### Note:

- 1, The testing has been conformed to  $10 \times 848.8 \text{ MHz} = 8,488 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## PCS Band (Part24E) result

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-48.67	V	10.25	2.73	-41.15	-13	-28.15
3700.4	-49.51	H	10.25	2.73	-41.99	-13	-28.99
328.7	-53.64	V	6.4	0.26	-47.5	-13	-34.5
605.2	-54.21	H	6.8	0.37	-47.78	-13	-34.78

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.67	V	10.25	2.73	-41.15	-13	-28.15
3760	-49.56	H	10.25	2.73	-42.04	-13	-29.04
324.1	-53.87	V	6.4	0.26	-47.73	-13	-34.73
601.8	-53.84	H	6.8	0.37	-47.41	-13	-34.41

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-48.76	V	10.36	2.73	-41.13	-13	-28.13
3819.6	-49.85	H	10.36	2.73	-42.22	-13	-29.22
323.5	-53.74	V	6.4	0.26	-47.6	-13	-34.6
608.5	-52.13	H	6.8	0.37	-45.7	-13	-32.7

#### Note:

- 1, The testing has been conformed to  $10 \times 1909.8 \text{ MHz} = 19,098 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## UMTS-FDD Band V (Part 22H)

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-46.87	V	7.95	0.78	-39.7	-13	-26.7
1652.8	-46.51	H	7.95	0.78	-39.34	-13	-26.34
324.1	-53.26	V	6.4	0.26	-47.12	-13	-34.12
607.3	-53.47	H	6.8	0.37	-47.04	-13	-34.04

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-46.59	V	7.95	0.78	-39.42	-13	-26.42
1670	-45.86	H	7.95	0.78	-38.69	-13	-25.69
326.9	-53.21	V	6.4	0.26	-47.07	-13	-34.07
605.4	-52.98	H	6.8	0.37	-46.55	-13	-33.55

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-46.88	V	7.95	0.78	-39.71	-13	-26.71
1693.2	-46.12	H	7.95	0.78	-38.95	-13	-25.95
326.7	-52.96	V	6.4	0.26	-46.82	-13	-33.82
600.2	-53.46	H	6.8	0.37	-47.03	-13	-34.03

**Note:**

- 1, The testing has been conformed to  $10 \times 846.6 \text{ MHz} = 8,466 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

## UMTS-FDD Band II (Part 24E)

### Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-49.53	V	10.25	2.73	-42.01	-13	-29.01
3704.8	-50.21	H	10.25	2.73	-42.69	-13	-29.69
325.8	-53.16	V	6.4	0.26	-47.02	-13	-34.02
603.7	-53.64	H	6.8	0.37	-47.21	-13	-34.21

### Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-49.87	V	10.25	2.73	-42.35	-13	-29.35
3760	-49.86	H	10.25	2.73	-42.34	-13	-29.34
330.2	-52.64	V	6.4	0.26	-46.5	-13	-33.5
606.1	-54.31	H	6.8	0.37	-47.88	-13	-34.88

### High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-48.56	V	10.36	2.73	-40.93	-13	-27.93
3815.2	-50.13	H	10.36	2.73	-42.5	-13	-29.5
324.7	-54.61	V	6.4	0.26	-48.47	-13	-35.47
608.5	-55.28	H	6.8	0.37	-48.85	-13	-35.85


**Note:**

- 1, The testing has been conformed to  $10 \times 1907.6 \text{ MHz} = 19,076 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

## 6.7 Band Edge

Temperature	24 °C
Relative Humidity	53%
Atmospheric Pressure	1011mbar
Test date :	April 11, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	<input checked="" type="checkbox"/>
Test setup	 <p>The diagram shows a Base Station (green box) and a Spectrum Analyzer (green box) connected to an EUT (blue box) via a power divider (black box). The Base Station and Spectrum Analyzer are connected to the power divider, which then splits the signal to the EUT.</p>		
Procedure	<ul style="list-style-type: none"> <li>- The EUT was connected to Spectrum Analyzer and Base Station via power divider.</li> <li>- The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data     Yes       N/A

Test Plot     Yes (See below)       N/A



**GSM Voice:**

**Cellular Band (Part 22H) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-18.45	-13
849.0025	-17.39	-13

**PCS Band (Part24E) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-16.07	-13
1910.0225	-14.40	-13

**GPRS:**

**Cellular Band (Part 22H) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9800	-16.50	-13
849.0200	-17.11	-13

**PCS Band (Part24E) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-15.23	-13
1910.0250	-15.17	-13

**EGPRS (MCS1):**

**Cellular Band (Part 22H) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9989	-14.69	-13
849.0025	-17.35	-13

**PCS Band (Part24E) result**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-15.09	-13
1910.0200	-14.87	-13

**RMC:**

**UMTS-FDD Band V (Part 22H)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
824.000	-28.32	-13
849.275	-25.92	-13

**UMTS-FDD Band II (Part 24E)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.925	-17.29	-13
1910.075	-20.82	-13

**HSDPA:**

**UMTS-FDD Band V (Part 22H)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.550	-28.12	-13
849.200	-25.92	-13

**UMTS-FDD Band II (Part 24E)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.900	-17.13	-13
1910.050	-14.89	-13

**HSUPA:**

**UMTS-FDD Band V (Part 22H)**


Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.825	-28.97	-13
849.875	-26.67	-13

**UMTS-FDD Band II (Part 24E)**

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.925	-16.48	-13
1910.025	-21.66	-13


### GSM Voice:

### Test Plots




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(3.17/3)=4.0+0.2=4.2\text{dB}$




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(3.18/3)=4.0+0.3=4.3\text{dB}$



PCS Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(3.20/3)=4.5+0.3=4.8\text{dB}$




PCS Band - High Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(3.18/3)=4.5+0.3=4.8\text{dB}$


**GPRS:**

**Test Plots**




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
(3.17/3)=4.0+0.2=4.2dB




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log  
(3.18/3)=4.0+0.3=4.3dB



PCS Band - Low Channel

Note: Offset=Cable loss (4.5) + 10log  
(3.20/3)=4.5+0.3=4.8dB



PCS Band - High Channel


Note: Offset=Cable loss (4.5) + 10log  
(3.18/3)=4.5+0.3=4.8dB

### EGPRS (MCS1):

#### Test Plots


<p>Agilent 14:25:08 Apr 11, 2017 R T</p> <p>Ref 40 dBm Atten 50 dB Mkr1 823.9975 MHz -14.69 dBm</p> <p>Peak Log 10 dB/Offset 4.3 dB DI -13.0 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 824 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 114.4 ms (401 pts) Span 1 MHz</p>	<p>Agilent 14:26:15 Apr 11, 2017 R T</p> <p>Ref 40 dBm Atten 50 dB Mkr1 849.0075 MHz -17.35 dBm</p> <p>Peak Log 10 dB/Offset 4.3 dB DI -13.0 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 849 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 114.4 ms (401 pts) Span 1 MHz</p>
<p>Cellular Band - Low Channel</p>	<p>Cellular Band - High Channel</p>
<p>Note: Offset=Cable loss (4.0) + 10log (3.20/3)=4.0+0.3=4.3dB</p>	<p>Note: Offset=Cable loss (4.0) + 10log (3.19/3)=4.0+0.3=4.3dB</p>
<p>Agilent 13:28:13 Apr 11, 2017 R T</p> <p>Ref 40 dBm Atten 50 dB Mkr1 1.8499975 GHz -15.09 dBm</p> <p>Peak Log 10 dB/Offset 4.8 dB DI -13.0 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 1.85 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 114.4 ms (401 pts) Span 1 MHz</p>	<p>Agilent 13:23:39 Apr 11, 2017 R T</p> <p>Ref 40 dBm Atten 50 dB Mkr1 1.9100175 GHz -14.87 dBm</p> <p>Peak Log 10 dB/Offset 4.8 dB DI -13.0 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 1.91 GHz #Res BW 3 kHz #VBW 10 kHz Sweep 114.4 ms (401 pts) Span 1 MHz</p>
<p>PCS Band - Low Channel</p>	<p>PCS Band - High Channel</p>
<p>Note: Offset=Cable loss (4.5) + 10log (3.22/3)=4.5+0.3=4.8dB</p>	<p>Note: Offset=Cable loss (4.5) + 10log (3.20/3)=4.5+0.3=4.8dB</p>

**RMC:**




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(47.06/30)=4.0+2.0=6.0$  dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(47.30/30)=4.0+2.0=6.0$  dB



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log  
 $(47.25/30)=4.5+2.0=6.5$  dB



UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log  
 $(47.05/30)=4.5+2.0=6.5$  dB

**HSDPA:**




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(47.07/30)=4.0+2.0=6.0$  dB



UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(47.22/30)=4.0+2.0=6.0$  dB



UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log  
 $(47.23/30)=4.0+2.5=6.5$  dB





UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log  
 $(47.18/30)=4.0+2.5=6.5$  dB



**HSUPA:**





UMTS-FDD Band V - Low Channel

UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log  
 $(47.14/30)=4.0+2.0=6.0$  dB

Note: Offset=Cable loss (4.0) + 10log  
 $(47.04/30)=4.0+2.0=6.0$  dB



UMTS-FDD Band II - Low Channel

UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log  
 $(47.03/30)=4.5+2.0=6.5$  dB

Note: Offset=Cable loss (4.5) + 10log  
 $(47.15/30)=4.5+2.0=6.5$  dB

## 6.8 Frequency Stability

Temperature	23 °C
Relative Humidity	58%
Atmospheric Pressure	1006mbar
Test date :	April 06, 2017
Tested By :	Loren Luo

### Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235	a)	<p>According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:</p> <p>Frequency Tolerance for Transmitters in the Public Mobile Services</p> <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th> <th>Base, fixed (ppm)</th> <th>Mobile ≤ 3 watts ( m)</th> <th>Mobile ≤ 3 watts (ppm)</th> </tr> </thead> <tbody> <tr> <td>25 to 50</td> <td>20.0</td> <td>20.0</td> <td>50.0</td> </tr> <tr> <td>50 to 450</td> <td>5.0</td> <td>5.0</td> <td>50.0</td> </tr> <tr> <td>45 to 512</td> <td>2.5</td> <td>5.0</td> <td>.0</td> </tr> <tr> <td>821 to 896</td> <td>1.5</td> <td>2.5</td> <td>2.5</td> </tr> <tr> <td>928 to 929</td> <td>5.0</td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>929 to 960.</td> <td>1.5</td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>2110 to 2220</td> <td>10.0</td> <td>N/A</td> <td>N/A</td> </tr> </tbody> </table> <p>According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.</p>	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts ( m)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	45 to 512	2.5	5.0	.0	821 to 896	1.5	2.5	2.5	928 to 929	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	<input checked="" type="checkbox"/>
		Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts ( m)	Mobile ≤ 3 watts (ppm)																														
		25 to 50	20.0	20.0	50.0																														
		50 to 450	5.0	5.0	50.0																														
		45 to 512	2.5	5.0	.0																														
		821 to 896	1.5	2.5	2.5																														
		928 to 929	5.0	N/A	N/A																														
		929 to 960.	1.5	N/A	N/A																														
2110 to 2220	10.0	N/A	N/A																																
Test setup	 <p style="text-align: center;"> <span>Base Station</span>      <span>EUT</span>  <span>Thermal Chamber</span> </p>																																		

Test Report	17070235-FCC-R1
Page	67 of 76

Procedure	<p>A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage.</p> <p>Limit: The frequency stability of the transmitter shall be maintained within <math>\pm 0.00025\%</math> (<math>\pm 2.5\text{ppm}</math>) of the center frequency.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data     Yes                       N/A

Test Plot     Yes (See below)             N/A

**GSM Voice:**

**Cellular Band (Part 22H) result**

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	19	0.0227	2.5
0		15	0.0179	2.5
10		19	0.0227	2.5
20		17	0.0203	2.5
30		15	0.0179	2.5
40		21	0.0251	2.5
50		18	0.0215	2.5
55		16	0.0191	2.5
25	4.2	16	0.0191	2.5
	3.5	12	0.0143	2.5

**PCS Band (Part 24E) result**

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	15	0.0080	2.5
0		16	0.0085	2.5
10		18	0.0096	2.5
20		21	0.0112	2.5
30		16	0.0085	2.5
40		15	0.0080	2.5
50		11	0.0059	2.5
55		20	0.0106	2.5
25	4.2	21	0.0112	2.5
	3.5	18	0.0096	2.5

RMC:

**UMTS-FDD Band V (Part 22H)**

Middle Channel, $f_o = 835$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0240	2.5
0		15	0.0180	2.5
10		17	0.0204	2.5
20		15	0.0180	2.5
30		17	0.0204	2.5
40		11	0.0132	2.5
50		16	0.0192	2.5
55		20	0.0240	2.5
25	4.2	16	0.0192	2.5
	3.5	14	0.0168	2.5

**UMTS-FDD Band II (Part 24E)**

Middle Channel, $f_o = 1880$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	15	0.0080	2.5
0		17	0.0090	2.5
10		15	0.0080	2.5
20		12	0.0064	2.5
30		16	0.0085	2.5
40		20	0.0106	2.5
50		16	0.0085	2.5
55		15	0.0080	2.5
25	4.2	16	0.0085	2.5
	3.5	14	0.0074	2.5

## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>RF Conducted Test</b>					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/15/2016	09/14/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	UHL-270	001	10/08/2016	10/07/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Amplifier	SMC150D	R1553-0313	03/08/2017	03/07/2018	<input checked="" type="checkbox"/>
Power Amplifier	S41-25D	R1553-0314	05/27/2016	05/26/2017	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-800/1000-S	AA4	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>




Test Report	17070235-FCC-R1
Page	71 of 76

Tunable Notch Filter	3NF- 1000/2000-S	AM 4	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
----------------------	---------------------	------	------------	------------	-------------------------------------

## Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex C.ii. TEST SET UP BLOCK

#### Block Configuration Diagram for Radiated Emissions





## Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

### Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
SMT TELECOMM HK LIMITED	Adapter	PCX4	A0425

### Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	A0425

## Annex C.ii. EUT OPERATING CONKITIONS

N/A

Test Report	17070235-FCC-R1
Page	75 of 76

**Annex D. User Manual / Block Diagram / Schematics / Partlist**

**Please see the attachment**

Test Report	17070235-FCC-R1
Page	76 of 76

## Annex E. DECLARATION OF SIMILARITY

N/A