

BSK-150
MULTIFUNCTIONAL
LIVE STREAMING AMP



Owner's Manual
JOYO

1. Introduction

- 1.1 Product Overview
- 1.2 Safety Precautions
- 1.3 Package Contents
- 1.4 Basic Controls
- 1.5 Power On/Off
- 1.6 Volume Control
- 1.7 Source Selection
- 1.8 EQ Settings
- 1.9 Reverb Settings
- 1.10 Delay Settings
- 1.11 Effects Settings
- 1.12 Preset Settings
- 1.13 Reset Settings
- 1.14 Maintenance
- 1.15 Troubleshooting
- 1.16 Specifications
- 1.17 Warranty

2. Features

- 2.1 150W x 2 RMS Power
- 2.2 120V AC Input
- 2.3 1/4" Input Jacks
- 2.4 1/8" Input Jacks
- 2.5 1/4" Output Jacks
- 2.6 1/8" Output Jacks
- 2.7 1/4" RCA Input Jacks
- 2.8 1/8" RCA Input Jacks
- 2.9 1/4" RCA Output Jacks
- 2.10 1/8" RCA Output Jacks
- 2.11 1/4" XLR Input Jacks
- 2.12 1/8" XLR Input Jacks
- 2.13 1/4" XLR Output Jacks
- 2.14 1/8" XLR Output Jacks
- 2.15 1/4" XLR Input Jacks
- 2.16 1/8" XLR Input Jacks
- 2.17 1/4" XLR Output Jacks
- 2.18 1/8" XLR Output Jacks
- 2.19 1/4" XLR Input Jacks
- 2.20 1/8" XLR Input Jacks
- 2.21 1/4" XLR Output Jacks
- 2.22 1/8" XLR Output Jacks
- 2.23 1/4" XLR Input Jacks
- 2.24 1/8" XLR Input Jacks
- 2.25 1/4" XLR Output Jacks
- 2.26 1/8" XLR Output Jacks
- 2.27 1/4" XLR Input Jacks
- 2.28 1/8" XLR Input Jacks
- 2.29 1/4" XLR Output Jacks
- 2.30 1/8" XLR Output Jacks
- 2.31 1/4" XLR Input Jacks
- 2.32 1/8" XLR Input Jacks
- 2.33 1/4" XLR Output Jacks
- 2.34 1/8" XLR Output Jacks
- 2.35 1/4" XLR Input Jacks
- 2.36 1/8" XLR Input Jacks
- 2.37 1/4" XLR Output Jacks
- 2.38 1/8" XLR Output Jacks
- 2.39 1/4" XLR Input Jacks
- 2.40 1/8" XLR Input Jacks
- 2.41 1/4" XLR Output Jacks
- 2.42 1/8" XLR Output Jacks
- 2.43 1/4" XLR Input Jacks
- 2.44 1/8" XLR Input Jacks
- 2.45 1/4" XLR Output Jacks
- 2.46 1/8" XLR Output Jacks
- 2.47 1/4" XLR Input Jacks
- 2.48 1/8" XLR Input Jacks
- 2.49 1/4" XLR Output Jacks
- 2.50 1/8" XLR Output Jacks
- 2.51 1/4" XLR Input Jacks
- 2.52 1/8" XLR Input Jacks
- 2.53 1/4" XLR Output Jacks
- 2.54 1/8" XLR Output Jacks
- 2.55 1/4" XLR Input Jacks
- 2.56 1/8" XLR Input Jacks
- 2.57 1/4" XLR Output Jacks
- 2.58 1/8" XLR Output Jacks
- 2.59 1/4" XLR Input Jacks
- 2.60 1/8" XLR Input Jacks
- 2.61 1/4" XLR Output Jacks
- 2.62 1/8" XLR Output Jacks
- 2.63 1/4" XLR Input Jacks
- 2.64 1/8" XLR Input Jacks
- 2.65 1/4" XLR Output Jacks
- 2.66 1/8" XLR Output Jacks
- 2.67 1/4" XLR Input Jacks
- 2.68 1/8" XLR Input Jacks
- 2.69 1/4" XLR Output Jacks
- 2.70 1/8" XLR Output Jacks
- 2.71 1/4" XLR Input Jacks
- 2.72 1/8" XLR Input Jacks
- 2.73 1/4" XLR Output Jacks
- 2.74 1/8" XLR Output Jacks
- 2.75 1/4" XLR Input Jacks
- 2.76 1/8" XLR Input Jacks
- 2.77 1/4" XLR Output Jacks
- 2.78 1/8" XLR Output Jacks
- 2.79 1/4" XLR Input Jacks
- 2.80 1/8" XLR Input Jacks
- 2.81 1/4" XLR Output Jacks
- 2.82 1/8" XLR Output Jacks
- 2.83 1/4" XLR Input Jacks
- 2.84 1/8" XLR Input Jacks
- 2.85 1/4" XLR Output Jacks
- 2.86 1/8" XLR Output Jacks
- 2.87 1/4" XLR Input Jacks
- 2.88 1/8" XLR Input Jacks
- 2.89 1/4" XLR Output Jacks
- 2.90 1/8" XLR Output Jacks
- 2.91 1/4" XLR Input Jacks
- 2.92 1/8" XLR Input Jacks
- 2.93 1/4" XLR Output Jacks
- 2.94 1/8" XLR Output Jacks
- 2.95 1/4" XLR Input Jacks
- 2.96 1/8" XLR Input Jacks
- 2.97 1/4" XLR Output Jacks
- 2.98 1/8" XLR Output Jacks
- 2.99 1/4" XLR Input Jacks
- 3.00 1/8" XLR Input Jacks

3. Controls

- 3.1 Power On/Off
- 3.2 Volume Control
- 3.3 Source Selection
- 3.4 EQ Settings
- 3.5 Reverb Settings
- 3.6 Delay Settings
- 3.7 Effects Settings
- 3.8 Preset Settings
- 3.9 Reset Settings
- 3.10 Maintenance
- 3.11 Troubleshooting
- 3.12 Specifications
- 3.13 Warranty

4. Connections

- 4.1 Power On/Off
- 4.2 Volume Control
- 4.3 Source Selection
- 4.4 EQ Settings
- 4.5 Reverb Settings
- 4.6 Delay Settings
- 4.7 Effects Settings
- 4.8 Preset Settings
- 4.9 Reset Settings
- 4.10 Maintenance
- 4.11 Troubleshooting
- 4.12 Specifications
- 4.13 Warranty

5. Troubleshooting

- 5.1 Power On/Off
- 5.2 Volume Control
- 5.3 Source Selection
- 5.4 EQ Settings
- 5.5 Reverb Settings
- 5.6 Delay Settings
- 5.7 Effects Settings
- 5.8 Preset Settings
- 5.9 Reset Settings
- 5.10 Maintenance
- 5.11 Troubleshooting
- 5.12 Specifications
- 5.13 Warranty

6. Specifications

- 6.1 Power On/Off
- 6.2 Volume Control
- 6.3 Source Selection
- 6.4 EQ Settings
- 6.5 Reverb Settings
- 6.6 Delay Settings
- 6.7 Effects Settings
- 6.8 Preset Settings
- 6.9 Reset Settings
- 6.10 Maintenance
- 6.11 Troubleshooting
- 6.12 Specifications
- 6.13 Warranty

7. Maintenance

- 7.1 Power On/Off
- 7.2 Volume Control
- 7.3 Source Selection
- 7.4 EQ Settings
- 7.5 Reverb Settings
- 7.6 Delay Settings
- 7.7 Effects Settings
- 7.8 Preset Settings
- 7.9 Reset Settings
- 7.10 Maintenance
- 7.11 Troubleshooting
- 7.12 Specifications
- 7.13 Warranty

8. Troubleshooting

- 8.1 Power On/Off
- 8.2 Volume Control
- 8.3 Source Selection
- 8.4 EQ Settings
- 8.5 Reverb Settings
- 8.6 Delay Settings
- 8.7 Effects Settings
- 8.8 Preset Settings
- 8.9 Reset Settings
- 8.10 Maintenance
- 8.11 Troubleshooting
- 8.12 Specifications
- 8.13 Warranty

9. Troubleshooting

- 9.1 Power On/Off
- 9.2 Volume Control
- 9.3 Source Selection
- 9.4 EQ Settings
- 9.5 Reverb Settings
- 9.6 Delay Settings
- 9.7 Effects Settings
- 9.8 Preset Settings
- 9.9 Reset Settings
- 9.10 Maintenance
- 9.11 Troubleshooting
- 9.12 Specifications
- 9.13 Warranty

10. Troubleshooting

- 10.1 Power On/Off
- 10.2 Volume Control
- 10.3 Source Selection
- 10.4 EQ Settings
- 10.5 Reverb Settings
- 10.6 Delay Settings
- 10.7 Effects Settings
- 10.8 Preset Settings
- 10.9 Reset Settings
- 10.10 Maintenance
- 10.11 Troubleshooting
- 10.12 Specifications
- 10.13 Warranty

11. Troubleshooting

- 11.1 Power On/Off
- 11.2 Volume Control
- 11.3 Source Selection
- 11.4 EQ Settings
- 11.5 Reverb Settings
- 11.6 Delay Settings
- 11.7 Effects Settings
- 11.8 Preset Settings
- 11.9 Reset Settings
- 11.10 Maintenance
- 11.11 Troubleshooting
- 11.12 Specifications
- 11.13 Warranty

12. Troubleshooting

- 12.1 Power On/Off
- 12.2 Volume Control
- 12.3 Source Selection
- 12.4 EQ Settings
- 12.5 Reverb Settings
- 12.6 Delay Settings
- 12.7 Effects Settings
- 12.8 Preset Settings
- 12.9 Reset Settings
- 12.10 Maintenance
- 12.11 Troubleshooting
- 12.12 Specifications
- 12.13 Warranty

13. Troubleshooting

- 13.1 Power On/Off
- 13.2 Volume Control
- 13.3 Source Selection
- 13.4 EQ Settings
- 13.5 Reverb Settings
- 13.6 Delay Settings
- 13.7 Effects Settings
- 13.8 Preset Settings
- 13.9 Reset Settings
- 13.10 Maintenance
- 13.11 Troubleshooting
- 13.12 Specifications
- 13.13 Warranty

14. Troubleshooting

- 14.1 Power On/Off
- 14.2 Volume Control
- 14.3 Source Selection
- 14.4 EQ Settings
- 14.5 Reverb Settings
- 14.6 Delay Settings
- 14.7 Effects Settings
- 14.8 Preset Settings
- 14.9 Reset Settings
- 14.10 Maintenance
- 14.11 Troubleshooting
- 14.12 Specifications
- 14.13 Warranty

15. Troubleshooting

- 15.1 Power On/Off
- 15.2 Volume Control
- 15.3 Source Selection
- 15.4 EQ Settings
- 15.5 Reverb Settings
- 15.6 Delay Settings
- 15.7 Effects Settings
- 15.8 Preset Settings
- 15.9 Reset Settings
- 15.10 Maintenance
- 15.11 Troubleshooting
- 15.12 Specifications
- 15.13 Warranty

16. Troubleshooting

- 16.1 Power On/Off
- 16.2 Volume Control
- 16.3 Source Selection
- 16.4 EQ Settings
- 16.5 Reverb Settings
- 16.6 Delay Settings
- 16.7 Effects Settings
- 16.8 Preset Settings
- 16.9 Reset Settings
- 16.10 Maintenance
- 16.11 Troubleshooting
- 16.12 Specifications
- 16.13 Warranty

FCC warning statements:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The device has been evaluated to meet general RF exposure requirement This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.