



FCC&IC TEST REPORT

FCC ID: 2AIN7-JSP-01

On Behalf of

JOYO TECHNOLOGY CO., LTD

Wireless page turner pedal

Model No.: JSP-01

Prepared for : JOYO TECHNOLOGY CO., LTD
Address : 2/F, Lushi Industry Building, 28th District, Bao'an, Shenzhen, 518101
China

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

Report Number : A2402073-C01-R05
Date of Receipt : February 27, 2024
Date of Test : February 27, 2024- April 18, 2024
Date of Report : April 26, 2024
Version Number : V0
Test Result : Pass

TABLE OF CONTENTS

Description	Page
1. Summary of Standards And Results	5
1.1. Description of Standards and Results	5
2. General Information	6
2.1. Description of Device (EUT)	6
2.2. Accessories of Device (EUT)	7
2.3. Tested Supporting System Details	7
2.4. Block Diagram of connection between EUT and simulators	7
2.5. Test Mode Description	7
2.6. Test Conditions	8
2.7. Test Facility	8
2.8. Measurement Uncertainty	8
2.9. Test Equipment List	9
3. Spurious Emission	10
3.1. Test Limits	10
3.2. Test Procedure	11
3.3. Test Setup	12
3.4. Test Results	13
4. Power Line Conducted Emission	21
4.1. Test Limits	21
4.2. Test Procedure	21
4.3. Test Setup	21
4.4. Test Results	21
5. Conducted Maximum Output Power	24
5.1. Test limits	24
5.2. Test Procedure	24
5.3. Test Setup	24
5.4. Test Results	24
6. Peak Power Spectral Density	25
6.1. Test limits	25
6.2. Test Procedure	25
6.3. Test Setup	25
6.4. Test Results	25
7. Bandwidth	29
7.1. Test limits	29
7.2. Test Procedure	29
7.3. Test Setup	29
7.4. Test Results	29
8. Band Edge Check	37
8.1. Test limits	37
8.2. Test Procedure	37
8.3. Test Setup	37
8.4. Test Results	37
9. Antenna Requirement	42
9.1. Standard Requirement	42
9.2. Antenna Connected Construction	42
9.3. Results	42
10. Test setup photo	43
10.1. Photo of Radiated Emission test	43
10.2. Photo of Conducted Emission test	44

TEST REPORT DECLARATION

Applicant : JOYO TECHNOLOGY CO., LTD
 Address : 2/F, Lushi Industry Building, 28th District, Bao' an, Shenzhen, 518101 China
 Manufacturer : JOYO TECHNOLOGY CO., LTD
 Address : 2/F, Lushi Industry Building, 28th District, Bao' an, Shenzhen, 518101 China
 EUT Description : Wireless page turner pedal
 (A) Model No. JSP-01
 (B) Trademark JOYO

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10:2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Yannis Wen
 Project Engineer



Approved by (name + signature).....: Reak Yang
 Project Manager



Date of issue.....: April 26, 2024

Revision History

Revision	Issue Date	Revisions	Revised By
V0	April 26, 2024	Initial released Issue	Yannis Wen

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Test Requirement	Standards Paragraph	Result
Conducted Emission	FCC PART 15	15.207	P
6dB Bandwidth	FCC PART 15	15.247 (a)(2)	P
Conducted Maximum Peak Output Power	FCC PART 15	15.247 (b)(3)	P
Radiated Spurious Emission	FCC PART 15	15.247 (c)	P
Conducted Spurious & Band Edge Emission	FCC PART 15	15.247 (d)	P
Power Spectral Density	FCC PART 15	15.247 (e)	P
Radiated Band Edge Emission	FCC PART 15	15.205	P
Antenna Requirement	FCC PART 15	15.203	P

Note: 1. P is an abbreviation for Pass.

2. F is an abbreviation for Fail.

3. N/A is an abbreviation for Not Applicable.

4. The conclusion of this test report is judged by actual test data without considering measurement uncertainty.

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description	:	Wireless page turner pedal
Model Number	:	JSP-01
Diff	:	N/A
Power supply	:	DC 5V from Type-C port, DC 3.7V from battery.
Radio Technology	:	Bluetooth LE
Operation frequency	:	2402-2480MHz
Channel No.	:	40 channels
Channel Separation	:	2MHz
Date Rate	:	1Mbps, 2Mbps
Modulation	:	GFSK
Antenna Type	:	Internal antenna, Maximum Gain is -0.59dBi (Antenna information is provided by applicant.)
Coaxial cable loss	:	Max. coaxial cable loss:0.5dB (Cable lossvalue is provided by applicant.)
Software version	:	V1.0
Hardware version	:	V1.0
Intend use environment	:	Residential, commercial and light industrial environment


2.2. Accessories of Device (EUT)

Accessories : N/A
 Manufacturer : N/A
 Model : N/A
 INPUT : N/A
 OUTPUT : N/A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDoC
1	--	--	--	--	--

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
GFSK (1Mbps, 2Mbps)	Low :CH0	2402
	Middle: CH19	2440
	High: CH39	2480

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35°C	24°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd
 Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
 Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission
 Registration Number: 293961

July 15, 2019 Certificated by IC
 Registration Number: 12135A

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	1.63dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.74dB(Polarize: V)
	3.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V)
	4.30 dB(Polarize: H)
Uncertainty for radio frequency	5.06×10^{-8} GHz
Uncertainty for conducted RF Power	0.40dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9. Test Equipment List

Equipment	Manufacture	Model No.	Firmware version	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	/	N/A	2022.05.17	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	2.3	102137	2023.08.16	1Year
Spectrum analyzer	Agilent	N9020A	A.14.16	MY499100060	2023.08.16	1Year
Receiver	ROHDE&SCHWARZ	ESR	2.28 SP1	1316.3003K03-10 2082-Wa	2023.08.16	1Year
Receiver	R&S	ESCI	4.42 SP1	101165	2023.08.16	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	/	VULB 9168#627	2023.08.28	1Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	/	2106	2023.08.19	1Year
Loop Antenna	SCHWARZBECK	FMZB 1519B	/	00128	2023.08.19	1Year
RF Cable	Resenberger	Cable 1	/	RE1	2023.08.16	1Year
RF Cable	Resenberger	Cable 2	/	RE2	2023.08.16	1Year
RF Cable	Resenberger	Cable 3	/	CE1	2023.08.16	1Year
Pre-amplifier	HP	HP8347A	/	2834A00455	2023.08.16	1Year
Pre-amplifier	Agilent	8449B	/	3008A02664	2023.08.16	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	/	8126-466	2023.08.16	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	/	101043	2023.08.16	1Year
Horn Antenna	SCHWARZBECK	BBHA 9170	/	00946	2023.08.19	1Year
Preamplifier	SKET	LNPA_1840 -50	/	SK2018101801	2023.08.16	1 Year
Power Meter	Agilent	E9300A	/	MY41496628	2023.08.16	1 Year
Power Sensor	DARE	RPR3006W	/	15100041SNO91	2023.08.16	1 Year
Temp. & Humid. Chamber	Teelong	TL-HW408S	/	TL-20191205-01	2023.07.25	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	/	20140927-6	2023.08.16	1 Year
Adjustable attenuator	MWRFTest	N/A	/	N/A	N/A	N/A
10dB Attenuator	Mini-Circuits	DC-6G	/	N/A	N/A	N/A

Software Information			
Test Item	Software Name	Manufacturer	Version
RE	EZ-EMC	EZ	Alpha-3A1
CE	EZ-EMC	EZ	Alpha-3A1
RF-CE	MTS 8310	MW	V2.0.0.0

3. SPURIOUS EMISSION

3.1. Test Limits

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	
Note 1: The peak limit is 20 dB higher than the average limit			
Note 2: Peak limit applies (AVG limit + 20 dB) as well as RSS-247 Section 5.5			

Harmonic emissions limits comply with below 54 dB $\mu\text{V}/\text{m}$ at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength ($\mu\text{V}/\text{m}$ at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) ($\mu\text{A}/\text{m}$)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

3.2. Test Procedure

The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1GHz, The EUT was placed on a rotating 0.8 m high above ground for below 1GHz and 1.5m high for above 1GHz testing, The table was rotated 360 degrees to determine the position of the highest radiation


The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set of make measurement.

The initial step in collecting conducted emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked. and then Qusia Peak Detector mode premeasured


If Peak value comply with QP limit Below 1GHz.The EUT deemed to comply with QP limit. But the Peak value and average value both need to comply with applicable limit above 1GHz.

For the actual test configuration, please see the test setup photo.


3.3. Test Setup



Below 30MHz Test Setup



Above 30MHz Test Setup



Above 1GHz Test Setup

3.4. Test Results

Test Condition

Continual Transmitting in maximum power.

9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHZ~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

We have scanned the 10th harmonic from 9 kHz to the EUT.


Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: 1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

2. Only show the test data of the worst Channel in this report.

Antenna polarity: Horizontal




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table
		MHz	Level	Factor	ment			Height	Degree
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		41.5767	9.38	14.26	23.64	40.00	-16.36	peak	
2		147.6105	10.85	14.61	25.46	43.50	-18.04	peak	
3		272.8192	9.84	12.98	22.82	46.00	-23.18	peak	
4		420.1381	10.65	16.47	27.12	46.00	-18.88	peak	
5		727.9104	11.03	21.77	32.80	46.00	-13.20	peak	
6	*	886.7803	11.01	23.43	34.44	46.00	-11.56	peak	

Note: 1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Antenna polarity: Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table
		MHz	dBuV	Factor	ment	dBuV/m	dB	Height	Degree
				dB	dBuV/m	dBuV/m	dB	cm	degree
1		42.0410	10.33	14.26	24.59	40.00	-15.41	peak	
2		139.5569	9.92	14.08	24.00	43.50	-19.50	peak	
3		231.9889	10.39	11.98	22.37	46.00	-23.63	peak	
4		410.8624	9.91	16.23	26.14	46.00	-19.86	peak	
5		649.7355	11.72	20.76	32.48	46.00	-13.52	peak	
6	*	858.0270	11.89	23.06	34.95	46.00	-11.05	peak	

Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Notes: Above is below 1GHz test data. This report only shall the worst case mode for GFSK 1M 2402MHz.

1Mbps
From 1G-25GHz


Test Mode: TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	42.51	V	33.95	10.18	34.26	52.38	74	-21.62	PK
4804	35.79	V	33.95	10.18	34.26	45.66	54	-8.34	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	45.35	H	33.95	10.18	34.26	55.22	74	-18.78	PK
4804	36.43	H	33.95	10.18	34.26	46.30	54	-7.70	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: TX Mid									
4880	42.99	V	33.93	10.2	34.29	52.83	74	-21.17	PK
4880	33.72	V	33.93	10.2	34.29	43.56	54	-10.44	AV
7320	/	/	/	/	/	/	/	/	/
9760	/	/	/	/	/	/	/	/	/
4880	45.20	H	33.93	10.2	34.29	55.04	74	-18.96	PK
4880	36.31	H	33.93	10.2	34.29	46.15	54	-7.85	AV
7320	/	/	/	/	/	/	/	/	/
9760	/	/	/	/	/	/	/	/	/
Test Mode: TX High									
4960	44.37	V	33.98	10.22	34.25	54.32	74	-19.68	PK
4960	33.84	V	33.98	10.22	34.25	43.79	54	-10.21	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	45.17	H	33.98	10.22	34.25	55.12	74	-18.88	PK
4960	33.73	H	33.98	10.22	34.25	43.68	54	-10.32	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
Note: 1, Result = Read level + Antenna factor + cable loss-Amp factor 2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

2Mbps
From 1G-25GHz


Test Mode: TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	44.87	V	33.95	10.18	34.26	54.74	74	-19.26	PK
4804	38.97	V	33.95	10.18	34.26	48.84	54	-5.16	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	44.96	H	33.95	10.18	34.26	54.83	74	-19.17	PK
4804	37.10	H	33.95	10.18	34.26	46.97	54	-7.03	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: TX Mid									
4880	42.48	V	33.93	10.2	34.29	52.32	74	-21.68	PK
4880	35.36	V	33.93	10.2	34.29	45.20	54	-8.80	AV
7320	/	/	/	/	/	/	/	/	/
9760	/	/	/	/	/	/	/	/	/
4880	43.34	H	33.93	10.2	34.29	53.18	74	-20.82	PK
4880	35.17	H	33.93	10.2	34.29	45.01	54	-8.99	AV
7320	/	/	/	/	/	/	/	/	/
9760	/	/	/	/	/	/	/	/	/
Test Mode: TX High									
4960	43.91	V	33.98	10.22	34.25	53.86	74	-20.14	PK
4960	35.85	V	33.98	10.22	34.25	45.80	54	-8.20	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	41.80	H	33.98	10.22	34.25	51.75	74	-22.25	PK
4960	32.30	H	33.98	10.22	34.25	42.25	54	-11.75	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
Note: 1, Result = Read level + Antenna factor + cable loss-Amp factor 2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

Conducted RF Spurious Emission


Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission




Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission




Date: 16.APR.2024 21:51:22

Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Emission




Date: 16.APR.2024 22:01:25

Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Emission



4. POWER LINE CONDUCTED EMISSION

4.1. Test Limits

Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.


3. The limit decreases in line with the logarithm of the frequency in rang of 0.15 to 0.50 MHz.

4.2. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Measurement.

The bandwidth of test receiver is set at 9 kHz.


4.3. Test Setup



4.4. Test Results

Pass

Polarity: L




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1590	26.94	9.94	36.88	65.52	-28.64	peak	
2	0.2490	25.59	9.97	35.56	61.79	-26.23	peak	
3 *	0.5250	27.10	9.95	37.05	56.00	-18.95	peak	
4	1.0289	17.46	9.92	27.38	56.00	-28.62	peak	
5	1.8900	18.17	9.88	28.05	56.00	-27.95	peak	
6	18.0300	17.34	10.41	27.75	60.00	-32.25	peak	

*:Maximum data x:Over limit !:over margin (Reference Only)

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Polarity: N



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1590	26.82	9.94	36.76	65.52	-28.76	peak	
2	0.5010	29.81	9.96	39.77	56.00	-16.23	peak	
3 *	0.5220	30.61	9.95	40.56	56.00	-15.44	peak	
4	0.8340	21.19	9.95	31.14	56.00	-24.86	peak	
5	1.3350	21.31	9.90	31.21	56.00	-24.79	peak	
6	18.4590	19.55	10.43	29.98	60.00	-30.02	peak	

*:Maximum data x:Over limit !:over margin (Reference Only)
 Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Note: All modes and channels have been tested and only the GFSK 1M 2402MHz mode with the worst data is listed.

5. CONDUCTED MAXIMUM OUTPUT POWER

5.1. Test limits

Please refer section 15.247.

5.2. Test Procedure


Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

5.2.1 Place the EUT on the table and set it in transmitting mode.

5.2.2 Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

5.3. Test Setup



5.4. Test Results

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	EIRP (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	2.221	1.631	30	Pass
NVNT	BLE 1M	2440	Ant1	1.646	1.056	30	Pass
NVNT	BLE 1M	2480	Ant1	1.542	0.952	30	Pass

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	EIRP (dBm)	Limit (dBm)	Verdict
NVNT	BLE 2M	2402	Ant1	2.299	1.709	30	Pass
NVNT	BLE 2M	2440	Ant1	1.641	1.051	30	Pass
NVNT	BLE 2M	2480	Ant1	1.474	0.884	30	Pass

6. PEAK POWER SPECTRAL DENSITY

6.1. Test limits

6.1.1 Please refer section 15.247.

6.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

6.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

6.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

6.2.1 Place the EUT on the table and set it in transmitting mode.


6.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

6.2.3 Set the spectrum analyzer as $RBW = 3\text{kHz}$ (Set the RBW to: $3\text{ kHz} \leq RBW \leq 100\text{ kHz}$.), $VBW = 10\text{kHz}$ (Set the $VBW \geq 3 \times RBW$), $\text{span} = 1.5 \times \text{DTS bandwidth}$., detail see the test plot.

6.2.4 Record the max reading.

6.2.5 Repeat the above procedure until the measurements for all frequencies are completed.

6.3. Test Setup




6.4. Test Results

Pass


The test results are listed in next pages.

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-14.123	8	Pass
NVNT	BLE 1M	2440	Ant1	-14.196	8	Pass
NVNT	BLE 1M	2480	Ant1	-14.521	8	Pass


PSD NVNT BLE 1M 2402MHz Ant1



PSD NVNT BLE 1M 2440MHz Ant1




PSD NVNT BLE 1M 2480MHz Ant1



Date: 16.APR.2024 21:47:02


Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 2M	2402	Ant1	-14.16	8	Pass
NVNT	BLE 2M	2440	Ant1	-14.623	8	Pass
NVNT	BLE 2M	2480	Ant1	-14.564	8	Pass

PSD NVNT BLE 2M 2402MHz Ant1




Date: 16.APR.2024 22:00:51

PSD NVNT BLE 2M 2440MHz Ant1



Date: 16.APR.2024 22:02:31

PSD NVNT BLE 2M 2480MHz Ant1



Date: 16.APR.2024 22:16:38

7. BANDWIDTH

7.1. Test limits

Please refer section 15.247

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.


7.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

a) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

b) The test receiver set RBW = 100kHz, VBW \geq 3*RBW =300kHz, sweep time set auto, detail see the test plot.

7.3. Test Setup




7.4. Test Results

-6dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.7	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.701	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.693	0.5	Pass

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1




Date: 16.APR.2024 21:33:35

-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1



Date: 16.APR.2024 21:40:44

-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1




Date: 16.APR.2024 21:45:24

Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1M	2402	Ant1	1.04
NVNT	BLE 1M	2440	Ant1	1.046
NVNT	BLE 1M	2480	Ant1	1.04

OBW NVNT BLE 1M 2402MHz Ant1




Date: 16.APR.2024 21:33:04

OBW NVNT BLE 1M 2440MHz Ant1



Date: 16.APR.2024 21:40:13

OBW NVNT BLE 1M 2480MHz Ant1




Date: 16.APR.2024 21:44:53

-6dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 2M	2402	Ant1	1.165	0.5	Pass
NVNT	BLE 2M	2440	Ant1	1.161	0.5	Pass
NVNT	BLE 2M	2480	Ant1	1.179	0.5	Pass

-6dB Bandwidth NVNT BLE 2M 2402MHz Ant1




Date: 16.APR.2024 22:00:33

-6dB Bandwidth NVNT BLE 2M 2440MHz Ant1



Date: 16.APR.2024 22:02:13

-6dB Bandwidth NVNT BLE 2M 2480MHz Ant1




Date: 16.APR.2024 22:16:19

Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 2M	2402	Ant1	2.054
NVNT	BLE 2M	2440	Ant1	2.05
NVNT	BLE 2M	2480	Ant1	2.05

OBW NVNT BLE 2M 2402MHz Ant1




Date: 16.APR.2024 22:00:23

OBW NVNT BLE 2M 2440MHz Ant1



Date: 16.APR.2024 22:02:03

OBW NVNT BLE 2M 2480MHz Ant1



Date: 16.APR.2024 22:16:10

8. BAND EDGE CHECK

8.1. Test limits

Please refer section 15.247.

8.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

8.2.1 Put the EUT on a 0.8m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission

8.2.2 Check the spurious emissions out of band.

8.2.3 RBW 1MHz, VBW 3MHz, peak detector for peak value, RBW 1MHz, VBW 3MHz, RMS detector for AV value.

8.3. Test Setup

Same as 5.2.2.


8.4. Test Results

Pass

The test results are listed in next pages.


GFSK (1M)

Band Edge NVNT BLE 1M 2402MHz Ant1 Emission




Date: 16.APR.2024 21:35:53

Band Edge NVNT BLE 1M 2480MHz Ant1 Emission




Date: 16.APR.2024 21:49:05


Band Edge NVNT BLE 2M 2402MHz Ant1 Emission




Band Edge NVNT BLE 2M 2480MHz Ant1 Emission





Radiated Method: GFSK(1M)
Test Mode: CH-L




Test Mode: CH-H




Radiated Method: GFSK(1M)
Test Mode: CH-H





Radiated Method: GFSK(2M)
Test Mode: CH-L



Test Mode: CH-H



Radiated Method: GFSK(2M)
Test Mode: CH-H



9. ANTENNA REQUIREMENT

9.1. Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2. Antenna Connected Construction



The antenna is internal antenna and no consideration of replacement. Please see EUT photo for details.

9.3. Results


The EUT antenna is Internal Antenna. It complies with the standard requirement.

10. TEST SETUP PHOTO

10.1. Photo of Radiated Emission test



10.2.Photo of Conducted Emission test



-----END OF REPORT-----