

FCC PART 15.247 TEST REPORT

For

Silicon Application Corp.

7F, Block 2, Kai Da Er Building, NO.168, TongSha Road, XiLi Town, Nanshan, Shenzhen,
China

FCC ID: 2AINMMT7687MODULE

Report Type: Original Report	Product Type: MT7687MODULE
Test Engineer: Lion Xiao	<i>Lion Xiao</i>
Report Number: RDG160725002-00B	
Report Date: 2016-07-29	
Reviewed By: Dean Liu RF Engineer	<i>Dean Liu</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
EUT EXERCISE SOFTWARE	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §15.247 (I) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY.....	11
EUT SETUP	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST RESULTS SUMMARY	13
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	16
APPLICABLE STANDARD	16
MEASUREMENT UNCERTAINTY.....	16
EUT SETUP	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST EQUIPMENT LIST AND DETAILS.....	18
TEST RESULTS SUMMARY	18
TEST DATA	18
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	25
APPLICABLE STANDARD	25
TEST PROCEDURE	25
TEST EQUIPMENT LIST AND DETAILS.....	25
TEST DATA	25
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	33

APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	33
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST EQUIPMENT LIST AND DETAILS.....	35
TEST DATA	35
FCC §15.247(e) - POWER SPECTRAL DENSITY	40
APPLICABLE STANDARD	40
TEST PROCEDURE	40
TEST EQUIPMENT LIST AND DETAILS.....	40
TEST DATA	40

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Silicon Application Corp.*'s product, model number: *MT7687MODULE (FCC ID: 2AINMMT7687 MODULE)* (the "EUT") in this report was a *MT7687MODULE*, which was measured approximately: 3.3 cm (L) x 2.1 cm (W) x 0.3 cm (H), rated input voltage: DC3.3V .

All measurement and test data in this report was gathered from production sample serial number: 160725002 (Assigned by BACL, Dongguan). The EUT was received on 2016-07-26.

Objective

This report is prepared on behalf of *Silicon Application Corp.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

N/A

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer.
For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with channel 1, 6 and 11.
For 802.11n ht40 mode were tested with Channel 3, 6 and 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

The worst condition (maximum power with 100% duty cycle) was setting by the software as following table:

Test Mode	Test Software Version	QATool_Dbg.exe		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	1E	1D	1C
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	1C	1B	1A
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	1C	1B	1A
802.11n ht40	Test Frequency	2422MHz	2437MHz	2452MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	1D	1C	1B


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Lenovo	Notebook	G510	CB30920865
/	Test jig	/	/

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (cm)	From Port	To
USB Cable	no	yes	0.8	USB Port of Laptop	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (I) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency Range (MHz)	Antenna Gain		Tune-up Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	1	1.26	22	158.49	20	0.040	1.0

Note: The tune-up power and tolerance is 21 ± 1.0 dBm.

Result: The device meet FCC MPE at 20 cm distance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one integral antenna arrangement for WiFi, and the antenna gain is 1 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.12 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-12-10	2016-12-09
R&S	L.I.S.N	ESH2-Z5	892107/021	2016-07-16	2017-07-15
R&S	Two-line V-network	ENV 216	3560.6550.12	2015-11-26	2016-11-25
N/A	Coaxial Cable	1.8m	N/A	2016-05-06	2017-05-06
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.


Test Data**Environmental Conditions**

Temperature:	29.5 °C
Relative Humidity:	50 %
ATM Pressure:	100.2 kPa

The testing was performed by Lion Xiao on 2016-07-26.


Test Mode: Transmitting

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	57.1	9.000	L1	10.2	8.9	66.0	Compliance
0.468757	31.2	9.000	L1	10.1	25.3	56.5	Compliance
1.073601	28.7	9.000	L1	10.4	27.3	56.0	Compliance
2.113432	38.1	9.000	L1	10.4	17.9	56.0	Compliance
2.420011	40.0	9.000	L1	10.4	16.0	56.0	Compliance
4.957528	33.6	9.000	L1	10.7	22.4	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.151200	36.6	9.000	L1	10.2	19.3	55.9	Compliance
0.340821	30.9	9.000	L1	10.3	18.3	49.2	Compliance
2.080018	31.6	9.000	L1	10.4	14.4	46.0	Compliance
2.325491	34.1	9.000	L1	10.4	11.9	46.0	Compliance
3.662393	25.2	9.000	L1	10.6	20.8	46.0	Compliance
4.957528	26.7	9.000	L1	10.7	19.3	46.0	Compliance

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	57.4	9.000	N	10.2	8.6	66.0	Compliance
1.023481	31.4	9.000	N	10.4	24.6	56.0	Compliance
2.113432	38.5	9.000	N	10.4	17.5	56.0	Compliance
2.270560	39.5	9.000	N	10.4	16.5	56.0	Compliance
3.604490	34.7	9.000	N	10.6	21.3	56.0	Compliance
4.957528	34.2	9.000	N	10.7	21.8	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.317235	30.4	9.000	N	10.3	19.4	49.8	Compliance
1.023481	26.3	9.000	N	10.4	19.7	46.0	Compliance
2.113432	32.8	9.000	N	10.4	13.2	46.0	Compliance
2.307034	34.3	9.000	N	10.4	11.7	46.0	Compliance
3.633326	27.4	9.000	N	10.6	18.6	46.0	Compliance
4.957528	28.9	9.000	N	10.7	17.1	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.


Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 10m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.55 dB for Horizontal, 4.57 dB for Vertical; 200M~1GHz: 4.66 dB for Horizontal, 4.56 dB for Vertical; measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical; 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical; 1G~6GHz: 4.45 dB, 6G~18GHz: 5.23 dB


Table 2 – Values of U_{cisp}

Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits. The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Av

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-02 1102	2014-09-16	2017-09-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2015-09-06	2016-09-06
N/A	Coaxial Cable	14m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	8m	N/A	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions


Temperature:	28.4 °C
Relative Humidity:	48 %
ATM Pressure:	100.2 kPa

* The testing was performed by Lion Xiao on 2016-07-26.


Test Mode: Transmitting

1) Below 1GHz(802.11b mode middle channel was the worst):

Horizontal



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
59.1000	42.80	QP	-13.00	29.80	40.00	10.20
166.7700	36.76	QP	-7.66	29.10	43.50	14.40
231.7600	38.39	QP	-7.99	30.40	46.00	15.60
283.1700	38.63	QP	-5.93	32.70	46.00	13.30
453.8900	32.55	QP	-2.35	30.20	46.00	15.80
505.3000	28.88	QP	-1.38	27.50	46.00	18.50

Vertical

Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
32.9100	32.14	QP	-1.24	30.90	40.00	9.10
59.1000	39.50	QP	-13.00	26.50	40.00	13.50
216.2400	35.99	QP	-8.89	27.10	46.00	18.90
231.7600	36.39	QP	-7.99	28.40	46.00	17.60
362.7100	30.52	QP	-4.52	26.00	46.00	20.00
507.2400	31.15	QP	-1.55	29.60	46.00	16.40

2) Above 1G:

802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	74.51	PK	H	25.67	3.68	0.00	103.86	N/A	N/A
2412	69.38	AV	H	25.67	3.68	0.00	98.73	N/A	N/A
2412	65.94	PK	V	25.67	3.68	0.00	95.29	N/A	N/A
2412	60.81	AV	V	25.67	3.68	0.00	90.16	N/A	N/A
2390	30.42	PK	H	25.61	3.63	0.00	59.66	74.00	14.34
2390	16.50	AV	H	25.61	3.63	0.00	45.74	54.00	8.26
4824	46.49	PK	H	30.64	5.03	27.41	54.75	74.00	19.25
4824	41.73	AV	H	30.64	5.03	27.41	49.99	54.00	4.01
7236	35.86	PK	H	34.17	6.65	25.90	50.78	74.00	23.22
7236	23.31	AV	H	34.17	6.65	25.90	38.23	54.00	15.77
9648	30.41	PK	H	36.76	8.55	27.46	48.26	74.00	25.74
9648	18.15	AV	H	36.76	8.55	27.46	36.00	54.00	18.00
3240	40.53	PK	H	27.97	6.26	27.34	47.42	74.00	26.58
3240	28.16	AV	H	27.97	6.26	27.34	35.05	54.00	18.95
Middle Channel: 2437 MHz									
2437	74.07	PK	H	25.74	3.75	0.00	103.56	N/A	N/A
2437	69.24	AV	H	25.74	3.75	0.00	98.73	N/A	N/A
2437	65.95	PK	V	25.74	3.75	0.00	95.44	N/A	N/A
2437	60.71	AV	V	25.74	3.75	0.00	90.20	N/A	N/A
4874	46.15	PK	H	30.77	5.14	27.42	54.64	74.00	19.36
4874	41.30	AV	H	30.77	5.14	27.42	49.79	54.00	4.21
7311	35.79	PK	H	34.35	6.74	25.88	51.00	74.00	23.00
7311	23.64	AV	H	34.35	6.74	25.88	38.85	54.00	15.15
9748	30.49	PK	H	36.80	8.61	27.24	48.66	74.00	25.34
9748	18.95	AV	H	36.80	8.61	27.24	37.12	54.00	16.88
3240	40.31	PK	H	27.97	6.26	27.34	47.20	74.00	26.80
3240	28.53	AV	H	27.97	6.26	27.34	35.42	54.00	18.58
4038	37.83	PK	H	29.89	4.65	27.18	45.19	74.00	28.81
4038	25.70	AV	H	29.89	4.65	27.18	33.06	54.00	20.94
High Channel: 2462 MHz									
2462	74.39	PK	H	25.80	3.75	0.00	103.94	N/A	N/A
2462	69.03	AV	H	25.80	3.75	0.00	98.58	N/A	N/A
2462	65.91	PK	V	25.80	3.75	0.00	95.46	N/A	N/A
2462	60.08	AV	V	25.80	3.75	0.00	89.63	N/A	N/A
2483.5	29.08	PK	H	25.86	3.67	0.00	58.61	74.00	15.39
2483.5	16.43	AV	H	25.86	3.67	0.00	45.96	54.00	8.04
4924	45.61	PK	H	30.90	5.34	27.43	54.42	74.00	19.58
4924	40.30	AV	H	30.90	5.34	27.43	49.11	54.00	4.89
7386	35.71	PK	H	34.53	6.83	25.86	51.21	74.00	22.79
7386	23.29	AV	H	34.53	6.83	25.86	38.79	54.00	15.21
9848	30.98	PK	H	36.84	8.66	26.94	49.54	74.00	24.46
9848	18.23	AV	H	36.84	8.66	26.94	36.79	54.00	17.21
3340	40.20	PK	H	28.29	4.86	27.25	46.10	74.00	27.90
3340	28.03	AV	H	28.29	4.86	27.25	33.93	54.00	20.07

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	73.18	PK	H	25.67	3.68	0.00	102.53	N/A	N/A
2412	63.72	AV	H	25.67	3.68	0.00	93.07	N/A	N/A
2412	64.95	PK	V	25.67	3.68	0.00	94.30	N/A	N/A
2412	54.64	AV	V	25.67	3.68	0.00	83.99	N/A	N/A
2390	34.62	PK	H	25.61	3.63	0.00	63.86	74.00	10.14
2390	20.76	AV	H	25.61	3.63	0.00	50.00	54.00	4.00
4824	35.55	PK	H	30.64	5.03	27.41	43.81	74.00	30.19
4824	23.91	AV	H	30.64	5.03	27.41	32.17	54.00	21.83
7236	31.48	PK	H	34.17	6.65	25.90	46.40	74.00	27.60
7236	19.27	AV	H	34.17	6.65	25.90	34.19	54.00	19.81
9648	30.74	PK	H	36.76	8.55	27.46	48.59	74.00	25.41
9648	18.23	AV	H	36.76	8.55	27.46	36.08	54.00	17.92
3240	40.77	PK	H	27.97	6.26	27.34	47.66	74.00	26.34
3240	28.25	AV	H	27.97	6.26	27.34	35.14	54.00	18.86
Middle Channel: 2437 MHz									
2437	73.40	PK	H	25.74	3.75	0.00	102.89	N/A	N/A
2437	63.03	AV	H	25.74	3.75	0.00	92.52	N/A	N/A
2437	64.33	PK	V	25.74	3.75	0.00	93.82	N/A	N/A
2437	54.26	AV	V	25.74	3.75	0.00	83.75	N/A	N/A
4874	35.82	PK	H	30.77	5.14	27.42	44.31	74.00	29.69
4874	23.46	AV	H	30.77	5.14	27.42	31.95	54.00	22.05
7311	32.69	PK	H	34.35	6.74	25.88	47.90	74.00	26.10
7311	20.26	AV	H	34.35	6.74	25.88	35.47	54.00	18.53
9748	30.25	PK	H	36.80	8.61	27.24	48.42	74.00	25.58
9748	18.40	AV	H	36.80	8.61	27.24	36.57	54.00	17.43
3240	40.10	PK	H	27.97	6.26	27.34	46.99	74.00	27.01
3240	28.78	AV	H	27.97	6.26	27.34	35.67	54.00	18.33
4038	37.62	PK	H	29.89	4.65	27.18	44.98	74.00	29.02
4038	25.27	AV	H	29.89	4.65	27.18	32.63	54.00	21.37
High Channel: 2462 MHz									
2462	73.88	PK	H	25.80	3.75	0.00	103.43	N/A	N/A
2462	63.01	AV	H	25.80	3.75	0.00	92.56	N/A	N/A
2462	64.49	PK	V	25.80	3.75	0.00	94.04	N/A	N/A
2462	54.53	AV	V	25.80	3.75	0.00	84.08	N/A	N/A
2483.5	33.96	PK	H	25.86	3.67	0.00	63.49	74.00	10.51
2483.5	20.38	AV	H	25.86	3.67	0.00	49.91	54.00	4.09
4924	35.64	PK	H	30.90	5.34	27.43	44.45	74.00	29.55
4924	23.28	AV	H	30.90	5.34	27.43	32.09	54.00	21.91
7386	31.22	PK	H	34.53	6.83	25.86	46.72	74.00	27.28
7386	19.88	AV	H	34.53	6.83	25.86	35.38	54.00	18.62
9848	30.60	PK	H	36.84	8.66	26.94	49.16	74.00	24.84
9848	18.03	AV	H	36.84	8.66	26.94	36.59	54.00	17.41
3240	40.41	PK	H	27.97	6.26	27.34	47.30	74.00	26.70
3240	28.41	AV	H	27.97	6.26	27.34	35.30	54.00	18.70

802.11 n ht20 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	73.03	PK	H	25.67	3.68	0.00	102.38	N/A	N/A
2412	61.66	AV	H	25.67	3.68	0.00	91.01	N/A	N/A
2412	64.69	PK	V	25.67	3.68	0.00	94.04	N/A	N/A
2412	52.41	AV	V	25.67	3.68	0.00	81.76	N/A	N/A
2390	34.07	PK	H	25.61	3.63	0.00	63.31	74.00	10.69
2390	20.81	AV	H	25.61	3.63	0.00	50.05	54.00	3.95
4824	32.03	PK	H	30.64	5.03	27.41	40.29	74.00	33.71
4824	20.69	AV	H	30.64	5.03	27.41	28.95	54.00	25.05
7236	32.18	PK	H	34.17	6.65	25.90	47.10	74.00	26.90
7236	20.08	AV	H	34.17	6.65	25.90	35.00	54.00	19.00
9648	30.96	PK	H	36.76	8.55	27.46	48.81	74.00	25.19
9648	19.06	AV	H	36.76	8.55	27.46	36.91	54.00	17.09
3240	40.84	PK	H	27.97	6.26	27.34	47.73	74.00	26.27
3240	28.41	AV	H	27.97	6.26	27.34	35.30	54.00	18.70
Middle Channel: 2437 MHz									
2437	73.45	PK	H	25.74	3.75	0.00	102.94	N/A	N/A
2437	61.79	AV	H	25.74	3.75	0.00	91.28	N/A	N/A
2437	64.28	PK	V	25.74	3.75	0.00	93.77	N/A	N/A
2437	52.69	AV	V	25.74	3.75	0.00	82.18	N/A	N/A
4874	31.43	PK	H	30.77	5.14	27.42	39.92	74.00	34.08
4874	19.51	AV	H	30.77	5.14	27.42	28.00	54.00	26.00
7311	32.19	PK	H	34.35	6.74	25.88	47.40	74.00	26.60
7311	20.09	AV	H	34.35	6.74	25.88	35.30	54.00	18.70
9748	32.28	PK	H	36.80	8.61	27.24	50.45	74.00	23.55
9748	20.10	AV	H	36.80	8.61	27.24	38.27	54.00	15.73
3240	40.85	PK	H	27.97	6.26	27.34	47.74	74.00	26.26
3240	28.29	AV	H	27.97	6.26	27.34	35.18	54.00	18.82
4038	37.49	PK	H	29.89	4.65	27.18	44.85	74.00	29.15
4038	25.24	AV	H	29.89	4.65	27.18	32.60	54.00	21.40
High Channel: 2462 MHz									
2462	73.51	PK	H	25.80	3.75	0.00	103.06	N/A	N/A
2462	61.11	AV	H	25.80	3.75	0.00	90.66	N/A	N/A
2462	64.73	PK	V	25.80	3.75	0.00	94.28	N/A	N/A
2462	52.81	AV	V	25.80	3.75	0.00	82.36	N/A	N/A
2483.5	32.04	PK	H	25.86	3.67	0.00	61.57	74.00	12.43
2483.5	20.68	AV	H	25.86	3.67	0.00	50.21	54.00	3.79
4924	31.70	PK	H	30.90	5.34	27.43	40.51	74.00	33.49
4924	18.90	AV	H	30.90	5.34	27.43	27.71	54.00	26.29
7386	30.65	PK	H	34.53	6.83	25.86	46.15	74.00	27.85
7386	18.15	AV	H	34.53	6.83	25.86	33.65	54.00	20.35
9848	32.15	PK	H	36.84	8.66	26.94	50.71	74.00	23.29
9848	20.56	AV	H	36.84	8.66	26.94	39.12	54.00	14.88
3240	40.51	PK	H	27.97	6.26	27.34	47.40	74.00	26.60
3240	28.23	AV	H	27.97	6.26	27.34	35.12	54.00	18.88

802.11 n ht40 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2422 MHz									
2422	73.43	PK	H	25.70	3.71	0.00	102.84	N/A	N/A
2422	61.10	AV	H	25.70	3.71	0.00	90.51	N/A	N/A
2422	64.79	PK	V	25.70	3.71	0.00	94.20	N/A	N/A
2422	52.54	AV	V	25.70	3.71	0.00	81.95	N/A	N/A
2390	34.30	PK	H	25.61	3.63	0.00	63.54	74.00	10.46
2390	21.18	AV	H	25.61	3.63	0.00	50.42	54.00	3.58
4844	31.85	PK	H	30.69	4.99	27.42	40.11	74.00	33.89
4844	19.56	AV	H	30.69	4.99	27.42	27.82	54.00	26.18
7266	32.27	PK	H	34.24	6.68	25.89	47.30	74.00	26.70
7266	20.99	AV	H	34.24	6.68	25.89	36.02	54.00	17.98
9688	31.14	PK	H	36.78	8.58	27.37	49.13	74.00	24.87
9688	19.74	AV	H	36.78	8.58	27.37	37.73	54.00	16.27
3240	40.69	PK	H	27.97	6.26	27.34	47.58	74.00	26.42
3240	28.75	AV	H	27.97	6.26	27.34	35.64	54.00	18.36
Middle Channel: 2437 MHz									
2437	73.30	PK	H	25.74	3.75	0.00	102.79	N/A	N/A
2437	61.74	AV	H	25.74	3.75	0.00	91.23	N/A	N/A
2437	64.17	PK	V	25.74	3.75	0.00	93.66	N/A	N/A
2437	52.43	AV	V	25.74	3.75	0.00	81.92	N/A	N/A
4874	31.01	PK	H	30.77	5.14	27.42	39.50	74.00	34.50
4874	19.27	AV	H	30.77	5.14	27.42	27.76	54.00	26.24
7311	32.19	PK	H	34.35	6.74	25.88	47.40	74.00	26.60
7311	20.44	AV	H	34.35	6.74	25.88	35.65	54.00	18.35
9748	30.64	PK	H	36.80	8.61	27.24	48.81	74.00	25.19
9748	18.32	AV	H	36.80	8.61	27.24	36.49	54.00	17.51
3240	40.74	PK	H	27.97	6.26	27.34	47.63	74.00	26.37
3240	28.12	AV	H	27.97	6.26	27.34	35.01	54.00	18.99
4038	37.35	PK	H	29.89	4.65	27.18	44.71	74.00	29.29
4038	25.29	AV	H	29.89	4.65	27.18	32.65	54.00	21.35
High Channel: 2452 MHz									
2452	73.25	PK	H	25.78	3.78	0.00	102.81	N/A	N/A
2452	61.06	AV	H	25.78	3.78	0.00	90.62	N/A	N/A
2452	64.20	PK	V	25.78	3.78	0.00	93.76	N/A	N/A
2452	52.95	AV	V	25.78	3.78	0.00	82.51	N/A	N/A
2483.5	33.56	PK	H	25.86	3.67	0.00	63.09	74.00	10.91
2483.5	20.99	AV	H	25.86	3.67	0.00	50.52	54.00	3.48
4904	31.26	PK	H	30.85	5.31	27.43	39.99	74.00	34.01
4904	19.87	AV	H	30.85	5.31	27.43	28.60	54.00	25.40
7356	32.97	PK	H	34.45	6.79	25.87	48.34	74.00	25.66
7356	20.02	AV	H	34.45	6.79	25.87	35.39	54.00	18.61
9808	31.23	PK	H	36.82	8.64	27.09	49.60	74.00	24.40
9808	19.75	AV	H	36.82	8.64	27.09	38.12	54.00	15.88
3240	40.88	PK	H	27.97	6.26	27.34	47.77	74.00	26.23
3240	28.07	AV	H	27.97	6.26	27.34	34.96	54.00	19.04

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.5°C
Relative Humidity:	46 %
ATM Pressure:	100.2kPa


* The testing was performed by Lion Xiao on 2016-07-27.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.60	≥ 0.5
	Middle	2437	9.60	≥ 0.5
	High	2462	9.12	≥ 0.5
802.11g	Low	2412	16.40	≥ 0.5
	Middle	2437	16.16	≥ 0.5
	High	2462	16.40	≥ 0.5
802.11n20	Low	2412	17.44	≥ 0.5
	Middle	2437	17.60	≥ 0.5
	High	2462	17.60	≥ 0.5
802.11n40	Low	2422	35.20	≥ 0.5
	Middle	2437	35.84	≥ 0.5
	High	2452	35.52	≥ 0.5

802.11b Low Channel




Date: 27.JUL.2016 20:58:04

802.11b Middle Channel




Date: 27.JUL.2016 21:07:06

802.11b High Channel




Date: 27.JUL.2016 21:05:15

802.11g Low Channel




Date: 27.JUL.2016 20:52:37

802.11g Middle Channel




Date: 27.JUL.2016 20:49:38

802.11g High Channel




Date: 27.JUL.2016 20:44:38

802.11n ht20 Low Channel




Date: 27.JUL.2016 21:13:42

802.11n ht20 Middle Channel




Date: 27.JUL.2016 21:10:40

802.11n ht20 High Channel




Date: 27.JUL.2016 21:15:39

802.11n ht40 Low Channel




Date: 27.JUL.2016 21:24:50

802.11n ht40 Middle Channel



Date: 27.JUL.2016 21:20:08

802.11n ht40 High Channel



Date: 27.JUL.2016 21:27:09

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r05

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2015-11-03	2016-11-03
Agilent	Wideband Power Sensor	N1921A	MY54170013	2015-11-03	2016-11-03
Agilent	P-Series Power Meter	N1912A	MY5000448	2015-11-03	2016-11-03
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.5 °C
Relative Humidity:	46 %
ATM Pressure:	100.2kPa

* The testing was performed by Lion Xiao on 2016-07-27.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
802.11b	Low	2412	19.64	30	Compliance
	Middle	2437	19.51	30	Compliance
	High	2462	19.55	30	Compliance
802.11g	Low	2412	20.62	30	Compliance
	Middle	2437	20.78	30	Compliance
	High	2462	20.66	30	Compliance
802.11n20	Low	2412	20.54	30	Compliance
	Middle	2437	20.49	30	Compliance
	High	2462	20.36	30	Compliance
802.11n40	Low	2422	20.91	30	Compliance
	Middle	2437	20.65	30	Compliance
	High	2452	20.53	30	Compliance

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.5 °C
Relative Humidity:	46 %
ATM Pressure:	100.2kPa

* The testing was performed by Lion Xiao on 2016-07-27.

Test Result: Compliant. Please refer to following plots.

[illegible]

Date: 27.JUL.2016 20:59:02

Ref 20 dBm *Att 30 dB

*RBW 100 kHz *VBW 300 kHz SWT 10 ms

Marker 1 [T1] 2.483516000 GHz 6.97 dBm

Marker 2 [T1] 2.486596000 GHz -46.30 dBm

20 Offset 0.5 dB


-13.03 dBm

1. PK MAXH

Center 2.4835 GHz 8.6 MHz/ Span 86 MHz


Date: 27.JUL.2016 21:06:16

802.11g: Band Edge, Left Side




Date: 27.JUL.2016 20:53:38

802.11g: Band Edge, Right Side




Date: 27.JUL.2016 20:45:47

802.11n ht20 Band Edge, Left Side




Date: 27.JUL.2016 21:14:50

802.11n ht20 Band Edge, Right Side




Date: 27.JUL.2016 21:16:42

802.11n ht40 Band Edge, Left Side



Date: 27.JUL.2016 21:26:07

802.11n ht40 Band Edge, Right Side



Date: 27.JUL.2016 21:28:26

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.5 °C
Relative Humidity:	46 %
ATM Pressure:	100.2kPa


* The testing was performed by Lion Xiao on 2016-07-27.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots


Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-7.94	≤ 8
	Middle	2437	-8.00	≤ 8
	High	2462	-7.99	≤ 8
802.11g	Low	2412	-12.56	≤ 8
	Middle	2437	-12.46	≤ 8
	High	2462	-12.53	≤ 8
802.11n20	Low	2412	-13.13	≤ 8
	Middle	2437	-13.15	≤ 8
	High	2462	-13.22	≤ 8
802.11n40	Low	2422	-15.63	≤ 8
	Middle	2437	-15.89	≤ 8
	High	2452	-15.95	≤ 8

Power Spectral Density, 802.11b Low Channel




Date: 27.JUL.2016 21:48:13

Power Spectral Density, 802.11b Middle Channel




Date: 27.JUL.2016 21:07:48

Power Spectral Density, 802.11b High Channel




Date: 27.JUL.2016 21:05:58

Power Spectral Density, 802.11g Low Channel




Date: 27.JUL.2016 21:42:49

Power Spectral Density, 802.11g Middle Channel




Date: 27.JUL.2016 21:39:49

Power Spectral Density, 802.11g High Channel




Date: 27.JUL.2016 21:44:42

Power Spectral Density, 802.11n ht20 Low Channel




Date: 27.JUL.2016 21:14:26

Power Spectral Density, 802.11n ht20 Middle Channel




Date: 27.JUL.2016 21:37:39

Power Spectral Density, 802.11n ht20 High Channel




Date: 27.JUL.2016 21:16:25

Power Spectral Density, 802.11n ht40 Low Channel




Date: 27.JUL.2016 21:34:41

Power Spectral Density, 802.11n ht40 Middle Channel



Date: 27.JUL.2016 21:21:07

Power Spectral Density, 802.11n ht40 High Channel



Date: 27.JUL.2016 21:28:08

***** END OF REPORT *****