

# TEST REPORT

**FCC ID: 2AIOC-C1001W**

**Product: Video Doorbell**

**Model No.: HKAP-C1001W**

**Additional Model No.: N/A**

**Trade Mark: N/A**

**Report No.: TCT170831E009**

**Issued Date: Oct. 20, 2017**

Issued for:

**HANK ELECTRONICS CO., LTD.**

**Floor 2nd-7th, A8, Hongye Industry City, Lezhujiao, Zhoushi Road, Baoan District, Shenzhen, China**

Issued By:

**Shenzhen Tongce Testing Lab.**

**1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China**

**TEL: +86-755-27673339**

**FAX: +86-755-27673332**

**Note:** This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

**TABLE OF CONTENTS**

1. Test Certification..... 3

2. Test Result Summary ..... 4

3. EUT Description ..... 5

4. Genera Information..... 7

    4.1. Test environment and mode..... 7

    4.2. Description of Support Units..... 9

5. Facilities and Accreditations ..... 10

    5.1. Facilities ..... 10

    5.2. Location ..... 10

    5.3. Measurement Uncertainty..... 10

6. Test Results and Measurement Data ..... 11

    6.1. Antenna requirement ..... 11

    6.2. Conducted Emission..... 12

    6.3. Emission Bandwidth ..... 17

    6.4. Power Spectral Density..... 18

    6.5. Conducted Band Edge and Spurious Emission Measurement ..... 19

    6.6. Radiated Spurious Emission Measurement..... 21

Appendix A: Test Result of Conducted Test

Appendix B: Photographs of Test Setup

Appendix C: Photographs of EUT

## 1. Test Certification

<b>Product:</b>	Video Doorbell
<b>Model No.:</b>	HKAP-C1001W
<b>Additional Model:</b>	N/A
<b>Trade Mark:</b>	N/A
<b>Applicant:</b>	HANK ELECTRONICS CO., LTD.
<b>Address:</b>	Floor 2nd-7th, A8, Hongye Industry City, Lezhujiao, Zhoushi Road, Baoan District, Shenzhen, China
<b>Manufacturer:</b>	HANK ELECTRONICS CO., LTD.
<b>Address:</b>	Floor 2nd-7th, A8, Hongye Industry City, Lezhujiao, Zhoushi Road, Baoan District, Shenzhen, China
<b>Date of Test:</b>	Sep. 01, 2017 – Oct. 19, 2017
<b>Applicable Standards:</b>	FCC CFR Title 47 Part 15 Subpart C Section 15.247 KDB 558074 D01 DTS Meas Guidance v04

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:



Jin Wang

Date:

Oct. 19, 2017

Reviewed By:



Joe Zhou

Date:

Oct. 20, 2017

Approved By:



Tomsin

Date:

Oct. 20, 2017

## 2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3) §2.1046	PASS
6dB Emission Bandwidth	§15.247 (a)(2) §2.1049	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	§15.247(d) §2.1051, §2.1057	PASS
Spurious Emission	§15.205/§15.209 §2.1053, §2.1057	PASS

**Note:**

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

### 3. EUT Description

<b>Product:</b>	Video Doorbell
<b>Model No.:</b>	HKAP-C1001W
<b>Additional Model:</b>	N/A
<b>Trade Mark:</b>	<b>N/A</b>
<b>Operation Frequency:</b>	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)) 2422MHz~2452MHz (802.11n(HT40))
<b>Channel Separation:</b>	5MHz
<b>Number of Channel:</b>	11 for 802.11b/802.11g/802.11n(HT20) 7 for 802.11n(HT40)
<b>Modulation Technology: (IEEE 802.11b)</b>	Direct Sequence Spread Spectrum (DSSS)
<b>Modulation Technology: (IEEE 802.11g/802.11n)</b>	Orthogonal Frequency Division Multiplexing(OFDM)
<b>Data speed (IEEE 802.11b):</b>	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
<b>Data speed (IEEE 802.11g):</b>	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
<b>Data speed (IEEE 802.11n):</b>	Up to 150Mbps
<b>Antenna Type:</b>	Integral Antenna
<b>Antenna Gain:</b>	2.0dBi
<b>Power Supply:</b>	AC 16-24V 1A / DC 12-30V 1A
<b>Adapter:</b>	Adapter Information: Model No.: BI12T-120100-BdV Input: AC 100-240V, 50/60Hz, 0.5A Output: DC 12V, 1A

**Operation Frequency each of channel For 802.11b/g/n(HT20)**

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

**Operation Frequency each of channel For 802.11n (HT40)**

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
--	--	4	2427MHz	7	2442MHz	--	--
--	--	5	2432MHz	8	2447MHz	--	--
3	2422MHz	6	2437MHz	9	2452MHz		

**Note:**

*In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:*

**802.11b/802.11g/802.11n (HT20)**

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The Highest channel	2462MHz

**802.11n (HT40)**

Channel	Frequency
The lowest channel	2422MHz
The middle channel	2437MHz
The Highest channel	2452MHz

## 4. Genera Information

### 4.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 98.46%)
<p>The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. For the full battery state and The output power to the maximum state.</p>	

<p>We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:</p>	
Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(H20)	6.5Mbps
802.11n(H40)	13.5Mbps
Final Test Mode:	
Operation mode:	Keep the EUT in continuous transmitting with modulation
<p>1. For WIFI function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.</p> <p>2. According to ANSI C63.10 standards, the test results are both the “worst case” and</p>	

“worst setup” 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20), 13.5Mbps for 802.11(H40). Duty cycle setting during the transmission is 98.5% with maximum power setting for all modulations.



## 4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

**Note:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

## 5. Facilities and Accreditations

### 5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

### 5.2. Location

Shenzhen Tongce Testing Lab

Address: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

TEL: +86-755-27673339

### 5.3. Measurement Uncertainty


The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^\circ\text{C}$
7	Humidity	$\pm 1.0\%$

## 6. Test Results and Measurement Data

### 6.1. Antenna requirement

<b>Standard requirement:</b>	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
<b>E.U.T Antenna:</b>	
The WIFI antenna is an integral antenna which permanently attached, and the best case gain of the antenna is 2.0dBi.	



## 6.2. Conducted Emission

### 6.2.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.207														
<b>Test Method:</b>	ANSI C63.10:2013														
<b>Frequency Range:</b>	150 kHz to 30 MHz														
<b>Receiver setup:</b>	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
<b>Limits:</b>	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
<b>Test Setup:</b>	<p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
<b>Test Mode:</b>	Charging + transmitting with modulation														
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>The E.U.T is connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</li> </ol>														
<b>Test Result:</b>	PASS														

**6.2.2. Test Instruments**


Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Test Receiver	R&S	ESPI	101401	Jun. 12, 2018
LISN	Schwarzbeck	NSLK 8126	8126453	Sep. 27, 2018
Coax cable (9KHz-30MHz)	TCT	CE-05	N/A	Sep. 27, 2018
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)




Site: Phase: **L1** Temperature: 25  
Limit: FCC Part 15B Class B Conduction(QP) Power: AC 120V/60Hz Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.3615	24.79	11.38	36.17	58.69	-22.52	peak	
2	*	0.6360	33.55	11.25	44.80	56.00	-11.20	peak	
3		1.1355	27.51	11.27	38.78	56.00	-17.22	peak	
4		1.6440	25.28	11.53	36.81	56.00	-19.19	peak	
5		2.5260	23.82	11.51	35.33	56.00	-20.67	peak	
6		27.8295	29.78	10.73	40.51	60.00	-19.49	peak	

Note:

- Freq. = Emission frequency in MHz
- Reading level (dBuV) = Receiver reading
- Corr. Factor (dB) = Antenna factor + Cable loss
- Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)
- Limit (dBuV) = Limit stated in standard
- Margin (dB) = Measurement (dBuV) – Limits (dBuV)
- Q.P. =Quasi-Peak
- AVG =average
- \* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

**Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)**



Site: \_\_\_\_\_ Phase: **N** Temperature: 25  
 Limit: FCC Part 15B Class B Conduction(QP) Power: AC 120V/60Hz Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.3525	28.55	11.38	39.93	58.90	-18.97	peak	
2		0.5775	33.14	11.28	44.42	56.00	-11.58	peak	
3	*	0.6360	34.16	11.25	45.41	56.00	-10.59	peak	
4		1.1310	31.16	11.27	42.43	56.00	-13.57	peak	
5		1.6305	28.90	11.52	40.42	56.00	-15.58	peak	
6		26.0610	31.15	10.77	41.92	60.00	-18.08	peak	

**Note:**

- Freq. = Emission frequency in MHz
- Reading level (dBuV) = Receiver reading
- Corr. Factor (dB) = Antenna factor + Cable loss
- Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)
- Limit (dBuV) = Limit stated in standard
- Margin (dB) = Measurement (dBuV) – Limits (dBuV)
- Q.P. =Quasi-Peak
- AVG =average
- \* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.








## 6.4. Power Spectral Density

### 6.4.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (e)
<b>Test Method:</b>	KDB 558074
<b>Limit:</b>	The average power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
<b>Test Setup:</b>	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The testing follows Measurement Procedure 10.3 Method AVGPSD of FCC KDB Publication No.558074 D01 DTS Meas. Guidance v04</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): <math>3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}</math>. Video bandwidth <math>\text{VBW} \geq 3 \times \text{RBW}</math>. Set the span to at least 1.5 times the OBW.</li> <li>5. Detector = RMS, Sweep time = auto couple.</li> <li>6. Employ trace averaging (RMS) mode over a minimum of 100 traces. Use the peak marker function to determine the maximum power level.</li> <li>6. Measure and record the results in the test report.</li> </ol>
<b>Test Result:</b>	PASS

### 6.4.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 27, 2018
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Sep. 27, 2018
Antenna Connector	TCT	RFC-01	N/A	Sep. 27, 2018

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



### 6.5.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 27, 2018
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Sep. 27, 2018
Antenna Connector	TCT	RFC-01	N/A	Sep. 27, 2018


**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

## 6.6. Radiated Spurious Emission Measurement


### 6.6.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.209					
<b>Test Method:</b>	ANSI C63.10: 2013					
<b>Frequency Range:</b>	9 kHz to 25 GHz					
<b>Measurement Distance:</b>	3 m					
<b>Antenna Polarization:</b>	Horizontal & Vertical					
<b>Operation mode:</b>	Transmitting mode with modulation					
<b>Receiver Setup:</b>	Frequency	Detector	RBW	VBW	Remark	
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value	
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	
	Above 1GHz	Peak	1MHz	3MHz	Peak Value	
		Peak	1MHz	10Hz	Average Value	
<b>Limit:</b>	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)			
	0.009-0.490	2400/F(KHz)	300			
	0.490-1.705	24000/F(KHz)	30			
	1.705-30	30	30			
	30-88	100	3			
	88-216	150	3			
	216-960	200	3			
	Above 960	500	3			
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector		
	Above 1GHz	500	3	Average		
	5000	3	Peak			
<b>Test setup:</b>	For radiated emissions below 30MHz					
	<p>The diagram illustrates the test setup for radiated emissions below 30MHz. It shows an EUT (Equipment Under Test) on a turn table at a height of 0.8m. A ground plane is positioned below the turn table. An antenna is placed at a distance of 3m from the EUT. The antenna is connected to a receiver system consisting of a Pre-Amplifier, a Receiver, and a Computer.</p>					

30MHz to 1GHz



Above 1GHz



**Test Procedure:**

- For the radiated emission test below 1GHz:  
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
- For the radiated emission test above 1GHz:  
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission

	<p>and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</p> <p>4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>5. Use the following spectrum analyzer settings:</p> <p>(1) Span shall wide enough to fully capture the emission being measured;</p> <p>(2) Set RBW=100 kHz for <math>f &lt; 1</math> GHz; <math>VBW \geq RBW</math>; Sweep = auto; Detector function = peak; Trace = max hold;</p> <p>(3) Set RBW = 1 MHz, VBW= 3MHz for <math>f \geq 1</math> GHz for peak measurement.</p> <p>For average measurement: <math>VBW = 10</math> Hz, when duty cycle is no less than 98 percent. <math>VBW \geq 1/T</math>, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p>
<b>Test results:</b>	<b>PASS</b>

6.6.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Test Receiver	ROHDE&SCHW ARZ	ESVD	100008	Sep. 27, 2018
Spectrum Analyzer	ROHDE&SCHW ARZ	FSQ	200061	Sep. 27, 2018
Pre-amplifier	EM Electronics Corporation CO.,LTD	EM30265	07032613	Sep. 27, 2018
Pre-amplifier	HP	8447D	2727A05017	Sep. 27, 2018
Loop antenna	ZHINAN	ZN30900A	12024	Sep. 27, 2018
Broadband Antenna	Schwarzbeck	VULB9163	340	Sep. 27, 2018
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Sep. 27, 2018
Horn Antenna	Schwarzbeck	BBH 9170	582	Jun. 07, 2018
Antenna Mast	Keleto	CC-A-4M	N/A	N/A
Coax cable (9KHz-1GHz)	TCT	RE-low-01	N/A	Sep. 27, 2018
Coax cable (9KHz-40GHz)	TCT	RE-high-02	N/A	Sep. 27, 2018
Coax cable (9KHz-1GHz)	TCT	RE-low-03	N/A	Sep. 27, 2018
Coax cable (9KHz-40GHz)	TCT	RE-high-04	N/A	Sep. 27, 2018
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A


**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



6.6.3. Test Data

Please refer to following diagram for individual  
Below 1GHz


Horizontal:



Site: Polarization: **Horizontal** Temperature: 25  
Limit: FCC Part 15B Class B 3M Radiation Power: AC 120V/60Hz Humidity: 55 %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree		
1		102.0014	42.00	-11.54	30.46	43.50	-13.04			QP	
2		183.2005	45.90	-12.84	33.06	43.50	-10.44			QP	
3		360.4476	43.60	-7.01	36.59	46.00	-9.41			QP	
4	*	499.4247	43.00	-2.99	40.01	46.00	-5.99			QP	
5		576.6443	42.10	-2.17	39.93	46.00	-6.07			QP	
6		916.0687	36.40	3.21	39.61	46.00	-6.39			QP	

Vertical:



Site: Polarization: **Vertical** Temperature: 25  
 Limit: FCC Part 15B Class B 3M Radiation Power: AC 120V/60Hz Humidity: 55 %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dB/m	dB	cm	degree
1		32.4059	37.40	-13.41	23.99	40.00	-16.01	QP	
2		100.9339	36.90	-11.49	25.41	43.50	-18.09	QP	
3		183.8439	36.40	-12.80	23.60	43.50	-19.90	QP	
4		360.4476	35.90	-7.01	28.89	46.00	-17.11	QP	
5	*	576.6443	40.00	-2.17	37.83	46.00	-8.17	QP	
6		654.2318	35.00	-0.81	34.19	46.00	-11.81	QP	

**Note:** 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low) and all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40) ), and the worst case Mode (Middle channel and 802.11b) was submitted only.

**Test Result of Radiated Spurious at Band edges**

Modulation Type: 802.11b

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)
2310	H	47.22	-4.20	43.02	74.00	54.00
2377.38	H	47.88	-4.10	43.78	74.00	54.00
2390	H	53.64	-3.94	49.70	74.00	54.00
2310	V	44.38	-4.20	40.18	74.00	54.00
2377.38	V	52.96	-4.10	48.86	74.00	54.00
2390	V	54.49	-3.94	50.55	74.00	54.00

Modulation Type: 802.11b

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)
2483.5	H	50.59	-3.60	46.99	74.00	54.00
2487.09	H	47.14	-3.50	43.64	74.00	54.00
2500	H	44.39	-3.34	41.05	74.00	54.00
2483.5	V	53.40	-3.60	49.80	74.00	54.00
2487.09	V	46.72	-3.50	43.22	74.00	54.00
2500	V	42.17	-3.34	38.83	74.00	54.00

Modulation Type: 802.11g

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)
2310	H	42.40	-4.20	38.20	74.00	54.00
2388.96	H	50.44	-4.12	46.32	74.00	54.00
2390	H	52.44	-3.94	48.50	74.00	54.00
2310	V	44.89	-4.20	40.69	74.00	54.00
2388.96	V	49.00	-4.12	44.88	74.00	54.00
2390	V	53.21	-3.94	49.27	74.00	54.00

Modulation Type: 802.11g

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)
2483.5	H	52.45	-3.60	48.85	74.00	54.00
2487.59	H	50.74	-3.52	47.22	74.00	54.00
2500	H	47.16	-3.34	43.82	74.00	54.00
2483.5	V	51.90	-3.60	48.30	74.00	54.00
2487.59	V	48.15	-3.52	44.63	74.00	54.00
2500	V	47.83	-3.34	44.49	74.00	54.00

Modulation Type: 802.11n(20MHz)

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dBμV/m)	AV limit (dBμV/m)
2310	H	45.96	-4.20	41.76	74.00	54.00
2388.01	H	51.24	-4.10	47.14	74.00	54.00
2390	H	52.87	-3.94	48.93	74.00	54.00
2310	V	47.42	-4.20	43.22	74.00	54.00
2388.01	V	51.99	-4.10	47.89	74.00	54.00
2390	V	53.78	-3.94	49.84	74.00	54.00

Modulation Type: 802.11n(20MHz)

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dBμV/m)	AV limit (dBμV/m)
2483.5	H	51.84	-3.60	48.24	74.00	54.00
2392.55	H	50.21	-3.50	46.71	74.00	54.00
2500	H	47.33	-3.34	43.99	74.00	54.00
2483.5	V	52.59	-3.60	48.99	74.00	54.00
2392.55	V	49.67	-3.50	46.17	74.00	54.00
2500	V	48.38	-3.34	45.04	74.00	54.00

Modulation Type: 802.11n(40MHz)

Low channel: 2422 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dBμV/m)	AV limit (dBμV/m)
2310	H	45.82	-4.20	41.62	74.00	54.00
2387.85	H	52.80	-4.10	48.70	74.00	54.00
2390	H	53.87	-3.94	49.93	74.00	54.00
2310	V	47.35	-4.20	43.15	74.00	54.00
2389.98	V	53.49	-4.10	49.39	74.00	54.00
2390	V	54.59	-3.94	50.65	74.00	54.00

Modulation Type: 802.11n(40MHz)

High channel: 2452 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	Correction Factor (dB/m)	Peak Final Emission Level	Peak limit (dBμV/m)	AV limit (dBμV/m)
2483.5	H	51.75	-3.60	48.15	74.00	54.00
2493.51	H	50.65	-3.50	47.15	74.00	54.00
2500	H	46.81	-3.34	43.47	74.00	54.00
2493.51	V	52.34	-3.60	48.74	74.00	54.00
2489.36	V	49.85	-3.50	46.35	74.00	54.00
2500	V	47.85	-3.34	44.51	74.00	54.00

**Note:**

1. Peak Final Emission Level=Peak Reading + Correction Factor;
2. Correction Factor=Antenna Factor + Cable loss – Pre-amplifier

**Above 1GHz**

Modulation Type: 802.11b

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	48.40	---	0.75	49.15	---	74	54	-4.85
7236	H	39.87	---	9.87	49.74	---	74	54	-4.26
---	H	---	---	---	---	---	---	---	---
4824	V	47.90	---	0.75	48.65	---	74	54	-5.35
7236	V	40.24	---	9.87	50.11	---	74	54	-3.89
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	48.43	---	0.97	49.40	---	74	54	-4.60
7311	H	40.23	---	9.83	50.06	---	74	54	-3.94
---	H	---	---	---	---	---	---	---	---
4874	V	48.50	---	0.97	49.47	---	74	54	-4.53
7311	V	40.19	---	9.83	50.02	---	74	54	-3.98
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	48.58	---	1.18	49.76	---	74	54	-4.24
7386	H	39.20	---	10.07	49.27	---	74	54	-4.73
---	H	---	---	---	---	---	---	---	---
4924	V	49.23	---	1.18	50.41	---	74	54	-3.59
7386	V	39.73	---	10.07	49.80	---	74	54	-4.20
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "---" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: 802.11g

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4824	H	48.70	---	0.75	49.45	---	74	54	-4.55
7236	H	40.03	---	9.87	49.90	---	74	54	-4.10
---	H	---	---	---	---	---	---	---	---
4824	V	47.73	---	0.75	48.48	---	74	54	-5.52
7236	V	40.39	---	9.87	50.26	---	74	54	-3.74
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	48.40	---	0.97	49.37	---	74	54	-4.63
7311	H	39.81	---	9.83	49.64	---	74	54	-4.36
---	H	---	---	---	---	---	---	---	---
4874	V	47.81	---	0.97	48.78	---	74	54	-5.22
7311	V	40.36	---	9.83	50.19	---	74	54	-3.81
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4924	H	48.19	---	1.18	49.37	---	74	54	-4.63
7386	H	39.39	---	10.07	49.46	---	74	54	-4.54
---	H	---	---	---	---	---	---	---	---
4924	V	47.33	---	1.18	48.51	---	74	54	-5.49
7386	V	39.59	---	10.07	49.66	---	74	54	-4.34
---	V	---	---	---	---	---	---	---	---

**Note:**

- Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
- Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
- Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: 802.11n (HT20)

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4824	H	48.73	---	0.75	49.48	---	74	54	-4.52
7236	H	40.31	---	9.87	50.18	---	74	54	-3.82
---	H	---	---	---	---	---	---	---	---
4824	V	48.10	---	0.75	48.85	---	74	54	-5.15
7236	V	39.36	---	9.87	49.23	---	74	54	-4.77
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	47.78	---	0.97	48.75	---	74	54	-5.25
7311	H	39.72	---	9.83	49.55	---	74	54	-4.45
---	H	---	---	---	---	---	---	---	---
4874	V	47.85	---	0.97	48.82	---	74	54	-5.18
7311	V	39.67	---	9.83	49.50	---	74	54	-4.50
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4924	H	47.38	---	1.18	48.56	---	74	54	-5.44
7386	H	39.83	---	10.07	49.90	---	74	54	-4.10
---	H	---	---	---	---	---	---	---	---
4924	V	47.11	---	1.18	48.29	---	74	54	-5.71
7386	V	39.53	---	10.07	49.60	---	74	54	-4.40
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: 802.11n (HT40)

Low channel: 2422 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4844	H	46.97	---	0.66	47.63	---	74	54	-6.37
7266	H	38.52	---	9.5	48.02	---	74	54	-5.98
---	H	---	---	---	---	---	---	---	---
4824	V	44.56	---	0.66	45.22	---	74	54	-8.78
7236	V	35.6	---	9.5	45.1	---	74	54	-8.9
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4874	H	42.95	---	0.99	43.94	---	74	54	-10.06
7311	H	34.61	---	9.85	44.46	---	74	54	-9.54
---	H	---	---	---	---	---	---	---	---
4874	V	43.7	---	0.99	44.69	---	74	54	-9.31
7311	V	37.35	---	9.85	47.2	---	74	54	-6.8
---	V	---	---	---	---	---	---	---	---

High channel: 2452 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4904	H	45.18	---	1.33	46.51	---	74	54	-7.49
7356	H	36.29	---	10.22	46.51	---	74	54	-7.49
---	H	---	---	---	---	---	---	---	---
4904	V	45.69	---	1.33	47.02	---	74	54	-6.98
7356	V	36.81	---	10.22	47.03	---	74	54	-6.97
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "—" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.



## Appendix A: Test Result of Conducted Test Conducted Average Output Power




**Result Table**




Mode	Channel	Meas.Level [dBm]	Verdict
11B	LCH	9.87	PASS
11B	MCH	9.86	PASS
11B	HCH	9.68	PASS
11G	LCH	9.30	PASS
11G	MCH	9.06	PASS
11G	HCH	9.01	PASS
11N20SISO	LCH	9.31	PASS
11N20SISO	MCH	9.07	PASS
11N20SISO	HCH	9.08	PASS
11N40SISO	LCH	9.10	PASS
11N40SISO	MCH	9.23	PASS
11N40SISO	HCH	9.18	PASS

**Test Graph**




<p>11B/HCH</p>	<p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.462000000 GHz</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Center 2.462 GHz #Res BW 1 MHz #VBW 3 MHz Span 24.42 MHz #Sweep 100 ms</p> <p>Channel Power: 9.68 dBm / 12.21 MHz</p> <p>Power Spectral Density: -60.69 dBm /Hz</p>	<p>Frequency</p> <p>Center Freq 2.462000000 GHz</p> <p>CF Step 2.442400 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11G/LCH</p>	<p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.412000000 GHz</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Center 2.412 GHz #Res BW 1 MHz #VBW 3 MHz Span 32.84 MHz #Sweep 100 ms</p> <p>Channel Power: 9.30 dBm / 16.47 MHz</p> <p>Power Spectral Density: -62.86 dBm /Hz</p>	<p>Frequency</p> <p>Center Freq 2.412000000 GHz</p> <p>CF Step 3.293800 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11G/MCH</p>	<p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.437000000 GHz</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Center 2.437 GHz #Res BW 1 MHz #VBW 3 MHz Span 32.92 MHz #Sweep 100 ms</p> <p>Channel Power: 9.06 dBm / 16.46 MHz</p> <p>Power Spectral Density: -63.10 dBm /Hz</p>	<p>Frequency</p> <p>Center Freq 2.437000000 GHz</p> <p>CF Step 3.292200 MHz</p> <p>Freq Offset 0 Hz</p>

11G/HCH	 <p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.462000000 GHz</p> <p>Channel Power: 9.01 dBm / 16.47 MHz</p> <p>Power Spectral Density: -63.16 dBm / Hz</p>	<p>Frequency</p> <p>Center Freq: 2.462000000 GHz</p> <p>CF Step: 3.293600 MHz</p> <p>Freq Offset: 0 Hz</p>
11N20SISO/LCH	 <p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.412000000 GHz</p> <p>Channel Power: 9.31 dBm / 17.56 MHz</p> <p>Power Spectral Density: -63.14 dBm / Hz</p>	<p>Frequency</p> <p>Center Freq: 2.412000000 GHz</p> <p>CF Step: 3.511200 MHz</p> <p>Freq Offset: 0 Hz</p>
11N20SISO/MCH	 <p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.437000000 GHz</p> <p>Channel Power: 9.07 dBm / 17.55 MHz</p> <p>Power Spectral Density: -63.37 dBm / Hz</p>	<p>Frequency</p> <p>Center Freq: 2.437000000 GHz</p> <p>CF Step: 3.509600 MHz</p> <p>Freq Offset: 0 Hz</p>

<p>11N20SISO/HCH</p>	 <p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.462000000 GHz Center Freq: 2.462000000 GHz Radio Std: None</p> <p>Trig: Free Run Avg/Hold: 10/10</p> <p>#Gain: Low #Atten: 30 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Center 2.462 GHz Span 35.1 MHz</p> <p>#Res BW 1 MHz #VBW 3 MHz #Sweep 100 ms</p> <p>Channel Power Power Spectral Density</p> <p>9.08 dBm / 17.55 MHz -63.36 dBm /Hz</p> <p>Frequency</p> <p>Center Freq 2.462000000 GHz</p> <p>CF Step 3.509800 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11N40SISO/LCH</p>	 <p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.422000000 GHz Center Freq: 2.422000000 GHz Radio Std: None</p> <p>Trig: Free Run Avg/Hold: 10/10</p> <p>#Gain: Low #Atten: 30 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Center 2.422 GHz Span 72.03 MHz</p> <p>#Res BW 1 MHz #VBW 3 MHz #Sweep 100 ms</p> <p>Channel Power Power Spectral Density</p> <p>9.10 dBm / 36.02 MHz -65.47 dBm /Hz</p> <p>Frequency</p> <p>Center Freq 2.422000000 GHz</p> <p>CF Step 7.203200 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11N40SISO/MCH</p>	 <p>Agilent Spectrum Analyzer - Channel Power</p> <p>Center Freq 2.437000000 GHz Center Freq: 2.437000000 GHz Radio Std: None</p> <p>Trig: Free Run Avg/Hold: 10/10</p> <p>#Gain: Low #Atten: 30 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Center 2.437 GHz Span 72.01 MHz</p> <p>#Res BW 1 MHz #VBW 3 MHz #Sweep 100 ms</p> <p>Channel Power Power Spectral Density</p> <p>9.23 dBm / 36.01 MHz -65.93 dBm /Hz</p> <p>Frequency</p> <p>Center Freq 2.437000000 GHz</p> <p>CF Step 7.201000 MHz</p> <p>Freq Offset 0 Hz</p>

11N40SISO/HCH



## 6dB Occupied Bandwidth


### Result Table

Mode	Channel	6dB Bandwidth [MHz]	99% OBW [MHz]	Verdict
11B	LCH	10.07	12.226	PASS
11B	MCH	10.07	12.205	PASS
11B	HCH	10.06	12.212	PASS
11G	LCH	16.36	16.469	PASS
11G	MCH	16.36	16.461	PASS
11G	HCH	16.35	16.468	PASS
11N20SISO	LCH	17.54	17.556	PASS
11N20SISO	MCH	17.32	17.548	PASS
11N20SISO	HCH	17.08	17.549	PASS
11N40SISO	LCH	35.61	36.016	PASS
11N40SISO	MCH	35.66	36.005	PASS
11N40SISO	HCH	35.54	36.016	PASS


### Test Graph

#### Graphs

11B/LCH



11B/MCH




<p>11B/HCH</p>	<p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.462000000 GHz</p> <p>Center Freq: 2.462000000 GHz</p> <p>Trig: Free Run AvgHold: 10/10</p> <p>#Gain: Low #Atten: 30 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Center 2.462 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 4.267 ms</p> <p>Occupied Bandwidth 12.212 MHz Total Power 16.9 dBm</p> <p>Transmit Freq Error -21.738 kHz OBW Power 99.00 %</p> <p>x dB Bandwidth 10.06 MHz x dB -6.00 dB</p>	<p>Frequency</p> <p>Center Freq 2.462000000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11G/LCH</p>	<p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.412000000 GHz</p> <p>Center Freq: 2.412000000 GHz</p> <p>Trig: Free Run AvgHold: 10/10</p> <p>#Gain: Low #Atten: 30 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 4.267 ms</p> <p>Occupied Bandwidth 16.469 MHz Total Power 15.6 dBm</p> <p>Transmit Freq Error -37.948 kHz OBW Power 99.00 %</p> <p>x dB Bandwidth 16.36 MHz x dB -6.00 dB</p>	<p>Frequency</p> <p>Center Freq 2.412000000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11G/MCH</p>	<p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.437000000 GHz</p> <p>Center Freq: 2.437000000 GHz</p> <p>Trig: Free Run AvgHold: 10/10</p> <p>#Gain: Low #Atten: 30 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 4.267 ms</p> <p>Occupied Bandwidth 16.461 MHz Total Power 15.2 dBm</p> <p>Transmit Freq Error -42.602 kHz OBW Power 99.00 %</p> <p>x dB Bandwidth 16.36 MHz x dB -6.00 dB</p>	<p>Frequency</p> <p>Center Freq 2.437000000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Freq Offset 0 Hz</p>

<p>11G/HCH</p>		<p>Frequency</p> <p>Center Freq 2.462000000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11N20SISO/LCH</p>		<p>Frequency</p> <p>Center Freq 2.412000000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11N20SISO/MCH</p>		<p>Frequency</p> <p>Center Freq 2.437000000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Freq Offset 0 Hz</p>



<p>11N20SISO/HCH</p>	<p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.462000000 GHz Center Freq: 2.462000000 GHz Radio Std: None</p> <p>Trig: Free Run AvgHold: 10/10</p> <p>#Gain: Low #Atten: 30 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Center 2.462 GHz Span 40 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4.267 ms</p> <p>Occupied Bandwidth 17.549 MHz Total Power 15.2 dBm</p> <p>Transmit Freq Error -35.666 kHz OBW Power 99.00 %</p> <p>x dB Bandwidth 17.08 MHz x dB -6.00 dB</p> <p>Frequency 2.462000000 GHz</p> <p>CF Step 4.000000 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11N40SISO/LCH</p>	<p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.422000000 GHz Center Freq: 2.422000000 GHz Radio Std: None</p> <p>Trig: Free Run AvgHold: 10/10</p> <p>#Gain: Low #Atten: 30 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Center 2.422 GHz Span 80 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 8 ms</p> <p>Occupied Bandwidth 36.016 MHz Total Power 16.2 dBm</p> <p>Transmit Freq Error -35.874 kHz OBW Power 99.00 %</p> <p>x dB Bandwidth 35.61 MHz x dB -6.00 dB</p> <p>Frequency 2.422000000 GHz</p> <p>CF Step 8.000000 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11N40SISO/MCH</p>	<p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.437000000 GHz Center Freq: 2.437000000 GHz Radio Std: None</p> <p>Trig: Free Run AvgHold: 10/10</p> <p>#Gain: Low #Atten: 30 dB Radio Device: BTS</p> <p>Ref Offset 0.9 dB Ref 20.00 dBm</p> <p>Center 2.437 GHz Span 80 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 8 ms</p> <p>Occupied Bandwidth 36.005 MHz Total Power 15.8 dBm</p> <p>Transmit Freq Error -43.068 kHz OBW Power 99.00 %</p> <p>x dB Bandwidth 35.66 MHz x dB -6.00 dB</p> <p>Frequency 2.437000000 GHz</p> <p>CF Step 8.000000 MHz</p> <p>Freq Offset 0 Hz</p>

11N40SISO/HCH



## Band-edge for RF Conducted Emissions


### Result Table

Mode	Channel	Carrier Power [dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
11B	LCH	-0.013	-56.457	-30.01	PASS
11B	HCH	-0.126	-55.656	-30.13	PASS
11G	LCH	-1.923	-51.846	-31.92	PASS
11G	HCH	-1.984	-54.747	-31.98	PASS
11N20SISO	LCH	-2.255	-49.075	-32.26	PASS
11N20SISO	HCH	-1.905	-55.467	-31.91	PASS
11N40SISO	LCH	-4.366	-43.152	-34.37	PASS
11N40SISO	HCH	-4.188	-53.805	-34.19	PASS


### Test Graph




11G/LCH




11G/HCH




11N20SISO/LCH




11N20SISO/HCH



11N40SISO/LCH



11N40SISO/HCH




## RF Conducted Spurious Emissions


### Result Table

Mode	Channel	Pref [dBm]	Puw [dBm]	Verdict
11B	LCH	-0.085	<Limit	PASS
11B	MCH	-0.123	<Limit	PASS
11B	HCH	-0.199	<Limit	PASS
11G	LCH	-2.272	<Limit	PASS
11G	MCH	-2.543	<Limit	PASS
11G	HCH	-2.006	<Limit	PASS
11N20SISO	LCH	-1.883	<Limit	PASS
11N20SISO	MCH	-2.109	<Limit	PASS
11N20SISO	HCH	-1.894	<Limit	PASS
11N40SISO	LCH	-4.171	<Limit	PASS
11N40SISO	MCH	-4.682	<Limit	PASS
11N40SISO	HCH	-4.407	<Limit	PASS



### Test Graph









## 11B MCH Graphs









## 11B\_HCH\_Graphs

