



# FCC RF Test Report

**APPLICANT** : AzulFlower LLC  
**EQUIPMENT** : Tablet PC  
**MODEL NAME** : SL056ZE  
**FCC ID** : 2AIP5-3975  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System

The testing was completed on Feb. 03, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL INC.**

No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



# TABLE OF CONTENTS

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION..... 5**

1.1 Applicant ..... 5

1.2 Product Feature of Equipment Under Test..... 5

1.3 Product Specification of Equipment Under Test..... 5

1.4 Modification of EUT ..... 5

1.5 Testing Location ..... 6

1.6 Applicable Standards..... 6

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 7**

2.1 Carrier Frequency Channel ..... 7

2.2 Descriptions of Test Mode..... 8

2.3 Test Mode..... 8

2.4 Connection Diagram of Test System..... 9

2.5 Support Unit used in test configuration and system ..... 10

2.6 EUT Operation Test Setup ..... 10

2.7 Measurement Results Explanation Example..... 10

**3 TEST RESULT ..... 11**

3.1 6dB and 99% Bandwidth Measurement ..... 11

3.2 Peak Output Power Measurement ..... 15

3.3 Power Spectral Density Measurement ..... 16

3.4 Conducted Band Edges and Spurious Emission Measurement ..... 20

3.5 Radiated Band Edges and Spurious Emission Measurement ..... 25

3.6 AC Conducted Emission Measurement..... 28

3.7 Antenna Requirements ..... 32

**4 LIST OF MEASURING EQUIPMENT..... 33**

**5 UNCERTAINTY OF EVALUATION..... 34**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. RADIATED SPURIOUS EMISSION**

**APPENDIX C. RADIATED SPURIOUS EMISSION PLOTS**

**APPENDIX D. DUTY CYCLE PLOTS**



### REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR671336-01B	Rev. 01	Initial issue of report	Mar. 10, 2017



### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass
3.1	-	99% Bandwidth	-	Pass
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass
3.6	15.207	AC Conducted Emission	15.207(a)	Pass
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass



# 1 General Description

## 1.1 Applicant

AzulFlower LLC

10 Dorrance Street Suite 700 Providence, RI 02903

## 1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Model Name	SL056ZE
FCC ID	2AIP5-3975
EUT supports Radios application	WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE

## 1.3 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	8.28 dBm (0.0067 W)
99% Occupied Bandwidth	1.03MHz
Antenna Type / Gain	Fixed Internal Antenna type with gain 2.10 dBi
Type of Modulation	Bluetooth LE : GFSK

## 1.4 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.		
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		
	TH05-HY	CO05-HY	03CH07-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

### 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- ♦ ANSI C63.10-2013

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
20	2442	-	-	



## 2.2 Descriptions of Test Mode

The RF output power was recorded in the following table:

Channel	Frequency	Bluetooth – LE RF Output Power	
		Data Rate / Modulation	
		GFSK	
		1Mbps	
Ch00	2402MHz	6.90 dBm	
Ch19	2440MHz	7.73 dBm	
Ch39	2480MHz	8.28 dBm	

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (X plane as worst plane) from all possible combinations.
- b. AC power line Conducted Emission was tested under maximum output power.

## 2.3 Test Mode


The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1 : WLAN (2.4GHz) Link + Bluetooth Link + MPEG4 + Earphone + MicroSD Card + USB Cable (Charging from Adapter)




## 2.4 Connection Diagram of Test System

<Bluetooth – LE Tx Mode>



<AC Conducted Emission Mode>





## 2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
5.	Earphone	N/A	N/A	Verification	Unshielded, 1.15 m	N/A

## 2.6 EUT Operation Test Setup

For Bluetooth - LE function, programmed RF utility, “cmd” installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

## 2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
6. Measure and record the results in the test report.

##### 3.1.4 Test Setup






### 3.1.5 Test Result of 6dB Bandwidth


Test data refer to Appendix A.

#### 6 dB Bandwidth Plot on Channel 00



Date: 30.JAN.2017 18:18:58


#### 6 dB Bandwidth Plot on Channel 19



Date: 30.JAN.2017 18:25:43



6 dB Bandwidth Plot on Channel 39




Date: 30.JAN.2017 18:28:47

3.1.6 Test Result of 99% Occupied Bandwidth

Test data refer to Appendix A.


99% Bandwidth Plot on Channel 00



Date: 30.JAN.2017 18:23:08




99% Occupied Bandwidth Plot on Channel 19



Date: 30.JAN.2017 18:27:09

99% Occupied Bandwidth Plot on Channel 39



Date: 30.JAN.2017 18:30:38

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Peak Output Power Measurement

### 3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r05 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Peak Output Power

Test data refers to Appendix A.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Power Spectral Density


Test data refers to Appendix A.






### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 00



Date: 30.JAN.2017 18:20:20


PSD 100kHz Plot on Channel 19



Date: 30.JAN.2017 18:26:27




PSD 100kHz Plot on Channel 39



Date: 30.JAN.2017 18:29:44

3.3.7 Test Result of Power Spectral Density Plots (3kHz)


PSD 3kHz Plot on Channel 00



Date: 30.JAN.2017 18:19:59




PSD 3kHz Plot on Channel 19



Date: 30.JAN.2017 18:26:11

PSD 3kHz Plot on Channel 39



Date: 30.JAN.2017 18:29:30

## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


### 3.4.4 Test Setup






### 3.4.5 Test Result of Conducted Band Edges Plots

#### Low Band Edge Plot on Channel 00



Date: 30.JAN.2017 18:20:43

#### High Band Edge Plot on Channel 39




Date: 30.JAN.2017 18:30:01




### 3.4.6 Test Result of Conducted Spurious Emission Plots

#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 30.JAN.2017 18:22:00


#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 30.JAN.2017 18:22:08




### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 30.JAN.2017 18:26:42


### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 30.JAN.2017 18:26:50




### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 30.JAN.2017 18:30:13

### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 30.JAN.2017 18:30:21





### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


#### 3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:


- (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.
- For average measurement:
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
  - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


**For radiated emissions below 30MHz**



**For radiated emissions from 30MHz to 1GHz**



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

### 3.5.7 Duty Cycle

Please refer to Appendix D.

### 3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.



### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.6.4 Test Setup




AMN = Artificial mains network (LISH)  
AE = Associated equipment  
EUT = Equipment under test  
ISN = Impedance stabilization network



### 3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~23°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	51~52%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WLAN (2.4GHz) Link + Bluetooth Link + MPEG4 + Earphone + MicroSD Card + USB Cable (Charging from Adapter)		



**Final Result : Quasi-Peak**


Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	46.4	Off	L1	19.6	19.6	66.0
0.206000	40.2	Off	L1	19.6	23.2	63.4
0.262000	34.9	Off	L1	19.6	26.5	61.4
0.342000	33.8	Off	L1	19.6	25.4	59.2
0.462000	31.2	Off	L1	19.6	25.5	56.7
0.574000	32.8	Off	L1	19.6	23.2	56.0
1.310000	31.8	Off	L1	19.6	24.2	56.0

**Final Result : Average**

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	35.2	Off	L1	19.6	20.8	56.0
0.206000	29.9	Off	L1	19.6	23.5	53.4
0.262000	24.3	Off	L1	19.6	27.1	51.4
0.342000	25.2	Off	L1	19.6	24.0	49.2
0.462000	25.9	Off	L1	19.6	20.8	46.7
0.574000	27.2	Off	L1	19.6	18.8	46.0
1.310000	25.8	Off	L1	19.6	20.2	46.0



Test Mode :	Mode 1	Temperature :	22~23°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	51~52%%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WLAN (2.4GHz) Link + Bluetooth Link + MPEG4 + Earphone + MicroSD Card + USB Cable (Charging from Adapter)		



**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	48.0	Off	N	19.6	18.0	66.0
0.198000	38.9	Off	N	19.6	24.8	63.7
0.286000	34.7	Off	N	19.6	25.9	60.6
0.350000	32.7	Off	N	19.6	26.3	59.0
0.462000	33.1	Off	N	19.6	23.6	56.7
0.630000	35.1	Off	N	19.6	20.9	56.0
1.070000	32.5	Off	N	19.6	23.5	56.0

**Final Result : Average**

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	36.2	Off	N	19.6	19.8	56.0
0.198000	29.5	Off	N	19.6	24.2	53.7
0.286000	25.4	Off	N	19.6	25.2	50.6
0.350000	26.1	Off	N	19.6	22.9	49.0
0.462000	27.7	Off	N	19.6	19.0	46.7
0.630000	29.4	Off	N	19.6	16.6	46.0
1.070000	26.2	Off	N	19.6	19.8	46.0



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.





## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB412923 44	300MHz~40GHz	Dec. 26, 2016	Jan. 25, 2017 ~ Jan. 30, 2017	Dec. 25, 2017	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US404415 48	300MHz~40GHz	Dec. 26, 2016	Jan. 25, 2017 ~ Jan. 30, 2017	Dec. 25, 2017	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 25, 2016	Jan. 25, 2017 ~ Jan. 30, 2017	Nov. 24, 2017	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890094	1V~20V 0.5A~5A	Oct. 11, 2016	Jan. 25, 2017 ~ Jan. 30, 2017	Oct. 10, 2017	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jan. 30, 2017	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2016	Jan. 30, 2017	Aug. 29, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 29, 2016	Jan. 30, 2017	Nov. 28, 2017	Conduction (CO05-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35419&03	30MHz to 1GHz	Jan. 07, 2017	Jan. 26, 2017 ~ Feb. 03, 2017	Jan. 06, 2018	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 19, 2016	Jan. 26, 2017 ~ Feb. 03, 2017	Aug. 18, 2017	Radiation (03CH07-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY541300 85	20Hz ~ 8.4GHz	Oct. 26, 2016	Jan. 26, 2017 ~ Feb. 03, 2017	Oct. 25, 2017	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Jan. 26, 2017 ~ Feb. 03, 2017	Sep. 01, 2017	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz ~ 18GHz	Apr. 15, 2016	Jan. 26, 2017 ~ Feb. 03, 2017	Apr. 14, 2017	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	Mar. 18, 2016	Jan. 26, 2017 ~ Feb. 03, 2017	Mar. 17, 2017	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A023 62	1GHz~ 26.5GHz	Oct. 12, 2016	Jan. 26, 2017 ~ Feb. 03, 2017	Oct. 11, 2017	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Feb. 27, 2016	Jan. 26, 2017 ~ Feb. 03, 2017	Feb. 26, 2017	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Jan. 26, 2017 ~ Feb. 03, 2017	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Jan. 26, 2017 ~ Feb. 03, 2017	N/A	Radiation (03CH07-HY)
Loop Cable	Rohde & Schwarz	N/A	N/A	9KHz~30MHz	Dec. 01, 2016	Jan. 26, 2017 ~ Feb. 03, 2017	Nov. 30, 2017	Radiation (03CH07-HY)
Preamplifier	MITEQ	JS44-180040 00-33-8P	1840917	18GHz ~ 40GHz	Jun. 14, 2016	Jan. 26, 2017 ~ Feb. 03, 2017	Jun. 13, 2017	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Nov. 08, 2016	Jan. 26, 2017 ~ Feb. 03, 2017	Nov. 07, 2017	Radiation (03CH07-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.7
---	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.7
---	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.5
---	-----

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.2
---	-----



## **Appendix A. Conducted Test Results**

**Bluetooth Low Energy**

Test Engineer:	Tommy Lee	Temperature:	21~25	°C
Test Date:	2017/1/25~2017/1/30	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.03	0.71	0.50	Pass
BLE	1Mbps	1	19	2440	1.03	0.71	0.50	Pass
BLE	1Mbps	1	39	2480	1.03	0.71	0.50	Pass

**TEST RESULTS DATA**  
**Peak Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	6.90	30.00	2.10	9.00	36.00	Pass
BLE	1Mbps	1	19	2440	7.73	30.00	2.10	9.83	36.00	Pass
BLE	1Mbps	1	39	2480	8.28	30.00	2.10	10.38	36.00	Pass

**TEST RESULTS DATA**  
**Average Power Table**  
**(Reporting Only)**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.20	6.57
BLE	1Mbps	1	19	2440	2.20	7.40
BLE	1Mbps	1	39	2480	2.20	7.95

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	5.53	-9.09	2.10	8.00	Pass
BLE	1Mbps	1	19	2440	6.39	-8.23	2.10	8.00	Pass
BLE	1Mbps	1	39	2480	6.76	-7.87	2.10	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.



## Appendix B. Radiated Spurious Emission

Test Engineer :	Jesse Wang, James Chiu, and Daniel Lee	Temperature :	21~22°C
		Relative Humidity :	44~48%

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	Limit	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
					Line	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		2346.855	54.71	-19.29	74	50.41	32.03	7.24	34.97	100	240	P	H
		2388.54	45.81	-8.19	54	41.28	32.19	7.31	34.97	100	240	A	H
	*	2402	104.14	-	-	99.62	32.19	7.31	34.98	100	240	P	H
	*	2402	103.63	-	-	99.11	32.19	7.31	34.98	100	240	A	H
		2375.52	54.58	-19.42	74	50.17	32.14	7.24	34.97	380	276	P	V
		2386.65	45.53	-8.47	54	41	32.19	7.31	34.97	380	276	A	V
	*	2402	103.32	-	-	98.8	32.19	7.31	34.98	380	276	P	V
	*	2402	102.87	-	-	98.35	32.19	7.31	34.98	380	276	A	V
BLE CH 19 2440MHz		2361.38	54.91	-19.09	74	50.55	32.09	7.24	34.97	100	240	P	H
		2381.54	45.7	-8.3	54	41.22	32.14	7.31	34.97	100	240	A	H
	*	2440	105.18	-	-	100.47	32.34	7.36	34.99	100	240	P	H
	*	2440	104.59	-	-	99.88	32.34	7.36	34.99	100	240	A	H
		2496.29	55.33	-18.67	74	50.44	32.5	7.4	35.01	100	240	P	H
		2489.08	45.9	-8.1	54	41	32.5	7.4	35	100	240	A	H
		2376.22	54.71	-19.29	74	50.3	32.14	7.24	34.97	358	272	P	V
		2346.54	45.45	-8.55	54	41.15	32.03	7.24	34.97	358	272	A	V
	*	2440	104.36	-	-	99.65	32.34	7.36	34.99	358	272	P	V
	*	2440	103.75	-	-	99.04	32.34	7.36	34.99	358	272	A	V
		2485.79	54.77	-19.23	74	49.92	32.45	7.4	35	358	272	P	V
		2495.94	45.79	-8.21	54	40.9	32.5	7.4	35.01	358	272	A	V



<b>BLE CH 39 2480MHz</b>	*	2480	105.46	-	-	100.61	32.45	7.4	35	102	240	P	H
	*	2480	104.95	-	-	100.1	32.45	7.4	35	102	240	A	H
		2486.44	55.41	-18.59	74	50.56	32.45	7.4	35	102	240	P	H
		2484.32	46.71	-7.29	54	41.86	32.45	7.4	35	102	240	A	H
	*	2480	105.05	-	-	100.2	32.45	7.4	35	358	272	P	V
	*	2480	104.58	-	-	99.73	32.45	7.4	35	358	272	A	V
		2498.6	55.11	-18.89	74	50.22	32.5	7.4	35.01	358	272	P	V
		2484.32	46.59	-7.41	54	41.74	32.45	7.4	35	358	272	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BLE CH 00 2402MHz		4804	39.76	-34.24	74	53.33	33.68	11.83	59.08	100	0	P	H
		4804	39.81	-34.19	74	53.38	33.68	11.83	59.08	100	0	P	V
BLE CH 19 2440MHz		4880	39.35	-34.65	74	53.22	33.54	11.53	58.94	100	0	P	H
		7320	39.35	-34.65	74	48.85	34.65	13.81	57.96	100	0	P	H
		4880	38.05	-35.95	74	51.92	33.54	11.53	58.94	100	0	P	V
		7320	38.69	-35.31	74	48.19	34.65	13.81	57.96	100	0	P	V
BLE CH 39 2480MHz		4960	38.55	-35.45	74	52.73	33.37	11.22	58.77	100	0	P	H
		7440	38.09	-35.91	74	47.84	34.33	14.05	58.13	100	0	P	H
		4960	37.95	-36.05	74	52.13	33.37	11.22	58.77	100	0	P	V
		7440	38.32	-35.68	74	48.07	34.33	14.05	58.13	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz BLE LF		30.54	27.75	-12.25	40	32.58	25.46	1.07	31.36	100	0	P	H
		155.28	21.86	-21.64	43.5	34.23	17.35	1.78	31.5	-	-	P	H
		259.77	23.56	-22.44	46	32.85	20	2.07	31.36	-	-	P	H
		823.6	30.96	-15.04	46	29.27	28.17	4.1	30.58	-	-	P	H
		885.2	31.81	-14.19	46	29.28	28.91	4.17	30.55	-	-	P	H
		951	33.06	-12.94	46	29.32	30.2	4.07	30.53	-	-	P	H
		31.35	26.99	-13.01	40	31.84	25.46	1.07	31.38	-	-	P	V
		135.03	19.13	-24.37	43.5	30.94	18.15	1.55	31.51	-	-	P	V
		270.57	21.14	-24.86	46	30.76	19.39	2.32	31.33	-	-	P	V
		404.3	26.86	-19.14	46	32.88	22.47	2.67	31.16	-	-	P	V
		850.9	32.64	-13.36	46	30.39	28.71	4.1	30.56	-	-	P	V
	947.5	33.05	-12.95	46	29.36	30.15	4.07	30.53	100	0	P	V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												





**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =  
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



## Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Jesse Wang, James Chiu, and Daniel Lee	Temperature :	21~22°C
		Relative Humidity :	44~48%





**Note symbol**

-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz





BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH07-FY            Condition : PEAK_BE_74 3m HF-ANT_130829 HORIZONTAL            REW: 1000.000kHz VBW: 3000.000kHz SWT: Auto            Detector : Peak            Project : 671336-01            Mode : 4</p>	 <p>Site : 03CH07-FY            Condition : PEAK_74 3m HF-ANT_130829 HORIZONTAL            REW: 1000.000kHz VBW: 3000.000kHz SWT: Auto            Detector : Peak            Project : 671336-01            Mode : 4</p>
Avg.	 <p>Site : 03CH07-FY            Condition : AVG_BE_74 3m HF-ANT_130829 HORIZONTAL            REW: 1000.000kHz VBW: 3.000kHz SWT: Auto            Detector : Peak            Project : 671336-01            Mode : 4</p>	 <p>Site : 03CH07-FY            Condition : AVG_74 3m HF-ANT_130829 HORIZONTAL            REW: 1000.000kHz VBW: 3.000kHz SWT: Auto            Detector : Peak            Project : 671336-01            Mode : 4</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Vertical	Fundamental
Peak	 <p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : PEAK_BE_74 3m HF-ANT_130829 VERTICAL            RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 671336-01            Mode : 4</p>	 <p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : PEAK_74 3m HF-ANT_130829 VERTICAL            RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 671336-01            Mode : 4</p>
Avg	 <p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : AVG_BE_54 3m HF-ANT_130829 VERTICAL            RBW:1000.000kHz VBW:3.000kHz SWT:Auto            Detector : Peak            Project : 671336-01            Mode : 4</p>	 <p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : AVG_54 3m HF-ANT_130829 VERTICAL            RBW:1000.000kHz VBW:3.000kHz SWT:Auto            Detector : Peak            Project : 671336-01            Mode : 4</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Horizontal	Fundamental
Peak	 <p>Date: 2017-02-02</p> <p>Site: 03CH07-HY            Condition: PEAK_BE_74 3m HF-ANT_130829 HORIZONTAL            RBW:1000 000kHz VSW:3000 000kHz SWT:Auto            Detector: Peak            Project: 671336-01            Mode: 5</p>	 <p>Date: 2017-02-02</p> <p>Site: 03CH07-HY            Condition: PEAK_74 3m HF-ANT_130829 HORIZONTAL            RBW:1000 000kHz VSW:3000 000kHz SWT:Auto            Detector: Peak            Project: 671336-01            Mode: 5</p>
Avg.	 <p>Date: 2017-02-02</p> <p>Site: 03CH07-HY            Condition: AVG_BE_54 3m HF-ANT_130829 HORIZONTAL            RBW:1000 000kHz VSW:3 000kHz SWT:Auto            Detector: Peak            Project: 671336-01            Mode: 5</p>	 <p>Date: 2017-02-02</p> <p>Site: 03CH07-HY            Condition: AVG_54 3m HF-ANT_130829 HORIZONTAL            RBW:1000 000kHz VSW:3 000kHz SWT:Auto            Detector: Peak            Project: 671336-01            Mode: 5</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Horizontal	Fundamental
Peak	 <p>Date: 2017.02.02</p> <p>Site : 03CH074Y  Condition : PEAK_BE_74 3m HF-ANT_130829 HORIZONTAL  Detector : Peak  Project : 671336-01  Mode : S</p>	Left blank
Avg.	 <p>Date: 2017.02.02</p> <p>Site : 03CH074Y  Condition : AVG_BE_54 3m HF-ANT_130829 HORIZONTAL  Detector : Peak  Project : 671336-01  Mode : S</p>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Vertical	Fundamental
Peak	<p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : PEAK_BE_74 3m HF-ANT_130829 VERTICAL            Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Project : Peak            Mode : 5</p>	<p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : PEAK_74 3m HF-ANT_130829 VERTICAL            Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Project : Peak            Mode : 5</p>
Avg.	<p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : AVG_BE_54 3m HF-ANT_130829 VERTICAL            Detector : RBW:1000.000kHz VBW:3.000kHz SWT:Auto            Project : Peak            Mode : 5</p>	<p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : AVG_54 3m HF-ANT_130829 VERTICAL            Detector : RBW:1000.000kHz VBW:3.000kHz SWT:Auto            Project : Peak            Mode : 5</p>









BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Vertical	Fundamental
<p><b>Peak</b></p>	 <p>Site : 63CH074Y            Condition : PEAK_BE_74 3m HF-ANT_130829 VERTICAL            Detector : Peak            Project : 671336-01            Mode : S</p>	<p>Left blank</p>
<p><b>Avg.</b></p>	 <p>Site : 63CH074Y            Condition : AVG_BE_54 3m HF-ANT_130829 VERTICAL            Detector : Peak            Project : 671336-01            Mode : S</p>	<p>Left blank</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Fundamental
Peak	<p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : PEAK_BE_74 3m HF-ANT_130829 HORIZONTAL            RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 671336-01            Mode : 6</p>	<p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : PEAK_74 3m HF-ANT_130829 HORIZONTAL            RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 671336-01            Mode : 6</p>
Avg.	<p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : AVG_BE_54 3m HF-ANT_130829 HORIZONTAL            RBW:1000.000kHz VBW:3.000kHz SWT:Auto            Detector : Peak            Project : 671336-01            Mode : 6</p>	<p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : AVG_54 3m HF-ANT_130829 HORIZONTAL            RBW:1000.000kHz VBW:3.000kHz SWT:Auto            Detector : Peak            Project : 671336-01            Mode : 6</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Vertical	Fundamental
Peak	 <p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : PEAK_BE_74 3m HF-ANT_130829 VERTICAL            RBW: 1000.000kHz VBW: 3000.000kHz SWT: Auto            Detector : Peak            Project : 671336-01            Mode : 6</p>	 <p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : PEAK_74 3m HF-ANT_130829 VERTICAL            RBW: 1000.000kHz VBW: 3000.000kHz SWT: Auto            Detector : Peak            Project : 671336-01            Mode : 6</p>
Avg.	 <p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : AVG_BE_54 3m HF-ANT_130829 VERTICAL            RBW: 1000.000kHz VBW: 3.000kHz SWT: Auto            Detector : Peak            Project : 671336-01            Mode : 6</p>	 <p>Date: 2017.02.02</p> <p>Site : 03CH074Y            Condition : AVG_54 3m HF-ANT_130829 VERTICAL            RBW: 1000.000kHz VBW: 3.000kHz SWT: Auto            Detector : Peak            Project : 671336-01            Mode : 6</p>



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

<b>BLE</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
<b>ANT</b>	<b>BLE CH00 2402MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak Avg.</b>	<p>Site : 03CH07-AYY  Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL  Detector : Peak  Project : 671336-01  Mode : 4</p>	<p>Site : 03CH07-AYY  Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL  Detector : Peak  Project : 671336-01  Mode : 4</p>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
1	Horizontal	Vertical
<p>Peak</p> <p>Avg.</p>		



<b>BLE</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
<b>ANT</b>	<b>BLE CH39 2480MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b>	<p>Horizontal spectrum plot showing Level (dBm/Vm) vs Frequency (MHz). The plot displays two distinct peaks at approximately 4.8 MHz and 7.2 MHz. The y-axis ranges from 0 to 140 dBm/Vm, and the x-axis ranges from 0 to 25000 MHz. Two horizontal red lines indicate levels: PEAK_74 at approximately 80 dBm/Vm and AVG_54 at approximately 55 dBm/Vm. The plot is dated 2017.02.02.</p> <p>Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 671336-01 Mode : 6</p>	<p>Vertical spectrum plot showing Level (dBm/Vm) vs Frequency (MHz). The plot displays two distinct peaks at approximately 4.8 MHz and 7.2 MHz. The y-axis ranges from 0 to 140 dBm/Vm, and the x-axis ranges from 0 to 25000 MHz. Two horizontal red lines indicate levels: PEAK_74 at approximately 80 dBm/Vm and AVG_54 at approximately 55 dBm/Vm. The plot is dated 2017.02.02.</p> <p>Site : 03CH07-4Y Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 671336-01 Mode : 6</p>



Emission below 1GHz

2.4GHz BLE (LF)


BLE	2.4GHz 2400~2483.5MHz	
ANT	BLE LF	
1	Horizontal	Vertical
<p><b>QP / Peak</b></p>	<p>Site : 03CM07-49Y            Condition : QP-3m LF-ANT-35419(6) HORIZONTAL            Detector : Peak            Project : 671336-01            Mode : 23</p>	<p>Site : 03CM07-49Y            Condition : QP-3m LF-ANT-35419(6) VERTICAL            Detector : Peak            Project : 671336-01            Mode : 23</p>



### Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth -LE	60.26	376.00	2.66	3kHz

#### Bluetooth - LE



Date: 25.JAN.2017 16:35:36