

# Shenzhen Super Global Electronics Co.,Ltd

## TEST REPORT

**SCOPE OF WORK**

FCC TESTING–V60093BT-NOC, V60093BT-BLK,  
SKU#2198088

**REPORT NUMBER**

230418094SZN-002

**ISSUE DATE**

26 May 2023

**[REVISED DATE]**

[-----]

**PAGES**

27

**DOCUMENT CONTROL NUMBER**

FCC ID 249\_C

© 2017 INTERTEK



**Shenzhen Super Global Electronics Co.,Ltd**

Application  
For  
Certification

**FCC ID: 2AIP7-V60093****Tower Firework Speaker****Model: V60093BT-NOC, V60093BT-BLK, SKU#2198088****Brand Name: Vivitar**

2.4GHz Transceiver

Report No.: 230418094SZN-002

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-21]

Prepared and Checked by:

Approved by:

*Tenet Cao*  
*Assistant Engineer*

---

*Ryan Chen*  
*Project Engineer*  
*Date: 26 May 2023*

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**Intertek Testing Services Shenzhen Ltd. Longhua Branch**

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen, P.R. China  
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

**MEASUREMENT/TECHNICAL REPORT**

This report concerns (check one:)                      Original Grant                       Class II Change

Equipment Type: DXX - Part 15 Low Power Communication Device Transmitter

---

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?                      Yes                       No

If yes, defer until: \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

---

Transition Rules Request per 15.37?                      Yes                       No

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-1-21 Edition] provision.

---

Report prepared by:

Tenet Cao  
Intertek Testing Services Shenzhen Ltd. Longhua Branch  
101, 201, Building B, No. 308 Wuhe Avenue,  
Zhangkengjing Community, GuanHu Subdistrict,  
LongHua District, ShenZhen, P.R. China  
Tel / Fax: 86-755-8614 0743/86-755-8601 6661

## Table of Contents

<b>1.0 Summary of Test Result</b> .....	4
<b>2.0 General Description</b> .....	5
2.1 Product Description .....	5
2.2 Related Submittal(s) Grants .....	5
2.3 Test Methodology .....	5
2.4 Test Facility.....	5
<b>3.0 System Test Configuration</b> .....	6
3.1 Justification .....	6
3.2 EUT Exercising Software .....	6
3.3 Special Accessories .....	6
3.4 Equipment Modification.....	6
3.5 Measurement Uncertainty .....	7
3.6 Support Equipment List and Description .....	7
<b>4.0 Emission Results</b> .....	8
4.1 Radiated Test Results .....	8
4.1.1 Field Strength Calculation .....	8
4.1.2 Radiated Emission Configuration Photograph .....	9
4.1.3 Radiated Emissions .....	9
4.1.4 Transmitter Spurious Emissions .....	12
4.2 Conducted Emission Configuration Photograph .....	16
4.2.1 Conducted Emission.....	16
<b>5.0 Equipment Photographs</b> .....	19
<b>6.0 Product Labelling</b> .....	19
<b>7.0 Technical Specifications</b> .....	19
<b>8.0 Instruction Manual</b> .....	19
<b>9.0 Miscellaneous Information</b> .....	20
9.1 Bandedge Plot .....	20
9.2 20dB Bandwidth.....	23
9.3 Discussion of Pulse Desensitization .....	24
9.4 Calculation of Average Factor.....	24
9.5 Emissions Test Procedures.....	25
<b>10.0 Test Equipment List</b> .....	27

## 1.0 Summary of Test Result

Applicant: Shenzhen Super Global Electronics Co.,Ltd  
Applicant Address: 2F Building 4 BaiHuaYuan Rode 11#, GuangMing New District ShenZhen 518107 China  
Manufacturer: Shenzhen Super Global Electronics Co.,Ltd  
Manufacturer Address: 2F Building 4 BaiHuaYuan Rode 11#, GuangMing New District ShenZhen 518107 China

MODEL: V60093BT-NOC, V60093BT-BLK, SKU#2198088  
FCC ID: 2AIP7-V60093

Test Specification	Reference	Results
Transmitter Radiated Emission	15.249 &15.209 &15.205	Pass
Conducted Emission	15.207	Pass
Band edge	15.249 &15.209 &15.205	Pass
20dB Bandwidth	15.215(c)	Pass

### Notes:

The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

## 2.0 General Description

### 2.1 Product Description

The equipment under test (EUT) is a Tower Firework Speaker with Bluetooth 5.0 (Single Mode EDR) function operating in 2402-2480MHz. The EUT is powered by DC 5V with adapter. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna  
Modulation Type:  $\pi/4$ -DQPSK  
Antenna Gain: -0.58dBi Max  
Bluetooth Version: 5.0 (Single Mode EDR)

The Model: V60093BT-BLK, SKU#2198088 are the same as the Model: V60093BT-NOC in hardware aspect. The difference in model number serves as marketing strategy.

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

### 2.2 Related Submittal(s) Grants

This is an application for certification of a transceiver for the Tower Firework Speaker, which has Bluetooth function, and related report for FCC SDOC is subjected to report number: 230418094SZN-001.

### 2.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in Semi-anechoic chamber. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst-case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

### 2.4 Test Facility

The Semi-Anechoic chamber used to collect the radiated data is **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen, P.R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: CN1188).

## 3.0 System Test Configuration

### 3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The EUT is powered by DC 5V with adapter during the test, only the worst data was reported in this report.

For maximizing emissions below 30 MHz, the EUT was rotated through 360°, the bottom of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Section 4.

The EUT and transmitting antenna was centered on the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

### 3.2 EUT Exercising Software

FCC\_assist\_1.0.2.2 (provided by client) used during testing was designed to exercise the various system components in a manner similar to a typical use.

### 3.3 Special Accessories

No special accessories used.

### 3.4 Equipment Modification

Any modifications installed previous to testing by Shenzhen Super Global Electronics Co.,Ltd will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

### 3.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

### 3.6 Support Equipment List and Description

Description	Manufacturer	Remark
Mobile Phone (Provided by Intertek)	SAMSUNG	Model: S7
Remote Control (Provided by Client)	billboard	/
AUX cable (Provided by Intertek)	/	Unshield, 1m length
Adapter (Provided by Client)	Shenzhen Super Global Electronics Co.,Ltd	SQ050150-S08USD Input:100-240V,50/60Hz 0.3A Output: 5V 1.5A



## 4.0 Emission Results

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

### 4.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

#### 4.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

Where

- FS = Field Strength in dB $\mu$ V/m
- RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB/m
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB
- AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB/m and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$\begin{aligned} RA &= 62.0 \text{ dB}\mu\text{V} \\ AF &= 7.4 \text{ dB/m} \\ CF &= 1.6 \text{ dB} \\ AG &= 29.0 \text{ dB} \\ PD &= 0 \text{ dB} \\ AV &= -10 \text{ dB} \\ FS &= 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m} \end{aligned}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

## 4.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

## 4.1.3 Radiated Emissions

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission  
at  
82.200000 MHz

Judgement: Passed by 5.5 dB

### **TEST PERSONNEL:**

*Sign on file*

Tenet Cao, Assistant Engineer  
*Typed/Printed Name*

15 May 2023  
*Date*

Applicant: Shenzhen Super Global Electronics Co.,Ltd


Date of Test: 15 May 2023

Model: V60093BT-NOC

Worst Case Operating Mode:

BT Link

ANT Polarity: Horizontal



Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
81.442333	21.5	1000.0	120.000	H	13.5	18.5	40.0
159.720000	37.3	1000.0	120.000	H	17.5	6.2	43.5
270.075000	38.0	1000.0	120.000	H	20.3	8.0	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

Applicant: Shenzhen Super Global Electronics Co.,Ltd

Date of Test: 15 May 2023


Model: V60093BT-NOC

Worst Case Operating Mode:

BT Link

ANT Polarity: Vertical

FCC Part 15



Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
82.200000	34.5	1000.0	120.000	V	13.6	5.5	40.0
164.215667	29.4	1000.0	120.000	V	17.2	14.1	43.5
864.006000	38.4	1000.0	120.000	V	32.3	7.6	46.0

Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

## 4.1.4 Transmitter Spurious Emissions (Radiated)

Worst Case Radiated Emission  
at  
9920.000 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 22.5 dB

**TEST PERSONNEL:**

*Sign on file*

Tenet Cao, Assistant Engineer

*Typed/Printed Name*

15 May 2023

*Date*

Applicant: Shenzhen Super Global Electronics Co.,Ltd

Date of Test: 15 May 2023

Model: V60093BT-NOC

Worst Case Operating Mode:

BT Link

Table 1

**Radiated Emissions**

(2402MHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	2402.000	97.7	36.7	28.1	89.1	114.0	-24.9
Horizontal	4804.000	43.3	36.7	35.5	42.1	74.0	-31.9
Horizontal	7206.000	45.1	36.1	36.5	45.5	74.0	-28.5
Horizontal	9608.000	47.8	36.3	38.0	49.5	74.0	-24.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Average Factor (-dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	2402.000	97.7	36.7	28.1	22.5	66.6	94.0	-27.4
Horizontal	4804.000	43.3	36.7	35.5	22.5	19.6	54.0	-34.4
Horizontal	7206.000	45.1	36.1	36.5	22.5	23.0	54.0	-31.0
Horizontal	9608.000	47.8	36.3	38.0	22.5	27.0	54.0	-27.0

- Notes:
1. Peak detector is used for the emission measurement.
  2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna is used for the emission over 1000MHz.

Applicant: Shenzhen Super Global Electronics Co.,Ltd

Date of Test: 15 May 2023

Model: V60093BT-NOC

Worst Case Operating Mode:

BT Link

Table 2

**Radiated Emissions**

(2441MHz)

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2441.000	92.1	36.7	28.1	83.5	114.0	-30.5
Horizontal	4882.000	39.7	36.7	35.5	38.5	74.0	-35.5
Horizontal	7323.000	45.1	36.1	36.5	45.5	74.0	-28.5
Horizontal	9764.000	46.8	36.3	38.0	48.5	74.0	-25.5

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Average Factor (-dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2441.000	92.1	36.7	28.1	22.5	61.0	94.0	-33.0
Horizontal	4882.000	39.7	36.7	35.5	22.5	16.0	54.0	-38.0
Horizontal	7323.000	45.1	36.1	36.5	22.5	23.0	54.0	-31.0
Horizontal	9764.000	46.8	36.3	38.0	22.5	26.0	54.0	-28.0

- Notes:
1. Peak detector is used for the emission measurement.
  2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna is used for the emission over 1000MHz.

Applicant: Shenzhen Super Global Electronics Co.,Ltd

Date of Test: 15 May 2023

Model: V60093BT-NOC

Worst Case Operating Mode:

BT Link

Table 3

## Radiated Emissions

(2480MHz)

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	2480.000	94.4	36.7	28.1	85.8	114.0	-28.2
Horizontal	4960.000	42.7	36.7	35.5	41.5	74.0	-32.5
Horizontal	7440.000	45.4	36.1	37.2	46.5	74.0	-27.5
Horizontal	9920.000	48.9	36.3	38.9	51.5	74.0	-22.5

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Average Factor (-dB)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Horizontal	2480.000	94.4	36.7	28.1	22.5	63.3	94.0	-30.7
Horizontal	4960.000	42.7	36.7	35.5	22.5	19.0	54.0	-35.0
Horizontal	7440.000	45.4	36.1	37.2	22.5	24.0	54.0	-30.0
Horizontal	9920.000	48.9	36.3	38.9	22.5	29.0	54.0	-25.0

Notes: 1. Peak detector is used for the emission measurement.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.



## 4.2 Conducted Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: conducted photos.pdf.

### 4.2.1 Conducted Emission

Worst Case Conducted Configuration  
at  
0.474000MHz

Judgement: Passed by 4.6dB margin

#### **TEST PERSONNEL:**

*Sign on file*

Tenet Cao, Assistant Engineer  
*Typed/Printed Name*

15 May 2023  
*Date*

Applicant: Shenzhen Super Global Electronics Co.,Ltd

Date of Test: 15 May 2023


Model: V60093BT-NOC

Worst Case Operating Mode: BT Link

Phase: Live

## Graphic / Data Table

### Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



#### Limit and Margin QP

Frequency (MHz)	Quasi Peak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.306000	38.2	9.000	L1	9.7	21.9	60.1
0.474000	45.9	9.000	L1	9.7	10.5	56.4
0.778000	35.4	9.000	L1	9.7	20.6	56.0
2.242000	35.5	9.000	L1	9.7	20.5	56.0
10.606000	35.3	9.000	L1	10.0	24.7	60.0
10.698000	34.7	9.000	L1	10.0	25.3	60.0

#### Limit and Margin AV

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.306000	31.2	9.000	L1	9.7	18.9	50.1
0.474000	41.8	9.000	L1	9.7	4.6	46.4
0.778000	30.1	9.000	L1	9.7	15.9	46.0
2.242000	29.9	9.000	L1	9.7	16.1	46.0
10.606000	24.3	9.000	L1	10.0	25.7	50.0
10.698000	24.7	9.000	L1	10.0	25.3	50.0

Applicant: Shenzhen Super Global Electronics Co.,Ltd

Date of Test: 15 May 2023


Model: V60093BT-NOC

Worst Case Operating Mode: BT Link

Phase: Neutral

## Graphic / Data Table

### Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



#### Limit and Margin QP

Frequency (MHz)	Quasi Peak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.306000	39.0	9.000	N	9.6	21.1	60.1
0.474000	43.9	9.000	N	9.6	12.5	56.4
0.782000	36.9	9.000	N	9.6	19.1	56.0
1.050000	35.2	9.000	N	9.7	20.8	56.0
2.002000	35.1	9.000	N	9.7	20.9	56.0
10.786000	35.8	9.000	N	10.0	24.2	60.0

#### Limit and Margin AV

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.306000	31.5	9.000	N	9.6	18.6	50.1
0.474000	37.5	9.000	N	9.6	8.9	46.4
0.782000	26.8	9.000	N	9.6	19.2	46.0
1.050000	25.5	9.000	N	9.7	20.5	46.0
2.002000	25.9	9.000	N	9.7	20.1	46.0
10.786000	20.6	9.000	N	10.0	29.4	50.0

## 5.0 Equipment Photographs

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

## 6.0 Product Labelling

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

## 7.0 Technical Specifications

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

## 8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

## 9.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandedge, 20dB Bandwidth, the test procedure and calculation of factor such as pulse desensitization.

### 9.1 Bandedge Plot

The test plots are attached as below. From the below plots, the field strength of any emissions outside of the specified frequency band are attenuated to the general radiated emission limits in section 15.209. It fulfils the requirement of 15.249(d).

#### Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e (Bandedge Plot).

#### **(i) Lowest frequency channel (2402MHz):**

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot

$$\begin{aligned} &= 89.1 \text{ dB}\mu\text{v/m} - 42.65 \text{ dB} \\ &= 46.45 \text{ dB}\mu\text{v/m} \end{aligned}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the bandedge plot

$$\begin{aligned} &= 66.6 \text{ dB}\mu\text{v/m} - 42.65 \text{ dB} \\ &= 23.95 \text{ dB}\mu\text{v/m} \end{aligned}$$

#### **(ii) Highest frequency channel (2480MHz):**

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot


$$\begin{aligned} &= 85.8 \text{ dB}\mu\text{v/m} - 48.89 \text{ dB} \\ &= 36.91 \text{ dB}\mu\text{v/m} \end{aligned}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the bandedge plot


$$\begin{aligned} &= 63.3 \text{ dB}\mu\text{v/m} - 48.89 \text{ dB} \\ &= 14.41 \text{ dB}\mu\text{v/m} \end{aligned}$$

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dB $\mu$ v/m (Peak Limit) and 54dB $\mu$ v/m (Average Limit).


Hopping function off  
Lowest frequency Channel




Highest frequency Channel



## Hopping function on Lowest frequency Channel





## Highest frequency Channel



## 9.2 20dB bandwidth

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered. The test plots are reported as below.





## 9.3 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately 625µs for Bluetooth. With a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

## 9.4 Calculation of Average Factor

Based on the Bluetooth Specification Version 5.0 (EDR mode) and worst case AFH mode, transmitter ON time is independent of packet type (2DH1, 2DH3 and 2DH5) and packet length, the AFH mode Duty cycle connection factor as below:

Channel hop rate = 800 hops/second (AFH Mode)

Adjusted channel hop rate for DH5 mode = 133.33 hops/second

Time per channel hop =  $1 / 133.33 \text{ hops/second} = 7.5 \text{ ms}$

Time to cycle through all channels =  $7.5 \times 20 \text{ channels} = 150 \text{ ms}$

Number of times transmitter hits on one channel =  $100 \text{ ms} / 150 \text{ ms} = 1 \text{ time(s)}$

Worst case dwell time = 7.5 ms

Duty cycle connection factor =  $20\log_{10} (7.5\text{ms} / 100\text{ms}) = -22.5 \text{ dB}$

## 9.5 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.10 - 2013.

The transmitting equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter and approximately 0.8 meter up to 1GHz and 1.5 meter above 1GHz in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjust through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in section 9.4.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

## 9.5 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used (RBW 3MHz used for fundamental emission).

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

## 10.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Cal. Date	Due Date
SZ061-13	Biconilog Antenna	ETS	3142E	13-Jul-2022	13-Jul-2025
SZ061-08	Horn Antenna	ETS	3115	05-Sep-2021	05-Sep-2024
SZ056-06	Spectrum Analyzer	R&S	FSV40	19-Dec-2022	19-Dec-2023
SZ185-03	EMI Receiver	R & S	ESR7	19-Dec-2022	19-Dec-2023
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	18-May-2021	18-May-2023
SZ181-04	Preamplifier	Agilent	8449B	16-May-2022	16-May-2023
SZ188-05	Anechoic Chamber	ETS	RFD-F/A-100	25-May-2021	25-May-2024
SZ062-24	RF Cable	HUBER+SUHNER	SF104PE	17-Oct-2022	17-Oct-2023
SZ062-25	RF Cable	HUBER+SUHNER	SF104PE	17-Oct-2022	17-Oct-2023
SZ062-38	RF Cable	Talent Microwave	A50-3.5M3.5M-8M	17-May-2022	17-May-2023
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	17-May-2022	17-May-2023
SZ185-02	EMI Test Receiver	R&S	ESCI	08-Jul-2022	08-Jul-2023
SZ187-01	Two-Line V-Network	R&S	ENV216	24-Oct-2022	24-Oct-2023
SZ187-02	Two-Line V-Network	R&S	ENV216	24-Oct-2022	24-Oct-2023
SZ188-03	Shielding Room	ETS	RFD-100	20-Dec-2022	20-Dec-2025

\*\*\*\*\* End of Report \*\*\*\*\*