

# **FCC ID : 2AIPD-FZ0001-4100US**

## **RF EXPOSURE EVALUATION**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

<b>Frequency Range(MHz)</b>	<b>Electric Field Strength(V/m)</b>	<b>Magnetic Field Strength(A/m)</b>	<b>Power Density(mW/cm<sup>2</sup>)</b>	<b>Average Time</b>
<b>(A) Limits for Occupational/Control Exposures</b>				
<b>300-1500</b>	--	--	<b>F/300</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
<b>300-1500</b>	--	--	<b>F/1500</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>1</b>	<b>30</b>

**11.1 Friis transmission formula:  $P_d = \frac{P_{out} \cdot G}{4 \cdot \pi \cdot R^2}$**

Where

$P_d$ = Power density in mW/cm<sup>2</sup>

$P_{out}$ =output power to antenna in mW

$G$ = Numeric gain of the antenna relative to isotropic antenna

$\pi$ =3.1416

R= distance between observation point and center of the radiator in cm (R=20cm)

Pd the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

### 11.2 Measurement Result

#### BT DSS

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
2402	GFSK	3.792	3dBm to 5dBm	5	2.818	0.0018	1
2441	GFSK	3.219	3dBm to 5dBm	5	2.818	0.0018	1
2480	GFSK	3.826	3dBm to 5dBm	5	2.818	0.0018	1
2402	$\pi/4$ -DQPSK	5.227	4dBm to 6dBm	6	2.818	0.0022	1
2441	$\pi/4$ -DQPSK	4.547	4dBm to 6dBm	6	2.818	0.0022	1
2480	$\pi/4$ -DQPSK	5.029	4dBm to 6dBm	6	2.818	0.0022	1
2402	8DPSK	5.794	4dBm to 6dBm	6	2.818	0.0022	1
2441	8DPSK	5.098	4dBm to 6dBm	6	2.818	0.0022	1
2480	8DPSK	5.509	4dBm to 6dBm	6	2.818	0.0022	1