

FCC Label

INPUT 1 Clip MAX - Mic Guitar Line

INPUT 2 Clip MAX - Mic Guitar Line

INPUT 3 Clip MAX - Off On/Pair

TREBLE Normal Floor Monitor

BASS - +

ROUTING

- Normal (Mono)
- Stereo Master
- Link In Slave

AUX

L(MONO)

RIGHT

OUTPUT

LINK OUT

TO RUN A PAIR OF SPEAKERS AS A SMART STEREO PAIR:
 Connect all sources to this left speaker only, and set its ROUTING to Stereo Master. Connect this speaker's LINK OUT to right speaker's INPUT 1. Set this speaker's ROUTING to Link In Slave. Make all volume and EQ adjustments on this left speaker.

HARBINGER VARI v2308 SERIES

CAUTION RISK OF ELECTRIC SHOCK DO NOT OPEN

AVIS RISQUE DE CHOC ELECTRIQUE NE PAS OUVRI

WARNING: To reduce the risk of fire or shock do not expose this equipment to rain or moisture.
AVERTISSEMENT: Pour réduire les risques d'incendie et d'électrocution, ne pas exposer ce matériel à la pluie ou à l'humidité.

CAUTION REPLACE FUSE WITH SAME FUSE TYPE AND RATING
ATTENTION UTILISER UN FUSIBLE DE RECHANGE DE MEME TYPE ET CALIBRE

110-120V ~ / 220-240V ~
 50/60Hz (100W)
 220-240V ~ FUSE: T2 AL/250V
 110-120V ~ FUSE: T4 AL/250V

ETL US
Intertek 3069848
 CONFORMS TO UL STD. 62368-1
 CERTIFIED TO CSA STD. C22.2 NO. 62368-1

CE **FC** **RoHS**
 FCC ID: 2A1QW-V2310
MADE IN CHINA

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
 (1) this device may not cause harmful interference, and
 (2) this device must accept any interference received, including interference that may cause undesired operation.

PRODUCTION DATE: _____

VOLTAGE
 110-120V 220-240V

