

# Snap Inc.

# RF TEST REPORT

**Report Type:**

FCC Part 15.247 & ISED RSS-247 RF report

**Model:**

006

**REPORT NUMBER:**

220100298SHA-001

**ISSUE DATE:**

April 27, 2022

**DOCUMENT CONTROL NUMBER:**

TTRF15.247-03\_V1 © 2018 Intertek



**Applicant:** Snap Inc.  
2772 Donald Douglas Loop North, Santa Monica, California, United States.

**Manufacturer:** Hangzhou Zero Zero Technology Co., Ltd  
401, 4th floor, building #2, Wudi Center, #2399 Yuhangtang Road, Yuhang District, Hangzhou, Zhejiang, China

**Product Name:** pixy

**Type/Model:** 006

**FCC ID:** 2AIRN-006

### SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

**47CFR Part 15 (2020):** Radio Frequency Devices (Subpart C)

**ANSI C63.10 (2013):** American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

### PREPARED BY:



---

Project Engineer  
Erick Liu

### REVIEWED BY:



---

Reviewer  
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT**

# Content

- REVISION HISTORY..... 5**
- MEASUREMENT RESULT SUMMARY ..... 6**
- 1 GENERAL INFORMATION ..... 7**
  - 1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) ..... 7
  - 1.2 TECHNICAL SPECIFICATION ..... 7
  - 1.3 ANTENNA INFORMATION..... 8
  - 1.4 DESCRIPTION OF TEST FACILITY ..... 8
- 2 TEST SPECIFICATIONS..... 9**
  - 2.1 STANDARDS OR SPECIFICATION ..... 9
  - 2.2 MODE OF OPERATION DURING THE TEST..... 9
  - 2.3 TEST SOFTWARE LIST ..... 10
  - 2.4 TEST PERIPHERALS LIST ..... 10
  - 2.5 TEST ENVIRONMENT CONDITION:..... 10
  - 2.6 INSTRUMENT LIST ..... 11
  - 2.7 MEASUREMENT UNCERTAINTY ..... 12
- 3 MINIMUM 6DB BANDWIDTH..... 13**
  - 3.1 LIMIT ..... 13
  - 3.2 MEASUREMENT PROCEDURE ..... 13
  - 3.3 TEST CONFIGURATION ..... 13
  - 3.4 TEST RESULTS OF MINIMUM 6DB BANDWIDTH ..... 13
- 4 MAXIMUM CONDUCTED OUTPUT POWER AND E.I.R.P..... 14**
  - 4.1 LIMIT ..... 14
  - 4.2 MEASUREMENT PROCEDURE ..... 14
  - 4.3 TEST CONFIGURATION ..... 15
  - 4.4 TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER..... 15
- 5 POWER SPECTRUM DENSITY ..... 16**
  - 5.1 LIMIT ..... 16
  - 5.2 MEASUREMENT PROCEDURE ..... 16
  - 5.3 TEST CONFIGURATION ..... 17
  - 5.4 TEST RESULTS OF POWER SPECTRUM DENSITY ..... 17
- 6 EMISSION OUTSIDE THE FREQUENCY BAND ..... 18**
  - 6.1 LIMIT ..... 18
  - 6.2 MEASUREMENT PROCEDURE ..... 18
  - 6.3 TEST CONFIGURATION ..... 19
  - 6.4 THE RESULTS OF EMISSION OUTSIDE THE FREQUENCY BAND..... 19
- 7 RADIATED EMISSIONS IN RESTRICTED FREQUENCY BANDS..... 20**
  - 7.1 LIMIT ..... 20
  - 7.2 MEASUREMENT PROCEDURE ..... 20
  - 7.3 TEST CONFIGURATION ..... 22
  - 7.4 TEST RESULTS OF RADIATED EMISSIONS ..... 24
- 8 POWER LINE CONDUCTED EMISSION..... 32**
  - 8.1 LIMIT ..... 32
  - 8.2 TEST CONFIGURATION ..... 32
  - 8.3 MEASUREMENT PROCEDURE ..... 33

**TEST REPORT**

8.4 TEST RESULTS OF POWER LINE CONDUCTED EMISSION..... 34

9 ANTENNA REQUIREMENT ..... 36

**TEST REPORT****Revision History**

<b>Report No.</b>	<b>Version</b>	<b>Description</b>	<b>Issued Date</b>
220100298SHA-001	Rev. 01	Initial issue of report	April 27, 2022

### Measurement result summary

TEST ITEM	FCC REFERENCE	RESULT
Minimum 6dB Bandwidth	15.247(a)(2)	Pass
Maximum conducted output power and e.i.r.p.	15.247(b)(3)	Pass
Power spectrum density	15.247(e)	Pass
Emission outside the frequency band	15.247(d)	Pass
Radiated Emissions in restricted frequency bands	15.247(d), 15.205&15.209	Pass
Power line conducted emission	15.207(a)	Pass
Antenna requirement	15.203	Pass

Notes: 1: NA =Not Applicable

2. Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

**TEST REPORT**

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

Product name:	pixy
Type/Model:	006
Description of EUT:	The EUT is a drone with BLE and WIFI function, it has only one model.
Rating:	Powered by Battery: 3.85V DC, 860mAh,3.311Wh
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Sample received date:	December 29, 2021
Date of test:	December 29, 2021 ~ March 1, 2022

### 1.2 Technical Specification

Frequency Band:	2400MHz ~ 2483.5MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n(HT20), IEEE 802.11n(HT40), IEEE 802.11ac(VHT20), IEEE 802.11ac(VHT40)
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n(HT20): OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n(HT40): OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11ac(VHT20): OFDMA (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11ac(VHT40): OFDMA (64-QAM, 16-QAM, QPSK, BPSK)
Operating Frequency:	2412MHz to 2462MHz for IEEE 802.11b/g/n(HT20)/ac(VHT20) 2422MHz to 2452MHz for IEEE 802.11n(HT40)/ac(VHT40)
Channel Number:	11 Channels for 802.11b, 802.11g, 802.11n(HT20) and 802.11ac(VHT20) 7 Channels for 802.11n(HT40) and 802.11ac(VHT40)

**TEST REPORT**

**1.3 Antenna information**

No.	Antenna Type	Gain	Note
1	Dipole Antenna	3.46dBi	-

Mode	Tx/Rx Function	Beamforming function	CDD function	Directional gain (dBi)
802.11b	1Tx/1Rx	NO	NO	-
802.11g	1Tx/1Rx	NO	NO	-
802.11n(HT20)	1Tx/1Rx	NO	NO	-
802.11n(HT40)	1Tx/1Rx	NO	NO	-
802.11ac(VHT20)	1Tx/1Rx	NO	NO	-
802.11ac(VHT40)	1Tx/1Rx	NO	NO	-

**1.4 Description of Test Facility**

<b>Name:</b>	Intertek Testing Services Shanghai
<b>Address:</b>	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
<b>Telephone:</b>	86 21 61278200
<b>Telefax:</b>	86 21 54262353

<b>The test facility is recognized, certified, or accredited by these organizations:</b>	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02



**TEST REPORT**

**2 TEST SPECIFICATIONS**

**2.1 Standards or specification**

47CFR Part 15 (2020)  
 ANSI C63.10 (2013)  
 KDB 558074 (v05r02)

**2.2 Mode of operation during the test**

While testing transmitting mode of EUT, the internal modulation and continuously transmission was applied.

Software name	Manufacturer	Version	Supplied by
QRCT	Qualcomm Technologies Inc	4.0	Client

The lowest, middle and highest channel were tested as representatives.

Frequency Band (MHz)	Mode	Lowest (MHz)	Middle (MHz)	Highest (MHz)
2400-2483.5	802.11b	2412	2437	2462
	802.11g	2412	2437	2462
	802.11n(HT20)	2412	2437	2462
	802.11n(HT40)	2422	2437	2452
	802.11ac(VHT20)	2412	2437	2462
	802.11ac(VHT40)	2422	2437	2452

**Data rate and Power setting:**

The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases. After this pre-scan, we choose the following table of the data rate as the worst case.

Frequency Band (MHz)	Mode	Worst case data rate
2400-2483.5	802.11b	1Mbps
	802.11g	6Mbps
	802.11n(HT20)	MCS0
	802.11n(HT40)	MCS0
	802.11ac(VHT20)	MCS0
	802.11ac(VHT40)	MCS0

**TEST REPORT**

**2.3 Test software list**

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

**2.4 Test peripherals list**

Item No.	Name	Band and Model	Description
1	Laptop computer	DELL 5480	-
2	RF cable	/	0.2m length; 0.5dB loss

**2.5 Test environment condition:**

Test items	Temperature	Humidity
Minimum 6dB Bandwidth	25°C	54% RH
Maximum conducted output power and e.i.r.p.		
Power spectrum density		
Emission outside the frequency band		
Occupied bandwidth		
Radiated Emissions in restricted frequency bands	24°C	52% RH
Power line conducted emission	24°C	51% RH

**TEST REPORT**

**2.6 Instrument list**

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESCS 30	EC 2107	2022-07-09
<input checked="" type="checkbox"/>	A.M.N.	R&S	ESH2-Z5	EC 3119	2022-11-10
<input type="checkbox"/>	A.M.N.	R&S	ENV4200	EC 3558	2022-10-11
<input checked="" type="checkbox"/>	Attenuator	Huaxiang	TS5-10dB-6G-B	21062303	2023-04-24
<input checked="" type="checkbox"/>	Shielded room	Zhongyu	-	EC 2838	2023-01-12
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESIB 26	EC 3045	2022-09-16
<input checked="" type="checkbox"/>	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2022-09-25
<input type="checkbox"/>	Horn antenna	R&S	HF 906	EC 3049	2023-01-17
<input checked="" type="checkbox"/>	Horn antenna	ETS	3117	EC 4792-1	2023-03-15
<input type="checkbox"/>	Horn antenna	TOYO	HAP18-26W	EC 4792-3	2022-07-09
<input checked="" type="checkbox"/>	Pre-amplifier	R&S	Pre-amp 18	EC5262	2022-06-11
<input checked="" type="checkbox"/>	Semi-anechoic chamber	Albatross project	-	EC 3048	2022-07-14
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2023-03-16
<input checked="" type="checkbox"/>	PXA Signal Analyzer	Keysight	N9030B	EC 6078	2022-06-10
<input checked="" type="checkbox"/>	Power sensor	Agilent	U2021XA	EC 5338-1	2023-03-16
<input checked="" type="checkbox"/>	Vector Signal Generator	Agilent	N5182B	EC 5175	2023-03-16
<input checked="" type="checkbox"/>	MXG Analog Signal Generator	Agilent	N5181A	EC 5338-2	2023-03-16
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESCI 7	EC 4501	2022-09-16
<input type="checkbox"/>	Universal Radio Communication Tester	R&S	CMW500	EC5944	2022-12-09
<input type="checkbox"/>	Universal Radio Communication Tester	R&S	CMW500	Ec6209	2022-12-30
<input checked="" type="checkbox"/>	Signal generator	Agilent	N5182A	Ec6172	2022-08-21
<input checked="" type="checkbox"/>	Signal generator	Agilent	N5181A	Ec6171	2022-08-21
<input checked="" type="checkbox"/>	Climate chamber	GWS	MT3065	EC 6021	2023-03-05
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3783	2023-03-03
<input checked="" type="checkbox"/>	Pressure meter	YM3	Shanghai Mengde	EC 4620	2022-09-09

**TEST REPORT**

**2.7 Measurement uncertainty**

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	± 0.74dB
Minimum 6dB bandwidth	
Power spectrum density	
Emission outside the frequency band	
Occupied bandwidth	
Radiated Emissions in restricted frequency bands below 1GHz	± 4.90dB
Radiated Emissions in restricted frequency bands above 1GHz	± 5.02dB
Emission outside the frequency band	± 2.89dB
Power line conducted emission	± 3.19dB

**TEST REPORT**

### 3 Minimum 6dB bandwidth

**Test result:** Pass

#### 3.1 Limit


For systems using digital modulation techniques that may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz and 5725 - 5850 MHz bands, the minimum 6 dB bandwidth shall be at least 500 kHz.

#### 3.2 Measurement Procedure

The EUT was tested according to Subclause 11.8 of ANSI C63.10.

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 3.3 Test Configuration



#### 3.4 Test Results of Minimum 6dB bandwidth

Please refer to Appendix A

**TEST REPORT**

## 4 Maximum conducted output power and e.i.r.p.

Test result: Pass

### 4.1 Limit


For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 W. (The e.i.r.p. shall not exceed 4 W)

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 30dBm and 30+ (6 –antenna gain-beam forming gain).

### 4.2 Measurement Procedure

The EUT was tested according to Subclause 11.9.2.2 of ANSI C63.10.

- a) Measure the duty cycle,  $x$ , of the transmitter output signal as described in Section 6.0.
- b) Set span to at least  $1.5 \times \text{OBW}$ .
- c) Set RBW = 1 % to 5 % of the OBW, not to exceed 1 MHz.
- d) Set VBW  $\geq 3 \times \text{RBW}$ .
- e) Number of points in sweep  $\geq 2 \times \text{span} / \text{RBW}$ . (This gives bin-to-bin spacing  $\leq \text{RBW}/2$ , so that narrowband signals are not lost between frequency bins.)
- f) Sweep time = auto.
- g) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- h) Do not use sweep triggering. Allow the sweep to “free run”.
- i) Trace average at least 100 traces in power averaging (i.e., RMS) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the on and off periods of the transmitter.
- j) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
- k) Add  $10 \log (1/x)$ , where  $x$  is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on- and off-times of the transmission). For example, add  $10 \log (1/0.25) = 6 \text{ dB}$  if the duty cycle is 25 %.

**TEST REPORT****4.3 Test Configuration****4.4 Test Results of Maximum conducted output power**

Please refer to Appendix A

## 5 Power spectrum density

**Test result:** Pass

### 5.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 8dBm/MHz and  $8 + (6 - \text{antenna gain} - \text{beam forming gain})$ .

### 5.2 Measurement Procedure


The EUT was tested according to Subclause 11.10 of ANSI C63.10.

This procedure is applicable when the EUT cannot be configured to transmit continuously (i.e., duty cycle < 98 %), and when sweep triggering/signal gating cannot be used to measure only when the EUT is transmitting at its maximum power control level, and when the transmission duty cycle is constant (i.e., duty cycle variations are less than  $\pm 2\%$ ):

- a) Measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.
- b) Set instrument center frequency to DTS channel center frequency.
- c) Set span to at least  $1.5 \times \text{OBW}$ .
- d) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- e) Set VBW  $\geq 3 \times \text{RBW}$ .
- f) Detector = power averaging (RMS) or sample detector (when RMS not available).
- g) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- h) Sweep time = auto couple.
- i) Do not use sweep triggering. Allow sweep to "free run".
- j) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- k) Use the peak marker function to determine the maximum amplitude level.
- l) Add  $10 \log(1/x)$ , where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.
- m) If resultant value exceeds the limit, then reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).



### 5.3 Test Configuration



### 5.4 Test Results of Power spectrum density

Please refer to Appendix A

**TEST REPORT**

## 6 Emission outside the frequency band

**Test result:** Pass

### 6.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

### 6.2 Measurement Procedure

The EUT was tested according to Subclause 11.11 of ANSI C63.10.

#### Reference level measurement

Establish a reference level by using the following procedure:


- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to  $\geq 1.5$  times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW  $\geq 3 \times$  RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

#### Emission level measurement

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq 3 \times$  RBW.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

### 6.3 Test Configuration



### 6.4 The results of Emission outside the frequency band

Please refer to Appendix A

**TEST REPORT**

## 7 Radiated Emissions in restricted frequency bands

**Test result:** Pass

### 7.1 Limit

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified showed as below:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

### 7.2 Measurement Procedure

The EUT was tested according to Subclause 11.12 of ANSI C63.10.

**For Radiated emission below 30MHz:**

- a) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) Both X and Y axes of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

**NOTE:**

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

**TEST REPORT****For Radiated emission above 30MHz:**

- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meters chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detector function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


**Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or  $3 \times \text{RBW}$  (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions were reported.


**TEST REPORT**

**7.3 Test Configuration**


For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:





**For Radiated emission above 1GHz:**



## TEST REPORT

### 7.4 Test Results of Radiated Emissions

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.





**TEST REPORT**

**Test data below 1GHz**

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	33.888	22.6	19.0	40.0	17.4	PK
H	214.615	21.5	11.3	43.5	22.0	PK
H	241.884	14.2	13.7	46.0	31.8	PK
H	379.900	21.1	17.9	46.0	24.9	PK
V	33.888	31.3	19.0	40.0	8.7	PK
V	43.607	26.0	13.3	40.0	14.0	PK
V	212.726	28.1	11.3	43.5	15.4	PK
V	797.836	30.1	23.6	46.0	15.9	PK

**TEST REPORT**

**Test result above 1GHz:**

The emission was conducted from 1GHz to 25GHz

802.11b

CH	Antenna	Frequency	Level	Reading Level	Margin	Limit	Factor (dB)	Type
		(MHz)	(dBuV/m)	(dBuV)	(dB)	(dBuV/m)		
L	H	2390.00	60.40	30.60	10.80	74.00	13.60	PK
	H	2390.00	47.70	17.50	3.90	54.00	6.30	AV
	V	2390.00	61.20	29.70	11.70	74.00	12.80	PK
	V	2390.00	48.10	16.20	5.20	54.00	5.90	AV
	H	7236.00	50.60	42.50	23.80	74.00	23.40	PK
	V	7236.00	51.20	41.30	25.00	74.00	22.80	PK
M	H	4874.00	48.20	44.10	26.90	74.00	25.80	PK
	V	4874.00	48.80	44.40	26.60	74.00	25.20	PK
H	H	2483.50	61.20	29.70	11.60	74.00	12.80	PK
	H	2483.50	48.10	19.50	1.80	54.00	5.90	AV
	V	2483.50	62.50	27.80	13.50	74.00	11.50	PK
	V	2483.50	48.60	16.40	4.90	54.00	5.40	AV
	H	4924.00	48.60	45.70	25.20	74.00	25.40	PK
	V	4924.00	49.20	43.90	27.00	74.00	24.80	PK

**TEST REPORT**

802.11g

CH	Antenna	Frequency	Level	Reading Level	Margin	Limit	Factor (dB)	Type
		(MHz)	(dBuV/m)	(dBuV)	(dB)	(dBuV/m)		
L	H	2390.00	59.80	27.00	14.40	74.00	14.20	PK
	H	2390.00	46.90	16.30	5.10	54.00	7.10	AV
	V	2390.00	60.10	25.70	15.70	74.00	13.90	PK
	V	2390.00	47.90	13.90	7.50	54.00	6.10	AV
	H	7236.00	50.30	40.50	25.80	74.00	23.70	PK
	V	7236.00	51.10	41.60	24.70	74.00	22.90	PK
M	H	7311.00	49.20	45.90	20.20	74.00	24.80	PK
	V	7311.00	49.40	44.90	21.20	74.00	24.60	PK
H	H	2483.50	60.10	27.70	13.60	74.00	13.90	PK
	H	2483.50	48.30	17.40	3.90	54.00	5.70	AV
	V	2483.50	61.80	27.00	14.30	74.00	12.20	PK
	V	2483.50	49.00	16.10	5.20	54.00	5.00	AV
	H	7386.00	47.10	44.10	21.70	74.00	26.90	PK
	V	7386.00	48.80	44.40	21.40	74.00	25.20	PK

**TEST REPORT**

802.11n(HT20)

CH	Antenna	Frequency	Level	Reading Level	Margin	Limit	Factor (dB)	Type
		(MHz)	(dBuV/m)	(dBuV)	(dB)	(dBuV/m)		
L	H	2390.00	60.50	28.00	13.40	74.00	13.50	PK
	H	2390.00	47.00	17.90	3.50	54.00	7.00	AV
	V	2390.00	61.40	26.50	14.90	74.00	12.60	PK
	V	2390.00	48.20	16.50	4.90	54.00	5.80	AV
	H	7236.00	50.10	44.40	21.90	74.00	23.90	PK
	V	7236.00	50.80	46.10	20.20	74.00	23.20	PK
M	H	7311.00	50.20	42.80	23.30	74.00	23.80	PK
	V	7311.00	51.20	44.50	21.60	74.00	22.80	PK
H	H	2483.50	61.20	27.60	13.70	74.00	12.80	PK
	H	2483.50	50.20	19.60	1.70	54.00	3.80	AV
	V	2483.50	62.20	26.70	14.60	74.00	11.80	PK
	V	2483.50	47.20	17.50	3.80	54.00	6.80	AV
	H	7386.00	48.20	43.10	22.80	74.00	25.80	PK
	V	7386.00	49.90	45.10	20.80	74.00	24.10	PK

**TEST REPORT**

802.11n (HT40):

CH	Antenna	Frequency (MHz)	Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
L	H	2390.00	60.10	25.50	15.90	74.00	13.90	PK
	H	2390.00	48.90	10.00	11.40	54.00	5.10	AV
	V	2390.00	60.80	25.70	15.70	74.00	13.20	PK
	V	2390.00	49.10	7.50	13.90	54.00	4.90	AV
	H	7266.00	48.30	40.50	25.70	74.00	25.70	PK
	V	7266.00	48.90	40.40	25.80	74.00	25.10	PK
M	H	7311.00	50.20	40.00	26.10	74.00	23.80	PK
	V	7311.00	50.70	40.70	25.40	74.00	23.30	PK
H	V	2483.50	61.20	25.50	15.80	74.00	12.80	PK
	V	2483.50	48.50	12.50	8.80	54.00	5.50	AV
	H	2483.50	61.70	25.30	16.00	74.00	12.30	PK
	H	2483.50	49.10	10.20	11.10	54.00	4.90	AV
	H	7356.00	51.20	40.30	25.60	74.00	22.80	PK
	V	7356.00	51.60	40.30	25.60	74.00	22.40	PK

**TEST REPORT**

802.11ac(VHT20)

CH	Antenna	Frequency	Level	Reading Level	Margin	Limit	Factor (dB)	Type
		(MHz)	(dBuV/m)	(dBuV)	(dB)	(dBuV/m)		
L	H	2390.00	59.60	28.00	13.40	74.00	14.40	PK
	H	2390.00	49.10	17.90	3.50	54.00	4.90	AV
	V	2390.00	60.10	26.50	14.90	74.00	13.90	PK
	V	2390.00	49.60	16.50	4.90	54.00	4.40	AV
	H	7236.00	50.20	44.40	21.90	74.00	23.80	PK
	V	7236.00	50.70	46.10	20.20	74.00	23.30	PK
M	H	7311.00	50.30	42.80	23.30	74.00	23.70	PK
	V	7311.00	51.10	44.50	21.60	74.00	22.90	PK
H	H	2483.50	61.20	27.60	13.70	74.00	12.80	PK
	H	2483.50	48.40	19.60	1.70	54.00	5.60	AV
	V	2483.50	61.60	26.70	14.60	74.00	12.40	PK
	V	2483.50	49.20	17.50	3.80	54.00	4.80	AV
	H	7386.00	51.10	43.10	22.80	74.00	22.90	PK
	V	7386.00	51.30	45.10	20.80	74.00	22.70	PK

**TEST REPORT**

802.11ac (VHT40):

CH	Antenna	Frequency (MHz)	Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB)	Type
L	H	2390.00	59.70	25.50	15.90	74.00	14.30	PK
	H	2390.00	47.30	10.00	11.40	54.00	6.70	AV
	V	2390.00	60.70	25.70	15.70	74.00	13.30	PK
	V	2390.00	48.20	7.50	13.90	54.00	5.80	AV
	H	7266.00	50.30	40.50	25.70	74.00	23.70	PK
	V	7266.00	50.70	40.40	25.80	74.00	23.30	PK
M	H	7311.00	50.70	40.00	26.10	74.00	23.30	PK
	V	7311.00	51.00	40.70	25.40	74.00	23.00	PK
H	V	2483.50	60.70	25.50	15.80	74.00	13.30	PK
	V	2483.50	48.00	12.50	8.80	54.00	6.00	AV
	H	2483.50	61.20	25.30	16.00	74.00	12.80	PK
	H	2483.50	48.50	10.20	11.10	54.00	5.50	AV
	H	7356.00	50.60	40.30	25.60	74.00	23.40	PK
	V	7356.00	51.10	40.30	25.60	74.00	22.90	PK

Note: Choose the worst power to test as representative.

Remark: 1. Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.

2. Level = Reading Level + Factor

3. Margin = Limit - Level

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB, Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV, Limit = 40.00dBuV/m.

Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;

Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;

Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

## 8 Power line conducted emission


Test result: Pass

### 8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### 8.2 Test Configuration





**TEST REPORT****8.3 Measurement Procedure**

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50  $\Omega$  LISN port (to which the EUT is connected), where permitted, terminated into a 50  $\Omega$  measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50  $\Omega$  measuring port is terminated by a measuring instrument having 50  $\Omega$  input impedance. All other ports are terminated in 50  $\Omega$  loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.


The bandwidth of the test receiver is set at 9 kHz.

**TEST REPORT**


**8.4 Test Results of Power line conducted emission**

Test Curve:

L line



N line



**TEST REPORT**

**Test Data:**

No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector	Phase
1	474.000kHz	56.4	32.8	-23.6	22.5	10.3	QP	N
2	532.500kHz	56.0	32.7	-23.3	22.3	10.4	QP	N
3	658.500kHz	56.0	31.6	-24.4	21.1	10.5	QP	N
4	888.000kHz	56.0	27.8	-28.2	17.2	10.6	QP	N
5	1.005MHz	56.0	32.8	-23.2	22.2	10.6	QP	N
6	1.122MHz	56.0	29.7	-26.3	19.1	10.6	QP	N
7	474.000kHz	46.4	24.9	-21.6	14.6	10.3	CAV	N
8	532.500kHz	46.0	23.2	-22.8	12.8	10.4	CAV	N
9	663.000kHz	46.0	19.6	-26.4	9.1	10.5	CAV	N
10	1.010MHz	46.0	20.6	-25.4	10.0	10.6	CAV	N

- Remark: 1. Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.  
 2. Level = Original Receiver Reading + Factor  
 3. Delta= Level - Limit  
 4. If the PK Level is lower than AV limit, the AV test can be elided.

Example: Assuming LISN Factor = 10.00dB, Cable Loss = 2.00dB,  
 Original Receiver Reading = 10.00dBuV, Limit = 66.00dBuV.  
 Then Factor = 10.00 + 2.00 = 12.00dB;  
 Level = 10dBuV + 12.00dB = 22.00dBuV;  
 Delta = 22.00dBuV - 66.00dBuV = -44.00dB.

**TEST REPORT**

**9 Antenna requirement**

**Requirement:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**Result:**

EUT use of a permanently attached antenna and unique coupling to the intentional radiator, so it can comply with the provisions of this section.

\*\*\*\*\* END \*\*\*\*\*