



FCC Part 15, Subpart B, Class B

Powerstick.com Inc.

Clearpad Glow

Test Model: CLRPADGLOW

Prepared for : Powerstick.com Inc.  
Address : 39 Camelot Drive, Ottawa, Ontario, Canada, K2W 5G6

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park  
Yabianxueziwei, Shajing Street, Baoan District,  
Shenzhen, 518000, China

Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : August 15, 2024  
Number of tested samples : 2  
Sample No. : A240814031-1, A240814031-2  
Serial number : Prototype  
Date of Test : August 15, 2024 ~ August 20, 2024  
Date of Report : August 21, 2024





FCC Part 15, Subpart B, Class B
FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014

Report Reference No. .... : LCSA08154063EA

Date Of Issue..... : August 21, 2024

Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park
Yabianxueziwei, Shajing Street, Baoan District, Shenzhen,
518000, China

Testing Location/ Procedure.... : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □

Applicant's Name..... : Powerstick.com Inc.

Address..... : 39 Camelot Drive, Ottawa, Ontario, Canada, K2W 5G6

Test Specification

Standard..... : FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014

Test Report Form No..... : TRF-4-E-010

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. is acknowledged as copyright owner and source of the material. SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : Clearpad Glow

Test Model ..... : CLRPADGLOW

Trade Mark..... : Powerstick

Ratings..... : Input: DC 5.0V, 350mA

Result ..... : Positive

Compiled by:

Li Huan

Li Huan/ Administrator

Supervised by:

Cary Luo

Cary Luo/ Technique principal

Approved by:

Gavin Liang

Gavin Liang/ Manager





### FCC -- TEST REPORT

<b>Test Report No. : LCSA08154063EA</b>	<u>August 21, 2024</u> Date of issue
---	---

Test Model ..... : CLRPADGLOW  EUT..... : Clearpad Glow
<b>Applicant..... : Powerstick.com Inc.</b> Address..... : 39 Camelot Drive, Ottawa, Ontario, Canada, K2W 5G6 Telephone..... : / Fax..... : /
<b>Manufacturer..... : Powerstick.com Inc.</b> Address..... : 39 Camelot Drive, Ottawa, Ontario, Canada, K2W 5G6 Telephone..... : / Fax..... : /
<b>Factory ..... : Powerstick.com Inc.</b> Address..... : 39 Camelot Drive, Ottawa, Ontario, Canada, K2W 5G6 Telephone..... : / Fax..... : /

**Test Result** according to the standards on page 6: **Positive**

The test report merely corresponds to the test sample.  
 It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





### Revision History

Report Version	Issue Date	Revision Content	Revised By
000	August 21, 2024	Initial Issue	---



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity



### TABLE OF CONTENTS

Test Report Description	Page
<b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>	<b>6</b>
1.1. Description of Standards and Results .....	6
<b>2. GENERAL INFORMATION .....</b>	<b>7</b>
2.1. Description of Device (EUT) .....	7
2.2. Support Equipment List .....	7
2.3 External I/O Cable .....	7
2.4. Description of Test Facility .....	8
2.5. Statement of the Measurement Uncertainty .....	8
2.6. Measurement Uncertainty .....	8
<b>3. TEST RESULTS .....</b>	<b>9</b>
3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT .....	9
3.2. Radiated emission Measurement .....	13
<b>4. TEST SETUP PHOTOGRAPHS OF EUT .....</b>	<b>18</b>
<b>5. EXTERIOR PHOTOGRAPHS OF THE EUT .....</b>	<b>19</b>
<b>6. INTERIOR PHOTOGRAPHS OF THE EUT .....</b>	<b>19</b>





# 1. SUMMARY OF STANDARDS AND RESULTS

## 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION			
Description of Test Item	Standard	Limits	Results
Conducted disturbance at mains terminals	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014	Class B	PASS
Radiated disturbance	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014	Class B	PASS

N/A is an abbreviation for Not Applicable.

Test mode:		
Mode 1	Normal Operation	Record





## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

EUT : Clearpad Glow

Trade Mark : Powerstick

Test Model : CLRPADGLOW

Ratings : Input: DC 5.0V, 350mA

Highest internal frequency (Fx) : Fx > 1 GHz

Highest internal frequency (Fx)	Highest measured frequency
Fx ≤ 108 MHz	1 GHz
108 MHz < Fx ≤ 500 MHz	2 GHz
500 MHz < Fx ≤ 1 GHz	5 GHz
Fx > 1 GHz	5 × Fx up to a maximum of 6 GHz

NOTE 1 For FM and TV broadcast receivers, Fx is determined from the highest frequency generated or used excluding the local oscillator and tuned frequencies.  
Where Fx is unknown, the radiated emission measurements shall be performed up to 6 GHz.

### 2.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
SHENZHEN TIANYIN ELECTRONICS CO., LTD	Power Adapter	TPA-46050 200UU	---	FCC

Note: The adapter is supplied by lab and only use tested.

### 2.3 External I/O Cable

I/O Port Description	Quantity	Cable
Type-C USB Port	1	N/A







### 2.4. Description of Test Facility

Site Description  
EMC Lab.

: NVLAP Accreditation Code is 600167-0.  
FCC Designation Number is CN5024.  
CAB identifier is CN0071.  
CNAS Registration Number is L4595.  
FCC Test Firm Registration Number: 254912.

### 2.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

### 2.6. Measurement Uncertainty

Test	Parameters	Expanded Uncertainty (Ulab)	Expanded Uncertainty (Ucisp)
Conducted Emission	Level accuracy (9kHz to 150kHz) (150kHz to 30MHz)	± 2.63 dB ± 2.35 dB	± 3.8 dB ± 3.4 dB
Radiated Emission	Level accuracy (30MHz to 1000MHz)	± 3.48 dB	± 5.3 dB
Radiated Emission	Level accuracy (above 1000MHz)	± 3.90 dB	± 5.2 dB

(1) Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus.

(2) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.





### 3. TEST RESULTS


#### 3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT

##### 3.1.1. Test Equipment

The following test equipments are used during the power line conducted measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	Farad	EZ	/	N/A	N/A
2	EMI Test Receiver	R&S	ESR3	102312	2024-03-02	2025-03-01
3	Artificial Mains	R&S	ENV216	101288	2024-06-06	2025-06-05
4	Pulse Limiter	R&S	ESH3-Z2	102750-NB	2024-06-06	2025-06-05
5	Impedance Stabilization Network	TESEQ	ISN T800	45130	2023-10-18	2024-10-17

##### 3.1.2. Block Diagram of Test Setup



##### 3.1.3. Test Standard

###### Power Line Conducted Emission Limits (Class B)

Frequency (MHz)			Limit (dB $\mu$ V)	
			Quasi-peak Level	Average Level
0.15	~	0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50	~	5.00	56.0	46.0
5.00	~	30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.

NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.





### 3.1.4.EUT Configuration on Test

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

### 3.1.5.Operating Condition of EUT

3.1.5.1.Setup the EUT as shown on Section 3.1.2

3.1.5.2.Turn on the power of all equipments.

3.1.5.3.Let the EUT work in measuring Lighting and measure it.

### 3.1.6.Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC/ANSI C63.4-2014 on Conducted Emission Measurement.

The bandwidth of the test receiver is set at 9kHz.

The frequency range from 150kHz to 30MHz is investigated

### 3.1.7.Test Results


**PASS.**

The test result please refer to the next page.





<b>Test Model</b>	CLRPADGLOW	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	22.5°C, 53.7% RH	<b>Test Engineer</b>	Paddi Chen
<b>Pol</b>	Line	<b>Test Voltage</b>	AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.164	40.04	19.82	59.86	65.26	-5.40	QP	
2		0.200	6.16	19.65	25.81	53.61	-27.80	AVG	
3		0.523	23.90	19.76	43.66	56.00	-12.34	QP	
4		0.573	4.24	19.61	23.85	46.00	-22.15	AVG	
5		1.486	10.75	19.05	29.80	56.00	-26.20	QP	
6		1.527	-0.34	19.04	18.70	46.00	-27.30	AVG	
7		2.706	9.91	19.16	29.07	56.00	-26.93	QP	
8		3.165	-2.87	19.23	16.36	46.00	-29.64	AVG	
9		4.965	19.25	18.94	38.19	56.00	-17.81	QP	
10		5.298	2.63	18.92	21.55	50.00	-28.45	AVG	
11		20.261	24.45	19.04	43.49	60.00	-16.51	QP	
12		21.665	16.57	18.95	35.52	50.00	-14.48	AVG	




Shenzhen LCS Compliance Testing Laboratory Ltd.  
 Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
 Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
 Scan code to check authenticity





<b>Test Model</b>	CLRPADGLOW	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	24.6°C, 53.2% RH	<b>Test Engineer</b>	Paddi Chen
<b>Pol</b>	Neutral	<b>Test Voltage</b>	AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.159	40.04	19.62	59.66	65.52	-5.86	QP	
2		0.168	6.02	19.66	25.68	55.06	-29.38	AVG	
3		0.303	31.11	19.78	50.89	60.16	-9.27	QP	
4		0.303	4.49	19.78	24.27	50.16	-25.89	AVG	
5		1.450	13.29	18.95	32.24	56.00	-23.76	QP	
6		1.509	2.98	18.97	21.95	46.00	-24.05	AVG	
7		2.783	10.24	19.03	29.27	56.00	-26.73	QP	
8		3.174	-0.26	18.99	18.73	46.00	-27.27	AVG	
9		4.960	20.94	18.83	39.77	56.00	-16.23	QP	
10		5.235	5.62	18.87	24.49	50.00	-25.51	AVG	
11		21.665	24.72	19.15	43.87	60.00	-16.13	QP	
12		23.131	17.22	19.24	36.46	50.00	-13.54	AVG	

Note: 1) Pre-scan all modes and recorded the worst case results in this report.

2) Margin= Reading level + Correct factor – Limit

Correct Factor= Lish Factor+Cable Factor




### 3.2. Radiated emission Measurement

#### 3.2.1. Test Equipment


The following test equipments are used during the radiated emission measurement:

Item	Test equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	AUDIX	E3	/	N/A	N/A
2	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2021-09-12	2024-09-11
3	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2021-09-05	2024-09-04
4	EMI Test Receiver	R&S	ESPI	101940	2024-06-06	2025-06-05
5	Low-frequency amplifier	SchwarzZBECK	BBV9745	00253	2023-10-18	2024-10-17
6	High-frequency amplifier	JS Denki Pte	PA0118-43	JSPA21009	2023-10-18	2024-10-17
7	EMI Test Software	Farad	EZ	/	N/A	N/A
8	MXA Signal Analyzer	Agilent	N9020A	MY50510140	2023-10-18	2024-10-17

#### 3.2.2. Block Diagram of Test Setup



Below 1GHz



Above 1GHz







### 3.2.3. Radiated Emission Limit (Class B)

Limits for Radiated Disturbance Below 1GHz

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46
960 ~ 1000	3	500	54

Remark: (1) Emission level (dB)μV = 20 log Emission level μV/m  
 (2) The smaller limit shall apply at the cross point between two frequency bands.  
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Limits for Radiated Emission Above 1GHz

Frequency (MHz)	Distance (Meters)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)
Above 1000	3	74	54

\*\*\*Note: The lower limit applies at the transition frequency.

### 3.2.4. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 3.2.5. Operating Condition of EUT

3.2.5.1. Setup the EUT as shown in Section 3.2.2.

3.2.5.2. Let the EUT work in test Lighting and measure it.

### 3.2.6. Test Procedure

EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated by-log antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2014 on radiated emission measurement.

The bandwidth of the EMI test receiver is set at 120kHz, 300kHz.

The frequency range from 30MHz to 1000MHz is checked.

### 3.2.7. Radiated Emission Noise Measurement Result


**PASS.**

The scanning waveforms please refer to the next page.





<b>Test Model</b>	CLRPADGLOW	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	23.8°C, 52.3% RH	<b>Detector Function</b>	Quasi-peak
<b>Pol</b>	Horizontal	<b>Distance</b>	3m
<b>Test Engineer</b>	Paddi Chen	<b>Test Voltage</b>	AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36.8953	33.28	-17.69	15.59	40.00	-24.41	QP
2	84.7019	38.44	-19.41	19.03	40.00	-20.97	QP
3	148.4410	35.05	-19.99	15.06	43.50	-28.44	QP
4	296.1836	32.01	-15.57	16.44	46.00	-29.56	QP
5	463.9696	29.11	-14.35	14.76	46.00	-31.24	QP
6	631.6884	29.44	-11.06	18.38	46.00	-27.62	QP



Shenzhen LCS Compliance Testing Laboratory Ltd.  
 Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
 Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
 Scan code to check authenticity







<b>Test Model</b>	CLRPADGLOW	<b>Test Mode</b>	Mode 1
<b>Environmental Conditions</b>	23.8°C, 52.1% RH	<b>Detector Function</b>	Quasi-peak
<b>Pol</b>	Vertical	<b>Distance</b>	3m
<b>Test Engineer</b>	Paddi Chen	<b>Test Voltage</b>	AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36.8953	44.61	-17.69	26.92	40.00	-13.08	QP
2	70.5836	41.00	-19.49	21.51	40.00	-18.49	QP
3	84.9995	41.54	-19.38	22.16	40.00	-17.84	QP
4	150.0108	34.86	-19.82	15.04	43.50	-28.46	QP
5	293.0842	34.90	-15.55	19.35	46.00	-26.65	QP
6	593.0497	29.35	-10.56	18.79	46.00	-27.21	QP


Note: Margin= Reading Level+Correct Factor – Limit  
 Correct Factor=Antenna Factor+Cable Factor – Pre-Amplifier Factor



Shenzhen LCS Compliance Testing Laboratory Ltd.  
 Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
 Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
 Scan code to check authenticity



<b>Test Model</b>	CLRPADGLOW	<b>Test Mode</b>	Mode 1 (Above 1GHz)
<b>Environmental Conditions</b>	23.9°C, 52.0% RH	<b>Detector Function</b>	Peak + AV
<b>Pol</b>	Horizontal	<b>Distance</b>	3m
<b>Test Engineer</b>	Paddi Chen	<b>Test Voltage</b>	AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1445.000	49.58	-15.12	34.46	74.00	-39.54	peak
2	1960.000	48.98	-13.31	35.67	74.00	-38.33	peak
3	2655.000	48.93	-10.81	38.12	74.00	-35.88	peak
4	3365.000	48.37	-9.46	38.91	74.00	-35.09	peak
5	4485.000	46.81	-6.64	40.17	74.00	-33.83	peak
6	5300.000	46.66	-3.57	43.09	74.00	-30.91	peak




Shenzhen LCS Compliance Testing Laboratory Ltd.  
 Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
 Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
 Scan code to check authenticity





<b>Test Model</b>	CLRPADGLOW	<b>Test Mode</b>	Mode 1 (Above 1GHz)
<b>Environmental Conditions</b>	23.9°C, 52.0% RH	<b>Detector Function</b>	Peak + AV
<b>Pol</b>	Vertical	<b>Distance</b>	3m
<b>Test Engineer</b>	Paddi Chen	<b>Test Voltage</b>	AC 120V/60Hz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1525.000	49.64	-14.86	34.78	74.00	-39.22	peak
2	2005.000	48.60	-13.08	35.52	74.00	-38.48	peak
3	2845.000	48.18	-10.13	38.05	74.00	-35.95	peak
4	3310.000	48.27	-9.48	38.79	74.00	-35.21	peak
5	4130.000	46.38	-8.04	38.34	74.00	-35.66	peak
6	5065.000	46.78	-3.99	42.79	74.00	-31.21	peak

Note:

- Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurements above show only up to 6 maximum emissions noted.
- Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- Factor = Antenna Factor + Cable Loss + Amplifier Factor  
 Emission Level = Reading level + Factor  
 Margin = Emission Level - Limit

#### 4. TEST SETUP PHOTOGRAPHS OF EUT



Shenzhen LCS Compliance Testing Laboratory Ltd.  
 Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
 Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
 Scan code to check authenticity



Please refer to separated files for Test Setup Photos of the EUT.

### 5. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

### 6. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF TEST REPORT-----

